

# Wheel Alignment

GENERAL MOTORS WHEEL ALIGNMENT SPECIFICATIONS					
Application	Axle Gap ②	Caster (Degrees) ③	Camber (Degrees) ③	Toe-In (Inches) ④	Steering Axis Inclin.
Chevrolet C10	3	+2	+1/4	3/16	.....
	3 1/2	+1 1/4	+1/4	3/16	.....
	4	+3/4	+1/4	3/16	.....
	4 1/2	+1/4	+1/4	3/16	.....
	5	-1/2	+1/4	3/16	.....
C20 & 30	2 1/2	+1 1/2	+1/4	3/16	.....
	3	+1	+1/4	3/16	.....
	3 1/2	+1/2	+1/4	3/16	.....
	4	0	+1/4	3/16	.....
	4 1/2	-1/2	+1/4	3/16	.....
K10 & 20 G10, 20 & 30	5	-1	+1/4	3/16	.....
	.....	+4	+1 1/2	0	.....
	2 1/2	+2 1/4	+1/4	3/16	.....
	3	+1 1/2	+1/4	3/16	.....
	3 1/2	+1	+1/4	3/16	.....
P10, 20 & 30 (Exc. MHC)	4	+1/2	+1/4	3/16	.....
	4 1/2	0	+1/4	3/16	.....
	5	-1/2	+1/4	3/16	.....
	2 1/2	+2 1/2	.....	3/16	.....
	3	+2	+1/4	3/16	.....
P30-MHC	3 1/2	+1 1/2	+1/4	3/16	.....
	4	+3/4	+1/4	3/16	.....
	4 1/2	+1/4	0	3/16	.....
	5	-1/4	-1/4	3/16	.....
	5 1/2	.....	-3/4	3/16	.....
GMC F.W.D. Motor Home Left Side Right Side	2 1/2	+4 3/4	.....	3/16	.....
	3	+5	+1/4	3/16	.....
	3 1/2	+4 1/2	+1/4	3/16	.....
	4	+4	0	3/16	.....
	4 1/2	3 1/2	0	3/16	.....
GMC F.W.D. Motor Home Left Side Right Side	5	+3	-1/2	3/16	.....
	5 1/2	.....	-1	3/16	.....
	.....	+2	.....	-1/8 ⑤	.....
	.....	.....	+3/4	.....	.....
	.....	.....	+1/2	.....	.....

- ① - The vehicle series and model application in this table has been abbreviated for common reference to both Chevrolet and GMC. Chevrolet models use numerical designations as listed; GMC models use numerical designations as follows: 1500 = 10; 2500 = 20; 3500 = 30.
- ② - Axle gap is clearance between jounce bumper bracket and frame.
- ③ - Plus or minus 1/2°.
- ④ - Plus or minus 1/16".
- ⑤ - This specification is 1/8" toe-out.

JEEP WHEEL ALIGNMENT SPECIFICATIONS					
Application	Axle Gap	Caster (Degrees)	Camber (Degrees)	Toe-In (Inches)	Steering Axis Inclin.
CJ Models Cherokee, Wagoneer & Truck	.....	+2 to +4	+1 to +2	3/4-3/32	.....
	.....	+3 to +5	+1 to +2	3/4-3/32	.....