

# Wheel Alignment

CHRYSLER CORP. WHEEL ALIGNMENT SPECIFICATIONS					
Application	Axle Gap	Caster (Degrees)	Camber (Degrees)	Toe-In (Inches)	Steering Axis Inclin.
<b>Dodge</b>					
"B", "CB" & "MB"					
Man. Steer.	.....	-1/2 to +1 1/2	0 to +1	1/8	.....
Pwr. Steer.	.....	+1 1/4 to +3 1/4	0 to +1	1/8	.....
W150, 200	.....	3	1.5	1/8	.....
W200, 300 & 400	.....	3	.5	1/8	.....
D100-400	.....	+1/2	+1/4	1/8	.....
MHC					
M300	.....	+3	+2	1/16	.....
M400, 500 & 600	.....	+2 1/2 ①	+1	1/8	.....
<b>Plymouth</b>					
"PB"					
Man. Steer.	.....	-1/2 to +1 1/2	0 to +1	1/8	.....
Pwr. Steer.	.....	+1 1/4 to +3 1/4	0 to +1	1/8	.....

① - Caster on M600 models is +2°.

IHC WHEEL ALIGNMENT SPECIFICATIONS					
Application	Axle Gap	Caster (Degrees)	Camber (Degrees)	Toe-In (Inches)	Steering Axis Inclin.
All Models	.....	0 ± 1	+1 ± 1/2	1/16 ± 1/16	8 1/2

JEEP WHEEL ALIGNMENT SPECIFICATIONS					
Application	Axle Gap	Caster (Degrees)	Camber (Degrees)	Toe-In (Inches)	Steering Axis Inclin.
"CJ" Models	.....	+3 to +4	+1 1/2 to +2	3/64 to 3/32	8 1/2
Cherokee, Wagoneer & Truck	.....	+4 to +5	+1 1/2 to +2	3/64 to 3/32	8 1/2