

Wheel Alignment

FORD WHEEL ALIGNMENT SPECIFICATIONS						
Application	Axle Gap ①	Caster (Degrees)	Camber (Degrees)	Toe-In (Inches)	Steering Axis Inclin.	
E100 & 150 4x2 Models	3 1/4 to 3 1/2	6 1/4 to 8	-1 3/4 to -1/4	1/32	
	3 1/2 to 3 3/4	5 3/4 to 7 1/4	-1 1/2 to -1/4	1/32	
	3 3/4 to 4	5 to 6 3/4	-1 to +7/8	1/32	
	4 to 4 1/4	4 1/2 to 5 3/4	-1/2 to +1 1/4	1/32	
	4 1/4 to 4 1/2	4 to 5 1/4	0 to +1 3/4	1/32	
	4 1/2 to 4 3/4	3 1/4 to 4 1/2	+1/2 to +2 1/4	1/32	
	4 3/4 to 5	2 1/2 to 4	+1 to +2 3/4	1/32	
	5 to 5 1/4	2 to 3 1/4	+1 1/2 to +3 1/4	1/32	
	5 1/4 to 5 1/2	1 1/2 to 2 3/4	+2 to +3 3/4	1/32	
	E250 & 350	3 1/4 to 3 1/2	9 to 10 1/2	-1 3/4 to -1/4	1/32
3 1/2 to 3 3/4		8 1/2 to 9 3/4	-1 1/2 to +1/4	1/32	
3 3/4 to 4		7 7/8 to 9	-1 to +3/4	1/32	
4 to 4 1/4		7 1/8 to 8 1/2	-1/2 to +1 1/4	1/32	
4 1/4 to 4 1/2		6 1/2 to 7 3/4	0 to +1 3/4	1/32	
4 1/2 to 4 3/4		5 3/4 to 7	+1/2 to +2 1/4	1/32	
4 3/4 to 5		5 1/4 to 6 1/2	+1 to +2 3/4	1/32	
5 to 5 1/4		4 5/8 to 6	+1 1/2 to +3 1/4	1/32	
F100, 150(All Models) & F250②		2 3/4 to 3	8 3/8 to 9 5/8	-2 to -1/4	3/32
		3 to 3 1/4	7 3/4 to 9	-1 1/2 to 1/8	3/32
	3 1/4 to 3 1/2	7 to 8 3/8	1/8 to +1/2	3/32	
	3 1/2 to 3 3/4	6 1/4 to 7 5/8	-3/4 to +1	3/32	
	3 3/4 to 4	5 7/8 to 7 1/8	3/8 to 9	3/32	
	4 to 4 1/4	5 1/8 to 6 1/2	0 to +1 5/8	3/32	
	4 1/4 to 4 1/2	4 1/2 to 5 7/8	+3/8 to +2	3/32	
	4 1/2 to 4 3/4	3 3/4 to 5 1/4	+3/4 to +2 3/8	3/32	
	4 3/4 to 5	3 1/4 to 4 5/8	1 1/4 to +2 3/4	3/32	
	5 to 5 1/4	2 1/2 to 4	1 7/8 to +3 1/8	3/32	
F250③	2 3/4 to 3	7 3/4 to 9	-1 7/8 to -1/4	3/32	
	3 to 3 1/4	7 to 8 3/8	-1 1/2 to +1/8	3/32	
	3 1/4 to 3 1/2	6 3/8 to 7 7/8	-1 1/8 to +1/2	3/32	
	3 1/2 to 3 3/4	5 7/8 to 7 1/8	-3/4 to +7/8	3/32	
	3 3/4 to 4	5 1/8 to 6 1/2	-3/8 to +1 1/4	3/32	
	4 to 4 1/4	4 1/2 to 5 7/8	0 to +1 5/8	3/32	
	4 1/4 to 4 1/2	3 7/8 to 5 1/4	3/8 to +2	3/32	
	4 1/2 to 4 3/4	3 1/4 to 4 5/8	7/8 to 2 1/2	3/32	
	4 3/4 to 5	2 5/8 to 4	1 1/4 to 2 3/4	3/32	
	5 to 5 1/4	2 to 3 3/8	1 5/8 to 3 1/8	3/32	
350 (All)	2 3/4 to 3	9 5/8 to 11	-2 1/8 to -5/8	3/32	
	3 to 3 1/4	8 7/8 to 10 3/8	-1 3/4 to -1/4	3/32	
	3 1/4 to 3 1/2	8 3/8 to 9 3/4	-1 3/8 to +1/8	3/32	
F150 & Bronco (4x4)	+6 1/2 to +9 1/2	+1 to 3	3/32	
F250 & 350 (4x4)	+2 1/2 to +5 1/2	0 to +3	3/32	

- ① - Clearance between top of axle and frame.
- ② - 6200-6800 G.V.W.
- ③ - 6300-7900 G.V.W.