

## ENGINE COOLANT CAPACITIES (Cont.)

### GENERAL MOTORS (Cont.)

#### CHEVROLET (Cont.)

#### THERMOSTAT

Thermostats should be checked to ensure that they are fully open 25°F above specified thermostat value or value stamped on thermostat. Thermostat applications are as follows:

Application	Thermostat (°F)
Chevette,Vega,Monza .....	180
350" Hi Performance .....	190
All Others .....	195

#### PRESSURE VALVE

All models use a 15 lb. pressure cap. Test at 14-16 lbs.

#### WATER PUMP

Water pumps are serviced as an assembly only.

#### MAINTENANCE

Inspect cooling system every 12 months or 15,000 miles. Drain and flush cooling system every 24 months or 30,000 miles.

### OLDSMOBILE

#### CAPACITY (Qts.)

Application	Standard	With A/C
Starfire		
140" 4 Cyl. ....	8.0	9.2
231" V6 .....	11.7	12.2
305" V8 .....	16.2	16.2
Omega		
231" V6 .....	12.2	12.2
260" V8 .....	16.7	17.2
305" V8 .....	16.0	①16.0
350"L V8 .....	16.0	16.7
350"R V8 .....	15.7	15.7
Cutlass		
231" V6 .....	12.7	12.7
260" V8 .....	17.0	①17.0
350"R V8 .....	15.0	①15.5
403" V8 .....	16.2	②16.5
88		
231" V6 .....	12.2	12.2
260" V8 .....	16.5	②16.5
350"L&G V8 .....	15.7	①15.7
88 & 98		
350"R V8 .....	14.5	①14.5
403" V8 .....	15.7	①15.7
Toronado		
403" V8 .....	17.5	17.5

- ① — With A/C add 1 Qt.
- ② — With Hvy. Duty Cooling or Trailer Tow Pkg. add .5 Qts.

#### THERMOSTAT

Application	Opens	Fully Opens
140" .....	180°F	212°F
231" .....	①195°F	222°F
All Others .....	195°F	222°F

① — Calif. models open at 180°F.

#### PRESSURE VALVE

All models use a 15 lb. radiator pressure cap. Test at 14-17 lbs. pressure.

#### WATER PUMP

Water pump on all models is serviced as an assembly only. Install pump assembly on front cover using new gasket and suitable sealer.

#### MAINTENANCE

Inspect cooling system every 12 months or 15,000 miles. Drain and flush cooling system every 24 months or 30,000 miles.