

Oil Pan Removal

JEEP

6 CYLINDER ENGINES

TIGHTENING SPECIFICATIONS

Oil Pan Attaching Bolts	Ft. Lbs.
4 Cyl. L4 & F4 Engines	
1965-71 All Models.....	9-14
6 Cyl. Engines	
1965-71 All Models	
1/4-20 Bolts.....	7-8
5/16-18 Bolts.....	10-12
1972-74 All Models	
1/4-20 Bolts.....	7
5/16-18 Bolts.....	11
V6 Engines	
1965-71 All Models.....	10-16
V8 Engines	
1965-71 All Models	
304" & 327".....	8-11
350" & 360".....	14
1972-74 All Models	
1/4-20 Bolts.....	7
5/16-18 Bolts.....	11

NOTE — Torque specifications for components other than oil pan attaching bolts may be found in Engine Removal Section.

NOTE — Oil pan removal procedure with engine installed in vehicle is unavailable for 1965-71 models.

1972-74

Drain crankcase and remove starter. On CJ, DJ and Comman-do models, position suitable jack under transmission housing, disconnect right support cushion bracket from block and raise engine to gain clearance for oil pan removal. Remove oil pan attaching bolts. Remove oil pan, seals and side gaskets.

V8 ENGINES

NOTE — Oil pan removal procedure with engine installed in vehicle is unavailable for 1965-71 models.

1972-74

Drain crankcase and remove starter. Remove oil pan attaching bolts. Remove oil pan, seals and side gaskets.