

1966 Distributor Specifications

CHRYSLER DISTRIBUTOR ADVANCE SPECIFICATIONS

NOTE - FOR ENGINE RPM AND DEGREES, MULTIPLY SPECIFICATIONS BELOW BY 2.

Distributor Part No.	Rot. Ⓢ	Automatic Advance (Distr. Degrees & RPM)						Vacuum Advance (Distr. Degrees & Inches of Hg.)							
		Deg.	RPM	Deg.	RPM	Deg.	RPM	Deg.	In. Hg.	Deg.	In. Hg.	Deg.	In. Hg.		
2444255	C	0	375-525	0-25	525	8-10	1010	12.5-14.5	2200	0	5-7.1	4.7	9.2	8.5-11.5	12
2444256	C	0	325-475	0-7	475	6-8	600	12.5-14.5	2200	0	5.7-1	3-6	8.5	6-8.5	10
2444258	C	0	320-480	0-2	480	4.5-6.5	850	10.5-12.5	2300	0	8-10	5-8	13	9-12	16
2444259	C	0	330-570	0-2	570	2-4	800	8-10	2300	0	8-10	5-8	13	9-12	16
2444648	C	0	325-475	0-25	475	7.5-9.5	960	10.5-12.5	2200	0	4.9-7.1	3-5	10.5	5.12-7.5	13
2444907	C	0	325-475	0-2.5	475	7.5-9.5	960	10.5-12.5	2200	0	6.9-9.1	3-5	12.5	5.25-7.5	15
2642234	C	0	300-450	0-2.5	450	7.5-9.5	870	10.5-12.5	1750	0	5-8	5-8	10	10.5-13.5	13.5
2642238	C	0	325-475	0-2	475	5-7	830	8-10	1750	0	5-8	5-8	10	10.5-13.5	13.5
2642242	C	0	325-475	0-3	475	5-7	725	8-10	1800	0	5-8	5-8	10	8.5-11.5	12
2642244	C	0	250-450	0-2	450	2.5-4.5	700	10.5-12.5	2150	0	4.5-8	4-7	10.5	8-11	13.6
2642248	CC	0	310-490	0-2	490	3-5	750	7-9	2400	0	6-9	4.5-7.5	12	8.25-11	15
2642252	CC	0	310-490	0-2	490	3-5	750	7-9	2400	0	6-9	4.5-7.5	12	8.25-11	15
2642289	CC	0	350-500	0-8.5	500	9.4-11.4	665	18-20	2200	0	4.5-8	6-9	12	11.5-14.5	16.5
2642329	C	0	325-475	0-7.5	475	9.25-11.25	660	15.5-17.5	2200	0	5-7.1	3-6	8.5	6-8.5	10
2642343	C	0	325-475	0-4	475	8.75-10.75	800	15.5-17.5	2350	0	8-10	5-8	13	9-12	16
2642346	C	0	350-500	0-7	500	11.25-13.25	735	15.5-17.5	1900	0	7-9	6-9	12	10.5-13.5	15
2642349	C	0	350-500	0-4	500	10.3-12.3	875	18-20	2500	0	5-7.1	4-7	9.2	8.5-11.5	12
2642352	C	0	325-475	0-5.5	475	10-12	750	18-20	2500	0	5-7.1	3-6	8.5	6-8.5	10
2642354	C	0	350-500	0-4.2	500	9.7-11.7	850	15.5-17.5	2200	0	4.9-7.1	3-5.2	10.5	5.25-7.5	13
2642356	C	0	350-500	0-8	500	10.4-12.4	690	15.5-17.5	1500	0	5-8	5-8	10	10.5-13.5	13.5
2642358	C	0	350-500	0-6.5	500	12-14	780	15.5-17.5	2000	0	5-8	5-8	10	8.5-11.5	12
2642360	C	0	325-475	0-6.5	475	7.75-9.75	660	15.5-17.5	2350	0	8-10	5-8	13	9-12	16
2642363	CC	0	475-625	0-4.5	625	8.2-10.1	900	12.5-14.5	2250	0	4.5-8	6-9	12	11.5-14.5	16.5
2642365	CC	0	350-500	0-3.6	500	8.1-10.1	830	12.5-14.5	2250	0	8-10	6.6-9.5	14	11.5-14.5	17.2
2642367	CC	0	350-500	0-7	500	10.7-12.7	730	15.5-17.5	2400	0	4.5-8	6-9	12	11.5-14.5	16.5
2642369	CC	0	350-500	0-7	500	10.7-12.7	730	15.5-17.5	2400	0	4.5-8	6-9	12	11.5-14.5	16.5
2642373	CC	0	350-500	0-8.5	500	9.4-11.4	665	18-20	2200	0	4.5-6.9	5-8	10	11.5-14.5	14.5
2642482	CC	0	425-575	0-3.5	575	3.7-5.7	740	7.5-9.5	1400	0	6-9	4.5-7.5	12	8.5-11	15
2642531	CC	0	400-550	0-4.5	550	7.5-9.5	800	15.5-17.5	2200	0	4.5-8	6-9	12	11.5-14.5	16.5
2642532	CC	0	350-500	0-5.5	500	5.6-7.6	650	10.5-12.5	2250	0	8-10	6.6-9.5	14	11.5-14.5	17.5
2642551	CC	0	1125-1275	0-1.75	1275	6.5	1700	8.5	1840	0	6-9	4.5-7.5	12	8.25-11	15

Ⓢ - C - Clockwise; CC - Counterclockwise (viewed from rotor end).

1966 Distributor Specifications

FORD MOTOR CO. DUAL ADVANCE DISTRIBUTOR ADVANCE SPECIFICATIONS

NOTE - FOR ENGINE RPM AND DEGREES. MULTIPLY SPECIFICATIONS BELOW BY 2.

Part No. ①	Rot. ②	Automatic Advance (Distr. Degrees & RPM)						Vacuum Advance (Distr. Degrees & In. of Hg.)									
		Deg.	RPM	Deg.	RPM	Deg.	RPM	Deg.	In.Hg.	Deg.	In.Hg.	Deg.	In.Hg.				
C5AF-AE		1 1/2-2 1/4	600	7 1/2-8 1/2	1200	9 1/4-10 3/4	1600	11 1/2-13	2000	0	.34	1-2	.90	4 1/2-5 1/2	2.1	8 1/4-10	4.8
C5AF-AK		0-1	300	3 1/4-4 1/4	700	5 1/2-6 3/4	1200	7 1/2-9	1800	3-6	7	6-9	9	9 1/2-12 1/2	14	9 1/2-12 1/2	20
C5AF-BG	CC	2 1/4-4	650	4-5 1/2	750	7 1/4-8 1/2	1000	9 1/4-11	1600	3 3/4-7	10	7-10	15	7 1/2-10 1/2	20		
C5AF-F ③	CC	1-2	500	3 1/4-4 1/4	600	5 3/4-6 3/4	800	7 3/4-9	1200								
C5AF-G	CC	1 1/2-2 1/2	450	5 1/4-6 1/4	600	7 1/4-8 1/4	800	8 3/4-10	1400	1 1/2-3 1/2	9	2 1/2-5 1/2	12	4 1/2-7 1/2	14		
C5AF-N	CC	1 1/2-2 1/2	650	4 1/4-5 3/4	800	8 1/2-9 1/2	1200	10 1/4-11 3/4	1600	1 1/2-4 1/4	8	5-8	10	8 1/4-11	14		
C5AF-M	CC									1 1/2-4 1/2	8	3 1/2-6 1/2	10	6 3/4-9 1/4	14		
C5DF-D	CC	1 1/2-2 1/4	550	5-6	700	6 3/4-7 3/4	1000	7 1/2-8 1/4	1400	1 1/4-2 1/4	8	3 3/4-4 3/4	1.8	5 1/2-6 1/4	3.0	6 3/4-8	3.9
C5GF-A	CC	2 1/4-3 3/4	650	4-5 1/2	750	6 1/2-7 1/2	1000	7 1/2-8 1/4	1600	1 1/2-4 1/2	8	3 1/2-6 3/4	10	6 1/4-9 1/4	14	8-11	20
C5OF-E ③	CC	1 1/4-2 1/4	600	3 1/4-4 1/4	700	5 1/2-6 3/4	1000	7 1/2-8 1/2	1600								
C6AF-AA	CC	1/4-1 1/4	500	4 1/2-5 3/4	1000	6-7 1/4	1000	9-10 1/2	1550	3-6	7	6-9	9	9 1/2-12 1/2	14	9 1/2-12 1/2	20
C6AF-AB	C	0-1/2	400	2-3	600	5 1/2-6 1/2	1000	7 1/4-8 1/2	1600	3-5 1/4	8	6 1/2-9 1/2	10	8-11	15	8-11	20
C6AF-AC	C	0-1/2	300	2 1/4-3 1/4	500	5 3/4-6 3/4	1000	7 1/2-9	1500	0-1	5	6-9	10	8-11	15		
C6AF-AD	CC	2-3	500	1 1/2-2 1/2	700	3 1/4-4 1/4	1000	5 1/2-6 1/2	1500	0-1	4	4 1/4-7 1/4	10	8 1/2-11 1/2	15	9-12	18
C6AF-AG	CC	0-1/2	300	1 1/2-2 1/2	500	4 3/4-5 3/4	1000	6 3/4-8	1500							6 1/2-10 1/2	18
C6AF-AH	CC	0-1/2	300	1 1/2-2 1/2	500	8-9	1000	10 1/4-11 1/2	1500	0-1	5	6-9	12	7-10	15	9 1/2-12 1/2	20
C6AF-AJ	CC	0-1/2	300	1 1/2-2 1/2	500	8 1/2-9 1/2	1000	10 1/2-11 3/4	1500	0-1	5	5 1/4-8	10	9 1/2-12 1/2	15		
C6AF-AK	CC	0-1/2	400	2 1/2-3 1/2	800	4 1/2-5 1/2	1200	7 1/4-8 1/4	1800	0-1	5	3 1/2-6 1/2	10	8 1/2-11 1/2	18		
C6AF-A	CC	1 1/4-2 3/4	625	5 3/4-7	1200	7-8 1/4	1500	9-10 1/2	2000	0-1	5	2-5 1/2	9	6-9	13		
C6AF-B	CC	2 1/4-3 1/4	600	5 3/4-7	1200	7 1/4-8 1/2	1600	8 3/4-10 1/4	2000	0-1	5	6-9	13	8 1/2-10 1/4	17		
C6AF-C	CC	2 1/4-3	500	5 3/4-7	1200	8-9 1/2	1850	8 1/2-10	2000	0-1	6	1-4 1/2	10	9-12	18		
C6AF-D	CC	1 1/2-2 1/2	500	5-6 1/4	1100	6 3/4-8	1500	8 3/4-10 1/4	2000	0-1	6	3-6	11	7-10	15		
C6AF-E	CC	6-7	600	11-12	1000	13 1/2-15	1800			0-1	7	2-5	13	5-8	16		
C6AF-J	CC	2-3	500	6 1/2-7 1/4	1000	7 3/4-9	1300	11 1/2-13	2000	0-1	5	6-9	13	8 1/4-11 1/4	17		
C6AF-K	CC	2-3	500	6 1/4-7	900	8 3/4-10	1400	10 1/4-12 1/4	2000	0-1	6	3-6	11	7-10	15		
C6AF-L	CC	2-3	600	6 1/4-7 1/4	800	11 1/4-12 1/4	1200	13-14 1/2	1800	0-1	5	2-5	7	7-10	12		
C6AF-S	CC	1 1/4-2 1/4	475	3 3/4-4 3/4	700	7-8 1/4	1300	9 1/4-11	1800	0-1	5	6-9	13	8 1/2-11 1/2	18		
C6AF-T	C	0-1/2	500	6 1/4-7 1/4	900	9 1/2-10 1/2	1200	12 1/2-13 3/4	1800	0-1	5	3 1/4-6 1/4	10	7-10 1/4	15		
C6DF-A	C	0-1/2	300	2 1/4-3 1/4	600	6 1/4-7 1/4	900	9-10	1200	0-1	4	7-10	10	9 1/2-12 1/2	15		
C6DF-C	C	0-1/2	300	2 1/2-3 1/2	600	7 3/4-8 3/4	900	9 1/4-10 1/2	1200	0-1	5	3-6	10	3-6	15		
C6DF-D	C	0-1/2	300	2-3	500	6 1/2-7 3/4	900	8 1/4-9 1/2	1200	0-1	5	3 1/2-6 1/4	10	7-10 1/4	15		
C6DF-E	C	0-1/2	300	2 1/2-3 1/2	600	8 1/4-9 1/4	1000	10 1/4-12 1/4	1500	0-1	4	4 1/2-7 1/2	8	7-10	10	9 1/2-12 1/2	15

③ - Centrifugal Distributor.

① - Stamped on housing or on attaching plate. Basic Ford Part No. is "12127"

② - C-Clockwise; CC - Counterclockwise (viewed from rotor end).

1966 Distributor Specifications

FORD MOTOR CO. DUAL ADVANCE DISTRIBUTOR ADVANCE SPECIFICATIONS (Continued)

NOTE - FOR ENGINE RPM AND DEGREES, MULTIPLY SPECIFICATIONS BELOW BY 2.

Part No. ①	Rot. ②	Automatic Advance (Distr. Degrees & RPM)						Vacuum Advance (Distr. Degrees & In. of Hg.)											
		Deg.	RPM	Deg.	RPM	Deg.	RPM	Deg.	In. Hg.	Deg.	In. Hg.	Deg.	In. Hg.						
C6MF-A	CC	2½-3½	500	5-6¼	1000	6¾-8¼	1500	8½-10	2000	0-1	5	2¼-5¾	10	7-10	15	8-11	18
C6OF-J	CC	0-½	300	3-4	500	5¾-6¾	800	7½-8¾	1200	10¾-12¼	2000	0-¾	5	1-4½	10	7-10	15	9½-12½	20
C6SF-B	CC	1½-2½	500	5-6¼	1100	6¾-8	1500	8¾-10¼	2000	0-1	6	3-6	11	7-10	15
C6SF-D	CC	2-3	500	6¼-7	900	8¾-10	1400	10¼-12¼	2000	0-1	6	3-6	11	7-10	15
C6VF-A	CC	2-3	450	4¼-6	1175	5¾-7¼	1750	6¼-7¾	2000	0-1	6	3-6	11	7-10	15
C6VF-B	CC	2-3	450	4¼-6	1175	5¾-7¼	1750	6¼-7¾	2000	0-1	6	3-6	11	7-10	15
C6ZF-A	CC	2½-3½	475	7-8	625	10¼-11½	1200	11-12¼	1850	0-1	5	5-8	10	6½-9½	15
C6ZF-B	CC	3-4	650	9-10	900	10½-11½	1200	11½-13	2000	0-1	5	2-5	9	4½-7½	14

① - Part No. prefix and suffix stamped on housing. Basic Ford Part No. (omitted) is "12127". ② - C (Clockwise), CC (Counterclockwise) viewed from rotor end.

FORD MOTOR CO. LOADOMATIC DISTRIBUTOR ADVANCE SPECIFICATIONS

NOTE - FOR ENGINE RPM AND DEGREES, MULTIPLY SPECIFICATIONS BELOW BY 2.

Distributor Part No. ①	Rot. ②	Distributor Advance Specifications						Max. Adv.						
		Deg.	Vac.	RPM	Deg.	Vac.	RPM							
C5DF-C	C	2½-3½	0.8	800	6½-7½	1.8	1200	8¾-10	3.0	1800	10¼-11½	3.9	2000	14½°
C5DF-E	C	1-2	0.44	600	5-6	1.8	800	8¾-9¼	1.9	1200	10¼-11½	3.8	2000	15½°
C5DF-K	C	¾-1¾	.79	800	3¾-4¾	1.9	1200	5¾-7	3.0	1600	7-8¼	3.8	2000	12¾°
C6TF-AC	C	4½-5½	1.2	800	7½-8¾	2.1	1200	9¼-10½	3.7	1600	10¼-11¾	4.9	2000	14°
C6AF-Y	C	1-2	.90	800	4½-5½	2.1	1200	7-8¼	3.6	1600	8¾-10	4.8	2000	12¾°

① - Stamped on housing or on attached plate. Basic Ford Part No. is "12127".

② - C - Clockwise; CC - Counterclockwise (viewed from rotor end).

1966 Distributor Specifications

DELCO-REMY DISTRIBUTOR ADVANCE SPECIFICATIONS

NOTE - FOR ENGINE RPM AND DEGREES, MULTIPLY SPECIFICATIONS BELOW BY 2.

Distributor Part No.	Rot. Ⓞ	Automatic Advance (Distr. Degrees & RPM)		RPM	Deg.	RPM	Deg.	RPM	Deg.	Vacuum Advance (Distr. Deg. & In. of Hg.)		Vacuum Unit Part No.			
		Deg.	RPM							Start Deg.	In. Hg.		Max. Deg.	In. Hg.	
1110280	C	0-2	450	600	4-6	600	6.5-8.5	750	14-16	1500	0	5-7	11.5	11-13.5	1116198
1110292	C	.5-2.5	400	750	6-8	750	9.5-11.5	1300	13-15	1850	0	5-7	11.5	11-13.5	1116198
1110310	C	0-2	450	7-9	1350	13-15	2100	0	5-7	12	12.75-14.75	1116229
1110311	C	0-2	975	1600	5-7	1600	9-11	2100	0	6-8	12	14-16	1116230
1110319	C	0-2	500	600	1-3	600	5-7	1500	9-11	2400	0	6-8	12	14-16	1116230
1110323	C	.5-2.5	400	750	6-8	750	9.5-11.5	1300	13-15	1850	0	5-7	11.5	11-13.5	1116198
1110324	C	0-2	375	700	5-7	700	12-14	1150	0	5-7	11.5	11-13.5	1116198
1110329	C	0	2000	9	2300	0	Ⓞ2	12Ⓞ	Ⓞ4.5	1116245
1110330	C	0	400	9	1400	0	6	11	14	1116248
1110339	C	0	800	1200	4	1200	18	3200	0	7	12	15	1116230
1110340	C	0-2	475	950	7-9	950	12-14	2200	0	5-7	11	16-17	1116207
1110341	C	0-2	475	1050	8-10	1050	10-12	2400	0	4-6	10	11.25-12.25	1115353
1110342	C	0	700-950	1800	7-9	1800	12-14	4200	0	6-8	7-9	16	1116210
1110343	C	0-3.5	500	1050	13-15	1050	15-17	2400	0	4-6	10	11.25-12.25	1115353
1110344	C	.5-3.5	500	1040	7.5-9.5	1040	9-12	3000	0	4-6	10	11-12.75	1115354
1110351	C	0	450	800	7.5	800	11.5	1150	14	1400	0	6	10	14.5	1116235
1110360	C	0	450	600	4.5	600	13	1150	0	6	10	14.5	1116235
1110362	C	0	450	650	5.5	650	7.5	750	15	1600	0	6	10	14.5	1116235
1110366	C	0-3.75	400	500	3.25-5	500	9.5-11.5	950	14.5-16.5	2200	0	5-7	11	16-17	1116207
1110368	C	0-4.2	500	660	7-11.5	660	10.2-12.2	740	23-25	2200	0	5-7	12	13.5-14.3	1116229
1110369	C	0-2.6	500	690	5-7.8	690	6.2-8.2	730	19-21	2200	0	6-8	12	14.5-15.5	1116230
1110370	C	0-3	500	680	5-7.8	680	6-8	710	17-19	2500	0	6-8	12	14.5-15.5	1116230
1110371	C	0-4	500	675	7-11	675	9.4-11.4	740	15-17	1500	0	5-7	11	13.8-14	1116248
1110372	C	0-3.6	500	670	6.4-9.8	670	8-10	710	19-21	2500	0	6-8	12	14.5-15.5	1116230
1110373	C	0-4.5	500	575	3.5-7.8	575	7-9	650	14-16	1125	0	5-7	10	14.2-14.5	1116235
1110376	C	0	700-950	1800	7-9	1800	12-14	4200	0	6-8	7-9	16	1116210
1110378	C	0-2	475	1050	8-10	1050	10-12	2400	0	4-6	10	11.25-12.25	1115353
1110379	C	0-3.5	500	1050	13-15	1050	15-17	2400	0	4-6	10	11.25-12.25	1115353
1110380	C	.5-3.5	500	1040	7.5-9.5	1040	9-12	3000	0	4-6	10	11-12.75	1115354
1111015	C	0-2	450	600	2.5-4.5	600	9-11	1200	14-16	2000	0	7-9	8	15-16	1116201
1111025	CC	0-2	350	775	7.5-9.5	775	12-14	1300	17-19	1900	0	5-7	10	14.25-15.75	1116212
1111029	CC	0-2	400	1025	7.7-9.7	1025	14-16	2000	0	7-9	9.5	15-16.6	1116232
1111042	CC	0-2	400	900	6-8	900	10-12	2000	0	6-8	9	15.5-19.5	1116232
1111047	CC	0-2	400	1000	7-9	1000	10-12	2200	9.2-12Ⓞ	3000	0	8-10	0	14.75-16.75	1116172
1111048	CC	0-2	400	1000	7.5-9.5	1000	12-14	2100	0	7-9	15.5	16.5-19.25	1116226
1111054	CC	.5-2.5	450	1000	7-9	1000	8-10	1450	10-12	2300	0	8-10	10	14.75-16.75	1116172
1111055	C	0	300-400	700	6.5-8.5	700	14-16	1900	0	3-4	7-9	8	1116210
1111074	C	0-2	550	900	6.5-8.5	900	13-15	2300	12-15	3000	0	6	7-8	12	1115355
1111077	CC	0-2	400	950	8.5-10.5	950	13-15	2300	0	6-8	10	13-14.5	1115037
1111078	CC	0-2	480	6-8	1000	10-12	2300	0	6-8	10.5	13-15	1116173
1111079	CC	0-2	400	950	6-8	950	11-13	2300	0	8-10	10	14.75-16.75	1116172
1111080	CC	0-2	480	1000	6-8	1000	10-12	2300	9-12Ⓞ	3000	0	8-10	10	14.75-16.75	1116172

See Page 9-6 for footnotes.

1966 Distributor Specifications

DELCO-REMY DISTRIBUTOR ADVANCE SPECIFICATIONS (Continued)

NOTE - FOR ENGINE RPM AND DEGREES MULTIPLY SPECIFICATIONS BELOW BY 2.

Distributor Part No.	Rot. Ⓞ	Automatic Advance (Distr. Degrees & RPM)		RPM	Deg.	RPM		Deg.	RPM		Deg.	Vacuum Advance (Distr. Deg. & In. of Hg.)		Vacuum Unit Part No.
		Deg.	RPM			Deg.	RPM		Start Deg.	In. Hg.		Max. Deg.	In. Hg.	
1111081	CC	0-2	400	9-11	1000	10.2-13	3000	0	8-10	10	14.75-16.75	1116172	
1111087	C	.5-2.5	450	6.5-8.5	750	12-14	2050	0	3-5	8.2	5.7-8.2	1116236	
1111088	C	0-2	425	7-9	800	13-15	2300	3000	0	3-5	8.2	5.7-8.2	1116236	
1111089	CC	0-2	400	2000	0	6-8	9	15.5-19.5	1116232	
1111090	CC	0-2	480	6-8	1000	10-12	2300	0	6-8	10	13-14.5	1116242	
1111093	C	0-2	550	6.5-8.5	900	13-15	2300	3000	0	6	7-8	12	1115355	
1111100	C	0-2	500	7-9	950	13-15	2200	0	7-9	8	15-16	1116201	
1111102	CC	0-6.8	500	13.5-15.5	950	18-20	2300	0	6-8	10	13-14.5	1116242	
1111103	CC	0-5	500	11-13	1000	15-17	2300	0	8-10	10	15-17	1116243	
1111107	C	.5-2.5	450	6.5-8.5	750	12-14	2050	0	7-9	8	15-16	1116201	
1111108	C	0-2	425	6.5-8.5	750	14-16	2550	0	3-5	8.2	5.7-8.2	1116236	
1111109	C	0	450	7	650	9.5	800	2500	0	8	10	17	1115357	
1111112	C	0	450	7	650	9.5	800	2500	0	6	7.5	12	1115355	
1111116	C	0-6.2	500	3.2-9.5	550	11.5-13.5	750	2050	0	7-9	8	15-16	1116201	
1111117	C	0-6.3	500	3.1-9.5	550	11.5-13.5	750	2550	0	5-7	8	11.2-12.7	1115355	
1111130	CC	0-2	350	4.25-6.5	450	9.75-11.75	750	1850	0	5-7	10	14.25-15.75	1116212	
1111131	C	0-1.5	400	7-9	2000	0	7.5-9.5	12	15	1116192	
1111134	C	0-2	425	6.5-8.5	750	14-16	2550	0	5-7	8	11.2-12.7	1115355	
1111137	C	0	450	7	650	9.5	800	2500	0	8	10	17	1115357	
1111138	C	0	450	7	650	9.5	800	2500	0	7	6	12	1115360	
1111139	C	0	450	7	650	9.5	800	2500	0	7	6	12	1115360	
1111140	C	0	450	7	650	9.5	800	2500	0	6	7.5	12	1115355	
1111141	C	0	450	7	600	9.5	800	2500	0	6	7.5	12	1115355	
1111142	C	0	450	7	600	9.5	800	2500	0	6	7.5	12	1115355	
1111144	C	0	275-425	5-7	850	13-15	2300	0	6-8	7-9	16	1116210	
1111147	C	0	275-375	6-8	700	15-17	2300	0	6-8	7-9	16	1116210	
1111150	C	0	450	3.5	600	8	1000	2200	0	8	7.5	15.5	1116201	
1111151	CC	0-2	600	3.5-5.5	900	8-10	2100	0	8-10	9	16.5-18.5	1115361	
1111152	C	0	450	7.5	750	13	2050	0	8	7.5	15.5	1116201	
1111153	C	0	450	7.5	750	13	2050	0	6	7.5	12	1115355	
1111154	C	0	450	7.5	750	15	2550	0	6	7.5	12	1115355	
1111155	C	0	450	7.5	750	15	2550	0	6	7.5	12	1115355	
1111156	C	0	450	7.5	750	15	2550	0	4	8	8	1116236	
1111157	C	0	450	7.5	750	15	2550	0	4	8	8	1116236	
1111158	C	0	275-375	6-8	700	15-17	2300	0	6-8	7-9	16	1116210	
1111159	C	0	275-425	5-7	850	13-15	2300	0	6-8	7-9	16	1116210	

Ⓞ - C - Clockwise; CC - Counterclockwise (viewed from rotor end). Ⓞ - Decrease 0.5° for each 500 RPM increase above this maximum.

Ⓟ - PSI (Pounds per square inch). Ⓟ - Retard.