

1966 Distributor Specifications

FORD MOTOR CO. DUAL ADVANCE DISTRIBUTOR ADVANCE SPECIFICATIONS (Continued)

NOTE - FOR ENGINE RPM AND DEGREES, MULTIPLY SPECIFICATIONS BELOW BY 2.

Part No. ①	Rot. ②	Automatic Advance (Distr. Degrees & RPM)						Vacuum Advance (Distr. Degrees & In. of Hg.)											
		Deg.	RPM	Deg.	RPM	Deg.	RPM	Deg.	In. Hg.	Deg.	In. Hg.	Deg.	In. Hg.						
C6MF-A	CC	2½-3½	500	5-6¼	1000	6¾-8¼	1500	8½-10	2000	0-1	5	2¼-5¾	10	7-10	15	8-11	18
C6OF-J	CC	0-½	300	3-4	500	5¾-6¾	800	7½-8¾	1200	10¾-12¼	2000	0-¾	5	1-4½	10	7-10	15	9½-12½	20
C6SF-B	CC	1½-2½	500	5-6¼	1100	6¾-8	1500	8¾-10¼	2000	0-1	6	3-6	11	7-10	15
C6SF-D	CC	2-3	500	6¼-7	900	8¾-10	1400	10¼-12¼	2000	0-1	6	3-6	11	7-10	15
C6VF-A	CC	2-3	450	4¼-6	1175	5¾-7¼	1750	6¼-7¼	2000	0-1	6	3-6	11	7-10	15
C6VF-B	CC	2-3	450	4¼-6	1175	5¾-7¼	1750	6¼-7¼	2000	0-1	6	3-6	11	7-10	15
C6ZF-A	CC	2½-3½	475	7-8	625	10¼-11½	1200	11-12¼	1850	0-1	5	5-8	10	6½-9½	15
C6ZF-B	CC	3-4	650	9-10	900	10½-11½	1200	11½-13	2000	0-1	5	2-5	9	4½-7½	14

① - Part No. prefix and suffix stamped on housing. Basic Ford Part No. (omitted) is "12127". ② - C (Clockwise), CC (Counterclockwise) viewed from rotor end.

FORD MOTOR CO. LOADOMATIC DISTRIBUTOR ADVANCE SPECIFICATIONS

NOTE - FOR ENGINE RPM AND DEGREES, MULTIPLY SPECIFICATIONS BELOW BY 2.

Distributor Part No. ①	Rot. ②	Distributor Advance Specifications						Max. Adv.						
		Deg.	Vac.	RPM	Deg.	Vac.	RPM							
C5DF-C	C	2½-3½	0.8	800	6½-7½	1.8	1200	8¾-10	3.0	1800	10¼-11½	3.9	2000	14½°
C5DF-E	C	1-2	0.44	600	5-6	1.8	800	8¾-9¼	1.9	1200	10¼-11½	3.8	2000	15½°
C5DF-K	C	¾-1¾	.79	800	3¾-4¾	1.9	1200	5¾-7	3.0	1600	7-8¼	3.8	2000	12¾°
C6TF-AC	C	4½-5½	1.2	800	7½-8¾	2.1	1200	9¼-10½	3.7	1600	10¼-11¾	4.9	2000	14°
C6AF-Y	C	1-2	.90	800	4½-5½	2.1	1200	7-8¼	3.6	1600	8¾-10	4.8	2000	12¾°

① - Stamped on housing or on attached plate. Basic Ford Part No. is "12127".

② - C - Clockwise; CC - Counterclockwise (viewed from rotor end).