

# 1966 Distributor Specifications

## DELCO-REMY DISTRIBUTOR ADVANCE SPECIFICATIONS

NOTE - FOR ENGINE RPM AND DEGREES, MULTIPLY SPECIFICATIONS BELOW BY 2.

Distributor Part No.	Rot. Ⓞ	Automatic Advance (Distr. Degrees & RPM)		RPM	Deg.	RPM	Deg.	RPM	Deg.	Vacuum Advance (Distr. Deg. & In. of Hg.)		Vacuum Unit Part No.		
		Deg.	RPM							Start Deg.	In. Hg.		Max. Deg.	In. Hg.
1110280	C	0-2	450	600	4-6	600	6.5-8.5	750	14-16	0	5-7	11.5	11-13.5	1116198
1110292	C	.5-2.5	400	750	6-8	750	9.5-11.5	1300	13-15	0	5-7	11.5	11-13.5	1116198
1110310	C	0-2	450	1350	.....	.....	.....	.....	.....	0	5-7	12	12.75-14.75	1116229
1110311	C	0-2	975	1600	5-7	1600	.....	.....	9-11	0	6-8	12	14-16	1116230
1110319	C	0-2	500	600	1-3	600	5-7	1500	9-11	0	6-8	12	14-16	1116230
1110323	C	.5-2.5	400	750	6-8	750	9.5-11.5	1300	13-15	0	5-7	11.5	11-13.5	1116198
1110324	C	0-2	375	700	5-7	700	.....	.....	12-14	0	5-7	11.5	11-13.5	1116198
1110329	C	0	2000	.....	.....	.....	.....	.....	9	0	Ⓞ2	12Ⓞ	Ⓞ4.5	1116245
1110330	C	0	400	.....	.....	.....	.....	.....	9	0	6	11	14	1116248
1110339	C	0	800	1200	4	1200	.....	.....	18	0	7	12	15	1116230
1110340	C	0-2	475	950	7-9	950	.....	.....	12-14	0	5-7	11	16-17	1116207
1110341	C	0-2	475	1050	8-10	1050	.....	.....	10-12	0	4-6	10	11.25-12.25	1115353
1110342	C	0	700-950	1800	7-9	1800	.....	.....	12-14	0	6-8	7-9	16	1116210
1110343	C	0-3.5	500	1050	13-15	1050	.....	.....	15-17	0	4-6	10	11.25-12.25	1115353
1110344	C	.5-3.5	500	1040	7.5-9.5	1040	.....	.....	9-12	0	4-6	10	11-12.75	1115354
1110351	C	0	450	800	7.5	800	11.5	1150	14	0	6	10	14.5	1116235
1110360	C	0	450	600	4.5	600	.....	.....	13	0	6	10	14.5	1116235
1110362	C	0	450	650	5.5	650	7.5	750	15	0	6	10	14.5	1116235
1110366	C	0-3.75	400	500	3.25-5	500	9.5-11.5	950	14.5-16.5	0	5-7	11	16-17	1116207
1110368	C	0-4.2	500	660	7-11.5	660	10.2-12.2	740	23-25	0	5-7	12	13.5-14.3	1116229
1110369	C	0-2.6	500	690	5-7.8	690	6.2-8.2	730	19-21	0	6-8	12	14.5-15.5	1116230
1110370	C	0-3	500	680	5-7.8	680	6-8	710	17-19	0	6-8	12	14.5-15.5	1116230
1110371	C	0-4	500	675	7-11	675	9.4-11.4	740	15-17	0	5-7	11	13.8-14	1116248
1110372	C	0-3.6	500	670	6.4-9.8	670	8-10	710	19-21	0	6-8	12	14.5-15.5	1116230
1110373	C	0-4.5	500	575	3.5-7.8	575	7-9	650	14-16	0	5-7	10	14.2-14.5	1116235
1110376	C	0	700-950	1800	7-9	1800	.....	.....	12-14	0	6-8	7-9	16	1116210
1110378	C	0-2	475	1050	8-10	1050	.....	.....	10-12	0	4-6	10	11.25-12.25	1115353
1110379	C	0-3.5	500	1050	13-15	1050	.....	.....	15-17	0	4-6	10	11.25-12.25	1115353
1110380	C	.5-3.5	500	1040	7.5-9.5	1040	.....	.....	9-12	0	4-6	10	11-12.75	1115354
1111015	C	0-2	450	600	2.5-4.5	600	9-11	1200	14-16	0	7-9	8	15-16	1116201
1111025	CC	0-2	350	775	7.5-9.5	775	12-14	1300	17-19	0	5-7	10	14.25-15.75	1116212
1111029	CC	0-2	400	1025	7.7-9.7	1025	.....	.....	14-16	0	7-9	9.5	15-16.6	1116232
1111042	CC	0-2	400	900	6-8	900	.....	.....	10-12	0	6-8	9	15.5-19.5	1116232
1111047	CC	0-2	400	1000	7-9	1000	10-12	2200	9.2-12Ⓞ	0	8-10	0	14.75-16.75	1116172
1111048	CC	0-2	400	1000	7.5-9.5	1000	.....	.....	12-14	0	7-9	15.5	16.5-19.25	1116226
1111054	CC	.5-2.5	450	1000	7-9	1000	8-10	1450	10-12	0	8-10	10	14.75-16.75	1116172
1111055	C	0	300-400	700	6.5-8.5	700	.....	.....	14-16	0	3-4	7-9	8	1116210
1111074	C	0-2	550	900	6.5-8.5	900	13-15	2300	12-15	0	6	7-8	12	1115355
1111077	CC	0-2	400	950	8.5-10.5	950	.....	.....	13-15	0	6-8	10	13-14.5	1115037
1111078	CC	0-2	480	.....	.....	.....	6-8	1000	10-12	0	6-8	10.5	13-15	1116173
1111079	CC	0-2	400	950	6-8	950	.....	.....	11-13	0	8-10	10	14.75-16.75	1116172
1111080	CC	0-2	480	1000	6-8	1000	10-12	2300	9-12Ⓞ	0	8-10	10	14.75-16.75	1116172

See Page 9-6 for footnotes.

# 1966 Distributor Specifications

## DELCO-REMY DISTRIBUTOR ADVANCE SPECIFICATIONS (Continued)

NOTE - FOR ENGINE RPM AND DEGREES MULTIPLY SPECIFICATIONS BELOW BY 2.

Distributor Part No.	Rot. Ⓞ	Automatic Advance (Distr. Degrees & RPM)		RPM	Deg.	RPM		Deg.	RPM		Deg.	Vacuum Advance (Distr. Deg. & In. of Hg.)		Vacuum Unit Part No.
		Deg.	RPM			Deg.	RPM		Start Deg.	In. Hg.		Max. Deg.	In. Hg.	
1111081	CC	0-2	400	9-11	1000	.....	10.2-13	3000	0	8-10	10	14.75-16.75	1116172	
1111087	C	.5-2.5	450	6.5-8.5	750	.....	12-14	2050	0	3-5	8.2	5.7-8.2	1116236	
1111088	C	0-2	425	7-9	800	13-15	2300	3000	0	3-5	8.2	5.7-8.2	1116236	
1111089	CC	0-2	400	.....	.....	.....	.....	2000	0	6-8	9	15.5-19.5	1116232	
1111090	CC	0-2	480	6-8	1000	.....	10-12	2300	0	6-8	10	13-14.5	1116242	
1111093	C	0-2	550	6.5-8.5	900	13-15	2300	3000	0	6	7-8	12	1115355	
1111100	C	0-2	500	7-9	950	.....	13-15	2200	0	7-9	8	15-16	1116201	
1111102	CC	0-6.8	500	13.5-15.5	950	.....	18-20	2300	0	6-8	10	13-14.5	1116242	
1111103	CC	0-5	500	11-13	1000	.....	15-17	2300	0	8-10	10	15-17	1116243	
1111107	C	.5-2.5	450	6.5-8.5	750	.....	12-14	2050	0	7-9	8	15-16	1116201	
1111108	C	0-2	425	6.5-8.5	750	.....	14-16	2550	0	3-5	8.2	5.7-8.2	1116236	
1111109	C	0	450	7	650	9.5	800	2500	0	8	10	17	1115357	
1111112	C	0	450	7	650	9.5	800	2500	0	6	7.5	12	1115355	
1111116	C	0-6.2	500	3.2-9.5	550	11.5-13.5	750	2050	0	7-9	8	15-16	1116201	
1111117	C	0-6.3	500	3.1-9.5	550	11.5-13.5	750	2550	0	5-7	8	11.2-12.7	1115355	
1111130	CC	0-2	350	4.25-6.5	450	9.75-11.75	750	1850	0	5-7	10	14.25-15.75	1116212	
1111131	C	0-1.5	400	.....	.....	.....	.....	2000	0	7.5-9.5	12	15	1116192	
1111134	C	0-2	425	6.5-8.5	750	.....	14-16	2550	0	5-7	8	11.2-12.7	1115355	
1111137	C	0	450	7	650	9.5	800	2500	0	8	10	17	1115357	
1111138	C	0	450	7	650	9.5	800	2500	0	7	6	12	1115360	
1111139	C	0	450	7	650	9.5	800	2500	0	7	6	12	1115360	
1111140	C	0	450	7	650	9.5	800	2500	0	6	7.5	12	1115355	
1111141	C	0	450	7	600	9.5	800	2500	0	6	7.5	12	1115355	
1111142	C	0	450	7	600	9.5	800	2500	0	6	7.5	12	1115355	
1111144	C	0	275-425	5-7	850	.....	13-15	2300	0	6-8	7-9	16	1116210	
1111147	C	0	275-375	6-8	700	.....	15-17	2300	0	6-8	7-9	16	1116210	
1111150	C	0	450	3.5	600	8	1000	2200	0	8	7.5	15.5	1116201	
1111151	CC	0-2	600	3.5-5.5	900	.....	8-10	2100	0	8-10	9	16.5-18.5	1115361	
1111152	C	0	450	7.5	750	.....	13	2050	0	8	7.5	15.5	1116201	
1111153	C	0	450	7.5	750	.....	13	2050	0	6	7.5	12	1115355	
1111154	C	0	450	7.5	750	.....	15	2550	0	6	7.5	12	1115355	
1111155	C	0	450	7.5	750	.....	15	2550	0	6	7.5	12	1115355	
1111156	C	0	450	7.5	750	.....	15	2550	0	4	8	8	1116236	
1111157	C	0	450	7.5	750	.....	15	2550	0	4	8	8	1116236	
1111158	C	0	275-375	6-8	700	.....	15-17	2300	0	6-8	7-9	16	1116210	
1111159	C	0	275-425	5-7	850	.....	13-15	2300	0	6-8	7-9	16	1116210	

Ⓞ - C - Clockwise; CC - Counterclockwise (viewed from rotor end). Ⓞ - Decrease 0.5° for each 500 RPM increase above this maximum.

Ⓟ - PSI (Pounds per square inch). Ⓟ - Retard.