

# 1967 Distributor Specifications

## CHRYSLER DISTRIBUTOR ADVANCE SPECIFICATIONS

NOTE - FOR ENGINE RPM AND DEGREES, MULTIPLY SPECIFICATIONS BELOW BY 2.

Distributor Part No.	Rot. ①	Automatic Advance (Distr. Degrees & RPM)						Vacuum Advance (Distr. Degrees & Inches of Hg.)							
		Deg.	RPM	Deg.	RPM	Deg.	RPM	Deg.	In. Hg.	Deg.	In. Hg.	Deg.	In. Hg.		
2444104	C	0	375-525	0-2.5	525	8-10	1010	12.5-14.5	2200	0	4.5-7.5	4-7	8.9	7-10	10.5
2444118	C	0	325-475	0-4.5	475	6.75-8.75	700	12.5-14.5	2200	0	5-7.1	3-6	8.5	6-8.5	10.0
2444648	C	0	325-475	0-2.5	475	7.5-9.5	960	10.5-12.5	2200	0	4.9-7.1	3-5	10.5	5.25-7.5	13.0
2444759	C	0	325-475	0-2.5	475	7.5-9.5	960	10.5-12.5	2200	0	4.9-7.1	3-5	10.5	5.25-7.5	13.0
2444760	C	0	320-480	0-2	480	4.5-6.5	850	10.5-12.5	2300	0	8-10	5-8	13	9-12	16.0
2444761	C	0	330-570	0-2	570	2-4	800	8-10	2300	0	8-10	5-8	13	9-12	16.0
2444907	C	0	325-475	0-2.5	475	7.5-9.5	960	10.5-12.5	2200	0	6.9-9.1	3-5	12.5	5.25-7.5	15.0
2444908	C	0	325-475	0-2.5	475	7.5-9.5	960	10.5-12.5	2200	0	6.9-9.1	3-5	12.5	5.25-7.5	15.0
2642234	C	0	300-450	0-2.5	450	7.5-9.5	870	10.5-12.5	1750	0	5-8	5-8	10	10.5-13.5	13.5
2642238	C	0	325-475	0-2	475	5-7	830	8-10	1750	0	5-8	5-8	10	10.5-13.5	13.5
2642242	C	0	325-475	0-3	475	5-7	725	8-10	1800	0	5-8	5-8	10	8.5-11.5	12.0
2642248	CC	0	310-490	0-2	490	3-5	750	7-9	2400	0	6-9	4.5-7.5	12	8.25-11	15.0
2642358	C	0	350-500	0-6.5	500	12-14	780	15.5-17.5	2000	0	5-8	5-8	10	8.5-11.5	12.0
2642482	CC	0	425-575	0-3.5	575	3.75-5.75	740	7.5-9.5	1400	0	6-9	4.5-7.5	12	8.25-11	15.0
2642718	C	0	320-480	0-1	480	3-4.25	1000	10.5-12.5	2350	0	7-9	6-9	12	10.5-13.5	15.0
2642721	C	0	325-475	0-2	475	3.75-5.75	780	12.5-14.5	2250	0	7-9	6-9	12	10.5-13.5	15.0
2642724	C	0	325-475	0-5	475	7.75-9.75	600	18-20	2350	0	7.5-10.5	7-10	14	10.5-13.5	16.0
2642727	CC	0	250-450	0-2	450	2.5-4.5	700	10.5-12.5	2150	0	5-8	5-8	10	10.5-13.5	13.5
2642730	CC	0	310-490	0-2	490	3.5-5.5	800	8.5-10.5	2300	0	8-10	5-8	13	9-12	16.0
2642745	CC	0	425-575	0-4.5	575	6-8	790	10.5-12.5	2450	0	4.5-8	6-9	12	11.5-14.5	16.5
2642748	CC	0	325-475	0-4	475	4.5-6.5	640	8.5-10.5	2200	0	8-10	5-8	13	9-12	16.0
2642755	C	0	325-475	0-4.5	475	6.75-8.75	700	12.5-14.5	2200	0	5-7.1	3-6	8.5	6-8.5	10.0
2642758	C	0	375-525	0-2.5	525	8-10	1010	12.5-14.5	2200	0	4.5-7.5	4-7	8.9	7-10	10.5
2642786	C	0	350-500	0-3.7	500	12.2-14.2	990	17-19	2200	0	5-7.1	4-7	9.2	8.5-11.5	12.0
2642789	C	0	325-475	0-6	475	11.2-13.2	750	17-19	2200	0	5-7.1	3-9	8.5	6-8.5	10.0
2642792	C	0	350-500	0-3	500	9-11	925	12.5-14.5	2400	0	6.9-9.1	3-5	12.5	6.5-8.5	16.2
2642795	C	0	325-475	0-4.5	475	8-10	750	12.5-14.5	2400	0	5-7.1	3-6	8.5	6-8.5	10.0
2642805	C	0	350-500	0-7	500	11.25-13.25	735	15.5-17.5	1900	0	5-8	5-8	10	10.5-13.5	13.5
2642810	CC	0	400-550	0-4	550	5.5-7.5	750	14.5-16.5	2200	0	4.5-8	6-9	12	11.5-14.5	16.5
2642813	CC	0	350-500	0-5	500	8.2-10.2	750	14.5-16.5	2300	0	8-10	5-8	13	11.5-14.5	17.5
2642816	CC	0	425-575	0-3.5	575	6.2-8.2	840	12.5-14.5	2400	0	8-10	5-8	13	11.5-14.5	17.5
2642819	CC	0	325-475	0-7	475	10.5-12.5	700	14.5-16.5	2250	0	8-10	5-8	13	9-12	16.0
2642822	CC	0	325-475	0-5.5	475	8-10	700	12.5-14.5	2400	0	8-10	5-8	13	9-12	16.0
2642832	CC	0	450-600	0-7	600	9.8-11.8	810	14-16	1550	0	6-9	4.5-7.5	12	8.25-11	15.0
2642899	CC	0	325-475	0-4	475	4.5-6.5	640	8.5-10.5	2200	0	8-10	5-8	13	9-12	16
2642911	CC	0	325-475	0-7	475	10.5-12.5	700	14.5-16.5	2250	0	8-10	5-8	13	9-12	16
2642949	CC	0	375-525	0-6.5	525	7.8-9.8	710	14.5-16.5	2300	0	4.5-8	6-9	12	11.5-14.5	16.5

① - C (Clockwise) CC (Counterclockwise) viewed from rotor end.

② - POL. IBS-4013A.

③ - POL. IBS-4013B.

④ - POL. IBS-4006P.

⑤ - POL. IBS-4006W.

⑥ - POL. IGS-4006Z.

⑦ - POL. IGS-4006Y.

# 1967 Distributor Specifications

## FORD MOTOR CO. DUAL ADVANCE DISTRIBUTOR ADVANCE SPECIFICATIONS

NOTE - FOR ENGINE RPM AND DEGREES, MULTIPLY SPECIFICATIONS BELOW BY 2.

Distributor Part No. ①	Rot. ②	Automatic Advance (Distr. Degrees & RPM)										Vacuum Advance (Distr. Degrees)								
		Degs.	RPM	Degs.	RPM	Degs.	RPM	Degs.	RPM	Degs.	RPM	Max. Degs.	Deg. In. Hg.	Deg. In. Hg.	Deg. In. Hg.					
C5AF-F	CC	2 1/4-4	650	4-5 1/2	750	7 1/4-8 1/2	1000	9 1/4-11	1600	11 1/2-13	2000	16								
C50F-E	CC	2 1/4-3 1/4	650	4-5 1/2	750	6 1/2-7 1/2	1000	7 1/2-8 3/4	1600	8 3/4-9 3/4	2000	14								
C6AF-AA	C	1 1/4-2 1/4	600	6-7 1/4	1000	7 1/4-8 1/2	1200	9 1/4-10 3/4	1600	11 1/2-13	2000	14	3-6	7	6-9	9	9 1/2-12 1/2	14	9 1/2-12 1/2	20
C6AF-AB	C	1 1/4-2 1/4	500	4 1/2-5 1/4	1000	5 1/2-6 1/4	1200	7 1/4-8 1/2	1600	9-10 1/2	2000	11	3-5 1/4	8	6 1/2-9 1/2	10	8-11	15	8-11	20
C6AF-AC	C	0-1/2	400	2-3	600	6-7 1/4	1000	9-10 1/2	1550			16	0-1	5	6-9	10	8-11	15	9-12	20
C6AF-AD	C	0-1/2	300	2 1/4-3 1/4	500	5 1/4-6 1/4	1000	7 1/2-9	1500	9 1/2-11	2000	14	0-1	4	4 1/4-7 1/4	10	8 1/2-11 1/2	15	9-12	20
C6DF-A	C	0-1/2	500	6 1/4-7 1/4	900	7-8	1000	9 1/2-10 1/2	1200	12 1/2-13 3/4	1800	16	0-1	5	3 1/4-6 1/4	10	7-10 1/4	15	9-12	20
C6DF-D	C	2 1/2-3 1/2	600	7 3/4-8 3/4	900	8 1/2-9 1/2	1000	9 1/4-10 1/2	1200	12 1/2-13 3/4	1800	16	0-1	5	3-6	10	3-6	15	3-6	20
C7AF-AA	CC	0-1/2	300	2 1/4-3 1/4	600	6 1/4-7 1/2	1000	8 1/2-9 1/4	1500	10 1/2-12	2000	14	0-1	5	4 1/4-7	10	8 1/2-11 1/2	15	8 1/2-11 1/2	20
C7AF-AB ③	CC	0-1/2	300	1/4-1 1/4	600	4 1/2-5 1/2	1000	6 1/2-7 1/2	1500	8 3/4-9 3/4	2000	14	0-1	5	4-7	10	8 1/2-11 1/2	15	8 1/2-11 1/2	20
C7AF-AC	CC	0-1/2	300	1-2	500	6 1/4-7 1/4	1000	8 3/4-10	1500	10 3/4-12 1/4	2000	14	0-1	5	1-5	10	7-10	15	9 1/2-12 1/2	20
C7AF-AD	CC	0-1/2	300	1/4-1 1/4	500	3 1/2-4 1/2	1000	5 1/4-7 1/4	1500	8 3/4-9 3/4	2000	14	0-1	5	5-8	10	9 1/2-12 1/2	15	9 1/2-12 1/2	20
C7AF-AE	CC	0-1/2	300	3 1/4-4 1/2	500	8 3/4-9 1/4	1000	9 1/2-11	1500	10 1/2-12	2000	14	0-1	5	6-9 1/2	10	9 1/2-12 1/2	15	9 1/2-12 1/2	20
C7AF-AF	CC	0-1/2	300	1 1/2-2 1/2	500	4 1/2-5 1/4	1000	6 3/4-8	1500	8 3/4-10 1/4	2000	11	0-1	5	1-4 1/2	10	7-10	15	9 1/2-12 1/2	20
C7AF-AG	CC	0-1/2	300	1/2-1 1/2	550	5 1/4-6 1/4	850	7 1/2-8 3/4	1400	10-11 1/2	2000	14	0-1	5	1/2-3 1/2	6	5-8	9	9 1/2-12 1/2	15
C7AF-AH	CC	0-1/2	300	1/4-1 1/4	600	7 1/4-8 1/4	1000	9 1/2-10 3/4	1500	10 3/4-12 1/4	2000	14	0-1	5	1 1/2-4 1/2	10	6-9 1/4	15	7-10	20
C7AF-A	CC	0-1/2	300	1/4-1 1/4	500	3 1/2-4 1/2	1000	5 1/4-7 1/4	1500	8 3/4-9 3/4	2000	14	0-1	5	3 1/2-6 1/4	10	7 1/4-10 1/4	15	9-12	20
C7AF-B	CC	0-1/2	300	1 1/4-2 1/2	500	5-6	1000	7-8 1/4	1500	9-10 1/2	2000	14	0-1	5	3 1/2-6 1/2	10	7-10	15	9-12	20
C7AF-C	CC	0-1/2	300	2-3	500	6-7 1/4	1000	8 3/4-10 1/4	1500	11 1/2-13	2000	16	0-1	5	3 1/2-6 3/4	10	7 1/4-10 1/4	15	9-12	20
C7AF-D	CC	0-1/2	300	2-3	500	5 1/4-6 1/2	1000	8-9 1/2	1500	10 3/4-12 1/4	2000	16	0-1	5	3 1/2-6 3/4	10	7-10 1/4	15	9-12	20
C7AF-E	CC	0-1/2	300	2 1/4-3 1/4	500	4 1/4-6 1/4	1000	7-8 1/4	1500	8 3/4-10 1/4	2000	14	0-1	5	3 1/2-6 3/4	10	7 1/2-10 1/2	15	9-12	20
C7AF-J	CC	0-1/2	300	1 1/2-2 1/2	500	4 1/4-5 1/4	1000	6 3/4-8	1500	8 3/4-10 1/4	2000	14	0-1/4	5	1-4 1/2	10	7-10	15	9 1/2-12 1/2	20
C7AF-L	CC	0-1/2	300	2-3 1/4	500	6-7 1/4	1000	8 3/4-9 1/4	1400	9-11	2000	14	0-1	5	1 1/2-4 1/2	10	5 3/4-8 1/4	15	8 1/2-11 1/2	20
C7AF-N	CC	0-1/2	300	1 1/2-2 1/2	500	4 1/2-5 1/4	1000	6 3/4-8	1500	8 3/4-10 1/4	2000	14	0-1/4	5	1-4 1/4	10	7-10	15	9 1/2-12 1/2	20
C7AF-U	CC	0-1/2	300	3 1/2-4 1/2	500	6 1/2-7 1/4	1000	8 3/4-9 1/2	1500	9 3/4-11 1/4	2000	14	0-1	5	1-4 1/4	10	7-10	15	8-11	20
C7AF-Y ③	CC	0-1/2	300	1 1/4-2 1/2	600	5-6	1000	7-8 1/4	1500	9-10 1/2	2000	14	0-1	5	5-8	10	9 1/2-12 1/2	15	9 1/2-12 1/2	20
C7AF-Z	CC	0-1/2	300	1 1/2-2 1/2	500	5 1/4-6 1/2	1000	8-9 1/2	1500	10 3/4-12 1/4	2000	14	0-1	5	5-8	10	9 1/2-12 1/2	15	9 1/2-12 1/2	20
C7DF-A	C	2-3	500	7 1/4-8 1/4	1000	8 3/4-10	1300	11 1/2-12 1/4	1800	12 1/2-14	2000	19	0-1	5	3 1/2-5 1/2	10	4-7	15	4-7	20
C7DF-C	C	1-2	500	7 1/2-8 1/2	1000	9-10	1300	10-11 1/2	1800	10 1/2-12	2000	19	0-1 1/2	5	7-10	10	9 1/2-12 1/2	15	9 1/2-12 1/2	20
C7DF-D	C	5-5 1/4	700	7 1/4-8 1/4	1000	8 3/4-9 1/4	1200	10-11 1/4	1600	11 1/2-13	2000	19	0-1 1/2	5	5 1/2-10	10	9 1/2-12 1/2	15	9 1/2-12 1/2	20
C7DF-F	C	0-1/2	300	1 1/2-2 1/4	600	5 3/4-6 1/4	1000	10-11 1/4	1500	12-14	2000	14	0-1	4	7-10	10	8-11	15	8-11	20
C7DF-G	C	0-1/2	300	1/2-1 1/2	600	6 1/4-7 1/4	1000	10 3/4-12 1/4	1500	14-16	2000	16	0-1	7	5 1/2-9	10	7 1/2-10 1/2	15	7 1/2-10 1/2	20
C7DF-J	C																			

① - Part No. prefix and suffix stamped on housing. Basic Ford Part No. (omitted) is "12127".  
 ② - C (Clockwise), CC (Counterclockwise) viewed from rotor end.  
 ③ - When distributor reworked, set advance to C7AF-AG specifications.

# 1967 Distributor Specifications

## FORD MOTOR CO. DUAL ADVANCE DISTRIBUTOR ADVANCE SPECIFICATIONS (Continued)

NOTE - FOR ENGINE RPM AND DEGREES, MULTIPLY SPECIFICATIONS BELOW BY 2.

Distributor Part No. Ⓒ	Rot. Ⓒ	Automatic Advance (Distr. Degrees & RPM)						Vacuum Advance (Distr. Degrees)												
		Degs.	RPM	Degs.	RPM	Degs.	RPM	Max. Degs.	Deg. In. Hg.	Deg. In. Hg.	Deg. In. Hg.	Deg. In. Hg.								
C7MF-A	CC	0-1/2	300	2 1/4-3 1/4	500	5-6 1/4	1000	6 1/4-8 1/4	1500	8 1/2-10	2000	14	0-1	5	2 1/2-6	10	7-10	15	8-11	20
C7MF-G	CC	0-1/2	300	2 1/4-3 1/4	500	5-6 1/4	1000	6 1/4-8 1/4	1500	8 1/2-10	2000	14	0-1	5	3 1/2-6 1/2	10	8-11	15	9 1/2-12 1/2	20
C7MF-H	CC	0-1/2	300	2-3	500	6 1/4-7 3/4	1000	8 1/4-10	1500	10 1/4-12 1/4	2000	14	0-1	5	3 1/2-6 1/2	10	8-11	15	9 1/2-12 1/2	20
C70F-A	CC	0-1/2	400	4 1/4-5 1/4	800	7 1/2-8 1/2	1000	9 1/4-11	1500	12-13 1/4	2000	14	0-1	5	3 1/2-6 1/2	10	7 1/4-10 1/4	15	8-11	20
C70F-B	CC	0-1/2	300	2 1/4-3 1/4	500	7 1/4-8 1/4	1000	9-10 1/2	1500	10 1/2-12	2000	14	0-1	5	5-8	10	9 1/4-12 1/4	15	9 1/2-12 1/2	20
C70F-D	CC	0-1/2	300	3-4	600	8-9	1000	10 1/4-11 1/2	1500	12 1/2-14	2000	16	0-1	5	6-9 1/2	10	9 1/2-12 1/2	15	9 1/2-12 1/2	20
C70F-E	CC	0-1/2	300	3 1/4-4 1/4	600	8 1/2-9 1/4	1000	10 1/2-11 3/4	1500	12 1/4-13 1/4	2000	16	0-1	5	5-8 1/4	10	8 1/2-11 1/2	15	8 1/2-11 1/2	20
C70F-F	CC	0-1/2	300	2-3	500	9 1/2-10 1/2	1000	11 1/4-12 1/2	1500	13-14 1/2	2000	16	0-1	5	1-4 3/4	10	7-10	15	8-11	20
C70F-H	CC	0-1/2	300	3 1/4-4 1/2	500	6 1/4-7 1/2	1000	8-9 1/2	1500	9 3/4-11 1/4	2000	14	0-1	5	1-5	10	6-9	15	6-9	20
C75F-A	CC	0-1/2	300	2 1/4-3 1/4	500	5-6 1/4	1000	6 1/4-8 1/4	1500	8 1/2-10	2000	14	0-3/4	5	1-4 3/4	10	7-10	15	9 1/2-12 1/2	20
C75F-B	CC	0-1/2	300	2-3	500	6 1/2-7 3/4	1000	8 1/4-10	1500	10 1/4-12 1/4	2000	16	0-3/4	5	1-4 3/4	10	7-10	15	9 1/2-12 1/2	20
C75F-F	CC	0-1/2	300	1-2	500	6 1/4-7 1/4	1000	8 1/4-9 1/2	1500	10 1/4-11 3/4	2000	14	0-1	5	1-5	10	7-10	15	9 1/2-12 1/2	20
C7TF-T	CC	0-1/2	300	1 1/4-2 1/4	600	6 1/2-7 1/2	1000	8 1/2-9 3/4	1500	10 1/4-12 1/4	2000	14	0-1	5	2 1/2-5 1/2	10	4 1/2-7 1/2	15	4 1/2-7 1/2	20
C7VF-A	CC	0-1/2	300	1 3/4-3 1/4	400	4 1/2-5 1/2	1000	5 1/4-6 1/4	1500	6 1/4-7 3/4	2000	...	0-1	5	1-4 1/2	10	7-10	15	9 1/2-12 1/2	20
C7ZF-A	CC	0-1/2	300	2 1/2-3 1/2	600	6 1/2-7 3/4	1000	7 1/2-8 1/4	1500	8 1/2-10	2000	11	0-1	5	3 1/2-6 1/4	10	7 1/4-10 1/4	15	8-11	20
C7ZF-C	CC	0-1/2	300	3 1/4-4 1/4	500	10-11 1/4	1000	10 3/4-12	1500	11 1/4-12 1/4	2000	14	0-1	5	5-8	10	6 1/2-9 1/2	15	6 1/2-9 1/2	20
C7ZF-D	CC	0-1/2	300	1 3/4-2 3/4	500	10 1/4-11 1/4	1000	11-12 1/4	1500	11 1/2-13	2000	14	0-1	5	3-6	10	4 1/2-7 1/2	15	4 1/2-7 1/2	20
C7ZF-E	CC	0-1/2	300	3-4 1/4	500	10-11 1/4	1000	10 3/4-12	1500	11 1/4-12 1/4	2000	14	0-1	5	6 1/2-9 1/2	10	9 1/2-12 1/2	15	9 1/2-12 1/2	20
C7ZF-F	CC	0-1/2	300	3-4	500	6 1/2-7 3/4	1000	7 3/4-9	1500	8 1/4-10 1/4	2000	13	0-1	5	6-9	10	9 1/2-12 1/2	15	9 1/2-12 1/2	20
C7ZF-G	CC	0-1/2	300	2 1/2-3 1/2	600	8 1/2-9 1/2	1000	9 1/4-10 1/4	1500	10 1/4-12 1/4	2000	14	0-1 1/2	5	3-6	10	6-9	15	7 1/4-10 1/4 @ 20	20
C7ZF-H	CC	0-1/2	300	1 3/4-2 3/4	600	10 1/4-11 1/4	1000	11-12	1500	11 1/2-13	2000	14	0-1	5	3-6	10	4 1/2-7 1/2	15	4 1/2-7 1/2	20

Ⓒ - Part No. prefix and suffix stamped on housing. Ⓓ - C (Clockwise), CC (Counterclockwise) Ⓔ - 8-11 degrees at 25 in. Hg. viewed from rotor end.

## FORD MOTOR CO. LOADOMATIC DISTRIBUTOR ADVANCE SPECIFICATIONS

NOTE - FOR ENGINE RPM AND DEGREES, MULTIPLY SPECIFICATIONS BELOW BY 2.

Distributor Part No. Ⓒ	Rot. Ⓒ	Distributor Advance (Distributor Degrees & RPM)						Max. Adv.						
		Degs.	Vacuum	RPM	Degs.	Vacuum	RPM							
C5DF-C	C	2 1/2-3 1/2	0.80	800	6 1/2-7 1/2	1.80	1200	8 1/4-10	3.00	1800	10 1/4-11 1/2	3.90	2000	1 1/4
E	C	1-2	0.44	600	5-6	0.80	800	8 1/4-9 1/4	1.90	1200	10 1/4-11 1/2	3.80	2000	1 1/2
K	C	3/4-1 1/4	0.79	800	3 3/4-4 1/4	1.90	1200	5 1/4-7	3.00	1600	7-8 1/4	3.80	2000	1 3/4
C6AF-Y	C	1-2	0.90	800	4 1/2-5 1/2	2.10	1200	7-8 1/4	3.60	1600	8 3/4-10	4.80	2000	1 3/4
C6TF-AC	C	4 1/4-5 1/2	1.20	800	7 1/2-8 1/4	2.10	1200	9 1/4-10 1/2	3.70	1600	10 1/4-11 1/4	4.90	2000	1 1/2

Ⓒ - Part No. prefix and suffix stamped on housing. Ⓓ - C (Clockwise), CC (Counterclockwise) viewed from r rotor end.

# 1967 Distributor Specifications

## DELCO-REMY DISTRIBUTOR ADVANCE SPECIFICATIONS NOTE - FOR ENGINE RPM AND DEGREES, MULTIPLY SPECIFICATIONS BELOW BY 2.

Distributor Part No.	Rot. Ⓞ	Automatic Advance (Distr. Degrees & RPM)				Vacuum Advance (Distr. Deg. & In. of Hg.)				Vacuum Unit Part No.		
		Deg.	RPM	Deg.	RPM	Start Deg.	In. Hg.	Max. Deg.	In. Hg.			
1110292	C	0	300	7	750	14	1850	0	6	11.5	12	1116229
1110310	C	0-2	450	7-9	1350	13-15	2100	0	5-7	12	13.5-14.3	1116230
1110311	C	0-2	975	5-7	1600	9-11	2100	0	6-8	12	14.5-15.5	1116230
1110319	C	0-2	500	1-3	600	5-7	1500	0	6-8	12	14.5-15.5	1116230
1110340	C	5-2.5	500	7-9	950	12-14	2200	0	5-7	11	16-17	1116207
1110351	C	0-2.5	500	2.5-4.5	565	6.5-8.5	800	0	5-7	10	14.2-14.5	1116235
1110362	C	2-5.5	570	4.7-6.7	640	6.5-8.5	750	0	5-7	10	14.2-14.5	1116235
1110366	C	0-2.8	360	2.5-4	450	9.5-11.5	950	0	5-7	11	16-17	1116207
1110369	C	0-2.6	500	5-7.8	690	6.2-8.2	730	0	6-8	12	14.5-15.5	1116230
1110376	C	0	350-475	7-9	900	.....	.....	0	6-8	7-9	16	1116163
1110386 Ⓞ	C	0-3	500	7-9.5	1000	10-12	2400	0	4-6	7.5	9-10.5	1115370
1110387	C	0	475	8.5	1050	13	2000	0	6	10.5	14.5	1116235
1110388	C	0	450	10	1000	14	1900	0	6	10.5	14.5	1116235
1110389	C	0	450	7	713	13	2200	0	7	12	15	1116230
1110391	C	0-2.5	500	10.5-12.5	1050	13-15	2800	0	4-6	7.5	Ⓞ9.5-10.5	1115372
1110396	C	0-4	500	11.5-13.5	1300	16-18	1900	0	4-6	7.5	9.5-10.5	1115369
1110397	C	0-5.5	500	12-16	1200	19-21	2000	0	4-6	7.5	9.5-10.5	1115369
1110398	C	0	400	3.5-5.5	750	9-11	2150	0	4-6	7.5 Ⓞ	9.25-10.25	1115368
1111029	CC	0-2	400	7.7-9.7	1025	14-16	2000	0	7-9	9.5	15-16.6	1116232
1111042	CC	0-2	400	6-8	900	10-12	2000	0	7-9	9.5	15-16.6	1116232
1111048	CC	0-2	400	7.5-9.5	1000	12-14	2125	0	7-9	9.5	15-16.6	1116232
1111089	CC	0-2	400	6.5-8.5	1200	13-15	2000	0	7-9	9.5	15-16.6	1116232
1111101	C	0-2	425	2-4	575	11-13	2000	0	8	7.5	15.5	1116201
1111106	C	6-2.6	500	7.5-9.5	925	15-17	2200	0	4-6	12	18-19.5	1115362
1111117	C	0-6.3	500	3.1-9.5	950	11.5-13.5	750	0	6	7.5	12	1115355
1111131	C	0-1.5	400	2.5-4	600	7-9	2000	0	10-12	12.75	18.5	1116192
1111144	C	2-4	430	5-7	850	13-15	2300	0	6-8	7-9	16	1116210
1111149	C	0-2.5	425	7.7-10.4	730	14-16	1850	0	6-8	7-9	16	1116163
1111150	C	0-2	500	4-6	700	13-15	2100	0	8	7.5	15.5	1116201
1111151	CC	0-2	600	3.5-5.5	900	8-10	2100	0	8-10	9	17.2-19	1115361
1111152	C	0-3	500	1.5-4.5	550	12-14	2050	0	8	7.5	15.5	1116201
1111157 Ⓞ	C	0	450	8.5	800	14	2300	0	4	8	7	.....
1111158	C	0	275-375	6-8	700	13-15	2300	0	6-8	7-9	16	1116163
1111159	C	0	275-425	5-7	850	13-15	2300	0	6-8	7-9	16	1116163
1111164	CC	0-2	450	8.5-9.5	1050	13-15	2300	0	6-8	10	13-14.5	1115364
1111165	CC	0-2	500	6.5-8.5	1000	11-13	2400	0	8-10	10	15-17	1115365
1111166 Ⓞ	CC	0-2	450	6-8	1000	10-13	3000	0	8-10	10	15-17	1115365
1111168	C	0	450	4.5	650	7.5	850	0	10	7.5	17	1988961

See Page 9-11 for footnotes.

# 1967 Distributor Specifications

## DELCO-REMY DISTRIBUTOR ADVANCE SPECIFICATIONS (Continued)

NOTE - FOR ENGINE RPM AND DEGREES, MULTIPLY SPECIFICATIONS BELOW BY 2.

Distributor Part No.	Rot. <sup>ⓐ</sup>	Automatic Advance (Distr. Degrees & RPM)				Vacuum Advance (Distr. Deg. & In. of Hg.)				Vacuum Unit Part No.				
		Deg.	RPM	Deg.	RPM	Start Deg.	In. Hg.	Max. Deg.	In. Hg.					
1111169	C	0	450	4.25	625	8.5	1000	16	2500	0	8	7.5	15.5	1116201
1111170	C	0	450	4.25	625	8.5	1000	16	2500	0	7	6	12	1115360
1111179	CC	0-2	600	3.5-5.5	900	8-10	2000	8-10	2000	0	8-10	9	17.2-19	1115361
1111180 <sup>Ⓢ</sup>	CC	0-2	500	10.5-12.5	1000	13-15	2200	12-15	3000	0	8-10	10	15-17	1115365
1111183	CC	0-2	500	10.5-12.5	1000	.....	.....	13-15	2200	0	8-10	10	15-17	1115365
1111188 <sup>Ⓢ</sup>	CC	0-2	400	6-8	900	.....	.....	10-12	2000	0	7-9	9.5	15-16.6	1116232
1111189 <sup>Ⓢ</sup>	CC	0-2	400	6.5-8.5	1200	.....	.....	13-15	2000	0	7-9	9.5	15-16.6	1116232
1111191	C	0-1	450	7.5-9.5	1000	.....	.....	13-15	2200	0	8-10	12	18.5-20.5	1115363
1111194	C	0	450	4.5	600	7.5	750	15	2550	0	6	7.5	12	1115355
1111195	C	0	450	4.5	600	7.5	750	15	2550	0	6	7.5	12	1115355
1111196	C	0	450	4.5	600	7.5	750	15	2550	0	4	8	7	1116236
1111198	C	0-1	375	7.5-9.5	800	.....	.....	14-16	1950	0	4-6	12	18-19.5	1115362
1111199	CC	0-2	450	8.5-9.5	950	.....	.....	13-15	2300	0	6-8	10	13-14.5	1115366
1111237	CC	0-2	500	10.5-12.5	1000	.....	.....	13-15	2200	0	8-10	10	15-17	1115367
1111238	CC	0-2	500	6.5-8.5	1000	.....	.....	11-13	2400	0	8-10	10	15-17	1115367
1111242	CC	0-2	500	5-7	1000	.....	.....	9-11	2300	0	6-8	10	13-14.5	1115364
1111243	CC	0-2	450	8.5-10.5	950	.....	.....	13-15	2300	0	8-10	10	15-17	1115365
1111244	CC	0-2	450	8.5-10.5	950	.....	.....	13-15	2300	0	8-10	10	15-17	1115367
1111245 <sup>Ⓢ</sup>	CC	0-2	450	8.5-10.5	950	.....	.....	12-15	3000	0	8-10	10	15-17	1115365
1111247	C	0	450	4.25	625	8.5	1000	16	2500	0	7	6	12	1115360
1111248	C	0	450	4.25	625	8.5	1000	16	2500	0	7	6	12	1115360
1111249	C	0	450	5.5	750	.....	.....	13	2050	0	8	7.5	15.5	1116201
1111250	CC	0-2	500	10.5-12.5	1000	.....	.....	13-15	2200	0	8-10	10	15-17	1115365
1111251 <sup>Ⓢ</sup>	CC	0-2	500	10.5-12.5	1000	13-15	2200	12-15	3000	0	8-10	10	15-17	1115365
1111252	CC	0-2	500	10.5-12.5	1000	.....	.....	13-15	2200	0	8-10	10	15-17	1115367
1111253	CC	0-2	500	5-7	1000	.....	.....	9-11	2300	0	10-12	10	17-19	1115374
1111254	CC	0-2	500	5-7	1000	.....	.....	9-11	2300	0	10-12	10	17-19	1115375
1111255 <sup>Ⓢ</sup>	CC	0-2	500	5-7	1000	9-11	2300	8-11	3000	0	10-12	10	17-19	1115374
1111256	C	0	450	7.75	800	.....	.....	15	2050	0	8	7.5	15.5	1116201
1111258 <sup>Ⓢ</sup>	C	0	450	.....	.....	.....	.....	15	1900	0	8	7.5	15.5	1116201
1111261	CC	0-2	500	5-7	1000	.....	.....	9-11	2300	0	6-8	10	13-14.5	1115366
1112795	C	0-2	425	4.5-6.5	800	8-10	1600	11-13	2300	.....	.....	.....	.....	.....

ⓐ - C (Clockwise), CC (Counterclockwise) viewed from rotor end.  
 Ⓢ - Breakerless (Pulse Generator) Distributors used with Transistor or Capacitor Ignition systems.

ⓐ - Maximum retard 4-6° with 11" of Hg.  
 Ⓢ - Maximum retard 9-11° with 11" of Hg.

# 1967 Distributor Specifications

## PRESTOLITE DISTRIBUTOR ADVANCE SPECIFICATIONS

NOTE - FOR ENGINE RPM AND DEGREES, MULTIPLY SPECIFICATIONS BELOW BY 2.

Distributor Part No.	Rot. Ⓢ	Automatic Advance (Distr. Degrees & RPM)						Vacuum Advance (Distr. Degrees & Inches of Hg.)					
		Deg.	RPM	Deg.	RPM	Deg.	RPM	Deg.	In. Hg.	Deg.	In. Hg.	Deg.	In. Hg.
IBP-4201	C	0-1	435	7-9	900	12-14	1700	15-17	2200	0	4-6	10.25-11.75	18-19
IBP-4201-A	C	0-1	490	7-9	970	10-12	1550	13-15	2200	0	8-10	10.25-11.75	18.5-20
IBS-4006-P	CC	0	425-575	0-3.5	575	3.75-5.75	740	7.5-9.5	1400	0	6-9	4.5-7.5	12
IBS-4006-W	CC	0	450-600	0-7	600	9.8-11.8	810	14-16	1550	0	6-9	4.5-7.5	12
IBS-4006-Y	CC	0	325-475	0-7	475	10.5-12.5	700	14.5-16.5	2250	0	8-10	5-8	13
IBS-4006-Z	CC	0	325-475	0-4	475	4.5-6.5	640	8.5-10.5	2200	0	8-10	5-8	13
IBS-4013-A	C	0	325-475	0-3	475	5-7	725	8-10	1800	0	5-8	8.5-11.5	12
IBS-4013-B	C	0	350-500	0-6.5	500	12-14	780	15.5-17.5	2000	0	5-8	8.5-11.5	12
IDC-4601-A	C	0-1	470	7-9	950	10-12	1700	12-14	2200	0	5-7	10.25-11.75	16-17

Ⓢ - C (Clockwise), CC (Counterclockwise) viewed from rotor end.