

1967 Distributor Specifications

FORD MOTOR CO. DUAL ADVANCE DISTRIBUTOR ADVANCE SPECIFICATIONS

NOTE - FOR ENGINE RPM AND DEGREES, MULTIPLY SPECIFICATIONS BELOW BY 2.

Distributor Part No. ①	Rot. ②	Automatic Advance (Distr. Degrees & RPM)										Vacuum Advance (Distr. Degrees)								
		Degs.	RPM	Degs.	RPM	Degs.	RPM	Degs.	RPM	Degs.	RPM	Max. Degs.	Deg. In. Hg.	Deg. In. Hg.	Deg. In. Hg.					
C5AF-F	CC	2 1/4-4	650	4-5 1/2	750	7 1/4-8 1/2	1000	9 1/4-11	1600	11 1/2-13	2000	16								
C50F-E	CC	2 1/4-3 1/4	650	4-5 1/2	750	6 1/2-7 1/2	1000	7 1/2-8 3/4	1600	8 3/4-9 3/4	2000	14								
C6AF-AA	C	1 1/4-2 1/4	600	6-7 1/4	1000	7 1/4-8 1/2	1200	9 1/4-10 3/4	1600	11 1/2-13	2000	14	3-6	7	6-9	9	9 1/2-12 1/2	14	9 1/2-12 1/2	20
C6AF-AB	C	1 1/4-2 1/4	500	4 1/2-5 1/4	1000	5 1/2-6 1/4	1200	7 1/4-8 1/2	1600	9-10 1/2	2000	11	3-5 1/4	8	6 1/2-9 1/2	10	8-11	15	8-11	20
C6AF-AC	C	0-1/2	400	2-3	600	6-7 1/4	1000	9-10 1/2	1550			16	0-1	5	6-9	10	8-11	15	9-12	20
C6AF-AD	C	0-1/2	300	2 1/4-3 1/4	500	5 1/4-6 1/4	1000	7 1/2-9	1500	9 1/2-11	2000	14	0-1	4	4 1/4-7 1/4	10	8 1/2-11 1/2	15	9-12	20
C6DF-A	C	0-1/2	500	6 1/4-7 1/4	900	7-8	1000	9 1/2-10 1/2	1200	12 1/2-13 3/4	1800	16	0-1	5	3 1/4-6 1/4	10	7-10 1/4	15	9-12	20
C6DF-D	C	2 1/2-3 1/2	600	7 3/4-8 3/4	900	8 1/2-9 1/2	1000	9 1/4-10 1/2	1200	12 1/2-13 3/4	1800	16	0-1	5	3-6	10	3-6	15	3-6	20
C7AF-AA	CC	0-1/2	300	2 1/4-3 1/4	600	6 1/4-7 1/2	1000	8 1/2-9 1/4	1500	10 1/2-12	2000	14	0-1	5	4 1/4-7	10	8 1/2-11 1/2	15	8 1/2-11 1/2	20
C7AF-AB ③	CC	0-1/2	300	3/4-1 1/4	600	4 1/2-5 1/2	1000	6 1/2-7 1/2	1500	8 3/4-9 3/4	2000	14	0-1	5	4-7	10	8 1/2-11 1/2	15	8 1/2-11 1/2	20
C7AF-AC	CC	0-1/2	300	1-2	500	6 1/4-7 1/4	1000	8 3/4-10	1500	10 3/4-12 1/4	2000	14	0-1	5	1-5	10	7-10	15	9 1/2-12 1/2	20
C7AF-AD	CC	0-1/2	300	1/4-1 1/4	500	3 1/2-4 1/2	1000	5 1/4-7 1/4	1500	8 3/4-9 3/4	2000	14	0-1	5	5-8	10	9 1/2-12 1/2	15	9 1/2-12 1/2	20
C7AF-AE	CC	0-1/2	300	3 1/4-4 1/2	500	8 3/4-9 1/4	1000	9 1/2-11	1500	10 1/2-12	2000	14	0-1	5	6-9 1/2	10	9 1/2-12 1/2	15	9 1/2-12 1/2	20
C7AF-AF	CC	0-1/2	300	1 1/2-2 1/2	500	4 1/2-5 1/4	1000	6 3/4-8	1500	8 3/4-10 1/4	2000	11	0-1	5	1-4 1/2	10	7-10	15	9 1/2-12 1/2	20
C7AF-AG	CC	0-1/2	300	1/2-1 1/2	550	5 1/4-6 1/4	850	7 1/2-8 3/4	1400	10-11 1/2	2000	14	0-1	5	1/2-3 1/2	6	5-8	9	9 1/2-12 1/2	15
C7AF-AH	CC	0-1/2	300	3/4-1 1/4	600	7 1/4-8 1/4	1000	9 1/2-10 3/4	1500	10 3/4-12 1/4	2000	14	0-1	5	1 1/2-4 1/2	10	6-9 1/4	15	7-10	20
C7AF-A	CC	0-1/2	300	1/4-1 1/4	500	3 1/2-4 1/2	1000	5 1/4-7 1/4	1500	8 3/4-9 3/4	2000	14	0-1	5	3 1/2-6 1/4	10	7 1/4-10 1/4	15	9-12	20
C7AF-B	CC	0-1/2	300	1 1/4-2 1/2	500	5-6	1000	7-8 1/4	1500	9-10 1/2	2000	14	0-1	5	3 1/2-6 1/2	10	7-10	15	9-12	20
C7AF-C	CC	0-1/2	300	2-3	500	6-7 1/4	1000	8 3/4-10 1/4	1500	11 1/2-13	2000	16	0-1	5	3 1/2-6 3/4	10	7 1/4-10 1/4	15	9-12	20
C7AF-D	CC	0-1/2	300	2-3	500	5 1/4-6 1/2	1000	8-9 1/2	1500	10 3/4-12 1/4	2000	16	0-1	5	3 1/2-6 3/4	10	7-10 1/4	15	9-12	20
C7AF-E	CC	0-1/2	300	2 1/4-3 1/4	500	4 1/4-6 1/4	1000	7-8 1/4	1500	8 3/4-10 1/4	2000	14	0-1	5	3 1/2-6 3/4	10	7 1/2-10 1/2	15	9-12	20
C7AF-J	CC	0-1/2	300	1 1/2-2 1/2	500	4 1/4-5 1/4	1000	6 3/4-8	1500	8 3/4-10 1/4	2000	14	0-1/4	5	1-4 1/2	10	7-10	15	9 1/2-12 1/2	20
C7AF-L	CC	0-1/2	300	2-3 1/4	500	6-7 1/4	1000	8 3/4-9 1/4	1400	9-11	2000	14	0-1	5	1 1/2-4 1/2	10	5 3/4-8 1/4	15	8 1/2-11 1/2	20
C7AF-N	CC	0-1/2	300	1 1/2-2 1/2	500	4 1/2-5 1/4	1000	6 3/4-8	1500	8 3/4-10 1/4	2000	14	0-1/4	5	1-4 1/4	10	7-10	15	9 1/2-12 1/2	20
C7AF-U	CC	0-1/2	300	3 1/2-4 1/2	500	6 1/2-7 1/4	1000	8 3/4-9 1/2	1500	9 3/4-11 1/4	2000	14	0-1	5	1-4 1/4	10	7-10	15	8-11	20
C7AF-Y ③	CC	0-1/2	300	1 1/4-2 1/2	600	5-6	1000	7-8 1/4	1500	9-10 1/2	2000	14	0-1	5	5-8	10	9 1/2-12 1/2	15	9 1/2-12 1/2	20
C7AF-Z	CC	0-1/2	300	1 1/2-2 1/2	500	5 1/4-6 1/2	1000	8-9 1/2	1500	10 3/4-12 1/4	2000	14	0-1	5	5-8	10	9 1/2-12 1/2	15	9 1/2-12 1/2	20
C7DF-A	C	2-3	500	7 1/4-8 1/4	1000	8 3/4-10	1300	11 1/2-12 1/4	1800	12 1/2-14	2000	19	0-1	5	3 1/2-5 1/2	10	4-7	15	4-7	20
C7DF-C	C	1-2	500	7 1/2-8 1/2	1000	9-10	1300	10-11 1/2	1800	10 1/2-12	2000	19	0-1 1/2	5	7-10	10	9 1/2-12 1/2	15	9 1/2-12 1/2	20
C7DF-D	C	5-5 1/4	700	7 1/4-8 1/4	1000	8 3/4-9 1/4	1200	10-11 1/4	1600	11 1/2-13	2000	19	0-1 1/2	5	5 1/2-10	10	9 1/2-12 1/2	15	9 1/2-12 1/2	20
C7DF-F	C	0-1/2	300	1 1/2-2 1/4	600	5 3/4-6 1/4	1000	10-11 1/4	1500	12-14	2000	14	0-1	4	7-10	10	8-11	15	8-11	20
C7DF-G	C	0-1/2	300	1/2-1 1/2	600	6 1/4-7 1/4	1000	10 3/4-12 1/4	1500	14-16	2000	16	0-1	7	5 1/2-9	10	7 1/2-10 1/2	15	7 1/2-10 1/2	20
C7DF-J	C																			

① - Part No. prefix and suffix stamped on housing. Basic Ford Part No. (omitted) is "12127".
 ② - C (Clockwise), CC (Counterclockwise) viewed from rotor end.
 ③ - When distributor reworked, set advance to C7AF-AG specifications.

1967 Distributor Specifications

FORD MOTOR CO. DUAL ADVANCE DISTRIBUTOR ADVANCE SPECIFICATIONS (Continued)

NOTE - FOR ENGINE RPM AND DEGREES, MULTIPLY SPECIFICATIONS BELOW BY 2.

Distributor Part No. Ⓒ	Rot. Ⓒ	Automatic Advance (Distr. Degrees & RPM)						Vacuum Advance (Distr. Degrees)												
		Degs.	RPM	Degs.	RPM	Degs.	RPM	Max. Degs.	Deg. In. Hg.	Deg. In. Hg.	Deg. In. Hg.	Deg. In. Hg.								
C7MF-A	CC	0-1/2	300	2 1/4-3 1/4	500	5-6 1/4	1000	6 1/4-8 1/4	1500	8 1/2-10	2000	14	0-1	5	2 1/2-6	10	7-10	15	8-11	20
C7MF-G	CC	0-1/2	300	2 1/4-3 1/4	500	5-6 1/4	1000	6 1/4-8 1/4	1500	8 1/2-10	2000	14	0-1	5	3 1/2-6 1/2	10	8-11	15	9 1/2-12 1/2	20
C7MF-H	CC	0-1/2	300	2-3	500	6 1/4-7 3/4	1000	8 1/4-10	1500	10 1/4-12 1/4	2000	14	0-1	5	3 1/2-6 1/2	10	8-11	15	9 1/2-12 1/2	20
C70F-A	CC	0-1/2	400	4 1/4-5 1/4	800	7 1/2-8 1/2	1000	9 1/4-11	1500	12-13 1/4	2000	14	0-1	5	3 1/2-6 1/2	10	7 1/4-10 1/4	15	8-11	20
C70F-B	CC	0-1/2	300	2 1/4-3 1/4	500	7 1/4-8 1/4	1000	9-10 1/2	1500	10 1/2-12	2000	14	0-1	5	5-8	10	9 1/4-12 1/4	15	9 1/2-12 1/2	20
C70F-D	CC	0-1/2	300	3-4	600	8-9	1000	10 1/4-11 1/2	1500	12 1/2-14	2000	16	0-1	5	6-9 1/2	10	9 1/2-12 1/2	15	9 1/2-12 1/2	20
C70F-E	CC	0-1/2	300	3 1/4-4 1/4	600	8 1/2-9 1/4	1000	10 1/2-11 3/4	1500	12 1/4-13 1/4	2000	16	0-1	5	5-8 1/4	10	8 1/2-11 1/2	15	8 1/2-11 1/2	20
C70F-F	CC	0-1/2	300	2-3	500	9 1/2-10 1/2	1000	11 1/4-12 1/2	1500	13-14 1/2	2000	16	0-1	5	1-4 3/4	10	7-10	15	8-11	20
C70F-H	CC	0-1/2	300	3 1/4-4 1/2	500	6 1/4-7 1/2	1000	8-9 1/2	1500	9 3/4-11 1/4	2000	14	0-1	5	1-5	10	6-9	15	6-9	20
C75F-A	CC	0-1/2	300	2 1/4-3 1/4	500	5-6 1/4	1000	6 1/4-8 1/4	1500	8 1/2-10	2000	14	0-3/4	5	1-4 3/4	10	7-10	15	9 1/2-12 1/2	20
C75F-B	CC	0-1/2	300	2-3	500	6 1/2-7 3/4	1000	8 1/4-10	1500	10 1/4-12 1/4	2000	16	0-3/4	5	1-4 3/4	10	7-10	15	9 1/2-12 1/2	20
C75F-F	CC	0-1/2	300	1-2	500	6 1/4-7 1/4	1000	8 1/4-9 1/2	1500	10 1/4-11 3/4	2000	14	0-1	5	1-5	10	7-10	15	9 1/2-12 1/2	20
C7TF-T	CC	0-1/2	300	1 1/4-2 1/4	600	6 1/2-7 1/2	1000	8 1/2-9 3/4	1500	10 1/4-12 1/4	2000	14	0-1	5	2 1/2-5 1/2	10	4 1/2-7 1/2	15	4 1/2-7 1/2	20
C7VF-A	CC	0-1/2	300	1 3/4-3 1/4	400	4 1/2-5 1/2	1000	5 1/4-6 1/4	1500	6 1/4-7 3/4	2000	...	0-1	5	1-4 1/2	10	7-10	15	9 1/2-12 1/2	20
C7ZF-A	CC	0-1/2	300	2 1/2-3 1/2	600	6 1/2-7 3/4	1000	7 1/2-8 3/4	1500	8 1/2-10	2000	11	0-1	5	3 1/2-6 1/4	10	7 1/4-10 1/4	15	8-11	20
C7ZF-C	CC	0-1/2	300	3 1/4-4 1/4	500	10-11 1/4	1000	10 3/4-12	1500	11 1/4-12 1/4	2000	14	0-1	5	5-8	10	6 1/2-9 1/2	15	6 1/2-9 1/2	20
C7ZF-D	CC	0-1/2	300	1 3/4-2 3/4	500	10 1/4-11 1/4	1000	11-12 1/4	1500	11 1/2-13	2000	14	0-1	5	3-6	10	4 1/2-7 1/2	15	4 1/2-7 1/2	20
C7ZF-E	CC	0-1/2	300	3-4 1/4	500	10-11 1/4	1000	10 3/4-12	1500	11 1/4-12 1/4	2000	14	0-1	5	6 1/2-9 1/2	10	9 1/2-12 1/2	15	9 1/2-12 1/2	20
C7ZF-F	CC	0-1/2	300	3-4	500	6 1/2-7 3/4	1000	7 3/4-9	1500	8 1/4-10 1/4	2000	13	0-1	5	6-9	10	9 1/2-12 1/2	15	9 1/2-12 1/2	20
C7ZF-G	CC	0-1/2	300	2 1/2-3 1/2	600	8 1/2-9 1/2	1000	9 1/4-10 1/4	1500	10 1/4-12 1/4	2000	14	0-1 1/2	5	3-6	10	6-9	15	7 1/4-10 1/4 @ 20	20
C7ZF-H	CC	0-1/2	300	1 3/4-2 3/4	600	10 1/4-11 1/4	1000	11-12	1500	11 1/2-13	2000	14	0-1	5	3-6	10	4 1/2-7 1/2	15	4 1/2-7 1/2	20

Ⓒ - Part No. prefix and suffix stamped on housing. Ⓓ - C (Clockwise), CC (Counterclockwise) Ⓔ - 8-11 degrees at 25 in. Hg. viewed from rotor end.

FORD MOTOR CO. LOADOMATIC DISTRIBUTOR ADVANCE SPECIFICATIONS

NOTE - FOR ENGINE RPM AND DEGREES, MULTIPLY SPECIFICATIONS BELOW BY 2.

Distributor Part No. Ⓒ	Rot. Ⓒ	Distributor Advance (Distributor Degrees & RPM)						Max. Adv.						
		Degs.	Vacuum	RPM	Degs.	Vacuum	RPM							
C5DF-C	C	2 1/2-3 1/2	0.80	800	6 1/2-7 1/2	1.80	1200	8 1/4-10	3.00	1800	10 1/4-11 1/2	3.90	2000	14 1/2
E	C	1-2	0.44	600	5-6	0.80	800	8 1/4-9 1/4	1.90	1200	10 1/4-11 1/2	3.80	2000	15 1/2
K	C	3/4-1 1/4	0.79	800	3 3/4-4 1/4	1.90	1200	5 1/4-7	3.00	1600	7-8 1/4	3.80	2000	12 3/4
C6AF-Y	C	1-2	0.90	800	4 1/2-5 1/2	2.10	1200	7-8 1/4	3.60	1600	8 3/4-10	4.80	2000	12 3/4
C6TF-AC	C	4 1/4-5 1/2	1.20	800	7 1/2-8 1/4	2.10	1200	9 1/4-10 1/2	3.70	1600	10 1/4-11 1/4	4.90	2000	14

Ⓒ - Part No. prefix and suffix stamped on housing. Ⓓ - C (Clockwise), CC (Counterclockwise) viewed from r rotor end.

1967 Distributor Specifications

DELCO-REMY DISTRIBUTOR ADVANCE SPECIFICATIONS NOTE - FOR ENGINE RPM AND DEGREES, MULTIPLY SPECIFICATIONS BELOW BY 2.

Distributor Part No.	Rot. Ⓞ	Automatic Advance (Distr. Degrees & RPM)				Vacuum Advance (Distr. Deg. & In. of Hg.)				Vacuum Unit Part No.		
		Deg.	RPM	Deg.	RPM	Start Deg.	In. Hg.	Max. Deg.	In. Hg.			
1110292	C	0	300	7	750	14	1850	0	6	11.5	12	1116229
1110310	C	0-2	450	7-9	1350	13-15	2100	0	5-7	12	13.5-14.3	1116230
1110311	C	0-2	975	5-7	1600	9-11	2100	0	6-8	12	14.5-15.5	1116230
1110319	C	0-2	500	1-3	600	5-7	1500	0	6-8	12	14.5-15.5	1116230
1110340	C	5-2.5	500	7-9	950	12-14	2200	0	5-7	11	16-17	1116207
1110351	C	0-2.5	500	2.5-4.5	565	6.5-8.5	800	0	5-7	10	14.2-14.5	1116235
1110362	C	2-5.5	570	4.7-6.7	640	6.5-8.5	750	0	5-7	10	14.2-14.5	1116235
1110366	C	0-2.8	360	2.5-4	450	9.5-11.5	950	0	5-7	11	16-17	1116207
1110369	C	0-2.6	500	5-7.8	690	6.2-8.2	730	0	6-8	12	14.5-15.5	1116230
1110376	C	0	350-475	7-9	900	0	6-8	7-9	16	1116163
1110386 Ⓞ	C	0-3	500	7-9.5	1000	10-12	2400	0	4-6	7.5	9-10.5	1115370
1110387	C	0	475	8.5	1050	13	2000	0	6	10.5	14.5	1116235
1110388	C	0	450	10	1000	14	1900	0	6	10.5	14.5	1116235
1110389	C	0	450	7	713	13	2200	0	7	12	15	1116230
1110391	C	0-2.5	500	10.5-12.5	1050	13-15	2800	0	4-6	7.5	Ⓞ9.5-10.5	1115372
1110396	C	0-4	500	11.5-13.5	1300	16-18	1900	0	4-6	7.5	9.5-10.5	1115369
1110397	C	0-5.5	500	12-16	1200	19-21	2000	0	4-6	7.5	9.5-10.5	1115369
1110398	C	0	400	3.5-5.5	750	9-11	2150	0	4-6	7.5 Ⓞ	9.25-10.25	1115368
1111029	CC	0-2	400	7.7-9.7	1025	14-16	2000	0	7-9	9.5	15-16.6	1116232
1111042	CC	0-2	400	6-8	900	10-12	2000	0	7-9	9.5	15-16.6	1116232
1111048	CC	0-2	400	7.5-9.5	1000	12-14	2125	0	7-9	9.5	15-16.6	1116232
1111089	CC	0-2	400	6.5-8.5	1200	13-15	2000	0	7-9	9.5	15-16.6	1116232
1111101	C	0-2	425	2-4	575	11-13	2000	0	8	7.5	15.5	1116201
1111106	C	6-2.6	500	7.5-9.5	925	15-17	2200	0	4-6	12	18-19.5	1115362
1111117	C	0-6.3	500	3.1-9.5	950	11.5-13.5	750	0	6	7.5	12	1115355
1111131	C	0-1.5	400	2.5-4	600	5-7	1400	0	10-12	12.75	18.5	1116192
1111144	C	2-4	430	5-7	850	13-15	2300	0	6-8	7-9	16	1116210
1111149	C	0-2.5	425	7.7-10.4	730	8.6-10.6	770	0	6-8	7-9	16	1116163
1111150	C	0-2	500	4-6	700	6.5-8.5	1000	0	8	7.5	15.5	1116201
1111151	CC	0-2	600	3.5-5.5	900	8-10	2100	0	8-10	9	17.2-19	1115361
1111152	C	0-3	500	1.5-4.5	550	6.5-8.5	750	0	8	7.5	15.5	1116201
1111157 Ⓞ	C	0	450	8.5	800	14	2300	0	4	8	7
1111158	C	0	275-375	6-8	700	13-15	2300	0	6-8	7-9	16	1116163
1111159	C	0	275-425	5-7	850	13-15	2300	0	6-8	7-9	16	1116163
1111164	CC	0-2	450	8.5-9.5	1050	13-15	2300	0	6-8	10	13-14.5	1115364
1111165	CC	0-2	500	6.5-8.5	1000	11-13	2400	0	8-10	10	15-17	1115365
1111166 Ⓞ	CC	0-2	450	6-8	1000	10-13	3000	0	8-10	10	15-17	1115365
1111168	C	0	450	4.5	650	7.5	850	0	10	7.5	17	1988961

See Page 9-11 for footnotes.

1967 Distributor Specifications

DELCO-REMY DISTRIBUTOR ADVANCE SPECIFICATIONS (Continued)

NOTE - FOR ENGINE RPM AND DEGREES, MULTIPLY SPECIFICATIONS BELOW BY 2.

Distributor Part No.	Rot. [Ⓐ]	Automatic Advance (Distr. Degrees & RPM)				Vacuum Advance (Distr. Deg. & In. of Hg.)				Vacuum Unit Part No.				
		Deg.	RPM	Deg.	RPM	Start Deg.	In. Hg.	Max. Deg.	In. Hg.					
1111169	C	0	450	4.25	625	8.5	1000	16	2500	0	8	7.5	15.5	1116201
1111170	C	0	450	4.25	625	8.5	1000	16	2500	0	7	6	12	1115360
1111179	CC	0-2	600	3.5-5.5	900	8-10	2000	8-10	2000	0	8-10	9	17.2-19	1115361
1111180 [Ⓢ]	CC	0-2	500	10.5-12.5	1000	13-15	2200	12-15	3000	0	8-10	10	15-17	1115365
1111183	CC	0-2	500	10.5-12.5	1000	13-15	2200	0	8-10	10	15-17	1115365
1111188 [Ⓢ]	CC	0-2	400	6-8	900	10-12	2000	0	7-9	9.5	15-16.6	1116232
1111189 [Ⓢ]	CC	0-2	400	6.5-8.5	1200	13-15	2000	0	7-9	9.5	15-16.6	1116232
1111191	C	0-1	450	7.5-9.5	1000	13-15	2200	0	8-10	12	18.5-20.5	1115363
1111194	C	0	450	4.5	600	7.5	750	15	2550	0	6	7.5	12	1115355
1111195	C	0	450	4.5	600	7.5	750	15	2550	0	6	7.5	12	1115355
1111196	C	0	450	4.5	600	7.5	750	15	2550	0	4	8	7	1116236
1111198	C	0-1	375	7.5-9.5	800	14-16	1950	0	4-6	12	18-19.5	1115362
1111199	CC	0-2	450	8.5-9.5	950	13-15	2300	0	6-8	10	13-14.5	1115366
1111237	CC	0-2	500	10.5-12.5	1000	13-15	2200	0	8-10	10	15-17	1115367
1111238	CC	0-2	500	6.5-8.5	1000	11-13	2400	0	8-10	10	15-17	1115367
1111242	CC	0-2	500	5-7	1000	9-11	2300	0	6-8	10	13-14.5	1115364
1111243	CC	0-2	450	8.5-10.5	950	13-15	2300	0	8-10	10	15-17	1115365
1111244	CC	0-2	450	8.5-10.5	950	13-15	2300	0	8-10	10	15-17	1115367
1111245 [Ⓢ]	CC	0-2	450	8.5-10.5	950	12-15	3000	0	8-10	10	15-17	1115365
1111247	C	0	450	4.25	625	8.5	1000	16	2500	0	7	6	12	1115360
1111248	C	0	450	4.25	625	8.5	1000	16	2500	0	7	6	12	1115360
1111249	C	0	450	5.5	750	13	2050	0	8	7.5	15.5	1116201
1111250	CC	0-2	500	10.5-12.5	1000	13-15	2200	0	8-10	10	15-17	1115365
1111251 [Ⓢ]	CC	0-2	500	10.5-12.5	1000	13-15	2200	12-15	3000	0	8-10	10	15-17	1115365
1111252	CC	0-2	500	10.5-12.5	1000	13-15	2200	0	8-10	10	15-17	1115367
1111253	CC	0-2	500	5-7	1000	9-11	2300	0	10-12	10	17-19	1115374
1111254	CC	0-2	500	5-7	1000	9-11	2300	0	10-12	10	17-19	1115375
1111255 [Ⓢ]	CC	0-2	500	5-7	1000	9-11	2300	8-11	3000	0	10-12	10	17-19	1115374
1111256	C	0	450	7.75	800	15	2050	0	8	7.5	15.5	1116201
1111258 [Ⓢ]	C	0	450	15	1900	0	8	7.5	15.5	1116201
1111261	CC	0-2	500	5-7	1000	9-11	2300	0	6-8	10	13-14.5	1115366
1112795	C	0-2	425	4.5-6.5	800	8-10	1600	11-13	2300

Ⓐ - C (Clockwise), CC (Counterclockwise) viewed from rotor end.
 Ⓢ - Breakerless (Pulse Generator) Distributors used with Transistor or Capacitor Ignition systems.

Ⓢ - Maximum retard 4-6° with 11" of Hg.
 Ⓐ - Maximum retard 9-11° with 11" of Hg.

1967 Distributor Specifications

PRESTOLITE DISTRIBUTOR ADVANCE SPECIFICATIONS

NOTE - FOR ENGINE RPM AND DEGREES, MULTIPLY SPECIFICATIONS BELOW BY 2.

Distributor Part No.	Rot. Ⓢ	Automatic Advance (Distr. Degrees & RPM)						Vacuum Advance (Distr. Degrees & Inches of Hg.)					
		Deg.	RPM	Deg.	RPM	Deg.	RPM	Deg.	In. Hg.	Deg.	In. Hg.	Deg.	In. Hg.
IBP-420I	C	0-1	435	7-9	900	12-14	1700	15-17	2200	0	4-6	10.25-11.75	18-19
IBP-420I-A	C	0-1	490	7-9	970	10-12	1550	13-15	2200	0	8-10	10.25-11.75	18.5-20
IBS-4006-P	CC	0	425-575	0-3.5	575	3.75-5.75	740	7.5-9.5	1400	0	6-9	4.5-7.5	12
IBS-4006-W	CC	0	450-600	0-7	600	9.8-11.8	810	14-16	1550	0	6-9	4.5-7.5	12
IBS-4006-Y	CC	0	325-475	0-7	475	10.5-12.5	700	14.5-16.5	2250	0	8-10	5-8	13
IBS-4006-Z	CC	0	325-475	0-4	475	4.5-6.5	640	8.5-10.5	2200	0	8-10	5-8	13
IBS-4013-A	C	0	325-475	0-3	475	5-7	725	8-10	1800	0	5-8	8.5-11.5	12
IBS-4013-B	C	0	350-500	0-6.5	500	12-14	780	15.5-17.5	2000	0	5-8	8.5-11.5	12
IDC-460I-A	C	0-1	470	7-9	950	10-12	1700	12-14	2200	0	5-7	10.25-11.75	16-17

Ⓢ - C (Clockwise), CC (Counterclockwise) viewed from rotor end.

CHRYSLER & PRESTOLITE DISTRIBUTOR ADVANCE SPECIFICATIONS

NOTE - FOR ENGINE RPM AND DEGREES, MULTIPLY SPECIFICATIONS BELOW BY 2.

Distributor Part No.	Rot. ①	Automatic Advance (Distr. Degrees & RPM)				Vacuum Advance (Distr. Degrees & Inches of Hg.)								
		Deg.	RPM	Deg.	RPM	Deg.	In. Hg.	Deg.	In. Hg.					
2875069,199	C	0	350-500	0-3.7	500	12.2-14.2	900	17-19	0	5-7.1	3-6	8.5	6-8.5	10
2875078,202	C	0	350-500	0-6.7	500	9.2-11.2	710	14-16	0	5-7.1	3-6	8.5	6-8.5	10
2875094,366	C	0	350-500	0-3.7	500	9.2-11.2	870	12.5-14.5	0	5-7	2.5-5.5	8	3.75-6.25	8.7
2875116,334	C	0	350-500	0-7	500	11.25-13.25	735	15.5-17.5	0	5-8	5-8	10	10.5-13.5	13.5
2875128,342	C	0	325-475	0-5	475	7.75-9.75	700	18-20	0	8.1-9.8	4-7	12.2	8.25-10.75	15
2875162,354	CC	0	325-475	0-3.8	475	7-9	750	14.5-16.5	0	5-8	5-8	10	10.5-13.5	13.5
2875166,358	CC	0	375-525	0-6.5	525	10.1-12.1	760	14.5-16.5	0	5-7.6	6-9	12.1	9-12	14.75
2875168,364	C	0	350-500	0-3.7	500	9.2-11.2	870	12.5-14.5	0	6.2-9.7	2-5	11.9	3.7-6.2	13.8
2875170,352	CC	0	375-525	0-6	525	9.75-11.75	760	18-20	0	5-8	5-8	10	10.5-13.5	13.5
2875182,360	CC	0	350-500	0-5	500	8.2-10.2	750	14.5-16.5	0	9.2-10.7	2.5-5.3	12	9-12	15.8
2875186,362	CC	0	325-475	0-3	475	5.1-7.1	730	10.5-12.5	0	9.2-10.7	2.5-5.3	12	9-12	15.8
2875194,209	CC	0	350-500	0-5.8	500	7.8-9.8	700	11-13	0	8-9.8	4-7	12.2	8.25-10.75	15
2875310,356	CC	0	375-525	0-6.2	525	11.6-13.6	800	17-19	0	5-7.6	6-9	12.1	9-12	14.75
2875086 ②	C	0	350-500	0-5.3	500	9.6-11.6	770	13-15	0	4.5-7.5	4-7	8.9	7-10	10.5
2875102 ③	CC	0	350-500	0-7.2	500	10.3-12.3	710	14-16	0	8-9.8	4-7	12.2	8.25-10.75	15
2875105 ④	C	0	325-475	0-3.6	475	7.1-9.1	770	10.5-12.5	0	4.5-7.5	4-7	8.9	7-10	10.5
2875140 ⑤	CC	0	450-600	0-7	600	9.8-11.8	810	14-16	0	6-9	4.5-7.5	12	8.25-11	15
2875191	C	0	375-525	0-2.5	525	8-10	1010	12.5-14.5	0	4.5-7.5	4-7	8.9	7-10	10.5
2875196	C	0	325-475	0-4.5	475	6.75-8.75	700	12.5-14.5	0	5-7.1	3-6	8.5	6-8.5	10
2875204	C	0	325-475	0-2.5	475	7.5-9.5	960	10.5-12.5	0	6.9-9.1	3-5	12.5	5.25-7.5	15
2875206	C	0	325-475	0-2.5	475	7.5-9.5	960	10.5-12.5	0	4.9-7.1	3-5	10.5	5.25-7.5	13
2875338	C	0	325-475	0-2	475	3.75-5.75	780	12.5-14.5	0	7-9	6-9	12	10.5-13.5	15
2875340	C	0	375-525	0-1.3	525	1-3	700	10.5-12.5	0	7-9	6-9	12	10.5-13.5	15
2875342	C	0	325-475	0-5	475	7.75-9.75	700	18-20	0	8.1-9.8	4-7	12.2	8.25-10.75	15

① - C (clockwise) CC (counterclockwise) viewed from rotor end.
 ② - Prestolite IBS - 4015.
 ③ - Prestolite IBS - 4014A.
 ④ - Prestolite IBS - 4015A.
 ⑤ - Prestolite IBS - 4014A.

FORD MOTOR CO. VACUUM ADVANCE RETARD SPECIFICATIONS

Distributor Part No.	Deg.	In. Hg.	Vacuum Retard (Distr. Degrees)		Distributor Part No.	Deg.	In. Hg.	Vacuum Retard (Distr. Degrees)	
			Deg.	In. Hg.				Deg.	In. Hg.
C7AF-AA	C8DF-A	0-1/4	5	3 1/2-6	10
C7OF-F	C8DF-B	0-1/4	5	3-6	10
C8AF-A	0-1/2	5	2 1/2-6	10	C8DF-C	0-1/4	5	3 1/4-6	10
C8AF-B	0-2/4	5	4-6	10	C8DF-D	0-1/2	5	3-6	10
C8AF-E	0-1	5	2.5-3/4	10	C8OF-C	0-2	5	4-6	10
C8AF-M	0-1	5	3 1/2-6	10	C8OF-D	0	5	1/4 - 3 1/2	10
C8AF-R	0-3/4	5	1 1/2-5 1/2	10	C8TF-F	0-1 1/4	5	3 1/2-6	10
C8AF-S	0	5	1 1/4-4 1/2	10	C8WF-B	0-3/4	5	1 1/2-5 1/2	10
C8AF-T	0-1/2	5	1 1/2-5 1/2	10	C8ZF-A	0-3/4	5	2 1/2-6	10
					C8ZF-D