

# 1967 Distributor Specifications

## DELCO-REMY DISTRIBUTOR ADVANCE SPECIFICATIONS

NOTE - FOR ENGINE RPM AND DEGREES, MULTIPLY SPECIFICATIONS BELOW BY 2.

Distributor Part No.	Rot. Ⓞ	Automatic Advance (Distr. Degrees & RPM)				Vacuum Advance (Distr. Deg. & In. of Hg.)				Vacuum Unit Part No.		
		Deg.	RPM	Deg.	RPM	Start Deg.	In. Hg.	Max. Deg.	In. Hg.			
1110292	C	0	300	7	750	14	1850	0	6	11.5	12	1116229
1110310	C	0-2	450	7-9	1350	13-15	2100	0	5-7	12	13.5-14.3	1116230
1110311	C	0-2	975	5-7	1600	9-11	2100	0	6-8	12	14.5-15.5	1116230
1110319	C	0-2	500	1-3	600	5-7	1500	0	6-8	12	14.5-15.5	1116230
1110340	C	5-2.5	500	7-9	950	12-14	2200	0	5-7	11	16-17	1116207
1110351	C	0-2.5	500	2.5-4.5	565	6.5-8.5	800	0	5-7	10	14.2-14.5	1116235
1110362	C	2-5.5	570	4.7-6.7	640	6.5-8.5	750	0	5-7	10	14.2-14.5	1116235
1110366	C	0-2.8	360	2.5-4	450	9.5-11.5	950	0	5-7	11	16-17	1116207
1110369	C	0-2.6	500	5-7.8	690	6.2-8.2	730	0	6-8	12	14.5-15.5	1116230
1110376	C	0	350-475	7-9	900	.....	.....	0	6-8	7-9	16	1116163
1110386 Ⓞ	C	0-3	500	7-9.5	1000	10-12	2400	0	4-6	7.5	9-10.5	1115370
1110387	C	0	475	8.5	1050	13	2000	0	6	10.5	14.5	1116235
1110388	C	0	450	10	1000	14	1900	0	6	10.5	14.5	1116235
1110389	C	0	450	7	713	13	2200	0	7	12	15	1116230
1110391	C	0-2.5	500	10.5-12.5	1050	13-15	2800	0	4-6	7.5	Ⓞ9.5-10.5	1115372
1110396	C	0-4	500	11.5-13.5	1300	16-18	1900	0	4-6	7.5	9.5-10.5	1115369
1110397	C	0-5.5	500	12-16	1200	19-21	2000	0	4-6	7.5	9.5-10.5	1115369
1110398	C	0	400	3.5-5.5	750	9-11	2150	0	4-6	7.5 Ⓞ	9.25-10.25	1115368
1111029	CC	0-2	400	7.7-9.7	1025	14-16	2000	0	7-9	9.5	15-16.6	1116232
1111042	CC	0-2	400	6-8	900	10-12	2000	0	7-9	9.5	15-16.6	1116232
1111048	CC	0-2	400	7.5-9.5	1000	12-14	2125	0	7-9	9.5	15-16.6	1116232
1111089	CC	0-2	400	6.5-8.5	1200	13-15	2000	0	7-9	9.5	15-16.6	1116232
1111101	C	0-2	425	2-4	575	11-13	2000	0	8	7.5	15.5	1116201
1111106	C	6-2.6	500	7.5-9.5	925	15-17	2200	0	4-6	12	18-19.5	1115362
1111117	C	0-6.3	500	3.1-9.5	950	11.5-13.5	750	0	6	7.5	12	1115355
1111131	C	0-1.5	400	2.5-4	600	7-9	2000	0	10-12	12.75	18.5	1116192
1111144	C	2-4	430	5-7	850	13-15	2300	0	6-8	7-9	16	1116210
1111149	C	0-2.5	425	7.7-10.4	730	14-16	1850	0	6-8	7-9	16	1116163
1111150	C	0-2	500	4-6	700	13-15	2100	0	8	7.5	15.5	1116201
1111151	CC	0-2	600	3.5-5.5	900	8-10	2100	0	8-10	9	17.2-19	1115361
1111152	C	0-3	500	1.5-4.5	550	12-14	2050	0	8	7.5	15.5	1116201
1111157 Ⓞ	C	0	450	8.5	800	14	2300	0	4	8	7	.....
1111158	C	0	275-375	6-8	700	13-15	2300	0	6-8	7-9	16	1116163
1111159	C	0	275-425	5-7	850	13-15	2300	0	6-8	7-9	16	1116163
1111164	CC	0-2	450	8.5-9.5	1050	13-15	2300	0	6-8	10	13-14.5	1115364
1111165	CC	0-2	500	6.5-8.5	1000	11-13	2400	0	8-10	10	15-17	1115365
1111166 Ⓞ	CC	0-2	450	6-8	1000	10-13	3000	0	8-10	10	15-17	1115365
1111168	C	0	450	4.5	650	7.5	850	0	10	7.5	17	1988961

See Page 9-11 for footnotes.

# 1967 Distributor Specifications

## DELCO-REMY DISTRIBUTOR ADVANCE SPECIFICATIONS (Continued)

NOTE - FOR ENGINE RPM AND DEGREES, MULTIPLY SPECIFICATIONS BELOW BY 2.

Distributor Part No.	Rot. <sup>Ⓐ</sup>	Automatic Advance (Distr. Degrees & RPM)				Vacuum Advance (Distr. Deg. & In. of Hg.)				Vacuum Unit Part No.				
		Deg.	RPM	Deg.	RPM	Start Deg.	In. Hg.	Max. Deg.	In. Hg.					
1111169	C	0	450	4.25	625	8.5	1000	16	2500	0	8	7.5	15.5	1116201
1111170	C	0	450	4.25	625	8.5	1000	16	2500	0	7	6	12	1115360
1111179	CC	0-2	600	3.5-5.5	900	8-10	2000	8-10	2000	0	8-10	9	17.2-19	1115361
1111180 <sup>Ⓢ</sup>	CC	0-2	500	10.5-12.5	1000	13-15	2200	12-15	3000	0	8-10	10	15-17	1115365
1111183	CC	0-2	500	10.5-12.5	1000	.....	.....	13-15	2200	0	8-10	10	15-17	1115365
1111188 <sup>Ⓢ</sup>	CC	0-2	400	6-8	900	.....	.....	10-12	2000	0	7-9	9.5	15-16.6	1116232
1111189 <sup>Ⓢ</sup>	CC	0-2	400	6.5-8.5	1200	.....	.....	13-15	2000	0	7-9	9.5	15-16.6	1116232
1111191	C	0-1	450	7.5-9.5	1000	.....	.....	13-15	2200	0	8-10	12	18.5-20.5	1115363
1111194	C	0	450	4.5	600	7.5	750	15	2550	0	6	7.5	12	1115355
1111195	C	0	450	4.5	600	7.5	750	15	2550	0	6	7.5	12	1115355
1111196	C	0	450	4.5	600	7.5	750	15	2550	0	4	8	7	1116236
1111198	C	0-1	375	7.5-9.5	800	.....	.....	14-16	1950	0	4-6	12	18-19.5	1115362
1111199	CC	0-2	450	8.5-9.5	950	.....	.....	13-15	2300	0	6-8	10	13-14.5	1115366
1111237	CC	0-2	500	10.5-12.5	1000	.....	.....	13-15	2200	0	8-10	10	15-17	1115367
1111238	CC	0-2	500	6.5-8.5	1000	.....	.....	11-13	2400	0	8-10	10	15-17	1115367
1111242	CC	0-2	500	5-7	1000	.....	.....	9-11	2300	0	6-8	10	13-14.5	1115364
1111243	CC	0-2	450	8.5-10.5	950	.....	.....	13-15	2300	0	8-10	10	15-17	1115365
1111244	CC	0-2	450	8.5-10.5	950	.....	.....	13-15	2300	0	8-10	10	15-17	1115367
1111245 <sup>Ⓢ</sup>	CC	0-2	450	8.5-10.5	950	.....	.....	12-15	3000	0	8-10	10	15-17	1115365
1111247	C	0	450	4.25	625	8.5	1000	16	2500	0	7	6	12	1115360
1111248	C	0	450	4.25	625	8.5	1000	16	2500	0	7	6	12	1115360
1111249	C	0	450	5.5	750	.....	.....	13	2050	0	8	7.5	15.5	1116201
1111250	CC	0-2	500	10.5-12.5	1000	.....	.....	13-15	2200	0	8-10	10	15-17	1115365
1111251 <sup>Ⓢ</sup>	CC	0-2	500	10.5-12.5	1000	13-15	2200	12-15	3000	0	8-10	10	15-17	1115365
1111252	CC	0-2	500	10.5-12.5	1000	.....	.....	13-15	2200	0	8-10	10	15-17	1115367
1111253	CC	0-2	500	5-7	1000	.....	.....	9-11	2300	0	10-12	10	17-19	1115374
1111254	CC	0-2	500	5-7	1000	.....	.....	9-11	2300	0	10-12	10	17-19	1115375
1111255 <sup>Ⓢ</sup>	CC	0-2	500	5-7	1000	9-11	2300	8-11	3000	0	10-12	10	17-19	1115374
1111256	C	0	450	7.75	800	.....	.....	15	2050	0	8	7.5	15.5	1116201
1111258 <sup>Ⓢ</sup>	C	0	450	.....	.....	.....	.....	15	1900	0	8	7.5	15.5	1116201
1111261	CC	0-2	500	5-7	1000	.....	.....	9-11	2300	0	6-8	10	13-14.5	1115366
1112795	C	0-2	425	4.5-6.5	800	8-10	1600	11-13	2300	.....	.....	.....	.....	.....

Ⓐ - C (Clockwise), CC (Counterclockwise) viewed from rotor end.  
 Ⓢ - Breakerless (Pulse Generator) Distributors used with Transistor or Capacitor Ignition systems.

Ⓢ - Maximum retard 4-6° with 11" of Hg.  
 Ⓐ - Maximum retard 9-11° with 11" of Hg.