

1967 Distributor Specifications

PRESTOLITE DISTRIBUTOR ADVANCE SPECIFICATIONS

NOTE - FOR ENGINE RPM AND DEGREES, MULTIPLY SPECIFICATIONS BELOW BY 2.

| Distributor Part No. | Rot. Ⓢ | Automatic Advance (Distr. Degrees & RPM) | | | | | | Vacuum Advance (Distr. Degrees & Inches of Hg.) | | | | | |
|----------------------|--------|--|---------|-------|-----|-----------|------|---|---------|------|---------|-------------|---------|
| | | Deg. | RPM | Deg. | RPM | Deg. | RPM | Deg. | In. Hg. | Deg. | In. Hg. | Deg. | In. Hg. |
| IBP-420I | C | 0-1 | 435 | 7-9 | 900 | 12-14 | 1700 | 15-17 | 2200 | 0 | 4-6 | 10.25-11.75 | 18-19 |
| IBP-420I-A | C | 0-1 | 490 | 7-9 | 970 | 10-12 | 1550 | 13-15 | 2200 | 0 | 8-10 | 10.25-11.75 | 18.5-20 |
| IBS-4006-P | CC | 0 | 425-575 | 0-3.5 | 575 | 3.75-5.75 | 740 | 7.5-9.5 | 1400 | 0 | 6-9 | 4.5-7.5 | 12 |
| IBS-4006-W | CC | 0 | 450-600 | 0-7 | 600 | 9.8-11.8 | 810 | 14-16 | 1550 | 0 | 6-9 | 4.5-7.5 | 12 |
| IBS-4006-Y | CC | 0 | 325-475 | 0-7 | 475 | 10.5-12.5 | 700 | 14.5-16.5 | 2250 | 0 | 8-10 | 5-8 | 13 |
| IBS-4006-Z | CC | 0 | 325-475 | 0-4 | 475 | 4.5-6.5 | 640 | 8.5-10.5 | 2200 | 0 | 8-10 | 5-8 | 13 |
| IBS-4013-A | C | 0 | 325-475 | 0-3 | 475 | 5-7 | 725 | 8-10 | 1800 | 0 | 5-8 | 8.5-11.5 | 12 |
| IBS-4013-B | C | 0 | 350-500 | 0-6.5 | 500 | 12-14 | 780 | 15.5-17.5 | 2000 | 0 | 5-8 | 8.5-11.5 | 12 |
| IDC-460I-A | C | 0-1 | 470 | 7-9 | 950 | 10-12 | 1700 | 12-14 | 2200 | 0 | 5-7 | 10.25-11.75 | 16-17 |

Ⓢ - C (Clockwise), CC (Counterclockwise) viewed from rotor end.