

CHRYSLER & PRESTOLITE DISTRIBUTOR ADVANCE SPECIFICATIONS

NOTE - FOR ENGINE RPM AND DEGREES, MULTIPLY SPECIFICATIONS BELOW BY 2.

Distributor Part No.	Rot. ①	Automatic Advance (Distr. Degrees & RPM)				Vacuum Advance (Distr. Degrees & Inches of Hg.)								
		Deg.	RPM	Deg.	RPM	Deg.	In. Hg.	Deg.	In. Hg.					
2875069,199	C	0	350-500	0-3.7	500	12.2-14.2	900	17-19	0	5-7.1	3-6	8.5	6-8.5	10
2875078,202	C	0	350-500	0-6.7	500	9.2-11.2	710	14-16	0	5-7.1	3-6	8.5	6-8.5	10
2875094,366	C	0	350-500	0-3.7	500	9.2-11.2	870	12.5-14.5	0	5-7	2.5-5.5	8	3.75-6.25	8.7
2875116,334	C	0	350-500	0-7	500	11.25-13.25	735	15.5-17.5	0	5-8	5-8	10	10.5-13.5	13.5
2875128,342	C	0	325-475	0-5	475	7.75-9.75	700	18-20	0	8.1-9.8	4-7	12.2	8.25-10.75	15
2875162,354	CC	0	325-475	0-3.8	475	7-9	750	14.5-16.5	0	5-8	5-8	10	10.5-13.5	13.5
2875166,358	CC	0	375-525	0-6.5	525	10.1-12.1	760	14.5-16.5	0	5-7.6	6-9	12.1	9-12	14.75
2875168,364	C	0	350-500	0-3.7	500	9.2-11.2	870	12.5-14.5	0	6.2-9.7	2-5	11.9	3.7-6.2	13.8
2875170,352	CC	0	375-525	0-6	525	9.75-11.75	760	18-20	0	5-8	5-8	10	10.5-13.5	13.5
2875182,360	CC	0	350-500	0-5	500	8.2-10.2	750	14.5-16.5	0	9.2-10.7	2.5-5.3	12	9-12	15.8
2875186,362	CC	0	325-475	0-3	475	5.1-7.1	730	10.5-12.5	0	9.2-10.7	2.5-5.3	12	9-12	15.8
2875194,209	CC	0	350-500	0-5.8	500	7.8-9.8	700	11-13	0	8-9.8	4-7	12.2	8.25-10.75	15
2875310,356	CC	0	375-525	0-6.2	525	11.6-13.6	800	17-19	0	5-7.6	6-9	12.1	9-12	14.75
2875086 ②	C	0	350-500	0-5.3	500	9.6-11.6	770	13-15	0	4.5-7.5	4-7	8.9	7-10	10.5
2875102 ③	CC	0	350-500	0-7.2	500	10.3-12.3	710	14-16	0	8-9.8	4-7	12.2	8.25-10.75	15
2875105 ④	C	0	325-475	0-3.6	475	7.1-9.1	770	10.5-12.5	0	4.5-7.5	4-7	8.9	7-10	10.5
2875140 ⑤	CC	0	450-600	0-7	600	9.8-11.8	810	14-16	0	6-9	4.5-7.5	12	8.25-11	15
2875191	C	0	375-525	0-2.5	525	8-10	1010	12.5-14.5	0	4.5-7.5	4-7	8.9	7-10	10.5
2875196	C	0	325-475	0-4.5	475	6.75-8.75	700	12.5-14.5	0	5-7.1	3-6	8.5	6-8.5	10
2875204	C	0	325-475	0-2.5	475	7.5-9.5	960	10.5-12.5	0	6.9-9.1	3-5	12.5	5.25-7.5	15
2875206	C	0	325-475	0-2.5	475	7.5-9.5	960	10.5-12.5	0	4.9-7.1	3-5	10.5	5.25-7.5	13
2875338	C	0	325-475	0-2	475	3.75-5.75	780	12.5-14.5	0	7-9	6-9	12	10.5-13.5	15
2875340	C	0	375-525	0-1.3	525	1-3	700	10.5-12.5	0	7-9	6-9	12	10.5-13.5	15
2875342	C	0	325-475	0-5	475	7.75-9.75	700	18-20	0	8.1-9.8	4-7	12.2	8.25-10.75	15

① - C (clockwise) CC (counterclockwise) ② - Prestolite IBS - 4015. ③ - Prestolite IBS - 4014.

④ - Prestolite IBS - 4015A. ⑤ - Prestolite IBS - 4014A.

viewed from rotor end.

FORD MOTOR CO. VACUUM ADVANCE RETARD SPECIFICATIONS

Distributor Part No.	Deg.	In. Hg.	Vacuum Retard (Distr. Degrees)		Distributor Part No.	Deg.	In. Hg.	Vacuum Retard (Distr. Degrees)	
			Deg.	In. Hg.				Deg.	In. Hg.
C7AF-AA	C8DF-A	0-1/4	5	3 1/2-6	10
C7OF-F	C8DF-B	0-1/4	5	3-6	10
C8AF-A	0-1/2	5	2 1/2-6	10	C8DF-C	0-1/4	5	3 1/4-6	10
C8AF-B	0-2/4	5	4-6	10	C8DF-D	0-1/2	5	3-6	10
C8AF-E	0-1	5	2.5-3/4	10	C8OF-C	0-2	5	4-6	10
C8AF-M	0-1	5	3 1/2-6	10	C8OF-D	0	5	1/4 - 3 1/2	10
C8AF-R	0-3/4	5	1 1/2-5 1/2	10	C8TF-F	0-1 1/4	5	3 1/2-6	10
C8AF-S	0	5	1 1/4-4 1/2	10	C8WF-B	0-3/4	5	1 1/2-5 1/2	10
C8AF-T	0-1/2	5	1 1/2-5 1/2	10	C8ZF-A	0-3/4	5	2 1/2-6	10
					C8ZF-D

1968 Distributor Specifications

FORD MOTOR CO. DUAL ADVANCE DISTRIBUTOR ADVANCE SPECIFICATIONS NOTE - FOR ENGINE RPM AND DEGREES, MULTIPLY SPECIFICATIONS BELOW BY 2.

Distributor Part No. Ⓞ	Rot. Ⓞ	Automatic Advance (Distr. Degrees & RPM)						Vacuum Advance (Distr. Degrees)												
		Degs.	RPM	Degs.	RPM	Degs.	RPM	Max. Degs.	Deg.	In.Hg.	Deg.	In.Hg.	Deg.	In.Hg.						
C50F-E	CC	2 1/2-3 3/4	650	4-5 1/2	750	6 1/2-7 1/2	1000	7 1/2-8 3/4	1600	8 3/4-9 3/4	2000	14				
C7AF-E	CC	0-1/2	300	2 1/2-3 1/4	500	4 3/4-6 1/4	1000	7-8 1/4	1500	8 3/4-10 1/4	2000	14	0-1	5	3 1/2-8 3/4	10	7 1/2-10 1/2	15	9-12	20
C7AF-J	CC	0-1/2	300	1 1/2-2 1/2	500	4 3/4-5 3/4	1000	6 3/4-8	1500	8 3/4-10 1/4	2000	14	0-3/4	5	1-4 1/2	10	7-10	15	9 1/2-12 1/2	20
C7AF-U	CC	0-1	375	5 3/4-6 3/4	550	7 1/2-8 3/4	1300	9 3/4-11 1/4	2000	14	0-1 1/2	8	0-4	9.5	4 1/4-7 1/4	12	11-18	16.4
C7AF-AA	CC	0-1/2	350	1/2-1 1/2	500	6 1/4-7 1/2	1000	8 3/4-9 3/4	1500	10 1/4-12	2000	14	0-1	5	4 1/4-7	10	8 1/2-11 1/2	15	8 1/2-11 1/2	20
C7AF-AC	CC	0-1/2	350	1-2	500	6 3/4-7 3/4	1000	8 3/4-10	1500	10 3/4-12 1/4	2000	14	0-1	5	1-5	10	7-10	15	9 1/2-12 1/2	25
C7AF-AD	CC	0-1/2	300	1/4-1 1/4	500	3 1/2-4 1/2	1000	5 3/4-7 1/4	1500	8 1/4-9 3/4	2000	14	0-1	5	5-8	10	9 1/2-12 1/2	15	9 1/2-12 1/2	20
C7AF-AG	CC	1/2-1 1/2	550	5 1/4-6 1/4	850	7 1/2-8 3/4	1400	10-11 1/2	2000	14	0-1	5	1/2-3 1/2	6	5-8	9	9 1/2-12 1/2	15
C7MF-G	CC	0-1/2	300	2 1/4-3 1/4	500	5-6 1/4	1000	6 3/4-8 1/4	1500	8 3/4-10	2000	14	0-1	5	3 1/2-6 1/2	10	8-11	15	9 1/2-12 1/2	20
C7MF-H	CC	0-1/2	300	2-3	500	6 3/4-7 3/4	1000	8 3/4-10	1500	10 3/4-12 1/4	2000	14	0-1	5	3 1/2-6 1/2	10	8-11	15	9 1/2-12 1/2	20
C7OF-A	CC	0-1/2	400	4 1/4-5 3/4	800	7 1/2-8 1/2	1000	9 3/4-11	1500	12-13 3/4	2000	14	0-1	5	3 1/2-6 1/2	10	7 1/4-10 1/4	15	8-11	17
C7OF-B	CC	0-1/2	300	2 3/4-3 3/4	500	7 1/4-8 3/4	1000	9-10 1/2	1500	10 3/4-12	2000	14	0-1	5	5-8	10	9 1/4-12 1/4	15	9 1/2-12 1/2	20
C7OF-D	CC	0-1/2	300	3-4	600	8-9	1000	10 1/4-11 1/2	1500	12 1/2-14	2000	16	0-1	5	6-9 1/2	10	9 1/2-12 1/2	15	9 1/2-12 1/2	20
C7OF-F	CC	0-1/2	350	2-3	500	9 1/2-10 1/2	1000	11 1/4-12 1/2	1500	13-14 1/2	2000	16	0-1	5	1-4 3/4	10	7-10	15	8-11	20
C7OF-G	CC
C7OF-H	CC	0-1/2	300	3 1/4-4 1/2	500	6 1/4-7 1/4	1000	8 3/4-9 3/4	1500	9 3/4-11 1/4	2000	14	0-1	5	1-5	10	6-9	15	6-9	13.8
C7SF-A	CC	0-1/2	300	2 1/4-3 1/4	500	5-6 1/4	1000	6 3/4-8 1/4	1500	8 3/4-10	2000	14	0-3/4	5	1-4 1/4	10	7-10	15	9 1/2-12 1/2	20
C7SF-B	CC	0-1/2	300	2-3	500	6 1/2-7 1/4	1000	6 3/4-8 1/4	1500	10 3/4-12 1/4	2000	16	0-3/4	5	1-4 3/4	10	7-10	15	9 1/2-12 1/2	20
C7VF-A	CC	0-1/2	300	1 3/4-3 1/4	400	4 1/2-5 1/2	1000	5 1/4-6 3/4	1500	6 1/4-7 3/4	2000	-	0-1	5	1-4 1/2	10	7-10	15	9 1/2-12 1/2	20
C7ZF-A	CC	0-1/2	300	2 1/2-3 1/2	600	6 1/2-7 3/4	1000	7 1/2-8 3/4	1500	8 1/2-10	2000	11	0-1	5	3 1/2-6 3/4	10	7 1/4-10 1/4	15	8-11	20
C7ZF-D	CC	0-1/2	300	1 3/4-2 3/4	500	10 1/4-11 1/4	1000	11-12 1/4	1500	11 1/2-13	2000	14	0-1	5	3-6	10	4 1/2-7 1/2	15	4 1/2-7 1/2	20
C7ZF-E	CC	0-1/2	300	3-4 1/4	500	10-11 1/4	1000	10 3/4-12	1500	11 1/4-12 3/4	2000	14	0-1	5	6 1/2-9 1/2	10	9 1/2-12 1/2	15	9 1/2-12 1/2	20
C7ZF-F	CC	0-1	390	6 1/2	600	7 1/4	1200	8 3/4-10 1/4	2000	14	0-3	5.8	6 1/4-9 1/4	10	9 1/2-12 1/2	14.5
C8AF-A	C	0-1/2	350	0-1 1/2	750	2 1/4-4 1/2	1000	6-8	1500	7 1/2-10	2000	0-3/4	5	1-3 3/4	10	5 1/2-8	15	5 1/2-8	25
C8AF-B	C	0-1/2	350	0-1/2	500	2 1/4-5	1000	4 1/2-6 3/4	1500	6 1/4-8 3/4	2000	11	0-1	5	3-6	10	6 1/2-9	15	6 1/2-9	25
C8AF-E	CC	0-1/2	350	0-1 3/4	500	6-8 1/4	1000	8-10 1/4	1500	10-12 1/2	2000	14	0-3/4	5	0-3	10	5 1/2-8 1/2	15	8 1/2-11	25
C8AF-J	CC	0-1/2	350	0-2	500	6 3/4-8 3/4	1000	8 3/4-11	1500	10 3/4-13 1/4	2000	14	0-1	5	1-5	10	7-10 1/4	15	10-12 1/2	25
C8AF-M	CC	0-1/2	350	1/2-2 1/2	500	3 1/2-5 1/2	1000	5 3/4-8 1/4	1500	8 1/4-10 3/4	2000	11	0-1	5	4-6 3/4	10	9 1/4-12 1/4	15	10-12 1/2	25
C8AF-R	CC	0-1/2	350	0-2	500	5 3/4-9 3/4	1000	7 3/4-10	1500	9 3/4-12 1/4	2000	14	0-3/4	5	1-4 3/4	10	6 1/4-9 3/4	15	10-12 1/2	25
C8AF-S	CC	0-1/2	350	1-3	500	5 1/4-7 1/4	1000	7 3/4-10	1500	9 3/4-12 1/4	2000	14	0-1	5	3 1/4-6 1/4	10	8-11	15	10-12 1/2	25
C8AF-T	CC	0-1/2	350	2 1/4-4 1/4	750	5 3/4-7 3/4	1000	7 3/4-10	1500	9 3/4-12 1/4	2000	14	0-3/4	5	1-4 3/4	10	6 3/4-10	15	10-12 1/2	25
C8AF-Y	CC	0-1/2	350	2 3/4-4 3/4	750	5 3/4-7 3/4	1000	7 3/4-10	1500	9 3/4-12 1/4	2000	14	0-3/4	5	1-4 3/4	10	7-10	15	9 1/2-12 1/2	20
C8DF-A	C	0-1/2	350	0-2	500	6 1/4-8 1/4	1000	8 3/4-11	1500	10 1/2-13	2000	14	0-1	5	3-6	10	5 1/2-8	15	5 1/2-8	25
C8DF-B	C	0-1/2	350	1-3	750	3 1/4-5 1/4	1000	8 1/2-10 1/2	1500	12-14	2000	14	0-3	5	6-9	10	7-9 1/2	15	7-9 1/2	25
C8DF-C	C	0-1/2	350	0-2	500	6 1/2-8 1/2	1000	8 1/4-10 1/2	1500	9 1/2-12	2000	14	0-1	5	6 3/4-9 1/2	10	10-12 1/2	15	10-12 1/2	25
C8DF-D	C	0-1/2	350	0-1 1/4	500	4 1/4-6 3/4	1000	9-11 1/4	1500	12-14	2000	14	0-1	5	6 1/2-9 1/2	10	8 1/2-11	15	8 1/2-11	25

Ⓞ - Part No. prefix and suffix stamped on housing. Ⓞ - C (Clockwise), CC (Counterclockwise) viewed from rotor end.
Basic Ford Part No. (omitted) is "12127".

FORD MOTOR CO. DUAL ADVANCE DISTRIBUTOR ADVANCE SPECIFICATIONS (Continued)

NOTE - FOR ENGINE RPM AND DEGREES, MULTIPLY SPECIFICATIONS BELOW BY 2.

Distributor Part No. ①	Rot. ②	Automatic Advance (Distr. Degrees & RPM)						Vacuum Advance (Distr. Degrees)												
		Degs.	RPM	Degs.	RPM	Degs.	RPM	Max. Degs.	Deg. In. Hg.	Deg. In. Hg.	Deg. In. Hg.	Deg. In. Hg.								
C80F-C	CC	0-1/2	350	0-1 3/4	500	6-8 1/4	1000	8-10 1/4	1500	10-12 1/2	2000	14	0-1	5	2-5	10	5 3/4-8 3/4	15	9-11 1/2	25
C80F-D	CC	0-1/2	350	3/4-2 3/4	500	8 1/2-10 1/2	1000	10 1/4-12 1/2	1500	12-14 1/2	2000	16	0-3/4	5	1 1/2-4 3/4	10	6 3/4-9 1/2	15	7-9 1/2	25
C8TF-F	CC	0-1/2	350	0-1/2	500	3 1/2-5 1/2	1000	7-9	1500	8 3/4-11	2000	11	0-1	5	2-5	10	5 3/4-8 3/4	15	9-11 1/2	25
C8VF-A	CC	0-1/2	350	2 1/2-4 1/2	750	6 1/2-8 1/2	1000	8-10 1/4	1500	9-11 1/2	2000	14	0-1	5	1-4	10	6-9	15	9 1/2-12	25
C8VF-C	CC
C8VF-F	CC	0-1/2	350	0-1 1/4	500	4 1/4-6 3/4	1000	5 3/4-8 3/4	1500	7-9 1/4	2000	11	0-1	5	1/2-4 1/4	10	6-9	15	9 1/2-12	25
C8VF-G	CC	0-1/2	350	3/4-2 3/4	750	4 1/2-6 1/2	1000	6-8 3/4	1500	7-9 1/2	2000	11	0-1	5	1-4 1/4	10	8 1/2-11 1/2	15	9 1/2-12	20
C8WF-A	C	0	500	4-6	800	9 1/4-12	2000	12	2000	16	0	1	0-4	9.5	7-10	15
C8WF-B	CC	0-1/2	350	1/2-1 1/2	500	5-7	1000	7 1/2-9 3/4	1500	9 3/4-12 1/4	2000	14	0-3/4	5	1-4 3/4	10	7-10	15	10-12 1/2	25
C8ZF-A	CC	0-1/2	350	3/4-2 3/4	500	5 1/2-7 1/2	1000	6 1/4-8 1/2	1500	7-9 1/2	2000	11	0-1	5	4 3/4-8	10	8-10 1/2	15	8-10 1/2	25
C8ZF-B	CC
C8ZF-D	CC	0-1/2	350	1-3	750	3 3/4-5 1/4	1000	6 1/4-8 1/2	1500	7-9 1/2	2000	11	0-3/4	5	1-4	10	5 1/2-8 1/2	15	6 1/2-9	25

① - Part No. prefix and suffix stamped on housing. ② - C (Clockwise), CC (Counterclockwise) viewed from rotor end.
Basic Ford Part No. (omitted) is "12127".

FORD MOTOR CO. LOADOMATIC DISTRIBUTOR ADVANCE SPECIFICATIONS

NOTE - FOR ENGINE RPM AND DEGREES, MULTIPLY SPECIFICATIONS BELOW BY 2.

Distributor Part No. ①	Rot. ②	Distributor Advance (Distributor Degrees & RPM)												
		Degs.	Vacuum	RPM	Degs.	Vacuum	RPM	Degs.	Vacuum	RPM	Degs.	Vacuum	RPM	Max. Adv.
C5DF-C ③	C	0-1	.5	625	5 1/4	1.3	1000	9 1/2	3	1600	11 1/2	3.9	2000	1 1/2
		13 1/2	5	500	13 3/4	6	800	13 3/4	6.3	1200	14	5.6	1600	14
C5DF-E ③	C	0-10	.3	550	7 3/4-8 3/4	6	1100	5 1/2-12	3.8	2000	12
		14-15	7.9	900	12 3/4	7	1600	12
C5DF-K ③	C	0-1	.44	712	3 3/4-4 3/4	1.9	1200	7-8 1/4	3.8	2000	8 1/4
		11-12	7.9	1100	12-15 1/2	7	1600	15 1/2
C6AF-Y ③	C	0-1	.72	740	5	2.1	1200	10	4.8	2000	10
		10 1/2	6.5	600	12	7	900	10 1/4	5	1600	10 1/4
C6TF-A ③		0-1	.55	550	6 3/4	1.6	1000	10	3.3	1500	12	4.9	2000	12
		11 1/2	5.5	600	13 1/4	6.9	900	12	6.7	1400	13	6	1700	13
C6TF-AC	C	4 1/2-5 1/2	1.20	800	7 1/2-8 1/4	2.10	1200	9 1/4-10 1/2	3.70	1600	10 1/4-11 3/4	4.90	2000	14
C70F-K	CC	3 3/4-5 1/4	750	7 1/4-9 1/4	1000	9 1/4-10 1/2	1500	9-11 1/2	2000	14

① - Part No. prefix and suffix stamped on housing. ② - Wide open throttle vacuum advance.
Basic Ford Part No. (omitted) is "12127".

③ - C (Clockwise), CC (Counterclockwise) viewed from rotor end. ④ - Part throttle vacuum advance.

1968 Distributor Specifications

DELCO-REMY DISTRIBUTOR ADVANCE SPECIFICATIONS

NOTE - FOR ENGINE RPM AND DEGREES, MULTIPLY SPECIFICATIONS BELOW BY 2.

Distributor Part No.	Rot ①	Automatic Advance (Distr. Degrees & RPM)				Vacuum Advance (Distr. Deg. & In. of Hg.)				Vacuum Unit No.		
		Deg.	RPM	Deg.	RPM	Start Deg.	In. Hg.	Max. Deg.	In. Hg.			
1110307	C	0-2	475	10-12	1200	17-19	1700	0	5-7	11.5	11.5-13	1116198
1110311	C	0-2	975	5-7	1600	9-11	2100	0	6-8	12	14.5-15.5	1116230
1110319	C	0-2	500	1-3	600	9-11	2400	0	6-8	12	14.5-15.5	1116230
1110371	C	0-4	500	7-11	675	5-7	1500	0	5-7	11	13.8-14	1116248
1110389	C	0-3	500	6-8	700	9.4-11.4	740	0	6-8	12	14.5-15.5	1116230
1110399	C	1.5-3.5	600	7.5-9.5	975	13-15	2100	0	6-8	11.5	15.5-17	1116217
1110426	C	1.5-3.5	600	6-8	850	11-13	1800	0	6-8	12	14.5-15.5	1116230
1110430	C	0-4.8	500	4.8-9.5	600	13-15	2200	0	4-6	7.5⊙	9.2-10.2	1973413
1110431	C	0-1.9	500	6-8	825	12-14	2500	0	4-6	7.5⊙	9.2-10.2	1973414
1110433	C	.6-2.6	600	7.5-9.5	1050	15-17	2300	0	6-8	11.5	15.5-17	1116217
1110434	C	2-4	800	13-15	2100	0	6-8	12	14.5-15.5	1116230
1110436	C	0-3.8	550	3-5	630	17-19	2300	0	6-8	11.5	15.5-17	1116217
1110437	C	.6-2.6	600	7.5-9.5	1050	15-17	2300	0	6-8	11.5	15.5-17	1116217
1110438	C	0-3.8	550	3-5	630	17-19	2300	0	6-8	11.5	15.5-17	1116217
1110439	C	0-3	500	2.2-5.2	580	15-17	2100	0	6-8	11.5	15.5-17	1116217
1110441	C	0-3	500	2.2-5.2	580	15-17	2100	0	6-8	11.5	15.5-17	1116217
1110442	C	0-1.9	500	8.5-10.5	1000	13-15	2100	0	6-8	11.5	15.5-17	1116217
1110443	C	0-3	500	2.2-5.2	580	15-17	2100	0	6-8	11.5	15.5-17	1116217
1110444	C	0-3	350	0-3.5	400	12-14	2000	0	5-7	11	15.5-17	1116207
1110447	C	0-2.1	500	7.5-9.5	850	13-15	1850	0	6-8	12	14.5-15.5	1116230
1110449	C	0-1.9	500	6-8	825	12-15	2500	0	4-6	7.5	9.2-10.2	1973413
1111106	C	.6-2.6	500	7.5-9.5	925	15-17	2200	0	4-6	12	18-19.3	1115362
1111150	C	1.5-3.5	600	4-6	750	13-15	2100	0	7-9	8	15-17	1116201
1111168	C	0-2.2	500	3.2-5.5	640	12-14	2350	0	9-11	8	16.5-17.5	1968861
1111169	C	0-2.7	500	2.5-5	600	15-17	2500	0	7-9	8	15-16	1116201
1111170	C	0-2.7	500	2.5-5	600	15-17	2500	0	6-8	6.4	11.3-12.5	1115360
1111191	C	.5-2.5	500	7.5-9.5	1000	13-15	2200	0	8-10	12	18.5-20.5	1115363
1111194	C	0-3	500	1.5-4.5	550	14-16	2550	0	5-7	8	11.2-12.7	1115355
1111198	C	.5-2.5	450	7.5-9.5	800	14-16	1950	0	4-6	12	18-19.3	1115362
1111239	C	.3-2.3	400	7.3-9.3	975	13-15	2200	0	8-10	12.5⊙	18.5-20.5	1973409
1111257	C	.7-2.7	600	4-6	800	13-15	2100	0	5-7	8	11.2-12.7	1115355
1111264	C	0-3	525	4.7-7.7	680	14-16	2350	0	9-11	8	16.5-17.5	1968861
1111266	C	0-2.6	550	10.3-13	960	15-17	2075	0	9-11	8	16.5-17.5	1968861
1111270	CC	0-2	500	5-7	1000	9-11	2300	0	10-12	10⊙	17-18.8	1973412

① - C (Clockwise); CC (Counterclockwise) viewed from rotor end ⊙ - Maximum retard is 1.75-3.25° at 11" Hg ⊙ - Maximum retard is 4-6° at 11" Hg

1968 Distributor Specifications

DELCO-REMY DISTRIBUTOR ADVANCE SPECIFICATIONS (Continued)

NOTE - FOR ENGINE RPM AND DEGREES, MULTIPLY SPECIFICATIONS BELOW BY 2.

Distributor Part No.	Rot. ①	Automatic Advance (Distr. Degrees & RPM)			RPM			Vacuum Advance (Distr. Deg. & In. of Hg.)		Vacuum Unit No.				
		Deg.	RPM	Deg.	Deg.	RPM	Start Deg.	In. Hg.	Max. Deg.		In. Hg.			
1111272	CC	.5-2.5	500	7.5-9.5	950	15-17	2275	0	8-10	10③	15-17	1973411
1111277	C	0-2.6	500	2-4.7	580	15-17	2500	3000	0	6-8	8	14.5-15.75	1116201
1111278	C	0-2.6	500	2-4.7	580	15-17	2500	3000	0	6-8	6.4	11.3-12.5	1115360
1111281	CC	1-3	550	6.5-8.5	975	11-13	2400	0	8-10	10③	15-17	1973411
1111282	CC	1.5-3.5	700	4-6	1000	8-10	2500	0	8-10	10③	15-17	1973411
1111284	C	.4-2.4	450	8.5-10.5	875	13-15	2300	0	6-8	8	14.5-15.75	1116210
1111285	C	0	500-600	9.5-11.5	900	15-17	2300	0	6-8	7-9	16	1116210
1111286	CC	0-1.8	400	1.7-4	500	2.2-4.2	520	2000	0	8-10	12.5	18.5-20.5	1973408
1111287	CC	.4-2.4	500	8-10	900	10-12	2000	0	8-10	12.5	18.5-20.5	1973408
1111289	CC	.4-2.4	700	6-8	1500	0	8-10	12.5	18.5-20.5	1973408
1111290	CC	.3-2.3	500	8-10	900	10-12	2000	3000	0	8-10	12.5	18.5-20.5	1973408
1111291	CC	0-2	425	8-10	900	13-15	2000	3000	0	6-8	13	16-17.5	1973407
1111292	CC	.5-2.5	750	6-8	1500	4.2-8	3000	0	8-10	12.5	18.5-20.5	1973408
1111293	C	0-2.7	500	2.5-5	600	7.5-9.5	1000	2500	0	6-8	6.4	11.3-12.5	1115360
1111294④	C	0-2.6	500	2-4.7	580	15-17	2500	3000	0	6-8	6.4	11.3-12.5	1115360
1111295④	C	.5-3.3	700	6.7-9.5	930	13.5-15.5	2500	3000	1115373
1111296④	C	0-2	550	14-16	1900	12.5-16	3000	0	6-8	8	14.5-15.75	1116201
1111297	C	1.5-3.5	600	7.5-9.5	950	14-16	2050	0	9-11	8	16.5-17.5	1968861
1111298	C	0-3	500	2-5	570	10-12	1000	2050	0	6-8	8	14.5-15.75	1116201
1111299	CC	0-2	400	6-8	900	9-11	2300	0	10-12	10	17-18.8	1973412
1111300	CC	0-2	500	5-7	1000	9-11	2300	0	10-12	10③	17-18.8	1973412
1111327	C	.5-3	400	11-13	1000	15-17	2200
1111328	C	.4-3	400	10-13	1000	15-17	2000	3000
1111330	C	0-3	600	7.5-10.5	870	8.5-10.5	900	2300	0	6-8	8	14.5-15.75	1116210
1111399	C	0	400-500	7.5-9.5	975	13-15	2100	0	6-8	10-12	17	1116217
1111435	CC	0-2	480	6-8	1000	10-12	2300	0	10-12	10③	17-18.8	1973412
1111438	C	0-3	525	4.7-7.7	680	9-11	900	2350	0	6-8	8	14.5-15.75	1116201
1111439	C	0-2.7	600	5.2-8.4	800	6.7-8.7	850	2200	0	5-7	8	11.2-12.7	1115355
1111440	C	0-2	550	3-5	700	17-19	1975	0	5-7	8	11.2-12.7	1115355
1111441④	C	0-3.3	500	6-9	685	14-16	2200	3000	0	6-8	8	14.5-15.75	1116201
1111443	C	0-2	600	4.7-7.7	680	15-17	1975	0	5-7	8	11.2-12.7	1115355
1111444	C	0-3	525	6.7-8.7	740	9-11	900	2350	0	6-8	8	14.5-15.75	1116201

① - C (Clockwise); CC (Counterclockwise) viewed from rotor end
 ② - Maximum retard is 4-6° at 11" Hg
 ③ - Breakerless (Pulse Generator) distributor used with transistor or Capacitor Ignition Systems.

1968 Distributor Specifications

DELCO-REMY DISTRIBUTOR ADVANCE SPECIFICATIONS (Continued)

NOTE - FOR ENGINE RPM AND DEGREES, MULTIPLY SPECIFICATIONS BELOW BY 2.

Distributor Part No.	Rot. ①	Automatic Advance (Distr. Degrees & RPM)		Vacuum Advance (Distr. Deg. & h. of Hg.)		Vacuum Unit No.						
		Deg.	RPM	Start Deg. In. Hg.	Max. Deg. In. Hg.							
1111445	C	0-4	500	9.5-11.5	1000	17-19	2500	0	6-8	8	14.5-15.75	1116201
1111447	CC	0-2	640	3.5-5.5	950	8-10	2400	0	8-10	10③	15-17	1973411
1111448	CC	1-3	700	5-7	1000	9-11	2300	0	10-12	10③	17-18.8	1973412
1111449	CC	1-3	700	5-7	1000	9-11	2300	0	8-10	10③	15-17	1973411
1111450	CC	1.3-3.3	700	6-8	1000	10-12	2300	0	8-10	10	15-17	1973411
1111463	CC	1.4-3.4	550	10-12	2000	0	6-8	13	16-17.5	1973407
1111466	CC	0-2	650	6.5-8.5	1300	11-13	2000	0	6-8	13	16-17.5	1973407
1111467	C	2-4.5	750	10.3-13	1090	15-17	2200	0	9-11	8	16.5-17.5	1968861
1111468	CC	.5-2.5	450	7-9	1000	9-11	1900	0	10-12	8.7	16.2-17.8	1973418
1111469	CC	0-2	550	9-11	1800	0	8-10	12.5	18.5-20.5	1973408
1111470	CC	.5-2.5	450	7-9	1000	7.8-11	3000	0	10-12	8.7	16.2-17.8	1973418
1111471	CC	0-2	550	5-7	1000	7.5-11	3000	0	8-10	12.5	18.5-20.5	1973408
1111472	C	.5-2.5	550	7.5-9.5	1000	13-15	2000	0	4-6	12	18-19.3	1115362
1111473	C	0-2.5	450	8-10.5	790	14-16	2200	0	8-10	12.5	18.5-20.5	1115363
1112795	C	0-2	425	4.5-6.5	800	11-13	2300

① - C (Clockwise); CC (Counterclockwise) viewed from rotor end

③ - Maximum retard is 4-6° at 11" Hg