

1968 Distributor Specifications

FORD MOTOR CO. DUAL ADVANCE DISTRIBUTOR ADVANCE SPECIFICATIONS NOTE - FOR ENGINE RPM AND DEGREES, MULTIPLY SPECIFICATIONS BELOW BY 2.

Distributor Part No. Ⓞ	Rot. Ⓞ	Automatic Advance (Distr. Degrees & RPM)						Vacuum Advance (Distr. Degrees)												
		Degs.	RPM	Degs.	RPM	Degs.	RPM	Max. Degs.	Deg.	In.Hg.	Deg.	In.Hg.	Deg.	In.Hg.						
C50F-E	CC	2 1/2-3 3/4	650	4-5 1/2	750	6 1/2-7 1/2	1000	7 1/2-8 3/4	1600	8 3/4-9 3/4	2000	14				
C7AF-E	CC	0-1/2	300	2 1/2-3 1/4	500	4 3/4-6 1/4	1000	7-8 1/4	1500	8 3/4-10 1/4	2000	14	0-1	5	3 1/2-8 3/4	10	7 1/2-10 1/2	15	9-12	20
C7AF-J	CC	0-1/2	300	1 1/2-2 1/2	500	4 3/4-5 3/4	1000	6 3/4-8	1500	8 3/4-10 1/4	2000	14	0-3/4	5	1-4 1/2	10	7-10	15	9 1/2-12 1/2	20
C7AF-U	CC	0-1	375	5 3/4-6 3/4	550	7 1/2-8 3/4	1300	9 3/4-11 1/4	2000	14	0-1 1/2	8	0-4	9.5	4 1/4-7 1/4	12	11-18	16.4
C7AF-AA	CC	0-1/2	350	1/2-1 1/2	500	6 1/4-7 1/2	1000	8 3/4-9 3/4	1500	10 1/4-12	2000	14	0-1	5	4 1/4-7	10	8 1/2-11 1/2	15	8 1/2-11 1/2	20
C7AF-AC	CC	0-1/2	350	1-2	500	6 3/4-7 3/4	1000	8 3/4-10	1500	10 3/4-12 1/4	2000	14	0-1	5	1-5	10	7-10	15	9 1/2-12 1/2	25
C7AF-AD	CC	0-1/2	300	1/4-1 1/4	500	3 1/2-4 1/2	1000	5 3/4-7 1/4	1500	8 1/4-9 3/4	2000	14	0-1	5	5-8	10	9 1/2-12 1/2	15	9 1/2-12 1/2	20
C7AF-AG	CC	1/2-1 1/2	550	5 1/4-6 1/4	850	7 1/2-8 3/4	1400	10-11 1/2	2000	14	0-1	5	1/2-3 1/2	6	5-8	9	9 1/2-12 1/2	15
C7MF-G	CC	0-1/2	300	2 1/4-3 1/4	500	5-6 1/4	1000	6 3/4-8 1/4	1500	8 3/4-10	2000	14	0-1	5	3 1/2-6 1/2	10	8-11	15	9 1/2-12 1/2	20
C7MF-H	CC	0-1/2	300	2-3	500	6 3/4-7 3/4	1000	8 3/4-10	1500	10 3/4-12 1/4	2000	14	0-1	5	3 1/2-6 1/2	10	8-11	15	9 1/2-12 1/2	20
C7OF-A	CC	0-1/2	400	4 1/4-5 3/4	800	7 1/2-8 1/2	1000	9 3/4-11	1500	12-13 3/4	2000	14	0-1	5	3 1/2-6 1/2	10	7 1/4-10 1/4	15	8-11	17
C7OF-B	CC	0-1/2	300	2 3/4-3 3/4	500	7 1/4-8 3/4	1000	9-10 1/2	1500	10 3/4-12	2000	14	0-1	5	5-8	10	9 1/4-12 1/4	15	9 1/2-12 1/2	20
C7OF-D	CC	0-1/2	300	3-4	600	8-9	1000	10 1/4-11 1/2	1500	12 1/2-14	2000	16	0-1	5	6-9 1/2	10	9 1/2-12 1/2	15	9 1/2-12 1/2	20
C7OF-F	CC	0-1/2	350	2-3	500	9 1/2-10 1/2	1000	11 1/4-12 1/2	1500	13-14 1/2	2000	16	0-1	5	1-4 3/4	10	7-10	15	8-11	20
C7OF-G	CC
C7OF-H	CC	0-1/2	300	3 1/4-4 1/2	500	6 1/4-7 1/4	1000	8 3/4-9 3/4	1500	9 3/4-11 1/4	2000	14	0-1	5	1-5	10	6-9	15	6-9	13.8
C7SF-A	CC	0-1/2	300	2 1/4-3 1/4	500	5-6 1/4	1000	6 3/4-8 1/4	1500	8 3/4-10	2000	14	0-3/4	5	1-4 1/4	10	7-10	15	9 1/2-12 1/2	20
C7SF-B	CC	0-1/2	300	2-3	500	6 1/2-7 1/4	1000	6 3/4-8 1/4	1500	10 3/4-12 1/4	2000	16	0-3/4	5	1-4 3/4	10	7-10	15	9 1/2-12 1/2	20
C7VF-A	CC	0-1/2	300	1 3/4-3 1/4	400	4 1/2-5 1/2	1000	5 1/4-6 3/4	1500	6 1/4-7 3/4	2000	-	0-1	5	1-4 1/2	10	7-10	15	9 1/2-12 1/2	20
C7ZF-A	CC	0-1/2	300	2 1/2-3 1/2	600	6 1/2-7 3/4	1000	7 1/2-8 3/4	1500	8 1/2-10	2000	11	0-1	5	3 1/2-6 3/4	10	7 1/4-10 1/4	15	8-11	20
C7ZF-D	CC	0-1/2	300	1 3/4-2 3/4	500	10 1/4-11 1/4	1000	11-12 1/4	1500	11 1/2-13	2000	14	0-1	5	3-6	10	4 1/2-7 1/2	15	4 1/2-7 1/2	20
C7ZF-E	CC	0-1/2	300	3-4 1/4	500	10-11 1/4	1000	10 3/4-12	1500	11 1/4-12 3/4	2000	14	0-1	5	6 1/2-9 1/2	10	9 1/2-12 1/2	15	9 1/2-12 1/2	20
C7ZF-F	CC	0-1	390	6 1/2	600	7 1/4	1200	8 3/4-10 1/4	2000	14	0-3	5.8	6 1/4-9 1/4	10	9 1/2-12 1/2	14.5
C8AF-A	C	0-1/2	350	0-1 1/2	750	2 1/4-4 1/2	1000	6-8	1500	7 1/2-10	2000	0-3/4	5	1-3 3/4	10	5 1/2-8	15	5 1/2-8	25
C8AF-B	C	0-1/2	350	0-1/2	500	2 1/4-5	1000	4 1/2-6 3/4	1500	6 1/4-8 3/4	2000	11	0-1	5	3-6	10	6 1/2-9	15	6 1/2-9	25
C8AF-E	CC	0-1/2	350	0-1 3/4	500	6-8 1/4	1000	8-10 1/4	1500	10-12 1/2	2000	14	0-3/4	5	0-3	10	5 1/2-8 1/2	15	8 1/2-11	25
C8AF-J	CC	0-1/2	350	0-2	500	6 3/4-8 3/4	1000	8 3/4-11	1500	10 3/4-13 1/4	2000	14	0-1	5	1-5	10	7-10 1/4	15	10-12 1/2	25
C8AF-M	CC	0-1/2	350	1/2-2 1/2	500	3 1/2-5 1/2	1000	5 3/4-8 1/4	1500	8 1/4-10 3/4	2000	11	0-1	5	4-6 3/4	10	9 1/4-12 1/4	15	10-12 1/2	25
C8AF-R	CC	0-1/2	350	0-2	500	5 3/4-9 3/4	1000	7 3/4-10	1500	9 3/4-12 1/4	2000	14	0-3/4	5	1-4 3/4	10	6 1/4-9 3/4	15	10-12 1/2	25
C8AF-S	CC	0-1/2	350	1-3	500	5 1/4-7 1/4	1000	7 3/4-10	1500	9 3/4-12 1/4	2000	14	0-1	5	3 1/4-6 1/4	10	8-11	15	10-12 1/2	25
C8AF-T	CC	0-1/2	350	2 1/4-4 1/4	750	5 3/4-7 3/4	1000	7 3/4-10	1500	9 3/4-12 1/4	2000	14	0-3/4	5	1-4 3/4	10	6 3/4-10	15	10-12 1/2	25
C8AF-Y	CC	0-1/2	350	2 3/4-4 3/4	750	5 3/4-7 3/4	1000	7 3/4-10	1500	9 3/4-12 1/4	2000	14	0-3/4	5	1-4 3/4	10	7-10	15	9 1/2-12 1/2	20
C8DF-A	C	0-1/2	350	0-2	500	6 1/4-8 1/4	1000	8 3/4-11	1500	10 1/2-13	2000	14	0-1	5	3-6	10	5 1/2-8	15	5 1/2-8	25
C8DF-B	C	0-1/2	350	1-3	750	3 1/4-5 1/4	1000	8 1/2-10 1/2	1500	12-14	2000	14	0-3	5	6-9	10	7-9 1/2	15	7-9 1/2	25
C8DF-C	C	0-1/2	350	0-2	500	6 1/2-8 1/2	1000	8 1/4-10 1/2	1500	9 1/2-12	2000	14	0-1	5	6 3/4-9 1/2	10	10-12 1/2	15	10-12 1/2	25
C8DF-D	C	0-1/2	350	0-1 1/4	500	4 1/4-6 3/4	1000	9-11 1/4	1500	12-14	2000	14	0-1	5	6 1/2-9 1/2	10	8 1/2-11	15	8 1/2-11	25

Ⓞ - Part No. prefix and suffix stamped on housing. Ⓞ - C (Clockwise), CC (Counterclockwise) viewed from rotor end.
Basic Ford Part No. (omitted) is "12127".

FORD MOTOR CO. DUAL ADVANCE DISTRIBUTOR ADVANCE SPECIFICATIONS (Continued)

NOTE - FOR ENGINE RPM AND DEGREES, MULTIPLY SPECIFICATIONS BELOW BY 2.

Distributor Part No. ①	Rot. ②	Automatic Advance (Distr. Degrees & RPM)						Vacuum Advance (Distr. Degrees)												
		Degs.	RPM	Degs.	RPM	Degs.	RPM	Max. Degs.	Deg. In. Hg.	Deg. In. Hg.	Deg. In. Hg.	Deg. In. Hg.								
C80F-C	CC	0-1/2	350	0-1 3/4	500	6-8 1/4	1000	8-10 1/4	1500	10-12 1/2	2000	14	0-1	5	2-5	10	5 3/4-8 3/4	15	9-11 1/2	25
C80F-D	CC	0-1/2	350	3/4-2 3/4	500	8 1/2-10 1/2	1000	10 1/4-12 1/2	1500	12-14 1/2	2000	16	0-3/4	5	1 1/4-4 3/4	10	6 3/4-9 1/2	15	7-9 1/2	25
C8TF-F	CC	0-1/2	350	0-1/2	500	3 1/2-5 1/2	1000	7-9	1500	8 3/4-11	2000	11	0-1	5	2-5	10	5 3/4-8 3/4	15	9-11 1/2	25
C8VF-A	CC	0-1/2	350	2 1/2-4 1/2	750	6 1/2-8 1/2	1000	8-10 1/4	1500	9-11 1/2	2000	14	0-1	5	1-4	10	6-9	15	9 1/2-12	25
C8VF-C	CC
C8VF-F	CC	0-1/2	350	0-1 1/4	500	4 1/4-6 3/4	1000	5 3/4-8 3/4	1500	7-9 1/4	2000	11	0-1	5	1/2-4 1/4	10	6-9	15	9 1/2-12	25
C8VF-G	CC	0-1/2	350	3/4-2 3/4	750	4 1/2-6 1/2	1000	6-8 3/4	1500	7-9 1/2	2000	11	0-1	5	1-4 1/4	10	8 1/2-11 1/2	15	9 1/2-12	20
C8WF-A	C	0	500	4-6	800	9 1/4-12	2000	12	2000	16	0	1	0-4	9.5	7-10	15
C8WF-B	CC	0-1/2	350	1/2-1 1/2	500	5-7	1000	7 1/2-9 3/4	1500	9 3/4-12 1/4	2000	14	0-3/4	5	1-4 3/4	10	7-10	15	10-12 1/2	25
C8ZF-A	CC	0-1/2	350	3/4-2 3/4	500	5 1/2-7 1/2	1000	6 1/4-8 1/2	1500	7-9 1/2	2000	11	0-1	5	4 3/4-8	10	8-10 1/2	15	8-10 1/2	25
C8ZF-B	CC
C8ZF-D	CC	0-1/2	350	1-3	750	3 3/4-5 1/4	1000	6 1/4-8 1/2	1500	7-9 1/2	2000	11	0-3/4	5	1-4	10	5 1/2-8 1/2	15	6 1/2-9	25

① - Part No. prefix and suffix stamped on housing. ② - C (Clockwise), CC (Counterclockwise) viewed from rotor end. Basic Ford Part No. (omitted) is "12127".

FORD MOTOR CO. LOADOMATIC DISTRIBUTOR ADVANCE SPECIFICATIONS

NOTE - FOR ENGINE RPM AND DEGREES, MULTIPLY SPECIFICATIONS BELOW BY 2.

Distributor Part No. ①	Rot. ②	Distributor Advance (Distributor Degrees & RPM)												
		Degs.	Vacuum	RPM	Degs.	Vacuum	RPM	Degs.	Vacuum	RPM	Degs.	Vacuum	RPM	Max. Adv.
C5DF-C ③	C	0-1	.5	625	5 1/4	1.3	1000	9 1/2	3	1600	11 1/2	3.9	2000	1 1/2
		13 1/2	5	500	13 3/4	6	800	13 3/4	6.3	1200	14	5.6	1600	14
C5DF-E ③	C	0-10	.3	550	7 3/4-8 3/4	6	1100	5 1/2-12	3.8	2000	12
		14-15	7.9	900	12 3/4	7	1600	12
C5DF-K ③	C	0-1	.44	712	3 3/4-4 3/4	1.9	1200	7-8 3/4	3.8	2000	8 3/4
		11-12	7.9	1100	12-15 1/2	7	1600	15 1/2
C6AF-Y ③	C	0-1	.72	740	5	2.1	1200	10	4.8	2000	10
		10 1/2	6.5	600	12	7	900	10 3/4	5	1600	10 3/4
C6TF-A ③		0-1	.55	550	6 3/4	1.6	1000	10	3.3	1500	12	4.9	2000	12
		11 1/2	5.5	600	13 1/4	6.9	900	12	6.7	1400	13	6	1700	13
C6TF-AC	C	4 1/2-5 1/2	1.20	800	7 1/2-8 3/4	2.10	1200	9 1/4-10 1/2	3.70	1600	10 3/4-11 3/4	4.90	2000	14
C70F-K	CC	3 3/4-5 1/4	750	7 1/4-9 1/4	1000	9 1/4-10 1/2	1500	9-11 1/2	2000	14

① - Part No. prefix and suffix stamped on housing. ② - Wide open throttle vacuum advance. Basic Ford Part No. (omitted) is "12127".

③ - C (Clockwise), CC (Counterclockwise) viewed from rotor end. ④ - Part throttle vacuum advance.

1968 Distributor Specifications

DELCO-REMY DISTRIBUTOR ADVANCE SPECIFICATIONS

NOTE - FOR ENGINE RPM AND DEGREES, MULTIPLY SPECIFICATIONS BELOW BY 2.

Distributor Part No.	Rot ①	Automatic Advance (Distr. Degrees & RPM)				Vacuum Advance (Distr. Deg. & In. of Hg.)				Vacuum Unit No.		
		Deg.	RPM	Deg.	RPM	Start Deg.	In. Hg.	Max. Deg.	In. Hg.			
1110307	C	0-2	475	10-12	1200	17-19	1700	0	5-7	11.5	11.5-13	1116198
1110311	C	0-2	975	5-7	1600	0	6-8	12	14.5-15.5	1116230
1110319	C	0-2	500	1-3	600	1500	0	6-8	12	14.5-15.5	1116230
1110371	C	0-4	500	7-11	675	740	0	5-7	11	13.8-14	1116248
1110389	C	0-3	500	6-8	700	0	6-8	12	14.5-15.5	1116230
1110399	C	1.5-3.5	600	7.5-9.5	975	0	6-8	11.5	15.5-17	1116217
1110426	C	1.5-3.5	600	6-8	850	0	6-8	12	14.5-15.5	1116230
1110430	C	0-4.8	500	4.8-9.5	600	0	4-6	7.5⊙	9.2-10.2	1973413
1110431	C	0-1.9	500	6-8	825	0	4-6	7.5⊙	9.2-10.2	1973414
1110433	C	.6-2.6	600	7.5-9.5	1050	0	6-8	11.5	15.5-17	1116217
1110434	C	2-4	800	0	6-8	12	14.5-15.5	1116230
1110436	C	0-3.8	550	3-5	630	1050	0	6-8	11.5	15.5-17	1116217
1110437	C	.6-2.6	600	7.5-9.5	1050	0	6-8	11.5	15.5-17	1116217
1110438	C	0-3.8	550	3-5	630	1050	0	6-8	11.5	15.5-17	1116217
1110439	C	0-3	500	2.2-5.2	580	975	0	6-8	11.5	15.5-17	1116217
1110441	C	0-3	500	2.2-5.2	580	975	0	6-8	11.5	15.5-17	1116217
1110442	C	0-1.9	500	8.5-10.5	1000	0	6-8	11.5	15.5-17	1116217
1110443	C	0-3	500	2.2-5.2	580	1000	0	6-8	11.5	15.5-17	1116217
1110444	C	0-3	350	0-3.5	400	1000	0	5-7	11	15.5-17	1116207
1110447	C	0-2.1	500	7.5-9.5	850	0	6-8	12	14.5-15.5	1116230
1110449	C	0-1.9	500	6-8	825	0	4-6	7.5	9.2-10.2	1973413
1111106	C	.6-2.6	500	7.5-9.5	925	0	4-6	12	18-19.3	1115362
1111150	C	1.5-3.5	600	4-6	750	1000	0	7-9	8	15-17	1116201
1111168	C	0-2.2	500	3.2-5.5	640	850	0	9-11	8	16.5-17.5	1968861
1111169	C	0-2.7	500	2.5-5	600	1000	0	7-9	8	15-16	1116201
1111170	C	0-2.7	500	2.5-5	600	1000	0	6-8	6.4	11.3-12.5	1115360
1111191	C	.5-2.5	500	7.5-9.5	1000	0	8-10	12	18.5-20.5	1115363
1111194	C	0-3	500	1.5-4.5	550	750	0	5-7	8	11.2-12.7	1115355
1111198	C	.5-2.5	450	7.5-9.5	800	0	4-6	12	18-19.3	1115362
1111239	C	.3-2.3	400	7.3-9.3	975	0	8-10	12.5⊙	18.5-20.5	1973409
1111257	C	.7-2.7	600	4-6	800	0	5-7	8	11.2-12.7	1115355
1111264	C	0-3	525	4.7-7.7	680	900	0	9-11	8	16.5-17.5	1968861
1111266	C	0-2.6	550	10.3-13	960	980	0	9-11	8	16.5-17.5	1968861
1111270	CC	0-2	500	5-7	1000	0	10-12	10⊙	17-18.8	1973412

① - C (Clockwise); CC (Counterclockwise) viewed from rotor end ⊙ - Maximum retard is 1.75-3.25° at 11" Hg ⊙ - Maximum retard is 4-6° at 11" Hg

1968 Distributor Specifications

DELCO-REMY DISTRIBUTOR ADVANCE SPECIFICATIONS (Continued)

NOTE - FOR ENGINE RPM AND DEGREES, MULTIPLY SPECIFICATIONS BELOW BY 2.

Distributor Part No.	Rot. ①	Automatic Advance (Distr. Degrees & RPM)			RPM			Vacuum Advance (Distr. Deg. & In. of Hg.)		Vacuum Unit No.		
		Deg.	RPM	Deg.	Deg.	RPM	Start Deg.	In. Hg.	Max. Deg.		In. Hg.	
1111272	CC	.5-2.5	500	7.5-9.5	950	15-17	0	8-10	10③	15-17	1973411
1111277	C	0-2.6	500	2-4.7	580	2500	14.3-17	0	6-8	8	14.5-15.75	1116201
1111278	C	0-2.6	500	2-4.7	580	2500	14.3-17	0	6-8	6.4	11.3-12.5	1115360
1111281	CC	1-3	550	6.5-8.5	975	11-13	0	8-10	10③	15-17	1973411
1111282	CC	1.5-3.5	700	4-6	1000	8-10	0	8-10	10③	15-17	1973411
1111284	C	.4-2.4	450	8.5-10.5	875	13-15	0	6-8	8	14.5-15.75	1116210
1111285	C	0	500-600	9.5-11.5	900	15-17	0	6-8	7-9	16	1116210
1111286	CC	0-1.8	400	1.7-4	500	2.2-4.2	14-16	0	8-10	12.5	18.5-20.5	1973408
1111287	CC	.4-2.4	500	8-10	900	10-12	0	8-10	12.5	18.5-20.5	1973408
1111289	CC	.4-2.4	700	6-8	0	8-10	12.5	18.5-20.5	1973408
1111290	CC	.3-2.3	500	8-10	900	2000	8.8-12	0	8-10	12.5	18.5-20.5	1973408
1111291	CC	0-2	425	8-10	900	2000	11.8-15	0	6-8	13	16-17.5	1973407
1111292	CC	.5-2.5	750	6-8	1500	4.2-8	0	8-10	12.5	18.5-20.5	1973408
1111293	C	0-2.7	500	2.5-5	600	7.5-9.5	15-17	0	6-8	6.4	11.3-12.5	1115360
1111294④	C	0-2.6	500	2-4.7	580	2500	14.3-17	0	6-8	6.4	11.3-12.5	1115360
1111295④	C	.5-3.3	700	6.7-9.5	930	2500	12.7-15.5	0	1115373
1111296④	C	0-2	550	14-16	1900	12.5-16	0	6-8	8	14.5-15.75	1116201
1111297	C	1.5-3.5	600	7.5-9.5	950	14-16	0	9-11	8	16.5-17.5	1968861
1111298	C	0-3	500	2-5	570	1000	16-18	0	6-8	8	14.5-15.75	1116201
1111299	CC	0-2	400	6-8	900	9-11	0	10-12	10	17-18.8	1973412
1111300	CC	0-2	500	5-7	1000	9-11	0	10-12	10③	17-18.8	1973412
1111327	C	.5-3	400	11-13	1000	15-17	0
1111328	C	.4-3	400	10-13	1000	2000	13.8-17	0
1111330	C	0-3	600	7.5-10.5	870	900	13-15	0	6-8	8	14.5-15.75	1116210
1111399	C	0	400-500	7.5-9.5	975	13-15	0	6-8	10-12	17	1116217
1111435	CC	0-2	480	6-8	1000	10-12	0	10-12	10③	17-18.8	1973412
1111438	C	0-3	525	4.7-7.7	680	900	14-16	0	6-8	8	14.5-15.75	1116201
1111439	C	0-2.7	600	5.2-8.4	800	850	15-17	0	5-7	8	11.2-12.7	1115355
1111440	C	0-2	550	3-5	700	17-19	0	5-7	8	11.2-12.7	1115355
1111441④	C	0-3.3	500	6-9	685	2200	12.8-16	0	6-8	8	14.5-15.75	1116201
1111443	C	0-2	600	4.7-7.7	680	15-17	0	5-7	8	11.2-12.7	1115355
1111444	C	0-3	525	6.7-8.7	740	900	14-16	0	6-8	8	14.5-15.75	1116201

① - C (Clockwise); CC (Counterclockwise) viewed from rotor end
 ② - Maximum retard is 4-6° at 11" Hg
 ③ - Breakerless (Pulse Generator) distributor used with transistor or Capacitor Ignition Systems.

1968 Distributor Specifications

DELCO-REMY DISTRIBUTOR ADVANCE SPECIFICATIONS (Continued)

NOTE - FOR ENGINE RPM AND DEGREES, MULTIPLY SPECIFICATIONS BELOW BY 2.

Distributor Part No.	Rot. ①	Automatic Advance (Distr. Degrees & RPM)		Vacuum Advance (Distr. Deg. & h. of Hg.)		Vacuum Unit No.								
		Deg.	RPM	Start Deg. In. Hg.	Max. Deg. In. Hg.									
1111445	C	0-4	500	2.5-6.7	560	9.5-11.5	1000	17-19	2500	0	6-8	8	14.5-15.75	1116201
1111447	CC	0-2	640	3.5-5.5	950	8-10	2400	0	8-10	10③	15-17	1973411
1111448	CC	1-3	700	5-7	1000	9-11	2300	0	10-12	10③	17-18.8	1973412
1111449	CC	1-3	700	5-7	1000	9-11	2300	0	8-10	10③	15-17	1973411
1111450	CC	1.3-3.3	700	6-8	1000	10-12	2300	0	8-10	10	15-17	1973411
1111463	CC	1.4-3.4	550	10-12	2000	0	6-8	13	16-17.5	1973407
1111466	CC	0-2	650	6.5-8.5	1300	11-13	2000	0	6-8	13	16-17.5	1973407
1111467	C	2-4.5	750	10.3-13	1090	10.7-13.1	1100	15-17	2200	0	9-11	8	16.5-17.5	1968861
1111468	CC	.5-2.5	450	7-9	1000	9-11	1900	0	10-12	8.7	16.2-17.8	1973418
1111469	CC	0-2	550	5-7	1000	9-11	1800	0	8-10	12.5	18.5-20.5	1973408
1111470	CC	.5-2.5	450	7-9	1000	9-11	1900	7.8-11	3000	0	10-12	8.7	16.2-17.8	1973418
1111471	CC	0-2	550	5-7	1000	9-11	1800	7.5-11	3000	0	8-10	12.5	18.5-20.5	1973408
1111472	C	.5-2.5	550	7.5-9.5	1000	13-15	2000	0	4-6	12	18-19.3	1115362
1111473	C	0-2.5	450	8-10.5	790	8.5-10.6	805	14-16	2200	0	8-10	12.5	18.5-20.5	1115363
1112795	C	0-2	425	4.5-6.5	800	8-10	1600	11-13	2300

① - C (Clockwise); CC (Counterclockwise) viewed from rotor end

③ - Maximum retard is 4-6° at 11" Hg