

1968 Distributor Specifications

DELCO-REMY DISTRIBUTOR ADVANCE SPECIFICATIONS

NOTE - FOR ENGINE RPM AND DEGREES, MULTIPLY SPECIFICATIONS BELOW BY 2.

| Distributor Part No. | Rot ① | Automatic Advance (Distr. Degrees & RPM) | | | | Vacuum Advance (Distr. Deg. & In. of Hg.) | | | | Vacuum Unit No. | | |
|----------------------|-------|--|-----|----------|-------|---|---------|-----------|---------|-----------------|-----------|---------|
| | | Deg. | RPM | Deg. | RPM | Start Deg. | In. Hg. | Max. Deg. | In. Hg. | | | |
| 1110307 | C | 0-2 | 475 | 10-12 | 1200 | 17-19 | 1700 | 0 | 5-7 | 11.5 | 11.5-13 | 1116198 |
| 1110311 | C | 0-2 | 975 | 5-7 | 1600 | | | 0 | 6-8 | 12 | 14.5-15.5 | 1116230 |
| 1110319 | C | 0-2 | 500 | 1-3 | 600 | | 1500 | 0 | 6-8 | 12 | 14.5-15.5 | 1116230 |
| 1110371 | C | 0-4 | 500 | 7-11 | 675 | | 740 | 0 | 5-7 | 11 | 13.8-14 | 1116248 |
| 1110389 | C | 0-3 | 500 | 6-8 | 700 | | | 0 | 6-8 | 12 | 14.5-15.5 | 1116230 |
| 1110399 | C | 1.5-3.5 | 600 | 7.5-9.5 | 975 | | | 0 | 6-8 | 11.5 | 15.5-17 | 1116217 |
| 1110426 | C | 1.5-3.5 | 600 | 6-8 | 850 | | | 0 | 6-8 | 12 | 14.5-15.5 | 1116230 |
| 1110430 | C | 0-4.8 | 500 | 4.8-9.5 | 600 | | | 0 | 4-6 | 7.5⊙ | 9.2-10.2 | 1973413 |
| 1110431 | C | 0-1.9 | 500 | 6-8 | 825 | | | 0 | 4-6 | 7.5⊙ | 9.2-10.2 | 1973414 |
| 1110433 | C | .6-2.6 | 600 | 7.5-9.5 | 1050 | | | 0 | 6-8 | 11.5 | 15.5-17 | 1116217 |
| 1110434 | C | 2-4 | 800 | | | | | 0 | 6-8 | 12 | 14.5-15.5 | 1116230 |
| 1110436 | C | 0-3.8 | 550 | 3-5 | 630 | | 1050 | 0 | 6-8 | 11.5 | 15.5-17 | 1116217 |
| 1110437 | C | .6-2.6 | 600 | 7.5-9.5 | 1050 | | | 0 | 6-8 | 11.5 | 15.5-17 | 1116217 |
| 1110438 | C | 0-3.8 | 550 | 3-5 | 630 | | 1050 | 0 | 6-8 | 11.5 | 15.5-17 | 1116217 |
| 1110439 | C | 0-3 | 500 | 2.2-5.2 | 580 | | 975 | 0 | 6-8 | 11.5 | 15.5-17 | 1116217 |
| 1110441 | C | 0-3 | 500 | 2.2-5.2 | 580 | | 975 | 0 | 6-8 | 11.5 | 15.5-17 | 1116217 |
| 1110442 | C | 0-1.9 | 500 | 8.5-10.5 | 1000 | | | 0 | 6-8 | 11.5 | 15.5-17 | 1116217 |
| 1110443 | C | 0-3 | 500 | 2.2-5.2 | 580 | | 1000 | 0 | 6-8 | 11.5 | 15.5-17 | 1116217 |
| 1110444 | C | 0-3 | 350 | 0-3.5 | 400 | | 1000 | 0 | 5-7 | 11 | 15.5-17 | 1116207 |
| 1110447 | C | 0-2.1 | 500 | 7.5-9.5 | 850 | | | 0 | 6-8 | 12 | 14.5-15.5 | 1116230 |
| 1110449 | C | 0-1.9 | 500 | 6-8 | 825 | | | 0 | 4-6 | 7.5 | 9.2-10.2 | 1973413 |
| 1111106 | C | .6-2.6 | 500 | 7.5-9.5 | 925 | | | 0 | 4-6 | 12 | 18-19.3 | 1115362 |
| 1111150 | C | 1.5-3.5 | 600 | 4-6 | 750 | | 1000 | 0 | 7-9 | 8 | 15-17 | 1116201 |
| 1111168 | C | 0-2.2 | 500 | 3.2-5.5 | 640 | | 850 | 0 | 9-11 | 8 | 16.5-17.5 | 1968861 |
| 1111169 | C | 0-2.7 | 500 | 2.5-5 | 600 | | 1000 | 0 | 7-9 | 8 | 15-16 | 1116201 |
| 1111170 | C | 0-2.7 | 500 | 2.5-5 | 600 | | 1000 | 0 | 6-8 | 6.4 | 11.3-12.5 | 1115360 |
| 1111191 | C | .5-2.5 | 500 | 7.5-9.5 | 1000 | | | 0 | 8-10 | 12 | 18.5-20.5 | 1115363 |
| 1111194 | C | 0-3 | 500 | 1.5-4.5 | 550 | | 750 | 0 | 5-7 | 8 | 11.2-12.7 | 1115355 |
| 1111198 | C | .5-2.5 | 450 | 7.5-9.5 | 800 | | | 0 | 4-6 | 12 | 18-19.3 | 1115362 |
| 1111239 | C | .3-2.3 | 400 | 7.3-9.3 | 975 | | | 0 | 8-10 | 12.5⊙ | 18.5-20.5 | 1973409 |
| 1111257 | C | .7-2.7 | 600 | 4-6 | 800 | | | 0 | 5-7 | 8 | 11.2-12.7 | 1115355 |
| 1111264 | C | 0-3 | 525 | 4.7-7.7 | 680 | | 900 | 0 | 9-11 | 8 | 16.5-17.5 | 1968861 |
| 1111266 | C | 0-2.6 | 550 | 10.3-13 | 960 | | 980 | 0 | 9-11 | 8 | 16.5-17.5 | 1968861 |
| 1111270 | CC | 0-2 | 500 | 5-7 | 1000 | | | 0 | 10-12 | 10⊙ | 17-18.8 | 1973412 |

① - C (Clockwise); CC (Counterclockwise) viewed from rotor end ⊙ - Maximum retard is 1.75-3.25° at 11" Hg ⊙ - Maximum retard is 4-6° at 11" Hg

1968 Distributor Specifications

DELCO-REMY DISTRIBUTOR ADVANCE SPECIFICATIONS (Continued)

NOTE - FOR ENGINE RPM AND DEGREES, MULTIPLY SPECIFICATIONS BELOW BY 2.

| Distributor Part No. | Rot. ① | Automatic Advance (Distr. Degrees & RPM) | | RPM | | Vacuum Advance (Distr. Deg. & In. of Hg.) | | Vacuum Unit No. | | | | | |
|----------------------|--------|--|---------|----------|-------|---|---------|-----------------|-----------|---------|-------|------------|---------|
| | | Deg. | RPM | Deg. | RPM | Start Deg. | In. Hg. | | Max. Deg. | In. Hg. | | | |
| 1111272 | CC | .5-2.5 | 500 | 7.5-9.5 | 950 | | 15-17 | 2275 | 0 | 8-10 | 10③ | 15-17 | 1973411 |
| 1111277 | C | 0-2.6 | 500 | 2-4.7 | 580 | 15-17 | 2500 | 3000 | 0 | 6-8 | 8 | 14.5-15.75 | 1116201 |
| 1111278 | C | 0-2.6 | 500 | 2-4.7 | 580 | 15-17 | 2500 | 3000 | 0 | 6-8 | 6.4 | 11.3-12.5 | 1115360 |
| 1111281 | CC | 1-3 | 550 | 6.5-8.5 | 975 | | | 2400 | 0 | 8-10 | 10③ | 15-17 | 1973411 |
| 1111282 | CC | 1.5-3.5 | 700 | 4-6 | 1000 | | | 2500 | 0 | 8-10 | 10③ | 15-17 | 1973411 |
| 1111284 | C | .4-2.4 | 450 | 8.5-10.5 | 875 | | | 2300 | 0 | 6-8 | 8 | 14.5-15.75 | 1116210 |
| 1111285 | C | 0 | 500-600 | 9.5-11.5 | 900 | | | 2300 | 0 | 6-8 | 7-9 | 16 | 1116210 |
| 1111286 | CC | 0-1.8 | 400 | 1.7-4 | 500 | 2.2-4.2 | 520 | 2000 | 0 | 8-10 | 12.5 | 18.5-20.5 | 1973408 |
| 1111287 | CC | .4-2.4 | 500 | 8-10 | 900 | | | 2000 | 0 | 8-10 | 12.5 | 18.5-20.5 | 1973408 |
| 1111289 | CC | .4-2.4 | 700 | | | | | 1500 | 0 | 8-10 | 12.5 | 18.5-20.5 | 1973408 |
| 1111290 | CC | .3-2.3 | 500 | 8-10 | 900 | 10-12 | 2000 | 3000 | 0 | 8-10 | 12.5 | 18.5-20.5 | 1973408 |
| 1111291 | CC | 0-2 | 425 | 8-10 | 900 | 13-15 | 2000 | 3000 | 0 | 6-8 | 13 | 16-17.5 | 1973407 |
| 1111292 | CC | .5-2.5 | 750 | 6-8 | 1500 | | | 3000 | 0 | 8-10 | 12.5 | 18.5-20.5 | 1973408 |
| 1111293 | C | 0-2.7 | 500 | 2.5-5 | 600 | 7.5-9.5 | 1000 | 2500 | 0 | 6-8 | 6.4 | 11.3-12.5 | 1115360 |
| 1111294④ | C | 0-2.6 | 500 | 2-4.7 | 580 | 15-17 | 2500 | 3000 | 0 | 6-8 | 6.4 | 11.3-12.5 | 1115360 |
| 1111295④ | C | .5-3.3 | 700 | 6.7-9.5 | 930 | 13.5-15.5 | 2500 | 3000 | | | | | 1115373 |
| 1111296④ | C | 0-2 | 550 | 14-16 | 1900 | | | 3000 | 0 | 6-8 | 8 | 14.5-15.75 | 1116201 |
| 1111297 | C | 1.5-3.5 | 600 | 7.5-9.5 | 950 | | | 2050 | 0 | 9-11 | 8 | 16.5-17.5 | 1968861 |
| 1111298 | C | 0-3 | 500 | 2-5 | 570 | 10-12 | 1000 | 2050 | 0 | 6-8 | 8 | 14.5-15.75 | 1116201 |
| 1111299 | CC | 0-2 | 400 | 6-8 | 900 | | | 2300 | 0 | 10-12 | 10 | 17-18.8 | 1973412 |
| 1111300 | CC | 0-2 | 500 | 5-7 | 1000 | | | 2300 | 0 | 10-12 | 10③ | 17-18.8 | 1973412 |
| 1111327 | C | .5-3 | 400 | 11-13 | 1000 | | | 2200 | | | | | |
| 1111328 | C | .4-3 | 400 | 10-13 | 1000 | 15-17 | 2000 | 3000 | | | | | |
| 1111330 | C | 0-3 | 600 | 7.5-10.5 | 870 | 8.5-10.5 | 900 | 2300 | 0 | 6-8 | 8 | 14.5-15.75 | 1116210 |
| 1111399 | C | 0 | 400-500 | 7.5-9.5 | 975 | | | 2100 | 0 | 6-8 | 10-12 | 17 | 1116217 |
| 1111435 | CC | 0-2 | 480 | 6-8 | 1000 | | | 2300 | 0 | 10-12 | 10③ | 17-18.8 | 1973412 |
| 1111438 | C | 0-3 | 525 | 4.7-7.7 | 680 | 9-11 | 900 | 2350 | 0 | 6-8 | 8 | 14.5-15.75 | 1116201 |
| 1111439 | C | 0-2.7 | 600 | 5.2-8.4 | 800 | 6.7-8.7 | 850 | 2200 | 0 | 5-7 | 8 | 11.2-12.7 | 1115355 |
| 1111440 | C | 0-2 | 550 | 3-5 | 700 | | | 1975 | 0 | 5-7 | 8 | 11.2-12.7 | 1115355 |
| 1111441④ | C | 0-3.3 | 500 | 6-9 | 685 | 14-16 | 2200 | 3000 | 0 | 6-8 | 8 | 14.5-15.75 | 1116201 |
| 1111443 | C | 0-2 | 600 | 4.7-7.7 | 680 | | | 1975 | 0 | 5-7 | 8 | 11.2-12.7 | 1115355 |
| 1111444 | C | 0-3 | 525 | 6.7-8.7 | 740 | 9-11 | 900 | 2350 | 0 | 6-8 | 8 | 14.5-15.75 | 1116201 |

① - C (Clockwise); CC (Counterclockwise) viewed from rotor end
 ② - Maximum retard is 4-6° at 11" Hg
 ③ - Breakerless (Pulse Generator) distributor used with transistor or Capacitor Ignition Systems.

1968 Distributor Specifications

DELCO-REMY DISTRIBUTOR ADVANCE SPECIFICATIONS (Continued)

NOTE - FOR ENGINE RPM AND DEGREES, MULTIPLY SPECIFICATIONS BELOW BY 2.

| Distributor Part No. | Rot. ① | Automatic Advance (Distr. Degrees & RPM) | | Vacuum Advance (Distr. Deg. & h. of Hg.) | | Vacuum Unit No. | | | | | | |
|----------------------|--------|--|-----|--|-------------------|-----------------|------|-------|-------|-------|------------|---------|
| | | Deg. | RPM | Start Deg. In. Hg. | Max. Deg. In. Hg. | | | | | | | |
| 1111445 | C | 0-4 | 500 | 9.5-11.5 | 1000 | 17-19 | 2500 | 0 | 6-8 | 8 | 14.5-15.75 | 1116201 |
| 1111447 | CC | 0-2 | 640 | 3.5-5.5 | 950 | 8-10 | 2400 | 0 | 8-10 | 10③ | 15-17 | 1973411 |
| 1111448 | CC | 1-3 | 700 | 5-7 | 1000 | 9-11 | 2300 | 0 | 10-12 | 10③ | 17-18.8 | 1973412 |
| 1111449 | CC | 1-3 | 700 | 5-7 | 1000 | 9-11 | 2300 | 0 | 8-10 | 10③ | 15-17 | 1973411 |
| 1111450 | CC | 1.3-3.3 | 700 | 6-8 | 1000 | 10-12 | 2300 | 0 | 8-10 | 10 | 15-17 | 1973411 |
| 1111463 | CC | 1.4-3.4 | 550 | | | 10-12 | 2000 | 0 | 6-8 | 13 | 16-17.5 | 1973407 |
| 1111466 | CC | 0-2 | 650 | 6.5-8.5 | 1300 | 11-13 | 2000 | 0 | 6-8 | 13 | 16-17.5 | 1973407 |
| 1111467 | C | 2-4.5 | 750 | 10.3-13 | 1090 | 15-17 | 2200 | 0 | 9-11 | 8 | 16.5-17.5 | 1968861 |
| 1111468 | CC | .5-2.5 | 450 | 7-9 | 1000 | 9-11 | 1900 | 0 | 10-12 | 8.7 | 16.2-17.8 | 1973418 |
| 1111469 | CC | 0-2 | 550 | | | 9-11 | 1800 | 0 | 8-10 | 12.5 | 18.5-20.5 | 1973408 |
| 1111470 | CC | .5-2.5 | 450 | 7-9 | 1000 | 7.8-11 | 3000 | 0 | 10-12 | 8.7 | 16.2-17.8 | 1973418 |
| 1111471 | CC | 0-2 | 550 | 5-7 | 1000 | 7.5-11 | 3000 | 0 | 8-10 | 12.5 | 18.5-20.5 | 1973408 |
| 1111472 | C | .5-2.5 | 550 | 7.5-9.5 | 1000 | 13-15 | 2000 | 0 | 4-6 | 12 | 18-19.3 | 1115362 |
| 1111473 | C | 0-2.5 | 450 | 8-10.5 | 790 | 14-16 | 2200 | 0 | 8-10 | 12.5 | 18.5-20.5 | 1115363 |
| 1112795 | C | 0-2 | 425 | 4.5-6.5 | 800 | 11-13 | 2300 | | | | | |

① - C (Clockwise); CC (Counterclockwise) viewed from rotor end

③ - Maximum retard is 4-6° at 11" Hg