

## 1969 Distributor Specifications

## FORD MOTOR CO. DUAL ADVANCE DISTRIBUTOR ADVANCE SPECIFICATIONS

NOTE - FOR ENGINE RPM AND DEGREES, MULTIPLY SPECIFICATIONS BELOW BY 2.

Distributor Part No. ①	Rot. ②	Automatic advance (Distr. Degrees & RPM)						Vacuum advance (distr. Degrees)											
		Degs.	RPM	Degs.	RPM	Degs.	RPM	Deg. In. Hg.	Deg. In. Hg.	Deg. In. Hg.	Deg. In. Hg.								
C7AF-AA	CC	0-1/2	350	4 1/2-6 1/4	750	5 1/2-7 1/2	1000	7 1/2-9 3/4	1500	9 1/2-12	2000	0-1/2	5	4-7 1/2	10	8 1/2-11 1/2	15	9-11 1/2	20
C7AF-AC	CC	0-1/2	350	4 3/4-6 3/4	750	5 3/4-7 3/4	1000	7 3/4-10	1500	9 3/4-12	2000	0-1	5	1-5	10	7-10	15	9 1/2-12 1/2	20
C7AF-L	CC	0-1/2	300	2-3 1/4	500	6-7 1/4	1000	8 1/4-9 3/4	1400	9-11	2000	0-1	5	1 1/2-4 1/2	10	5 3/4-8 3/4	15	8 1/2-11 1/2	20
C7AF-N	CC	0-1/2	300	1 1/2-2 1/2	500	4 1/2-5 3/4	1000	6 3/4-8	1500	8 3/4-10 1/4	2000	0-3/4	5	1-4 1/4	10	7-10	15	9 1/2-12 1/2	20
C7OF-F	CC	0-1/2	300	2-3	500	9 1/2-10 1/2	1000	11 1/2-12 1/2	1500	13-14 1/2	2000	0-1	5	1-4 1/4	10	7-10	15	8-11	20
C8AF-A	C	0-1/2	300	0-1 1/2	750	2 1/4-4 1/2	1000	6-8	1500	7 1/2-10	2000	0-3/4	5	1-3 1/4	10	5 1/2-8	15	5 1/2-8	20
C8AF-B	CC	0-1/2	350	1 3/4-3 3/4	750	2 3/4-5	1000	4 1/2-6 1/4	1500	6 1/4-8 3/4	2000	0-1	5	3-6	10	6 1/2-9	15	6 1/2-9	20
C8AF-E	CC	0-1/2	350	4 1/2-6 1/4	750	6-8 1/4	1000	8-10 1/4	1500	10-12 1/4	2000	0-3/4	5	0-3	10	5 1/4-8 1/2	15	8 1/4-11	20
C8AF-J	CC	0-1/2	350	0-2	500	5 1/2-7 3/4	750	6 3/4-11	1500	10 3/4-13 1/4	2000	0-1	5	1-5	10	7-10 1/4	20	10 1/4-12 1/2	25
C8AF-R	CC	0-1/2	350	0-2	500	5 3/4-7 3/4	1000	7 3/4-10	1500	9 3/4-12 1/4	2000	0-3/4	5	1-4 1/4	10	6 3/4-9 3/4	15	10-12 1/2	25
C8DF-C	C	0-1/2	350	0-2	500	3 1/2-5 1/4	750	6 1/2-8 1/2	1500	9 1/2-12	2000	0-1	5	6 3/4-9 1/2	10	10-12 1/2	15	10-12 1/2	20
C8DF-D	C	0-1/2	350	2 3/4-4 3/4	750	4 3/4-6 3/4	1000	9-11 1/4	1500	12-14	2000	0-1	5	6 1/2-9 1/2	10	8 1/2-11	15	8 1/2-11	20
C8DF-J	C	0-1/2	350	3 1/4-5 1/4	750	7-9	1000	9 1/2-11 3/4	1500	12 1/4-14 3/4	2000	0-1	5	5 3/4-8 3/4	10	8 1/2-11	15	8 1/2-11	20
C8OF-C	CC	0-1/2	350	0-1 1/4	750	6-8 1/2	1000	8-10 1/4	1500	10-12 1/2	2000	0-1	5	2-5	10	5 3/4-8 3/4	15	9-11 1/2	25
C8OF-D	CC	0-1/2	350	3/4-2 3/4	500	8 1/2-10 1/2	1000	10 1/4-12 1/2	1500	12-14 1/2	2000	0-3/4	5	1 3/4-4 3/4	10	6 3/4-9 1/2	15	7-9 1/2	25
C8OF-G	CC	0-1/2	350	4 1/2-6 1/2	750	7-8 1/4	1000	8-10 1/4	1500	9-11 1/2	2000	0-1	5	1-4 1/4	10	7-10	15	8 1/2-11	20
C8OF-H	CC	0-1/2	350	3/4-2 3/4	500	7 1/2-9 1/2	750	9 1/2-11 3/4	1500	11-13 1/2	2000	0-3/4	5	2-5	10	7-9 1/2	15	7-9 1/2	20
C8OF-J	CC	0-1/2	350	3/4-2 3/4	500	7 1/2-9 1/2	750	9 1/4-12	1500	11-13 1/2	2000	0-3/4	5	1-4 1/4	10	7-10	15	8 1/2-11	20
C8VF-A	CC	0-1/2	500	2 1/2-4 1/2	750	6 1/2-8 1/2	1000	8-10 1/4	1500	9-11 1/2	2000	0-1	5	1-4	10	6-9	15	9 1/2-12	25
C8VF-C	CC	0-1/2	500	2 1/4-4 1/2	750	6 1/2-8 1/2	1000	8-10 1/4	1500	9-11 1/2	2000	0-3/4	5	1/2-4	10	6-9	15	9 1/2-12	25
C8VF-G	CC	0-1/2	500	3/4-2 3/4	750	4 1/2-6 1/2	1000	6-8 1/4	1500	7-9 1/2	2000	0-1	5	1-4 1/2	10	6-9	15	9 1/2-12	25
C9AF-J	CC	0-1/2	350	1/2-2 1/2	500	3 1/2-5 1/2	1000	5 3/4-8 1/4	1500	8 1/4-10 3/4	2000	0-1	5	5-8	10	9 1/2-12 1/4	15	10-12 1/2	20
C9AF-K	CC	0-1/2	500	2 3/4-4 3/4	750	5 3/4-7 3/4	1000	7 3/4-10	1500	9 1/4-12 1/4	2000	0-1	5	3 3/4-6 3/4	10	7-10	15	9-11 1/2	25
C9AF-N	CC	0-1/2	350	1 3/4-3 3/4	500	5 1/2-7 1/2	750	6-8 1/4	1000	8 1/4-10 3/4	2000	0-1	5	3 1/2-6 3/4	10	7 1/2-10 1/2	15	9-11 1/2	20
C9AF-R	CC	0-1/2	350	1 3/4-3 3/4	500	5 1/2-7 1/2	750	7 1/4-9 1/2	1500	8 1/4-10 3/4	2000	0-1	5	3 1/4-6 1/2	10	7 1/2-10 1/2	15	9-11 1/2	20
C9AF-Y	CC	0-1/2	350	2-4	500	5 3/8-8 3/4	750	7 1/2-9	1000	9 1/2-12	2000	0-1	5	2 3/4-6	10	6-8 1/2	15	6-8 1/2	20
C9DF-B	C	0-1 1/2	500	4 1/2-6 1/2	750	7-9	1000	9-11 1/4	1500	11 1/4-13 3/4	2000	0-1	5	5 1/4-8 3/4	10	8 1/2-11	15	8 1/2-11	25
C9OF-M	CC	0-2	500	4 1/4-6 1/4	750	5 1/4-7 1/2	1000	7 1/2-9 3/4	1500	9 3/4-12 1/4	2000	0-1	5	5 1/2-8	10	5 1/2-8	15	5 1/2-8	20
C9OF-N	CC	0-1/2	350	0-2	500	3 3/4-5 1/4	750	6 1/4-8 1/4	1000	8 1/2-11	2000	0-1	5	1-4 1/2	10	5 1/2-8 1/2	15	8-10 1/2	20
C9OF-R	C	0-2	500	4 1/2-6 1/2	750	5 1/2-7 1/2	1000	7 1/4-9 1/2	1500	9-11 1/2	2000	0-3/4	5	3 1/4-6 1/4	10	6-8 1/2	15	6-8 1/2	20
C9OF-T	CC	0-1/2	350	1/4-2 1/4	500	4 1/4-6 1/4	750	8-10 1/4	1000	9 1/2-12	2000	0-1	5	5-8	10	8 3/4-11 3/4	15	10-12 1/2	20
C9OF-U	C	0-1/2	350	1 1/4-3 1/4	500	4 1/2-6 1/2	750	5 1/2-7 1/2	1000	8 3/4-11 3/4	2000	0-1 1/2	5	7-10	10	10-12 1/2	15	10-12 1/2	20
C9OF-V	C	0-1/2	350	2 1/4-4 1/2	500	7 3/4-9 1/4	700	9-11	1000	13 1/2-16	2000	0-1 1/2	5	5-7 3/4	10	6 1/2-9	15	6 1/2-9	20
D0DF-C	C	0-1/2	350	4 3/4-6 3/4	750	9-11	1000	10-12 1/2	1500	11 1/2-13 1/2	2000	0-1	5	4-7	10	4 1/2-7	15	4 1/2-7	20
D0DF-E	C	0-1/2	350	1/4-2 1/2	750	9-9	1000	9 1/2-12	1500	12 1/2-15	2000	0-1	5	5 1/2-8 1/2	10	8 1/2-11	15	8 1/2-11	20

① - Part No. prefix and suffix stamped on housing.  
 Basic Ford Part No. (omitted) is "12127".  
 © - C (Clockwise), CC (counterclockwise)  
 viewed from rotor end.

## DELCO-REMY DISTRIBUTOR ADVANCE SPECIFICATIONS

NOTE - FOR ENGINE RPM AND DEGREES, MULTIPLY SPECIFICATIONS BELOW BY 2.

Distributor Part No.	Rot ①	Automatic Advance (Distr. Degrees & RPM)				Vacuum Advance (Distr. Deg. & In. of Hg.)				Vacuum Unit No.				
		Deg.	RPM	Deg.	RPM	Start Deg.	In. Hg.	Max. Deg.	In. Hg.					
1110439	C	0-3	500	2.2-5.2	580	9.5-11.5	975	15-17	2100	0	6-8	11.5	15.5-17	1116217
1110444	C	0-3	350	0-3.5	400	8-10	1000	12-14	2000	0	5-7	11	15.5-17	1116207
1110452	C	0	450					14	2100	0	7	12	15	1116217
1110453	C	0	350					10	2100	0	7	12	15	1116217
1110454	C	0	450					13	2200	0	7	12	15	1116217
1110455	C	0	400					10	2400	0	7	12	15	1116217
1110457	C	0	450	8.5	850			14	1850	0	7	12	15	-----
1110458	C	0	450	7	850			12	1800	0	7	12	15	-----
1110459	C	0	500	3.5	600	10.5	1050	18	2300	0	7	11.5	16	-----
1110460	C	0	500	8.5	1050			16	2300	0	7	11.5	16	-----
1110463	C	0-3	500	2.2-5.2	580	9.5-11.5	975	15-17	2100	0	6-8	12	17	1116217
1110464	C	0-2	510	1.5-3.5	600	7.5-9.5	975	13-15	2100	0	6-8	12	17	1116217
1110474	C	0-2	550	6-8	875			11.5-13.5	2375	0	5-7	7.5	10.5-11.5	1973419
1110475	C	0-4.5	500	9-11	1050			13-15	2200	0	5-7	7.5	10.5-11.5	1973419
1111106	C	.6-2.6	500	7.5-9.5	925			15-17	2200	0	4-6	12	18-19.3	1115362
1111198	C	.5-2.5	450	7.5-9.5	800			14-16	1950	0	4-6	12	18-19.3	1115362
1111253	CC	0-2	500	5-7	1000			9-11	2300	0	10-12	10	17-18.8	1115374
1111334	C	0	550	8.5-10.5	900			13-15	2300	0	6-8	7-9	16	-----
1111335	C	0	550	9.5-11.5	900			15-17	2300	0	6-8	7-9	16	-----
1111341 ④	CC	.5-2.5	450	7-9	1000	9-11	1900	7.8-11	3000	0	10-12	8.7	16.2-17.8	1973418
1111472	C	.5-2.5	550	7.5-9.5	1000			13-15	2000	0	4-6	12	18-19.3	1115362
1111473	C	0-2.5	450	8-10.5	790	8.5-10.6	805	14-16	2200	0	8-10	12.5	18.5-20.5	1115363
1111474	C	0-2	470	9.5-11.5	890			15-17	2300	0	6-8	8	14.5-15.75	1116210
1111480	C	0	675	11	1100			16	2200	0	8	7.5	15.5	-----
1111481	C	0	500	5	800			14	2150	0	6	7.5	12	-----
1111482	C	0	500	5	700			16	2150	0	6	1.5	12	-----
1111483	C	0	450	6	1000			14	2150	0	6	7.5	12	-----
1111486	C	0	400	1.5	500	7.5	900	18	2050	0	7	6.5	17	-----
1111487	C	0	450	1	650	4	700	16	2200	0	7	6.5	17	-----
1111488	C	0	475	7	700	10	900	15	2350	0	10	5	17	-----
1111489	C	0	450	4.5	650	7.5	750	13	2350	0	10	5	17	-----
1111490	C	0	450	4.5	600	7.5	750	15	2550	0	8	5	17	-----
1111491 ④	C	0-2	575	4-6	850	12-14	2500	11.3-14	3000	0	7-9	8	15-16	1116201
1111493	C	0-2	570	4-6	850			12-14	2500	0	7	7.5	12	111536b
1111497	C	0	450	4.5	625	8.5	1000	16	2500	0	8	7.5	15.5	-----

④ - Breakerless (Pulse Generator) distributors used with Transistor or Capacitor Ignition Systems.

① - C (Clockwise) CC (Counterclockwise) viewed from rotor end.

## 1969 Distributor Specifications

## DELCO-REMY DISTRIBUTOR ADVANCE SPECIFICATIONS (Continued)

NOTE - FOR ENGINE RPM AND DEGREES, MULTIPLY SPECIFICATIONS BELOW BY 2.

Distributor Part No.	Rot ①	Automatic Advance (Distr. Degrees & RPM)				Vacuum Advance (Distr. Deg. & In. of Hg.)				Vacuum Unit No.				
		Deg.	RPM	Deg.	RPM	Start Deg.	In. Hg.	Max. Deg.	In. Hg.					
1111498	C	0	450	6.5	650	10.5	1000	18	2500	0	8	7.5	15.5	---
1111499	C	0	450	4.5	625	8.5	1000	16	2500	0	6	7.5	12	---
1111925	C	0	400	4	625	9.5	1000	13	1900	0	8	7.5	15.5	---
1111926	C	0	400	4	625	8.5	1000	13	1900	0	7	6	12	---
1111927 <sup>Ⓢ</sup>	C	0	600	8	950	14.5	2500	14.5	2500	.....	.....	.....	.....	None
1111928 <sup>Ⓢ</sup>	C	0	450	1	550	.....	.....	15	1900	0	8	7.5	15.5	---
1111930	CC	0-2	400	6-8	900	.....	.....	10-12	2000	0	8-10	9	16.5-18.5	1115361
1111932	CC	.4-2.4	500	8-10	900	.....	.....	10-12	2000	0	8-10	12	18.5-20.5	1973408
1111933	CC	.5-2.5	450	7-9	1000	.....	.....	9-11	1900	0	10-12	8	16-18	1973418
1111934	CC	0-2	400	6.5-8.5	1200	.....	.....	13-15	2000	0	6-8	12	15-17.5	1973407
1111935	CC	.4-2.4	700	.....	.....	.....	.....	6-8	1500	0	8-10	12	18.5-20.5	1973408
1111936	CC	0-2	550	5-7	1000	9-11	1800	9-11	1800	0	8-10	12	18.5-20.5	1973408
1111938	C	0	450	9.5-11.5	975	.....	.....	15-17	2300	0	6-8	7-9	16	.....
1111939	C	0	300	7.25-9.25	975	.....	.....	13-15	2200	0	8-11	12.75	16	.....
1111940	CC	.5-2.5	500	7.5-9.5	950	.....	.....	15-17	2275	0	8-10	10	15-17	1115365
1111941	CC	0-2	660	5-7	1100	.....	.....	10-12	2300	0	8-10	10	15-17	1115365
1111942	CC	1-3	550	6.5-8.5	975	.....	.....	11-13	2400	0	6-8	10	13-14.75	.....
1111945	CC	1.5-3.5	700	4-6	1000	.....	.....	8-10	2500	0	8-10	10	15-17	1115365
1111946	CC	0-2	500	5-7	1000	.....	.....	9-11	2300	0	10-12	10	17-18.8	1115374
1111948	C	0-1	400	0-2.5	450	8.5-10.5	800	14-16	2200	0	4-6	12	18-19.5	1115362
1111949	C	0	450	5.5	650	11	1000	19	2100	0	8	7.5	15.5	.....
1111950	C	0	450	1.5	550	8.5	950	17	2150	0	8	7.5	15.5	.....
1111951	CC	0-2	640	3.5-5.5	950	.....	.....	8-10	2400	0	8-10	10	15-17	1115365
1111952	CC	1-3	700	5-7	1000	.....	.....	9-11	2300	0	10-12	10	17-18.8	.....
1111955	C	0	450	8.5	950	11	1000	16	2200	0	7	6.5	17	.....
1111956	C	0	450	5	600	10.5	1000	16	2200	0	7	12	13	.....
1111959	CC	0-2.2	550	4.5-6.5	1200	.....	.....	10-12	2300	0	8-10	10	15-17	1115365
1111960	CC	1.3-3.3	700	6-8	1000	.....	.....	10-12	2300	0	10-12	10	17-18.8	.....
1111961	CC	0-1.8	400	1.7-4	500	2.2-4.2	520	14-16	2000	0	8-10	12.5	18.5-20.5	1973408

① - C (Clockwise), CC (Counterclockwise) viewed from rotor end.

Ⓢ - Breakerless (Pulse Generator) distributors used with Transistor or Capacitor Ignition Systems.