

DELCO-REMY DISTRIBUTOR ADVANCE SPECIFICATIONS

NOTE - FOR ENGINE RPM AND DEGREES, MULTIPLY SPECIFICATIONS BELOW BY 2.

Distributor Part No.	Rot ①	Automatic Advance (Distr. Degrees & RPM)				Vacuum Advance (Distr. Deg. & In. of Hg.)				Vacuum Unit No.				
		Deg.	RPM	Deg.	RPM	Start Deg.	In. Hg.	Max. Deg.	In. Hg.					
1110439	C	0-3	500	2.2-5.2	580	9.5-11.5	975	15-17	2100	0	6-8	11.5	15.5-17	1116217
1110444	C	0-3	350	0-3.5	400	8-10	1000	12-14	2000	0	5-7	11	15.5-17	1116207
1110452	C	0	450					14	2100	0	7	12	15	1116217
1110453	C	0	350					10	2100	0	7	12	15	1116217
1110454	C	0	450					13	2200	0	7	12	15	1116217
1110455	C	0	400					10	2400	0	7	12	15	1116217
1110457	C	0	450	8.5	850			14	1850	0	7	12	15	-----
1110458	C	0	450	7	850			12	1800	0	7	12	15	-----
1110459	C	0	500	3.5	600	10.5	1050	18	2300	0	7	11.5	16	-----
1110460	C	0	500	8.5	1050			16	2300	0	7	11.5	16	-----
1110463	C	0-3	500	2.2-5.2	580	9.5-11.5	975	15-17	2100	0	6-8	12	17	1116217
1110464	C	0-2	510	1.5-3.5	600	7.5-9.5	975	13-15	2100	0	6-8	12	17	1116217
1110474	C	0-2	550	6-8	875			11.5-13.5	2375	0	5-7	7.5	10.5-11.5	1973419
1110475	C	0-4.5	500	9-11	1050			13-15	2200	0	5-7	7.5	10.5-11.5	1973419
1111106	C	.6-2.6	500	7.5-9.5	925			15-17	2200	0	4-6	12	18-19.3	1115362
1111198	C	.5-2.5	450	7.5-9.5	800			14-16	1950	0	4-6	12	18-19.3	1115362
1111253	CC	0-2	500	5-7	1000			9-11	2300	0	10-12	10	17-18.8	1115374
1111334	C	0	550	8.5-10.5	900			13-15	2300	0	6-8	7-9	16	-----
1111335	C	0	550	9.5-11.5	900			15-17	2300	0	6-8	7-9	16	-----
1111341 ④	CC	.5-2.5	450	7-9	1000	9-11	1900	7.8-11	3000	0	10-12	8.7	16.2-17.8	1973418
1111472	C	.5-2.5	550	7.5-9.5	1000			13-15	2000	0	4-6	12	18-19.3	1115362
1111473	C	0-2.5	450	8-10.5	790	8.5-10.6	805	14-16	2200	0	8-10	12.5	18.5-20.5	1115363
1111474	C	0-2	470	9.5-11.5	890			15-17	2300	0	6-8	8	14.5-15.75	1116210
1111480	C	0	675	11	1100			16	2200	0	8	7.5	15.5	-----
1111481	C	0	500	5	800			14	2150	0	6	7.5	12	-----
1111482	C	0	500	5	700			16	2150	0	6	1.5	12	-----
1111483	C	0	450	6	1000			14	2150	0	6	7.5	12	-----
1111486	C	0	400	1.5	500	7.5	900	18	2050	0	7	6.5	17	-----
1111487	C	0	450	1	650	4	700	16	2200	0	7	6.5	17	-----
1111488	C	0	475	7	700	10	900	15	2350	0	10	5	17	-----
1111489	C	0	450	4.5	650	7.5	750	13	2350	0	10	5	17	-----
1111490	C	0	450	4.5	600	7.5	750	15	2550	0	8	5	17	-----
1111491 ④	C	0-2	575	4-6	850	12-14	2500	11.3-14	3000	0	7-9	8	15-16	1116201
1111493	C	0-2	570	4-6	850			12-14	2500	0	7	7.5	12	111536b
1111497	C	0	450	4.5	625	8.5	1000	16	2500	0	8	7.5	15.5	-----

④ - Breakerless (Pulse Generator) distributors used with Transistor or Capacitor Ignition Systems.

① - C (Clockwise) CC (Counterclockwise) viewed from rotor end.

1969 Distributor Specifications

DELCO-REMY DISTRIBUTOR ADVANCE SPECIFICATIONS (Continued)

NOTE - FOR ENGINE RPM AND DEGREES, MULTIPLY SPECIFICATIONS BELOW BY 2.

Distributor Part No.	Rot ①	Automatic Advance (Distr. Degrees & RPM)				Vacuum Advance (Distr. Deg. & In. of Hg.)				Vacuum Unit No.				
		Deg.	RPM	Deg.	RPM	Start Deg.	In. Hg.	Max. Deg.	In. Hg.					
1111498	C	0	450	6.5	650	10.5	1000	18	2500	0	8	7.5	15.5	---
1111499	C	0	450	4.5	625	8.5	1000	16	2500	0	6	7.5	12	---
1111925	C	0	400	4	625	9.5	1000	13	1900	0	8	7.5	15.5	---
1111926	C	0	400	4	625	8.5	1000	13	1900	0	7	6	12	---
1111927 [Ⓢ]	C	0	600	8	950	14.5	2500	14.5	2500	None
1111928 [Ⓢ]	C	0	450	1	550	15	1900	0	8	7.5	15.5	---
1111930	CC	0-2	400	6-8	900	10-12	2000	0	8-10	9	16.5-18.5	1115361
1111932	CC	.4-2.4	500	8-10	900	10-12	2000	0	8-10	12	18.5-20.5	1973408
1111933	CC	.5-2.5	450	7-9	1000	9-11	1900	0	10-12	8	16-18	1973418
1111934	CC	0-2	400	6.5-8.5	1200	13-15	2000	0	6-8	12	15-17.5	1973407
1111935	CC	.4-2.4	700	6-8	1500	0	8-10	12	18.5-20.5	1973408
1111936	CC	0-2	550	5-7	1000	9-11	1800	9-11	1800	0	8-10	12	18.5-20.5	1973408
1111938	C	0	450	9.5-11.5	975	15-17	2300	0	6-8	7-9	16
1111939	C	0	300	7.25-9.25	975	13-15	2200	0	8-11	12.75	16
1111940	CC	.5-2.5	500	7.5-9.5	950	15-17	2275	0	8-10	10	15-17	1115365
1111941	CC	0-2	660	5-7	1100	10-12	2300	0	8-10	10	15-17	1115365
1111942	CC	1-3	550	6.5-8.5	975	11-13	2400	0	6-8	10	13-14.75
1111945	CC	1.5-3.5	700	4-6	1000	8-10	2500	0	8-10	10	15-17	1115365
1111946	CC	0-2	500	5-7	1000	9-11	2300	0	10-12	10	17-18.8	1115374
1111948	C	0-1	400	0-2.5	450	8.5-10.5	800	14-16	2200	0	4-6	12	18-19.5	1115362
1111949	C	0	450	5.5	650	11	1000	19	2100	0	8	7.5	15.5
1111950	C	0	450	1.5	550	8.5	950	17	2150	0	8	7.5	15.5
1111951	CC	0-2	640	3.5-5.5	950	8-10	2400	0	8-10	10	15-17	1115365
1111952	CC	1-3	700	5-7	1000	9-11	2300	0	10-12	10	17-18.8
1111955	C	0	450	8.5	950	11	1000	16	2200	0	7	6.5	17
1111956	C	0	450	5	600	10.5	1000	16	2200	0	7	12	13
1111959	CC	0-2.2	550	4.5-6.5	1200	10-12	2300	0	8-10	10	15-17	1115365
1111960	CC	1.3-3.3	700	6-8	1000	10-12	2300	0	10-12	10	17-18.8
1111961	CC	0-1.8	400	1.7-4	500	2.2-4.2	520	14-16	2000	0	8-10	12.5	18.5-20.5	1973408

① - C (Clockwise), CC (Counterclockwise) viewed from rotor end.

Ⓢ - Breakerless (Pulse Generator) distributors used with Transistor or Capacitor Ignition Systems.