

CHRYSLER & PRESTOLITE DISTRIBUTOR ADVANCE SPECIFICATIONS

NOTE - FOR ENGINE RPM AND DEGREES, MULTIPLY SPECIFICATIONS BELOW BY 2.

Distributor Part No.	Rot. ①	Automatic Advance (Distr. Degrees & RPM)				Vacuum Advance (Distr. Degrees & Inches of Hg.)					
		Deg.	RPM	Deg.	RPM	Deg.	In. Hg.	Deg.	In. Hg.		
2875822	C	1-5	550	9.2-11.2	900	12-14	2000	5-3.5	10	5.25-7.75	15
2875826	C	1-5	550	9.2-11.2	900	12-14	2000	5-3.5	7	5.25-7.75	10
2875982 ②	CC	0-5.3	600	9-11	850	12-14	2400	5-3.5	11	9.5-12.5	15.5
2875987 ③	CC	0-4.5	650	12.2-14.2	1050	14-16	1600	0-3.5	9	6.7-9.2	13.5
2875989 ④	CC	0-4.2	600	9.7-11.7	950	11.5-13.5	1600	0-3.5	9	6.7-9.2	13.5
3438219	CC	5-3.7	650	5.7-7.7	900	12-14	2300	5-4.3	10.5	9.7-12	15.5
3438222	CC	0-4.6	600	5.6-7.6	800	10-12	2300	5-4.3	10.5	9.7-12	15.5
3438225	C	1-6	550	8.5-10.5	800	12-14	2100	1.25-4.25	12	8.25-10.75	15
3438231	CC	0-3.8	550	7.5-9.5	850	14-16	2200	5-4	7.5	9.3-11.8	12
3438233	CC	0-4.6	600	5.6-7.6	800	10-12	2300	5-4.3	10.5	9.7-12	15.5
3438237	C	0-7.5	525	9.3-11.3	750	12-14	1600	5-3.5	7	5.25-7.75	10
3438255	C	1-6	550	8.5-10.5	800	14-16	2100	1-4	10.5	8.25-10.75	15
3438314 ⑤	CC	0-4.5	650	9-11	950	12-14	2400	5-3.5	11	9.5-12.5	15.5
3438317 ⑥	C	1.5-6.5	700	8-10	900	1-4.6	7.7	7-10	10.5
3438325	C	1.5-5.5	650	8-10	850	1-4.6	7.7	7-10	10.5

① - C (Clockwise), CC (Counterclockwise) viewed from rotor end.

② - Prestolite Built IBS-4014E.

③ - Prestolite Built IBS-4014.

④ - Prestolite Built IBS-4014D.

⑤ - Prestolite Built IBS-4014F.

⑥ - Prestolite Built IBS-4015B.

DELCO-REMY DISTRIBUTOR ADVANCE SPECIFICATIONS

NOTE - FOR ENGINE RPM AND DEGREES, MULTIPLY SPECIFICATIONS BELOW BY 2.

Distributor Part No.	Rot. ①	Automatic Advance (Distr. Degrees & RPM)				Vacuum Adv. (Distr. Degrees & In. of Hg.)				Vacuum Unit No.		
		Deg.	RPM	Deg.	RPM	Deg.	In. Hg.	Max. Deg.	In. Hg.			
1110439	C	0-3	500	2.2-5.5	580	15-17	2100	0	6-8	11.5	15.5-17	116217
1110444	C	0-3	350	1.9-3.9	440	12-14	2000	0	5-7	11	15.5-17	116207
1110457	C	0-2.1	500	7.5-9.5	850	13-15	1850	0	6-8	12	14.5-15.5	116230
1110458	C	7-2.7	550	6-8	850	11-13	1800	0	6-8	12	14.5-15.5	116230
1110459	C	0-3.8	550	3-5	630	17-19	2300	0	6-8	11.5	15.5-17	116217
1110460	C	6-2.6	600	7.5-9.5	1050	15-17	2300	0	6-8	11.5	15.5-17	116217
1110463	C	0-3	500	7.5-9.5	975	15-17	2100	0	6-8	11.5	15.5-17	116217
1110464	C	1.5-3.5	600	7.5-9.5	975	13-15	2100	0	6-8	11.5	15.5-17	116217
1110481	C	0-2	437	7-9	1050	11-13	2750	0	5-7	9	13.5-14.25	1973425 ③
1110482	C	1.5-3.5	600	7.5-9.5	975	13-15	2100	0	6-8	11.5	15.5-17	116217
1110483	C	0-3	500	9.5-11.5	975	15-17	2100	0	6-8	11.5	15.5-17	116217
1111105	CC	0-1.5	500	0-2	625	7-9	2200	0	8-10	10	15-17	115365
1111148	CC	1-2.1	500	5-7	950	12-14	2300	0	8-10	10	15-17	115365
1111176	CC	5-2.5	650	5-7	950	12-14	2350	0	8-10	10	15-17	115365
1111436	C	0-2	550	7.5-9.5	1050	12-14	2000	0	7-9	8	15-16	116201
1111437	C	0-2.7	500	2.2-4.9	590	12-14	1900	0	6-8	6.4	11.3-12.5	115360
1111473	C	0-2.5	450	8-10.5	790	14-16	2200	0	8-10	12.5	18.5-20.5	115363

1970 Distributor Specifications

DELCO-REMY DISTRIBUTOR ADVANCE SPECIFICATIONS (Cont.) NOTE - FOR ENGINE RPM AND DEGREES, MULTIPLY SPECIFICATIONS BELOW BY 2.

Distributor Part No.	Ret. Ⓢ	Automatic Advance (Distr. Degrees & RPM)				Vacuum Adv. (Distr. Degrees & In. of Hg.)				Vacuum Unit No.				
		Deg.	RPM	Deg.	RPM	Deg.	RPM	In. Hg.	Max. Deg.		In. Hg.			
111492	C	0-2	500	2.5-4.5	625	9-11	1225	15-17	2200	0	7-9	8	15-16	1116201
111494	C	0-2	541			5-7	1000	13-15	2200	0	7-9	8	15-16	1116201
111939	CC	.3-2.3	400			7.3-9.3	975	13-15	2200	0	8-10	12	13-15.8	1973409
111948	C	0-2.5	450	8-10.5	790	8.5-10.6	805	14-16	2200	0	4-6	12	18-19.3	1115362
111962	C	0-1.9	500			4.5-6.5	900	10-12	2300	0	6-8	8	14.5-15.75	1116210
111963	C	1-3	610			7.5-9.5	1050	10-12	1600	0	7-9	8	15-16	1116201
111964	C	1.3-3.3	600			6.5-8.5	900	13-15	2400	0	6-8	8	14.5-15.75	1116210
111975	CC	.5-2.5	450			6.5-8.5	750	12-14	2050	0	8-10	9	17.2-19	1115361
111976	CC	0-2	400			7.7-9.7	1025	14-16	2000	0	8-10	12.5	18.5-20.5	1973408
111977	CC	.4-2.4	500			8-10	900	10-12	2000	0	8-10	12.5	18.5-20.5	1973408
111978	CC	.5-2.5	450			7-9	1000	9-11	1900	0	10-12	8.7	16.2-17.8	1973418
111979	CC	0-3.5	375	7-10.3	575	8.6-10.6	625	14-16	1500	0	11-13	8.75	17.2-19	1973427
111980	CC	0-2	400			6.5-8.5	1200	13-15	2000	0	6-8	13	16-17.5	1973407
111981	CC	.4-2.4	700					6-8	1500	0	8-10	9	17.2-19	1115361
111982	CC	0-2	550			5-7	1000	9-11	1800	0	8-10	12.5	18.5-20.5	1973408
111984	C	1.2-3.4	600	7-9.2	860	7.2-10	900	13-15	2300	0	6-8	8	14.5-15.75	1116210
111986	C	0-1.9	500			4.5-6.5	900	10-12	2300	0	6-8	8	14.5-15.75	1116210
111987	C	0-2	450			6-8	750	11-13	2000	0	5-7	9	14-15.5	1973426 ②
111988	C	0-1.8	500			5-7	825	12-14	2100	0	5-7	9	14-15.5	1973426 ②
111995	C	.7-2.7	600			4-6	800	14	2150	0	5-7	8	11.2-12.7	1115355
111996	C	0-3	525	4.7-7.7	680	9-11	900	14-16	2350	0	9-11	8	16.5-17.5	1968861
111997	C	0-2.2	500	3.2-5.5	640	6.5-8.5	850	12-14	2350	0	9-11	8	16.5-17.5	1968861
111998	C	0-2.7	500	2.2-4.9	590	7.5-9.5	1000	15-17	2500	0	7-9	8	15-16	1116201
111999	C	0-4	500	2.5-6.7	560	9.5-11.5	1000	17-19	2500	0	7-9	8	15-16	1116201
112000	C	0-2.7	500	2.2-4.9	590	7.5-9.5	1000	15-17	2500	0	5-7	8	11.2-12.7	1115355
112001	C	0-2.5	500	3.3-5.8	630	6.5-8.5	900	17-19	2050	0	6-8	13	16-17.5	1973421
112002	C	0-2	550			3-5	700	15-17	2200	0	6-8	13	16-17.5	1973407
112005	C	0-2	600			5-7	1100	11-13	2150	0	7-9	10.3	16.5-17.8	1115357
112006	C	0-2	570			3.5-5.5	1000	8-10	2300	0	6-8	8	14.5-15.75	1116210
112007	CC	0-2	400			5-7	950	12-14	2300	0	8-10	10	15-17	1115365
112008	CC	0-2	550			5-7	950	12-14	2350	0	6-8	10	13-14.75	1115364
112009	CC	0-2	400			4.5-6	1100	10-12	2300	0	8-10	10	15-17	1115365
112010	CC	0-2	650			4.5-6.5	1100	10-12	2300	0	8-10	10	15-17	1115365
112011	CC	0-2	600			6	1050	14	3050	0	8-10	10	15-17	1115365
112012	CC	0-1.5	500			0-2	625	7-9	2200	0	8-10	10	15-17	1115365
112013	CC	0-2	600			5-7	1050	13-15	3050	0	8-10	10	15-17	1115365
112016	C	0-1.9	500			4.5-6.5	900	10-12	2300	0	6-8	8	14.5-15.75	1116210
112018	C	0-1.8	500			5-7	825	12-14	2100	0				1973429 ②
112019	C	0	550			7	1050	13	2500	0	7-9	8	15-16	1116201
112024	CC	0-2	550			4.5-6.5	1150	10-12	2300	0	8-10	10	15-17	1115365

Ⓢ - C (Clockwise), CC (Counterclockwise) viewed from rotor end.

② - Retard 4.5-7° with 14" Hg.

③ - Retard 4.75-7° with 14" Hg.

1970 Distributor Specifications

FORD MOTOR CO. CENTRIFUGAL ADVANCE SPECIFICATIONS

NOTE - FOR ENGINE RPM AND DEGREES, MULTIPLY SPECIFICATIONS BELOW BY 2.

Distributor Part No. ①	Rot. ②	Automatic Advance (Distr. Degrees & RPM)													
		Degs.	RPM	Degs.	RPM	Degs.	RPM	Degs.	RPM	Degs.	RPM	Degs.	RPM	Max. Degs.	RPM
C7AF-AA	CC	0-1/2	350	0-1 1/2	500	4 1/4-6 1/4	750	5 1/4-7 1/2	1000	7 1/2-9 3/4	1500	9 1/2-12	2000	14	2425
C8AF-A	C	0-1/2	300	0-1/2	500	0-1 1/2	750	2 1/4-4 1/2	1000	6-8	1500	7 1/2-10	2000		
C8AF-B	C	0-1/2	350	0-1/2	500	1 3/4-3 3/4	750	2 3/4-5	1000	4 1/2-6 3/4	1500	6 1/4-8 3/4	2000		
C8AF-E	CC	0-1/2	350	-	-	4 1/2-6 3/4	750	6-8 1/4	1000	8-10 1/2	1500	10-12 1/4	2000	14	2000
C8AF-H	CC	0-1/2	350	1/2-2 1/2	500	2 1/4-4 1/4	750	3 1/2-5 1/2	1000	5 3/4-8 3/4	1500	8 1/4-10 3/4	2000	11	2050
C8AF-M	CC	0-1/2	350	0-2	500	4 1/4-6 3/4	750	5 3/4-7 3/4	1000	7 3/4-10	1500	9 3/4-12 1/4	2000	14	2375
C8AF-R	CC	0-1/2	350	0-1/2	500	2 1/4-4 1/2	750	6 1/2-8 1/2	1000	9-10 1/4	1500	9-11 1/2	2000	14	2975
C8VF-C	CC	0-1/2	350	0-1/2	500	6 3/4-8 3/4	750	7 1/2-9 1/2	1000	8 1/2-10 3/4	1500	9 1/2-12	2000	14	2775
C9AF-Y	CC	0-1/2	350	2-4	500	4 1/2-6 1/2	750	7-9	1000	9-11 1/4	1500	11 1/4-13 3/4	2000	14	2050
C9DF-B	C	0-1/2	350	0-1 1/2	500	2 3/4-4 3/4	750	6-8	1000	8 1/4-10 1/2	1500	8 1/2-11	2000	11	2000
C9ZF-D	CC	0-1/2	350	0-1/2	500	0-1 3/4	750	2 1/2-4 3/4	1000	7 3/4-10	1500	8 1/2-11	2000	11	2000
C9ZF-E	CC	0-1/2	350	0-1/2	500	4 1/4-6 1/4	750	5 1/4-7 1/2	1000	7 1/2-9 3/4	1500	9 3/4-12 1/4	2000	14	2325
D0AF-AC	CC	0-1/2	350	0-2	500	4 1/4-6 1/4	750	5 1/4-7 1/2	1000	7 1/2-9 3/4	1500	9 3/4-12 1/4	2000	14	2950
D0AF-H	CC	0-1/2	350	0-2	500	5 1/4-7 1/4	750	6 3/4-8 3/4	1000	8 3/4-11	1500	10 3/4-13 1/4	2000	14	2175
D0AF-M	CC	0-1/2	350	0-1/2	500	0-1 3/4	750	6-8	1000	7 1/4-9 1/4	1500	8 1/4-10 3/4	2000	14	3150
D0AF-T	CC	0-1/2	350	0-1/2	500	0-1 3/4	750	6-8	1000	8-10 1/4	1500	10-12 1/2	2000	14	2325
D0AF-Y	CC	0-1/2	350	0-1/2	500	2 1/4-4 1/4	750	6 1/2-8 1/2	1000	8-10 1/4	1500	9-11 1/2	2000	14	2950
D0AF-Z	CC	0-1/2	350	1/2-2 1/2	500	4 3/4-6 3/4	750	9-11	1000	10-12 1/4	1500	11 1/4-13 3/4	2000	16	2800
D0DF-C	C	0-1/2	350	0-1/2	500	1/4-2 1/2	750	7-9	1000	9 3/4-12	1500	12 1/2-15	2000	19	2650
D0DF-E	C	0-1/2	350	0-1/2	500	6-8	750	7 1/4-9 1/2	1000	10-12 1/2	1500	12 1/2-15	2000	16	2175
D0DF-J	-													16	2000
D0OF-A	C	0-1/2	350	1/2-2 1/2	500	5-7 1/4	750	8-10	1000	10-12 1/4	1500	12 1/2-15	2000	16	2000
D0OF-AA	CC	0-1/2	350	0-1 1/4	500	4 3/4-6 3/4	750	7 1/4-9 1/4	1000	8 1/4-10 1/2	1500	9 1/2-12	2000	Not Applicable	
D0OF-AB	-													Not Applicable	
D0OF-T	CC	0-1/2	350	0-1 1/2	500	2-4	750	4 1/2-6 1/2	1000	7 3/4-10	1500	10-12 1/2	2000	14	2300
D0OF-U	CC	0-1/2	350	1 1/4-3 1/4	500	5 1/4-7 1/4	750	6 1/4-8 1/4	1000	8 1/4-10 1/2	1500	10 1/4-12 3/4	2000	14	2275
D0OF-V	CC	0-1/2	350	0-1/2	500	3/4-2 3/4	750	3 3/4-5 3/4	1000	8 1/2-10 3/4	1500	10 1/4-12 3/4	2000	14	2300
D0OF-Y	CC	0-1/2	350	2 1/8-4 1/2	500	8-10	750	8 3/4-10 3/4	1000	10 1/4-12 1/2	1500	11 3/4-14 1/4	2000	14 1/4	2525
D0OF-Z	CC	0-1/2	350	0-1/2	500	3-5	750	5 1/2-7 1/2	1000	6 3/4-9	1500	7 3/4-10 1/4	2000	Not Applicable	
D0VF-B	CC	0-1/2	350	0-1/2	500	3/4-2 3/4	750	4 1/2-6 1/2	1000	6-8 1/4	1500	7-9 1/2	2000	11	2575
D0ZF-C	CC	0-1/2	350	0-1 1/2	500	5-7	750	8 3/4-10 1/4	1000	9 3/4-12	1500	11-13 1/2	2000	14	2150
D0ZF-G	CC	0-1/2	350	0-1 1/2	500	4 1/4-6 1/4	750	6 3/4-8 3/4	1000	8 3/4-11	1500	11-13 1/2	2000	14	2075

① - Part No. prefix and suffix stamped on housing.
 Basic Ford Part No. (omitted) is "12127".
 ② - C (Clockwise), CC (Counterclockwise) viewed from rotor end.

1970 Distributor Specifications

FORD MOTOR CO. VACUUM ADVANCE & RETARD SPECIFICATIONS

NOTE - FOR ENGINE RPM AND DEGREES, MULTIPLY SPECIFICATIONS BELOW BY 2.

Distributor Part No. ①	Vacuum Advance (Distr. Degrees)						Vacuum Retard (Distr. Degrees)									
	Deg.	In. Hg.	Deg.	In. Hg.	Deg.	In. Hg.	Deg.	In. Hg.	Deg.	In. Hg.	Deg.	In. Hg.				
	Deg.	In. Hg.	Deg.	In. Hg.	Deg.	In. Hg.	Deg.	In. Hg.	Deg.	In. Hg.	Deg.	In. Hg.				
C7AF-AA	0-1/2	5	4-7 1/2	10	8 1/2-11 1/2	15	9-11 1/2	20	5 1/2-8	25	5 1/2-8	10	2 1/2-6	15	5-6	20
C8AF-A	0-3/4	5	1-3 3/4	10	5 1/2-8	15	5 1/2-8	20	6 1/2-9	25	6 1/2-9	10	4-6	15	5-6	20
C8AF-B	0-1	5	3-6	10	6 1/2-8	15	6 1/2-8	20	8 1/4-11	25	8 1/4-11	10	2-5 3/4	15	5-6	20
C8AF-E	0-3/4	5	0-3	10	5 1/4-8 1/2	15	8 1/4-11	20	-	-	-	-	-	-	-	-
C8AF-H	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
C8AF-M	0-1	5	4-6 3/4	10	9 1/4-12 1/4	15	10-12 1/2	20	10-12 1/2	25	10-12 1/2	10	3 1/2-6	15	5-6	20
C8AF-R	0-3/4	5	1-4 1/4	10	6 1/4-9 1/4	15	9 1/2-12 1/2	20	10-12 1/2	25	10-12 1/2	10	1 1/2-5 1/2	15	5-6	20
C8VF-C	0-3/4	5	1/2-4	10	6-9	15	8 1/2-11 1/2	20	9 1/2-12	25	9 1/2-12	10	1-5 1/4	15	5-6	20
C9AF-Y	0-1	5	2 3/4-6	10	6-8 1/2	15	6-8 1/2	20	6-8 1/2	25	6-8 1/2	10	2 1/4-6	15	5-6	20
C9DF-B	0-3/4	5	1 1/4-4 3/4	10	5 1/2-8	15	5 1/2-8	20	5 1/2-8	25	5 1/2-8	10	3 1/4-6	15	5-6	20
C9ZF-D	0-3/4	5	0-2	10	4-6 3/4	15	7-10	20	7 1/2-10	25	7 1/2-10	10	3 1/4-6	15	5-6	20
C9ZF-E	0-1	5	2 1/2-5 1/2	10	4 1/2-7	15	4 1/2-7	20	4 1/2-7	25	4 1/2-7	10	3-6	15	5-6	20
D0AF-AC	0-3/4	5	0-1 1/2	10	4 1/2-7 1/2	15	7-9 1/2	20	7-9 1/2	25	7-9 1/2	10	2-6	15	5-6	20
D0AF-H	0-1 1/4	5	5 1/2-8	10	5 1/2-8	15	5 1/2-8	20	5 1/2-8	25	5 1/2-8	10	2-6	15	5-6	20
D0AF-M	0-3/4	5	1-4 3/4	10	6 3/4-10	15	9 1/2-12 1/2	20	10-12 1/2	25	10-12 1/2	10	3-6	15	5-6	20
D0AF-T	0-1 1/4	5	3 1/2-6 1/2	10	7 1/2-10 1/2	15	9-11 1/2	20	9-11 1/2	25	9-11 1/2	10	2-3 1/2	15	2 1/2-3 1/2	20
D0AF-Y	0-3/4	5	0-2 1/4	10	3 1/4-6 3/4	15	7 1/4-10 1/4	20	8 1/2-11	25	8 1/2-11	10	1 1/4-6	15	5-6	20
D0AF-Z	0-3/4	5	0-1 1/4	10	3-6	15	6 3/4-9 3/4	20	8 1/2-11	25	8 1/2-11	10	-	-	-	-
D0DF-C	0-1	5	4-7	10	4 1/2-7	15	4 1/2-7	20	4 1/2-7	25	4 1/2-7	10	1 1/2-6	15	5-6	20
D0DF-E	0-1	5	5 1/2-8 1/2	10	8 1/2-11	15	8 1/2-11	20	8 1/2-11	25	8 1/2-11	10	2 1/2-6	15	5-6	20
D0DF-J	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
D0DF-A	0-1	5	4-7	10	6 1/2-9	15	6 1/2-9	20	6 1/2-9	25	6 1/2-9	10	3-6	15	5-6	20
D0DF-AA	0-1 1/4	5	3-6	10	6-8 1/2	15	6-8 1/2	20	6-8 1/2	25	6-8 1/2	10	2 3/4-6	15	5-6	20
D0DF-AB	0-1	5	3-6	10	6-8 1/2	15	6-8 1/2	20	6-8 1/2	25	6-8 1/2	10	2 1/4-6	15	5-6	20
D0DF-T	0-2	5	5-8	10	9-12	15	10-12 1/2	20	10-12 1/2	25	10-12 1/2	10	1 1/2-6	15	5-6	20
D0DF-U	0-1	5	2-5 1/4	10	6 1/2-9 1/4	15	9 1/2-12 1/2	20	10-12 1/2	25	10-12 1/2	10	-	-	-	-
D0DF-V	0-1	5	1-4 1/2	10	5 1/2-8 1/2	15	8-10 1/2	20	8-10 1/2	25	8-10 1/2	10	1-6	15	5-6	20
D0DF-Y	0-1	5	3-6	10	6-8 1/2	15	6-8 1/2	20	6-8 1/2	25	6-8 1/2	10	2-6	15	5-6	20
D0DF-Z	0-3/4	5	1 1/4-4 1/2	10	5 1/2-8 1/2	15	6-10 1/2	20	8-10 1/2	25	8-10 1/2	10	1-3 1/2	15	2 1/2-3 1/2	20
D0VF-B	0-1	5	1-4	10	5-8	15	6-8 1/2	20	6-8 1/2	25	6-8 1/2	10	-	-	-	-
D0ZF-C	0-3/4	5	1 1/2-4 1/2	10	7-10	15	8 1/2-11	20	8 1/2-11	25	8 1/2-11	10	2 1/2-3 1/2	15	5-6	20
D0ZF-G	0-1	5	2-5	10	7-9 1/2	15	7-9 1/2	20	-	-	-	-	-	-	-	-

① - Part No. prefix and suffix stamped on housing.
Basic Ford Part No. (omitted) is "12127".