

CHRYSLER & PRESTOLITE DISTRIBUTOR ADVANCE SPECIFICATIONS

NOTE - FOR ENGINE RPM AND DEGREES, MULTIPLY SPECIFICATIONS BELOW BY 2.

Distributor Part No.	Rot. ①	Automatic Advance (Distr. Degrees & RPM)				Vacuum Advance (Distr. Degrees & Inches of Hg.)					
		Deg.	RPM	Deg.	RPM	Deg.	In. Hg.	Deg.	In. Hg.		
2875822	C	1-5	550	9.2-11.2	900	12-14	2000	5-3.5	10	5.25-7.75	15
2875826	C	1-5	550	9.2-11.2	900	12-14	2000	5-3.5	7	5.25-7.75	10
2875982 ②	CC	0-5.3	600	9-11	850	12-14	2400	5-3.5	11	9.5-12.5	15.5
2875987 ③	CC	0-4.5	650	12.2-14.2	1050	14-16	1600	0-3.5	9	6.7-9.2	13.5
2875989 ④	CC	0-4.2	600	9.7-11.7	950	11.5-13.5	1600	0-3.5	9	6.7-9.2	13.5
3438219	CC	5-3.7	650	5.7-7.7	900	12-14	2300	5-4.3	10.5	9.7-12	15.5
3438222	CC	0-4.6	600	5.6-7.6	800	10-12	2300	5-4.3	10.5	9.7-12	15.5
3438225	C	1-6	550	8.5-10.5	800	12-14	2100	1.25-4.25	12	8.25-10.75	15
3438231	CC	0-3.8	550	7.5-9.5	850	14-16	2200	5-4	7.5	9.3-11.8	12
3438233	CC	0-4.6	600	5.6-7.6	800	10-12	2300	5-4.3	10.5	9.7-12	15.5
3438237	C	0-7.5	525	9.3-11.3	750	12-14	1600	5-3.5	7	5.25-7.75	10
3438255	C	1-6	550	8.5-10.5	800	14-16	2100	1-4	10.5	8.25-10.75	15
3438314 ⑤	CC	0-4.5	650	9-11	950	12-14	2400	5-3.5	11	9.5-12.5	15.5
3438317 ⑥	C	1.5-6.5	700	8-10	900	1-4.6	7.7	7-10	10.5
3438325	C	1.5-5.5	650	8-10	850	1-4.6	7.7	7-10	10.5

① - C (Clockwise), CC (Counterclockwise) viewed from rotor end.

② - Prestolite Built IBS-4014D.

③ - Prestolite Built IBS-4014E.

④ - Prestolite Built IBS-4014F.

⑤ - Prestolite Built IBS-4014.

⑥ - Prestolite Built IBS-4015B.

DELCO-REMY DISTRIBUTOR ADVANCE SPECIFICATIONS

NOTE - FOR ENGINE RPM AND DEGREES, MULTIPLY SPECIFICATIONS BELOW BY 2.

Distributor Part No.	Rot. ①	Automatic Advance (Distr. Degrees & RPM)				Vacuum Adv. (Distr. Degrees & In. of Hg.)				Vacuum Unit No.		
		Deg.	RPM	Deg.	RPM	Deg.	In. Hg.	Max. Deg.	In. Hg.			
1110439	C	0-3	500	2.2-5.5	580	15-17	2100	0	6-8	11.5	15.5-17	116217
1110444	C	0-3	350	1.9-3.9	440	12-14	2000	0	5-7	11	15.5-17	116207
1110457	C	0-2.1	500	7.5-9.5	850	13-15	1850	0	6-8	12	14.5-15.5	116230
1110458	C	7-2.7	550	6-8	850	11-13	1800	0	6-8	12	14.5-15.5	116230
1110459	C	0-3.8	550	3-5	630	17-19	2300	0	6-8	11.5	15.5-17	116217
1110460	C	6-2.6	600	7.5-9.5	1050	15-17	2300	0	6-8	11.5	15.5-17	116217
1110463	C	0-3	500	7.5-9.5	975	15-17	2100	0	6-8	11.5	15.5-17	116217
1110464	C	1.5-3.5	600	7.5-9.5	975	13-15	2100	0	6-8	11.5	15.5-17	116217
1110481	C	0-2	437	7-9	1050	11-13	2750	0	5-7	9	13.5-14.25	1973425 ③
1110482	C	1.5-3.5	600	7.5-9.5	975	13-15	2100	0	6-8	11.5	15.5-17	116217
1110483	C	0-3	500	9.5-11.5	975	15-17	2100	0	6-8	11.5	15.5-17	116217
1111105	CC	0-1.5	500	0-2	625	7-9	2200	0	8-10	10	15-17	115365
1111148	CC	1-2.1	500	5-7	950	12-14	2300	0	8-10	10	15-17	115365
1111176	CC	5-2.5	650	5-7	950	12-14	2350	0	8-10	10	15-17	115365
1111436	C	0-2	550	7.5-9.5	1050	12-14	2000	0	7-9	8	15-16	116201
1111437	C	0-2.7	500	2.2-4.9	590	12-14	1900	0	6-8	6.4	11.3-12.5	115360
1111473	C	0-2.5	450	8-10.5	790	14-16	2200	0	8-10	12.5	18.5-20.5	115363

1970 Distributor Specifications

DELCO-REMY DISTRIBUTOR ADVANCE SPECIFICATIONS (Cont.) NOTE - FOR ENGINE RPM AND DEGREES, MULTIPLY SPECIFICATIONS BELOW BY 2.

Distributor Part No.	Ret. Ⓢ	Automatic Advance (Distr. Degrees & RPM)				Vacuum Adv. (Distr. Degrees & In. of Hg.)				Vacuum Unit No.				
		Deg.	RPM	Deg.	RPM	Deg.	In. Hg.	Max. Deg.	In. Hg.					
111492	C	0-2	500	2.5-4.5	625	9-11	1225	15-17	2200	0	7-9	8	15-16	1116201
111494	C	0-2	541			5-7	1000	13-15	2200	0	7-9	8	15-16	1116201
111939	CC	.3-2.3	400			7.3-9.3	975	13-15	2200	0	8-10	12	13-15.8	1973409
111948	C	0-2.5	450	8-10.5	790	8.5-10.6	805	14-16	2200	0	4-6	12	18-19.3	1115362
111962	C	0-1.9	500			4.5-6.5	900	10-12	2300	0	6-8	8	14.5-15.75	1116210
111963	C	1-3	610			7.5-9.5	1050	10-12	1600	0	7-9	8	15-16	1116201
111964	C	1.3-3.3	600			6.5-8.5	900	13-15	2400	0	6-8	8	14.5-15.75	1116210
111975	CC	.5-2.5	450			6.5-8.5	750	12-14	2050	0	8-10	9	17.2-19	1115361
111976	CC	0-2	400			7.7-9.7	1025	14-16	2000	0	8-10	12.5	18.5-20.5	1973408
111977	CC	.4-2.4	500			8-10	900	10-12	2000	0	8-10	12.5	18.5-20.5	1973408
111978	CC	.5-2.5	450			7-9	1000	9-11	1900	0	10-12	8.7	16.2-17.8	1973418
111979	CC	0-3.5	375	7-10.3	575	8.6-10.6	625	14-16	1500	0	11-13	8.75	17.2-19	1973427
111980	CC	0-2	400			6.5-8.5	1200	13-15	2000	0	6-8	13	16-17.5	1973407
111981	CC	.4-2.4	700					6-8	1500	0	8-10	9	17.2-19	1115361
111982	CC	0-2	550			5-7	1000	9-11	1800	0	8-10	12.5	18.5-20.5	1973408
111984	C	1.2-3.4	600	7-9.2	860	7.2-10	900	13-15	2300	0	6-8	8	14.5-15.75	1116210
111986	C	0-1.9	500			4.5-6.5	900	10-12	2300	0	6-8	8	14.5-15.75	1116210
111987	C	0-2	450			6-8	750	11-13	2000	0	5-7	9	14-15.5	1973426 ②
111988	C	0-1.8	500			5-7	825	12-14	2100	0	5-7	9	14-15.5	1973426 ②
111995	C	.7-2.7	600			4-6	800	14	2150	0	5-7	8	11.2-12.7	1115355
111996	C	0-3	525	4.7-7.7	680	9-11	900	14-16	2350	0	9-11	8	16.5-17.5	1968861
111997	C	0-2.2	500	3.2-5.5	640	6.5-8.5	850	12-14	2350	0	9-11	8	16.5-17.5	1968861
111998	C	0-2.7	500	2.2-4.9	590	7.5-9.5	1000	15-17	2500	0	7-9	8	15-16	1116201
111999	C	0-4	500	2.5-6.7	560	9.5-11.5	1000	17-19	2500	0	7-9	8	15-16	1116201
112000	C	0-2.7	500	2.2-4.9	590	7.5-9.5	1000	15-17	2500	0	5-7	8	11.2-12.7	1115355
112001	C	0-2.5	500	3.3-5.8	630	6.5-8.5	900	17-19	2050	0	6-8	13	16-17.5	1973421
112002	C	0-2	550			3-5	700	15-17	2200	0	6-8	13	16-17.5	1973407
112005	C	0-2	600			5-7	1100	11-13	2150	0	7-9	10.3	16.5-17.8	1115357
112006	C	0-2	570			3.5-5.5	1000	8-10	2300	0	6-8	8	14.5-15.75	1116210
112007	CC	0-2	400			5-7	950	12-14	2300	0	8-10	10	15-17	1115365
112008	CC	0-2	550			5-7	950	12-14	2350	0	6-8	10	13-14.75	1115364
112009	CC	0-2	400			4.5-6	1100	10-12	2300	0	8-10	10	15-17	1115365
112010	CC	0-2	650			4.5-6.5	1100	10-12	2300	0	8-10	10	15-17	1115365
112011	CC	0-2	600			6	1050	14	3050	0	8-10	10	15-17	1115365
112012	CC	0-1.5	500			0-2	625	7-9	2200	0	8-10	10	15-17	1115365
112013	CC	0-2	600			5-7	1050	13-15	3050	0	8-10	10	15-17	1115365
112016	C	0-1.9	500			4.5-6.5	900	10-12	2300	0	6-8	8	14.5-15.75	1116210
112018	C	0-1.8	500			5-7	825	12-14	2100	0				1973429 ②
112019	C	0	550			7	1050	13	2500	0	7-9	8	15-16	1116201
112024	CC	0-2	550			4.5-6.5	1150	10-12	2300	0	8-10	10	15-17	1115365

Ⓢ - C (Clockwise), CC (Counterclockwise) viewed from rotor end. ② - Retard 4.5-7° with 14" Hg. ③ - Retard 4.75-7° with 14" Hg.