

CHRYSLER & PRESTOLITE DISTRIBUTOR ADVANCE SPECIFICATIONS

NOTE - FOR ENGINE RPM AND DEGREES, MULTIPLY SPECIFICATIONS BELOW BY 2.

Distributor Part No.	Rot. [Ⓒ]	Automatic Advance (Distr. Degrees & RPM)				Vacuum Advance (Distr. Degrees & Inches of Hg.)					
		Deg.	RPM	Deg.	RPM	Deg.	In. Hg.	Deg.	In. Hg.		
2875822	C	1-5	550	9.2-11.2	900	12-14	2000	.5-3.5	10	5.25-7.75	15
2875826	C	1-5	550	9.2-11.2	900	12-14	2000	.5-3.5	7	5.25-7.75	10
2875987 [Ⓒ]	CC	0-4.5	650	12.2-14.2	1050	14-16	1600	0-3.5	9	6.7-9.2	13.5
3438225	C	1-6	550	8.5-10.5	800	14-16	2100	1.25-4.25	12	8.25-10.75	15
3438255	C	1-6	550	8.5-10.5	800	14-16	2100	1-4	10.5	8.25-10.75	15
3438422	C	1-6	550	8.5-10.5	800	14-16	2100	1-4	9.5	8-10.5	15
3438440	C	.5-3.5	800	8-10.5	1200	12-14	2200	.5-3.5	10	5.25-7.75	15
3438442	C	.5-3.5	800	8-10.5	1200	12-14	2200	.5-3.5	7	5.25-7.75	10
3438453	C	0-4	600	8-10.5	1000	14-16	2100	1-4	9.5	8-10.5	15
3438509	C	1-6.5	550	8-10	750	12-14	2000	.5-3	7	6-8.5	11
3438517	C	.5-4	600	9.5-12	1000	10-12	2100	.5-3.5	9	7-10	12.5
3438522	C	.5-4	650	5.5-8.5	850	10-12	2000	.5-3.5	7	7-10	11
3438524	C	2-6	700	8.5-10.5	900	12-14	2000	.5-3.5	7	5.25-7.75	10
3438534	CC	1-4.5	600	5-7	800	12-14	2000	1-3.5	9	8-10	15
3438544	CC	.5-3.5	700	5-7.5	900	12-14	2000	1-3.5	9	8-10	15
3438559	CC	.5-3.5	700	3.5-5.5	900	10-12	2400	1-4.5	12	8-10	16
3438572	CC	0-3.5	600	4.5-6.5	800	8-10	2200	.5-4.3	10.5	9.7-12	15.5
3438577	CC	1-3	700	4.5-6.5	950	4.5-6.5	2200	1-4	10.5	7.5-10	15
3438579 [Ⓒ]	CC	0-4	600	9.5-12.5	1250	13-15	1600	0-3.5	9	6.7-9.2	13.5
3438615 [Ⓒ]	C	.5-4	700	9-11	1100	13-15	2200	.5-3.5	7	7-10	11
3438617 [Ⓒ]	C	.5-4	700	9-11	1100	13-15	2200	.5-3.5	9	7-10	12.5
3438690	CC	.5-3.5	650	6-8	900	12-14	2400	1-4	10.5	8-10	15
3438694	CC	.5-4	700	5-7	900	8-10	2200	.5-4.3	10.5	9.7-12	15.5

Ⓒ - C (Clockwise), CC (Counterclockwise) viewed from rotor end. [Ⓒ] - Prestolite Built IBS-4017E [Ⓒ] - Prestolite Built IBS-4018E
[Ⓒ] - Prestolite Built IBS-4017B [Ⓒ] - Prestolite Built IBS-4018D

DELCO-REMY DISTRIBUTOR ADVANCE SPECIFICATIONS

NOTE - FOR ENGINE RPM AND DEGREES, MULTIPLY SPECIFICATIONS BELOW BY 2.

Distributor Part No.	Rot. [Ⓒ]	Automatic Advance (Distr. Degrees & RPM)				Vacuum Adv. (Distr. & In. of Hg.)				Vacuum Unit No.
		Deg.	RPM	Deg.	RPM	Deg.	In. Hg.	Max. Deg.	In. Hg.	
1110340	C	.5-2.5	500	12-14	2200	1116207
1110435	C	1-3	850	10-12	2000	1973428
1110489	C	0-2	650	11-13	2050	1973434
1110492	C	0-2	800	11-13	2000	1973428
1111948	C	0-2.5	450	8-10.5	750	14-16	2200	1115362
1111968	C	0-2	600	5-7	1100	10-13	3000	1115357
1112005	C	0-2	600	11-13	2150	1115357
1112006	C	0-2	570	8-10	2300	1116210

1971 Distributor Specifications

DELCO-REMY DISTRIBUTOR ADVANCE SPECIFICATIONS (Cont.)

NOTE - FOR ENGINE RPM AND DEGREES, MULTIPLY SPECIFICATIONS BELOW BY 2.

Distributor Part No.	Rot. ①	Automatic Advance (Di str. Degrees & RPM)				Vacuum Advance (Di str. Degrees & In. of Hg.)				Vacuum Unit No.				
		Deg.	RPM	Deg.	RPM	Deg.	In. Hg.	Max. Deg.	In. Hg.					
1112016	C	0-1.9	500	4.5-6.5	900	10-12	2300	0	6-8	8	14.5-15.75	1116210
1112028	C	.5-3	500	5-7	750	14-16	2300	0	4-6	12	18-19.2	1115362
1112033	CC	0-2	400	6.5-8.5	1200	13-15	2000	0	7-9	12.5	17.0-19.5	1973433
1112034	CC	.5-4	450	4.5-8	550	6-8.5	600	12-14	1500	0	11-13	8.75	17.2-19	1973427
1112036	CC	0-2.5	500	8-10	900	10-12	2000	0	7-9	8	15-16	1973437
1112037	C	0-2	800	1.5-3.5	875	5-7	2300	0	6-8	8.5	14.5-16	1116210
1112038	C	0-2	650	7-10	1200	11-13	2400	10-13	3000	0	7-9	8	15-16	1973437
1112039	C	0-2	650	9-11	2100	0	7-9	10.5	16.5-18	1973436
1112042	C	0-2	550	4-6	800	6.5-8.5	1100	13-15	2150	0	7-9	10.5	16.5-18	1973436
1112044	C	0-2	550	4-6	900	6.5-8.5	1200	10-12	2100	0	7-9	8	15-16	1973437
1112045	C	0-2	650	4.5-6.5	1200	8-10	2100	0	7-9	8	15-16	1973437
1112049	C	0-2	650	7-9	1125	11-13	2500	0	7-9	8	15-16	1973437
1112050	C	0-2	650	4.5-6.5	1200	8-10	2100	0	7-9	8	15-16	1973437
1112051	C	.5-2.5	600	6-8	1000	10-12	1950	0	7-9	10.5	16.5-18	1973436
1112052	C	.5-2.5	600	6-8	1000	10-12	1950	0	7-9	10.5	16.5-18	1973436
1112053	C	0-2	650	10-12	1200	13-15	2700	12-15	3000	0	6-8	6.5	11-12.5	1973439
1112054	C	0-2	650	9.5-11.5	1175	13-15	2500	0	6-8	6.5	11-12.5	1973439
1112056	C	0-2	600	6-8	1150	11-13	2250	0	9-11	9	16-18	1973438
1112057	C	0-2	600	7-9	1200	14-16	2200	0	7-9	10.5	16.5-18	1973436
1112065	C	0-2	500	4.5-6.5	950	11-13	2000	0	8-10	12	13-15.8	1973409
1112068	CC	0-3	850	5-7	1000	13-15	2300	0	6-8	10	13-14.75	1115364
1112069	CC	0-2.7	850	4.5-6.5	1000	10-12	2300	0	6-8	10	13-14.75	1115364
1112070	CC	0-2	650	2-4	800	10-12	2300	0	6-8	10	13-14.75	1115364
1112071	CC	0-2	900	11-13	2300	0	8-10	10	15-17	1115365
1112072	CC	0-2	650	2-4	800	10-12	2300	0	6-8	10	13-14.75	1115364
1112073	CC	0-2	550	3-5	750	12-14	2250	0	6-8	10	13-14.75	1115364
1112074	C	0-2	700	5-7	1100	9-11	2500	0	7-9	8	15-16	1973437
1112075	C	0-3	650	3-6.5	750	11.5-14	1200	15-17	2500	0	6-8	6.5	11-12.5	1973439
1112076	C	0-3	650	4-7	800	11-14	1200	15-17	2500	0	6-8	6.5	11-12.5	1973439
1112077	C	0-3	800	6-9	1000	7-10	350	8-10	1500	0	6.5-8.5	10	12-14	1973440
1112078	CC	0-2	500	0-3	550	7-8	2000	0	8-10	12.5	18.5-20.5	1973408
1112079	CC	0-2	400	10-12	1000	16-18	2050	0	6-8	13	16-17.5	1973407
1112080	C	0-3	800	6-8	1100	9-11	2300	0	6-8	8.5	14.5-16	1116210
1112083	CC	0-2	700	5-7	1050	10-12	2300	0	6-8	10	13-14.75	1115364
1112085	CC	0-2	400	7-10	1000	14-16	2000	0	6-8	13	16-17.5	1973407

① - C (Clockwise), CC (Counter clockwise) viewed from rotor end.