

1972 Distributor Specifications

CHRYSLER DISTRIBUTOR ADVANCE SPECIFICATIONS

NOTE - FOR ENGINE RPM AND DEGREES, MULTIPLY SPECIFICATIONS BELOW BY 2.

Distributor Part No.	Rot. Ⓞ	Automatic Advance (Distr. Degrees & RPM)				Vacuum Advance (Dist. Deg. & Inches of Hg.)					
		Deg.	RPM	Deg.	RPM	Deg.	In. Hg.	Deg.	In. Hg.		
3656237	C	0-5	550	8-10	800	12-14	2000	5-3	7	6-8.5	11
3656243	C	1-4.5	650	8-10.5	950	12-14	2000	5-3	7	6-8.5	11
3656252	C	5-4.5	550	9-11	900	12-14	2000	5-3.5	10	5-8	15
3656257	C	5-4.5	550	9-11	900	12-14	2000	5-3	7	5-7.5	9.5
3656260	C	5-3.5	700	9-11.5	1150	12-14	2000	5-3.5	10	5-8	15
3656266	C	5-3.5	700	9-11.5	1150	12-14	2000	5-3	7	5-7.5	9.5
3656272	C	1-6	550	8-10.5	800	14-16	2100	1-4	9.5	8-10.5	15
3656275	C	0-4	600	9-11	1000	14-16	2100	1-4	9.5	8-10.5	15
3656278 Ⓞ	C	1-5	650	12-14	1050	11-13.5	2400	5-3.5	9	7-10	12.5
3656329	CC	1-5	650	8-10	900	12-14	2000	1-4	10.5	8-10.5	15.5
3656332	CC	5-4	650	6-8	950	10-12	2000	1-4	10.5	8-10.5	15.5
3656335 Ⓞ	CC	1-5	650	8-10	900	13-15	2250	1-4	10.5	8-10.5	15.5
3656338 Ⓞ	CC	5-4	650	6-8	950	10-12.5	2500	1-4	10.5	8-10.5	15.5
3656341 Ⓞ	CC	5-4	650	6-8	950	10-12.5	2500	1-4	10.5	8-10.5	15.5
3656344	CC	5-4	650	6-8	950	10-12	2000	1-4	10.5	8-10.5	15.5
3656347 Ⓞ	CC	1-5	650	8-10	900	13-15	2250	1-4	10.5	8-10.5	15.5
3656350	CC	1-5	650	8-10	900	12-14	2000	1-4	10.5	8-10.5	15.5
3656353 Ⓞ	CC	0-3.5	650	8-10.5	1000	8-10.5	2150	1-4	10.5	8-10.5	15.5
3656390	C	1-6	550	8-10.5	800	14-16	2100	1-4.5	12	8-10.5	15
3656429 Ⓞ	C	1-6	550	8-10.5	800	13-15	1900	0-3	9	7-10	14
3656435 Ⓞ	C	0-4	600	9-11	1100	13-15	1900	0-3	9	7-10	14
3656587 Ⓞ	C	1-6	550	8-10.5	800	14-16	2100	1-4.5	12	7-10	14.5
3656593	CC	1-4.5	550	7.5-9.5	800	14-16	1900	1-4	10.5	8-10.5	15.5
3656596 Ⓞ	CC	1-4.5	550	7.5-9.5	800	13-15	1800	1-4	10.5	8-10.5	15.5

Ⓞ - C (Clockwise); CC - (Counterclockwise).

Ⓞ - Electronic Distributor.

DELCO-REMY DISTRIBUTOR ADVANCE SPECIFICATIONS

NOTE - FOR ENGINE RPM AND DEGREES, MULTIPLY SPECIFICATIONS BELOW BY 2.

Distributor Part No.	Rot. Ⓞ	Automatic Advance (Distr. Degrees & RPM)				Vacuum Adv. (Distr. Degrees & In. of Hg.)				Vacuum Unit No.		
		Deg.	RPM	Deg.	RPM	Deg.	In. Hg.	Max. Deg.	In. Hg.			
1110435	C	1-3	850	10-12	2000	0	6-8	12	14.5-15.5	1973428
1110461	C	5-2.5	500	1200	17-19	1700	0	5-7	11.5	11.5-13	1116198
1110489	C	0-2	650	1150	11-13	2050	0	7-9	11.5	15-16.5	1973434
1110492	C	0-2	800	11-13	2000	0	6-8	12	14.5-15.5	1973428
1110497	C	0	600	1000	13-15	2200	0	5-7	6-8	10-11	1973419
1110498	C	0-2	650	1150	11-13	2050	1973442
1111369	C	0-2	550	850	9-11	1900
1111370	C	0-2	600	1200	12-14	2200

Ⓞ - C (Clockwise); CC (Counterclockwise) viewed from rotor end.

1972 Distributor Specifications

DELCO-REMY DISTRIBUTOR ADVANCE SPECIFICATIONS (Cont.)

NOTE - FOR ENGINE RPM AND DEGREES, MULTIPLY SPECIFICATIONS BELOW BY 2.

Distributor Part No.	Rot. Ⓢ	Automatic Advance (Dist. Degrees & RPM)						Vacuum Advance (Dist. Degrees & In. of Hg.)				Vacuum Unit No.		
		Deg.	RPM	Deg.	RPM	Deg.	RPM	Deg.	In. Hg.	Max. Deg.	In. Hg.			
1112005	C	0-2	600	5-7	1100	11-13	2150	0	7-9	10.3	16.5-17.8	1115357
1112016	C	0-2	500	4-6.5	900	10-12	2300	0	6-8	8	14.5-16	1116210
1112033	CC	0-2	400	6-8.5	1200	13-15	2000	0	7-9	12.5	17-20	1973433
1112034	CC	.5-4	450	550	6-8.5	600	12-14	1500	0	11-13	8.75	17-19	1973427
1112036	CC	0-2.5	500	8-10	900	10-12	2000	0	6-8	13	16-17.5	1973407
1112039	C	0-2	650	9-11	2100	0	7-9	10.5	16.5-18	1973436
1112044	C	0-2	550	900	6-8.5	1200	10-12	2100	0	7-9	8	15-16	1973437
1112045	C	0-2	650	4-6.5	1200	8-10	2100	0	7-9	8	15-16	1973437
1112049	C	0-2	650	7-9	1125	11-13	2500	0	7-9	8	15-16	1973437
1112050	C	0-2	650	4-6.5	1200	8-10	2100	0	7-9	8	15-16	1973437
1112051	C	.5-2.5	600	6-8	1000	10-12	1950	0	7-9	10.5	16.5-18	1973436
1112052	C	.5-2.5	600	6-8	1000	10-12	1950	0	7-9	10.5	16.5-18	1973436
1112057	C	0-2	600	7-9	1200	14-16	2200	0	7-9	10.5	16.5-18	1973436
1112085	CC	0-2	400	7-10	1000	14-16	2000	0	6-8	13	16-17.5	1973407
1112095	C	0-2	650	9-12	1200	13-15	2500	0	7-9	8	15-16	1973437
1112099	C	0-2	600	6-8	1150	11-13	2300	0	7-9	10.5	16.5-18	1973436
1112101	C	0-2	650	9-12	1200	13-15	2500	0	7-9	8	15-16	1973437
1112106	CC	0-2	500	8-11	1000	14-16	2000	0	6-8	13	16-17.5	1973407
1112108	C	0-2	500	5-7	1000	13-15	2300	0	7-9	15	14-16	1973441
1112109	C	0-2	500	5-8	900	7-9	1500	0	6-8	8.5	14.5-16.5	1116210
1112110	C	0-2	500	7-9	1050	8-10	1500	0	6-8.5	10	12-14	1973440
1112111	C	0-2	600	9-11	1200	14-16	2200	0	5-7	6-9	11-13	1115355
1112112	C	0-2	500	7-10	1000	12-14	2000	0	5-7	6-9	11-13	1115355
1112118	CC	0-2	800	3-6	1000	9-11	2300	0	6-8	10	13-15	1115364
1112119	CC	0-2	800	4-7	1000	13-15	2400	0	6-8	10	13-15	1115364
1112121	CC	0-2	800	4-6	1200	11-13	2300	0	6-8	10	13-15	1115364
1112122	CC	0-2	900	1000	11-13	2300	0	8-10	10	15-17	1115365
1112124	CC	0-2	800	900	8-10	2300	0	8-10	10	15-17	1115365
1112126	CC	0-3	650	1100	12-14	2200	0	6-8	10	13-15	1115364
1112127	CC	0-2	800	1200	8-11	2400	0	8-10	10	15-17	1115365
1112133	CC	0-2	650	4-7	1000	12-16	2400	0	6-8	10	13-15	1115364
1112134	C	0-2	600	1100	11-13	2200	0	7-9	10.5	16.5-18	1973436
1112136	CC	0-2	800	1000	10-12	2300	0	6-8	10	13-15	1115364
1112138	CC	0-2	850	1000	8-10	2300	0	6-8	10	13-15	1115364
1112139	CC	0-2	850	1000	11-13	2300	0	6-8	10	13-15	1115364
1112140	CC	0-2	800	1000	10-12	2300	0	6-8	10	13-15	1115364
1112141	CC	0-2	800	1200	11-13	2300	0	6-8	10	13-15	1115364
1112142	CC	0-2	900	11-13	2300	0	8-10	10	15-17	1115365
1112144	CC	0-2	800	1000	9-11	2100	0	8-10	10	15-17	1115365
1112145	CC	0-2	800	3-5	1000	9-11	2100	0	8-10	10	15-17	1115365

Ⓢ - C (Clockwise), CC (Counterclockwise) viewed from rotor end.

1972 Distributor Specifications

DELCO-REMY DISTRIBUTOR ADVANCE SPECIFICATIONS (Cont.)

NOTE - FOR ENGINE RPM AND DEGREES, MULTIPLY SPECIFICATIONS BELOW BY 2.

Distributor Part No.	Ret. Ⓢ	Automatic Advance (Distr. Degrees & RPM)				Vacuum Advance (Distr. Degrees & In. of Hg.)				Vacuum Unit No.				
		Deg.	RPM	Deg.	RPM	Deg.	RPM	Deg.	In. Hg.		Max. Deg.	In. Hg.		
1112146	CC	0-2	650	5-8	1050	12-14	2200	0	6-8	10	13-15	1115364
1112147	C	0-2	650	9-11	2100	0	7-9	10.5	16.5-18	1973436
1112152	C	0-2	600	4-6	900	6-9	1200	10-12	2100	0	7-9	8	15-16	1973437
1112153	C	0-2	650	9-12	1200	13-15	2500	0	7-9	8	15-16	1973437
1112154	C	0-2	700	4-7	1200	8-10	2100	0	7-9	8	15-16	1973437
1112156	C	0-2	700	7-9	1100	11-13	2500	0	7-9	8	15-16	1973437
1112162	C	0-2	600	7-9	1200	14-16	2200	0	7-9	10.5	16.5-18	1973436
1112163	C	0-2	600	6-8	1000	10-12	2000	0	7-9	10.5	16.5-18	1973436
1112165	C	0-2	700	4-7	1200	8-10	2100	0	7-9	8	15-16	1973437
1112167	C	0-2	650	9-12	1200	13-15	2500	0	7-9	8	15-16	1973437
1112169	C	0-2	600	6-8	1000	10-12	2000	0	7-9	10.5	16.5-18	19436
1112172	CC	0-2	550	3-6	1000	7-9	1700	0-1	8-10	12.5	18-20	1973408
1112173	C	0-2	500	6-9	900	13-15	2400	0-1	6-8	8.5	14-16	1116210
1112179	C	0-3	500	7-10	900	15-17	2200	0	5-7	6-9	11-13	1115355
1112481	CC	0-2	400	13-15	1050
1112482	C	0-3	500	6-9	800	10-12	1100	13-15	1400

Ⓢ - C (Clockwise), CC (Counterclockwise) viewed from rotor end.