

1973 Distributor Specifications

CHRYSLER DISTRIBUTOR ADVANCE SPECIFICATIONS

NOTE — FOR ENGINE RPM AND DEGREES, MULTIPLY SPECIFICATIONS BELOW BY 2.

Distributor Part No.	Rot. (1)	Automatic Advance (Distr. Degrees & RPM)				Vacuum Advance (Distr. Deg. & In. of Hg.)					
		Deg.	RPM	Deg.	RPM	Deg.	In. Hg.	Deg.	In. Hg.		
3656859	C	0-5	550	8-10	800	12-14	2000	.5-3	7	7-10	11
3755037	C	.5-4.5	550	9-11	900	12-14	2000	.5-3	9.5	7-10	15
3755042	C	.5-4.5	550	9-11	900	12-14	2000	.5-3	7	7-10	11
3656763	C	1-4.5	525	6.5-8.5	750	13-15	1900	.5-3	9	9.5-12.5	15
3656771	C	.5-3.5	600	8.5-11	1000	11-13	2000	.5-3.5	9	7-10	12.5
3656780	C	.5-3.5	500	10-12.5	800	13-15	1750	.5-3	9	9.5-12.5	15
3656791	CC	.5-3.5	550	8-10.5	850	13-15	1950	1-4	10.5	8-10.5	15.5
3755308	CC	0-2.5	600	8-10.5	1000	13.5-15.5	2150	1-4	10.5	8-10.5	15.5
3656802	CC	.5-4	650	6-8	950	10.5-12.5	2500	1-4	10.5	8-10.5	15.5
3755157	CC	.5-4	650	6-8	950	10.5-12.5	2500	1-4	10.5	8-10.5	15.5
3755336	C	0-2.5	600	6.5-8.5	900	9.5-12.5	2000	.5-3	9	9.5-12.5	15
3755365	C	.5-4	550	8-10	800	12-14	2000	.5-3	9	12-14	15

(1) — C (Clockwise), CC (Counterclockwise) viewed from rotor end.

DELCO-REMY DISTRIBUTOR ADVANCE SPECIFICATIONS

NOTE — FOR ENGINE RPM AND DEGREES, MULTIPLY SPECIFICATIONS BELOW BY 2.

Distributor Part No.	Rot (1)	Automatic Advance (Distr. Degrees & RPM)				Vacuum Advance (Distr. Deg. & In. of Hg.)					
		Deg.	RPM	Deg.	RPM	Deg.	In. Hg.	Deg.	In. Hg.		
1110496	C	0	800	2.5	1000	11	2400	0	7	12	15
1110499	C	0	450	7	1150	12	2050	0	6-8	6	14.5-15.5
1110522	C	0-2.5	500	9-11	1500	12-14	2200	0	5-7	6.25-9	12.5-13.25
1110523	C	0-1	550	9-11	1500	13-15	2200	0	5-7	6.25-9	12.5-13.25
1112016	C	0	350-525	4.5-6.5	900	10-12	2300	0	6-8	7-9	16
1112093	C	0	550	3	900	9	2100	0	6	7.5	14
1112094	C	0	550	3	1200	7	2100	0	6	7.5	14
1112098	C	0	550	3	1200	7	2100	0	6	7.5	14
1112102	C	0	500	5	1050	10	2100	0	6	7.5	12
1112109	C	0	375-525	5.5-7.5	900	7-9	1450	0	6-8	7-9	16
1112110	C	0	375-525	6-8	1050	8-10	1500	0	6.5-8.5	7-9.5	13
1112112	C	0-1.5	500	7.5-9.5	1000	12-14	2000	0	5-7	6.25-8.25	11.5-12.5
1112113	C	0	550	5.5	1200	9	2100	0	6	10	15
1112114	C	0	550	5.5	1200	9	2100	0	6	10	15
1112148	C	0	600	6	1100	10	2500	0	6	7.5	12
1112150	C	0	600	6	1100	10	2500	0	6	7.5	12

(1) — C (Clockwise), CC (Counterclockwise) viewed from rotor end.

1973 Distributor Specifications

DELCO-REMY DISTRIBUTOR ADVANCE SPECIFICATIONS (Cont.)

NOTE — FOR ENGINE RPM AND DEGREES, MULTIPLY SPECIFICATIONS BELOW BY 2.

Distributor Part No.	Rot ^①	Automatic Advance (Distr. Degrees & RPM)				Vacuum Advance (Distr. Deg. & In. of Hg.)					
		Deg.	RPM	Deg.	RPM	Deg.	In. Hg.	Deg.	In. Hg.		
1112166	C	0	500	5	1300	10	2100	0	8	7.5	15.5
1112168	C	0	500	5	1100	10	2100	0	4	7.5	7
1112179	C	0-1	400	8-9.75	1000	15-17	2200	0	5-7	6-8	11.5-12.5
1112191	CC	0	575	3-8	850	9	1950	0	10	12.5	16
1112195	CC	0-2	400	8-10	1050	14-16	2000	0	5-7	8	10-12
1112197	CC	0-2	540	5-7	1000	9-11	1800	0	7-9	9	15-16.5
1112198	CC	0-2	575	3.5-5.5	1000	7-9	1700	0	7-9	9	12-14
1112199	CC	0	610	4	790	12	1875	0	8	12.5	15
1112201	CC	0	600	6.5	1065	12	1790	0	7	12.5	12
1112202	CC	0	700	8	1050	13	1725	0	7	12.5	12
1112203	CC	0	600	4	750	9	2000	0	10	12.5	16
1112205	CC	0	600	5	850	11	2300	0	8-10	12.5	14
1112214	C	0-2.25	450	11-13	1500	15-17	2200	0	4-6	6.75-8.25	11.5-13
1112215	C	0-3.25	400	9.5-11.5	1500	14-16	2300	0	4-6	6.75-8.25	12-13
1112216	CC	0	600	6.5	1065	12	1790	0	3	10	9.6
1112218	CC	0	600	8.5	950	10	1650	0	6	10	12
1112220	CC	0	575	3.8	850	9	1950	0	5	12.5	11
1112222	CC	0-2	485	8-11	1000	14-16	2000	0	5-7	8	10-12
1112224	CC	0	610	4	790	12	1875	0	5	12.5	11
1112225	CC	5-7	550	11-13	1050	17-19	2000	0	5-7	8	10-12
1112226	CC	0-2	400	8-10	1050	14-16	2000	0	3.5-4.5	10	12-13
1112227	C	0	500	6	1100	12	2150	0	6	7.5	12
1112229	C	0-2	500	6-8	1200	11-13	2000	0	5-7	11.25-12.75	14
1112230	C	0	500	5	1300	10	2100	0	4	5	5.8
1112231	CC	0	600	5	850	11	2300	0	9	12.5	14
1112232	CC	0	600	5	850	11	2300	0	5	12.5	11
1112233	CC	0	600	5	850	11	2300	0	9	12.5	14
1112507	CC	0	600	4	750	9	2000	0	5	12.5	11
1112510	CC	0	500	4	700	12	1900	0	7	12.5	12
1112511	CC	0	500	4	700	12	1900	0	8	12.5	15
1112804	CC	0	600	6.5	1065	12	1790	0	6-8	10	14
1112805	CC	0	615	4	790	12	1875	0	8-10	10	16
1112806	CC	0	700	8	1050	13	1725	0	6-8	10	14
1112806	CC	0	575	3.8	850	9	1950	0	8-10	10	16
1112808	CC	0	600	6.5	1065	12	1790	0	4-6	12.5	11
1112809	CC	0	615	4	790	12	1875	0	6-8	12.5	12
1112810	CC	0	600	4	750	9	2000	0	8-10	10	16

1973 Distributor Specifications

DELCO-REMY DISTRIBUTOR SPECIFICATIONS (Cont.)

NOTE — FOR ENGINE RPM AND DEGREES, MULTIPLY SPECIFICATIONS BELOW BY 2

Distributor Part No.	Rot ①	Automatic Advance (Distr. Degrees & RPM)				Vacuum Advance (Distr. Deg. & In. of Hg.)					
		Deg.	RPM	Deg.	RPM	Deg.	In. Hg.	Deg.	In. Hg.		
1112811	CC	0	575	3.8	850	9		0	6-8	12.5	12
1112812	CC	0	600	5	850	11		0	8-10	10	16
1112913	CC	0	600	5	850	11		0	8-10	10	16
1112914	CC	0	600	5	850	11		0	6-8	12.4	12

1973 Distributor Specifications

FORD MOTOR CO. DISTRIBUTOR ADVANCE AND RETARD SPECIFICATIONS

NOTE — FOR ENGINE RPM AND DEGREES, MULTIPLY SPECIFICATIONS BELOW BY 2.

Distributor Part No.	Rot. ⓐ	Automatic Advance (Distr. Degrees @ RPM)						Vacuum Advance (Distr. Degrees) Operate Distr. @ 1000 RPM					Vacuum Retard (Distr. Degrees) Operate Distr. @ 1000 RPM					
		500	750	1000	1500	2000	5	10	15	20	5	10	15	20	5	10	15	20
721F-AHA	CC	0-5	1-3	5-7	7.25-9.25	9.5-11.5	0-1.5	4.25-7.25	4.25-7.25	4.25-7.25	0	0-1.5	3.5-7	5-7	0	0-1.5	3.5-7	5-7
731F-AHA	CC	0-5	1-3	5-7	7.25-9.25	9.5-11.5	0-1.5	4.25-7.25	4.25-7.25	4.25-7.25	0	0-1.5	3.5-7	5-7	0	0-1.5	3.5-7	5-7
73HF-AA	C	5-2.5	5-7	6.5-8.5	9.25-11.25	12-14	0-2	5.5-7.5	5.5-7.5	5.5-7.5
73HF-BA	C	0-1	1-3	3-5	7.5-9.5	12-14	0-2	5.5-7.5	5.5-7.5	5.5-7.5
73HF-GA	C	0-5	5-2.5	2.5-4.5	5.5-7.5	9-11	0-2	5.5-7.5	5.5-7.5	5.5-7.5
D30F-AA	C	0-1.5	6.5-8.5	7-9	8-10.5	9-11.5	0-1.5	6.5-9	6.5-9	6.5-9	0-4	2-4	2-4	2-4	0-4	2-4	2-4	2-4
D30F-BA	C	0-1.5	4-6	4.5-6.5	6-8.25	7.25-10	0-1.5	6.5-9.25	6.5-9.25	6.5-9.25	0-3.5	2-4	2-4	2-4	0-3.5	2-4	2-4	2-4
D30F-DA	CC	0-1	0-1.5	4-6	7-9.5	8.5-11	0-1.25	2.5-5.25	2.5-5.25	2.5-5.25	0-2	3.5-7	5-7	5-7	0-2	3.5-7	5-7	5-7
D30F-EA	CC	0-1	0-1.5	4-6	7.25-9.5	8.25-11	0-2	2.5-5.25	2.5-5.25	2.5-5.25	0-4	2-4	2-4	2-4	0-4	2-4	2-4	2-4
D30F-FA	CC	0-1	0-1.5	1-3	5.5-8	10.5-13	0-3	2.5-5.25	2.5-5.25	2.5-5.25	0-3.5	4.5-7	5-7	5-7	0-3.5	4.5-7	5-7	5-7
D30F-GA	CC	0-1	0-1.5	1-3.5	6-8.5	11-13.5	0-3.5	2.5-5.25	2.5-5.25	2.5-5.25
D30F-HA	CC	0-1	0-2.5	2-4.5	5.5-8.5	9.5-12	0-5	0-2	2.5-5.25	2.5-5.25
D30F-JA	CC	0-1.25	0-2.5	2-4.5	5.5-8.5	9.5-12	0-1.25	2.5-5.25	2.5-5.25	2.5-5.25
D30F-LA	C	0-1.5	4.5-6.5	6-8	8-10.5	9.25-12	0-1.5	6.5-9.25	6.5-9.25	6.5-9.25	0-3.5	2-4	2-4	2-4	0-3.5	2-4	2-4	2-4
D30F-PA	CC	0-1	0-2.5	2-4.5	6-8.5	9.5-12.5	0-1.5	2.5-5.25	2.5-5.25	2.5-5.25	0-4	2-4	2-4	2-4	0-4	2-4	2-4	2-4
D30F-RA	C	0-1.5	3.5-5.5	5.5-7.5	6.5-8.5	7.5-10	.5-3.5	6.5-9.5	6.5-9.5	6.5-9.5	0-3.5	2-4	2-4	2-4	0-3.5	2-4	2-4	2-4
D3AF-AA	CC	0-1.5	4-6	6-8.25	10-12.5	14-16.5	0-2	6-9	9.5-12.5	10.5-13.25
D3AF-BA	CC	0-1.5	3.5-5.5	5.5-7.5	8.5-11	12-14.5	0-1.5	4-7	8-11	10-13.25
D3BF-BA	CC	0-1	2.5-4.5	6.5-8.5	8.5-11	9.5-12	0-1	0-1	5.5-8.5	8.5-11.25	0-3.5	4.5-7	5-7	5-7	0-3.5	4.5-7	5-7	5-7
D3DF-AA	C	0-1.5	5-7	9-11	10.25-12.5	11.25-14	0-1	4.25-7.25	4.25-7.25	4.25-7.25	0-2	2-4	2-4	2-4	0-2	2-4	2-4	2-4
D3DF-BA	C	0-1.5	4.5-6.5	7-9	9-11.5	11.5-14	0-1	4.5-7	8-11	10-13
D3MF-AA	CC	0-1	3-6.5	6-8	8-10.5	10-12.5	0-1	2.5-5.5	6.5-9.5	6.5-9.5	0-4	5-7	5-7	5-7	0-4	5-7	5-7	5-7
D3MF-BA	CC	0-1	0-1.5	3.5-5.5	7.5-10	8.5-11	0-1.25	2-5	4.5-7.25	4.5-7.25
D3MF-CA	CC	0-1.5	4.5-6.5	6-8	8-10.5	10-12.5	0-1	2.5-5.5	6.5-9.5	6.5-9.5	0-4	5-7	5-7	5-7	0-4	5-7	5-7	5-7
D3MF-DA	CC	0-1	1.5-4	5.5-7.5	7.5-9	8.25-10.5	0-1	1-4	5.5-8.5	8.5-11.25
D3MF-GA	CC	0-1	0-2.25	1.5-3.5	4.5-7	8-10.5	.5-4.5	8-11	10.5-13.5	10.5-13.5
D3SF-BA	CC	0-1	5-2.5	5.5-8	10-12	11.25-13.5	0-1	1.5-4.5	5.5-9	8.5-11.25
D3JF-GA	CC	0-1	0-2.5	2-4.5	5.5-8.5	9.5-12	0-1	0-2.5	2.5-5.25	2.5-5.25	0-3	2-4	2-4	2-4	0-3	2-4	2-4	2-4
D3VF-AA	CC	0-1	0-1.5	3-5	4-6.25	5-7.5	0-2.25	5.5-8.5	8.5-11.25	8.5-11.25
D3VF-BA	CC	0-1	0-2.5	5-7	7.5-10	10-12.25	0-1.5	4-7.25	4.5-7.25	4.5-7.25
D3VF-CA	CC	0-1	0-1.5	4-6	6-8	7.25-10	0-1.25	5-8	8.5-11.25	8.5-11.25
D3ZF-CA	CC	0-1.25	3.25-5.25	4.5-6.5	6.5-9	9-11.5	0-1.25	4.5-7.5	8.5-11.5	10.5-13.25
D3ZF-GA	CC	0-1	0-2.5	2.25-4.25	5.5-7.5	8.25-11	0-1	2.25-5.25	6.5-9.5	9.5-12.5

ⓐ — C (Clockwise), CC (Counterclockwise) viewed from rotor end.