

1973 Distributor Specifications

FORD MOTOR CO. DISTRIBUTOR ADVANCE AND RETARD SPECIFICATIONS

NOTE — FOR ENGINE RPM AND DEGREES, MULTIPLY SPECIFICATIONS BELOW BY 2.

Distributor Part No.	Rot. ⓐ	Automatic Advance (Distr. Degrees @ RPM)						Vacuum Advance (Distr. Degrees) Operate Distr. @ 1000 RPM			Vacuum Retard (Distr. Degrees) Operate Distr. @ 1000 RPM			
		500	750	1000	1500	2000	5	10	15	20	5	10	15	20
721F-AHA	CC	0-5	1-3	5-7	7.25-9.25	9.5-11.5	0-1.5	4.25-7.25	4.25-7.25	4.25-7.25	0	0-1.5	3.5-7	5-7
731F-AHA	CC	0-5	1-3	5-7	7.25-9.25	9.5-11.5	0-1.5	4.25-7.25	4.25-7.25	4.25-7.25	0	0-1.5	3.5-7	5-7
73HF-AA	C	5-2.5	5-7	6.5-8.5	9.25-11.25	12-14	0-2	5.5-7.5	5.5-7.5	5.5-7.5
73HF-BA	C	0-1	1-3	3-5	7.5-9.5	12-14	0-2	5.5-7.5	5.5-7.5	5.5-7.5
73HF-GA	C	0-5	5-2.5	2.5-4.5	5.5-7.5	9-11	0-2	5.5-7.5	5.5-7.5	5.5-7.5
D30F-AA	C	0-1.5	6.5-8.5	7-9	8-10.5	9-11.5	0-1.5	6.5-9	6.5-9	6.5-9	0-4	2-4	2-4	2-4
D30F-BA	C	0-1.5	4-6	4.5-6.5	6-8.25	7.25-10	0-1.5	6.5-9.25	6.5-9.25	6.5-9.25	0-3.5	2-4	2-4	2-4
D30F-DA	CC	0-1	0-1.5	4-6	7-9.5	8.5-11	0-1.25	2.5-5.25	2.5-5.25	2.5-5.25	0-2	3.5-7	5-7	5-7
D30F-EA	CC	0-1	0-1.5	4-6	7.25-9.5	8.25-11	0-2	2.5-5.25	2.5-5.25	2.5-5.25	0-4	2-4	2-4	2-4
D30F-FA	CC	0-1	0-1.5	1-3	5.5-8	10.5-13	0-3	2.5-5.25	2.5-5.25	2.5-5.25	0-3.5	4.5-7	5-7	5-7
D30F-GA	CC	0-1	0-1.5	1-3.5	6-8.5	11-13.5	0-3.5	2.5-5.25	2.5-5.25	2.5-5.25
D30F-HA	CC	0-1	0-2.5	2-4.5	5.5-8.5	9.5-12	0-5	0-2	2.5-5.25	2.5-5.25
D30F-JA	CC	0-1.25	0-2.5	2-4.5	5.5-8.5	9.5-12	0-1.25	2.5-5.25	2.5-5.25	2.5-5.25
D30F-LA	C	0-1.5	4.5-6.5	6-8	8-10.5	9.25-12	0-1.5	6.5-9.25	6.5-9.25	6.5-9.25	0-3.5	2-4	2-4	2-4
D30F-PA	CC	0-1	0-2.5	2-4.5	6-8.5	9.5-12.5	0-1.5	2.5-5.25	2.5-5.25	2.5-5.25	0-4	2-4	2-4	2-4
D30F-RA	C	0-1.5	3.5-5.5	5.5-7.5	6.5-8.5	7.5-10	5-3.5	6.5-9.5	6.5-9.5	6.5-9.5	0-3.5	2-4	2-4	2-4
D3AF-AA	CC	0-1.5	4-6	6-8.25	10-12.5	14-16.5	0-2	6-9	9.5-12.5	10.5-13.25
D3AF-BA	CC	0-1.5	3.5-5.5	5.5-7.5	8.5-11	12-14.5	0-1.5	4-7	8-11	10-13.25
D3BF-BA	CC	0-1	2.5-4.5	6.5-8.5	8.5-11	9.5-12	0-1	0-1	5.5-8.5	8.5-11.25	0-3.5	4.5-7	5-7	5-7
D3DF-AA	C	0-1.5	5-7	9-11	10.25-12.5	11.25-14	0-1	4.25-7.25	4.25-7.25	4.25-7.25	0-2	2-4	2-4	2-4
D3DF-BA	C	0-1.5	4.5-6.5	7-9	9-11.5	11.5-14	0-1	4.5-7	8-11	10-13
D3MF-AA	CC	0-1	3-6.5	6-8	8-10.5	10-12.5	0-1	2.5-5.5	6.5-9.5	6.5-9.5	0-4	5-7	5-7	5-7
D3MF-BA	CC	0-1	0-1.5	3.5-5.5	7.5-10	8.5-11	0-1.25	2-5	4.5-7.25	4.5-7.25
D3MF-CA	CC	0-1.5	4.5-6.5	6-8	8-10.5	10-12.5	0-1	2.5-5.5	6.5-9.5	6.5-9.5	0-4	5-7	5-7	5-7
D3MF-DA	CC	0-1	1.5-4	5.5-7.5	7.5-9	8.25-10.5	0-1	1-4	5.5-8.5	8.5-11.25
D3MF-GA	CC	0-1	0-2.25	1.5-3.5	4.5-7	8-10.5	5-4.5	8-11	10.5-13.5	10.5-13.5
D3SF-BA	CC	0-1	5-2.5	5-5.8	10-12	11.25-13.5	0-1	1.5-4.5	5.5-9	8.5-11.25
D3JF-GA	CC	0-1	0-2.5	2-4.5	5.5-8.5	9.5-12	0-1	0-2.5	2.5-5.25	2.5-5.25	0-3	2-4	2-4	2-4
D3VF-AA	CC	0-1	0-1.5	3-5	4-6.25	5-7.5	0-2.25	5.5-8.5	8.5-11.25	8.5-11.25
D3VF-BA	CC	0-1	0-2.5	5-7	7.5-10	10-12.25	0-1.5	4-7.25	4.5-7.25	4.5-7.25
D3VF-CA	CC	0-1	0-1.5	4-6	6-8	7.25-10	0-1.25	5-8	8.5-11.25	8.5-11.25
D3ZF-CA	CC	0-1.25	3.25-5.25	4.5-6.5	6.5-9	9-11.5	0-1.25	4.5-7.5	8.5-11.5	10.5-13.25
D3ZF-GA	CC	0-1	0-2.5	2.25-4.25	5.5-7.5	8.25-11	0-1	2.25-5.25	6.5-9.5	9.5-12.5

ⓐ — C (Clockwise), CC (Counterclockwise) viewed from rotor end.