

CHRYSLER DISTRIBUTOR ADVANCE SPECIFICATIONS

NOTE — FOR ENGINE RPM AND DEGREES, MULTIPLY SPECIFICATIONS BELOW BY 2.

Distributor Part No.	Rot ①	Automatic Advance (Distr. Degrees & RPM)				Vacuum Advance (Distr. Deg. & In. of Hg.)					
		Deg.	RPM	Deg.	RPM	Deg.	In. Hg.	Deg.	In. Hg.		
3656763	C	1.5-5.5	550	6-8.5	700	13.5-16	2100	.5-2.5	9	9.5-12.5	15.5
3656859	C	.5-4	550	8-10.5	800	11.5-14	2000	.5-2.5	7	7-10	11.5
3755037	C	1-4	550	9-11.5	900	11.5-14	2000	.5-2	9	7-10	15.5
3755042	C	1-4	550	9-11.5	900	11.5-14	2000	.5-2	9	7-10	15.5
3755467	C	.5-3.5	550	7-9.5	950	12-14	2000	.5-2	9	7-10	15.5
3755470	C	.5-3.5	550	7-9.5	950	12-14	2000	.5-2	9	7-10	15.5
3755475	C	.5-4	550	8-10.5	800	11.5-14	2000	.5-2.5	7	10-12	12.5
3755486	C	1-5	600	8-10	850	12-14	2000	.5-2.5	8	10-12	13.5
3755508	CC	1-4.5	650	8-10.5	950	11.5-14	2000	.5-2.5	8	9.5-12	16
3755512	CC	1-4.5	650	8.5-11	950	13.5-16	2150	.5-2.5	8	9-11	14
3755518	CC	.5-3.5	650	5.5-8	900	9.5-12	2000	.5-2.5	8	9-11	14
3755522	CC	.5-3	650	4-6.5	900	8-10	2000	.5-2.5	8	9-11	14
3755681	CC	1-4.5	650	8.5-11	950	13.5-16	2150	.5-2.5	8	9-11	14

① — C (Clockwise). CC (Counterclockwise) viewed from rotor end.

1974 Distributor Specifications

6a-41

DELCO-REMY DISTRIBUTOR SPECIFICATIONS

NOTE — FOR ENGINE RPM AND DEGREES, MULTIPLY SPECIFICATIONS BELOW BY 2

Distributor Part No.	Ref ①	Automatic Advance (Distr. Degrees & RPM)				Vacuum Advance (Distr. Deg. & In. of Hg.)					
		Deg.	RPM	Deg.	RPM	Deg.	In. Hg.	Deg.	In. Hg.		
1110496	CC	0	800	2.5	1000	11	1400	0	7	12	15
1110499	C	0	550	7	1150	12	2050	0	7	12	15
1110528	C	0-2	600	6.5-9	1500	12.5-15	2200	0	5-7	6.5-9	12.75-13
1110529	C	0-2	500	7-9.5	1500	12-14	2150	0	5-7	6.5-9	12.75-13
1112093	C	0	550	5.5	1200	9	2100	0	5-7	7.5	13-14
1112112	C	0-2	500	7.5-9.5	1000	12-14	2000	0	5-7	6.75-8.25	11.2-12.7
1112113	C	0	550	5.5	1200	9	2100	0	5-7	10	14.2-15.7
1112114	C	0	550	5.5	1200	9	2100	0	5-7	10	14.2-15.7
1112168	C	0	500	-----	----	10	1200	0	2-4	7	7.5-8.5
1112179	C	0-2	500	8-10	1000	15-17	2200	0	5-7	6.75-8.25	11.2-12.7
1112195	CC	0-2	400	8-10	1050	14-16	2000	0	5-7	8	10-12
1112197	CC	0-2	540	5-7	1000	9-11	1800	0	7-9	9	15-16.6
1112205	CC	0	600	5	850	11	2300	0	9	12.5	13.5
1112210	CC	0	600	4	850	9	1950	0	9	10	16
1112212	CC	0	600	5	850	11	2300	0	9	10	16
1112213	CC	0	600	5	850	11	2300	0	7	12.5	12
1112214	C	0-2.5	500	11-13	1500	15-17	2200	0	4-6	6.75-8.25	11.5-13
1112215	C	0-1.5	400	6.5-8.5	1000	14-16	2200	0	4-6	6.75-8.25	11.5-13
1112225	CC	0-2	380	10-11	1050	17-19	2000	0	5-7	8	10-12
1112226	CC	0-2	400	8-10	1050	14-16	2000	0	3.5-4.5	10	12-13
1112231	CC	0	600	5	850	11	2300	0	9	12.5	14
1112234	CC	0	600	6.5	1065	12	1790	0	7	10	14
1112235	CC	0	600	6.5	1075	13	1725	0	5	12.5	11
1112236	CC	0	650	8	1050	13	1725	0	7	10	14
1112237	CC	0	600	4	775	12	1875	0	9	10	16
1112238	CC	0	600	4	790	12	1875	0	7	12	12
1112239	CC	0	600	5	850	11	2300	0	9	12.5	14
1112240	CC	0	600	5	850	11	2300	0	7	12.5	11.5
1112243	CC	0	600	5	850	11	2300	0	9	12.5	13.5
1112247	C	0	550	5.5	1200	9	2100	0	5-7	7.5	13-14
1112250	CC	0	550	5.5	1200	9	2100	0	9-11	5	15.5-16
1112504	C	0	550	5.5	1200	9	2100	0	7-9	8	15-16
1112506	--	0-2	540	5.7	1000	9-11	1800	0	7-9	9	15-16.6
1112512	CC	0	600	5	850	11	2300	0	9	10	16
1112513	CC	0	575	4.5	850	9	1950	0	9	10	16
1112520	--	0	500	7-9	1200	8-10	1500	0	6.5-8.5	6.5	14-19
1112521	--	0	500	4.5-6.5	900	10-12	2300	0	6-8	8	14-18
1112531	CC	0-2	540	5-7	1000	9-11	1800	0	6	9	10

1974 Distributor Specifications

DELCO-REMY DISTRIBUTOR SPECIFICATIONS (Cont.)

NOTE — FOR ENGINE RPM AND DEGREES, MULTIPLY SPECIFICATIONS BELOW BY 2

Distributor Part No.	Ref. ①	Automatic Advance (Distr. Degrees & RPM)				Vacuum Advance (Distr. Deg. & In. of Hg.)					
		Deg.	RPM	Deg.	RPM	Deg.	In. Hg.	Deg.	In. Hg.		
1112532	CC	0-2	540	5-7	1000	9-11	1800	0	4	10	13
1112541	..	0	500	5.5-7.5	900	9.5-12	1800	0	6-8	8	14-18
1112542	C	0	500	7-9	1050	11.5-14	2050	0	6.5-8.5	6.5	14-19
1112546	CC	0	600	4	800	12	1800	0	9	10	16
1112547	CC	0	600	4	800	12	1800	0	7	12.5	18
1112550	CC	0	375	7	600	13	1500	0	12	8	12
1112528	..	0	600	6	1100	10	2500	0	2-4	7	7.5-8.5
1112802	C	0	500	5.5-7.5	900	9.5-12	1800	0	6-8	8	14-18
1112803	C	0	500	7-9	1050	11.5-14	2050	0	6.5-8.5	6.5	14-19
1112804	CC	0	600	6.5	1065	12	1790	0	7	10	14
1112805	CC	0	600	4	775	12	1875	0	9	10	16
1112806	CC	0	650	8	1050	13	1725	0	7	10	14
1112807	CC	0	575	4.5	850	9	1950	0	9	10	16
1112808	CC	0	600	6.5	1075	13	1725	0	5	12.5	11
1112809	CC	0	600	4	790	12	1875	0	7	12	12
1112810	CC	0	600	4	800	9	2000	0	9	10	16
1112812	CC	0	600	5	850	11	2300	0	9	10	16
1112813	CC	0	600	5	850	11	2300	0	9	10	16
1112814	CC	0	600	5	850	11	2300	0	7	12.5	11.5
1112821	CC	0	500	4	700	12	1900	0	7	10	14
1112822	CC	0	500	4	700	12	1900	0	7	10	14
1112825	CC	0-2	575	3.5-5.5	1000	7-9	1400	0	6	9	10
1112827	CC	0-2	575	3.5-5.5	1000	7-9	1400	0	7	12	17
1112828	CC	0-2	400	8-10	1050	14-16	2000	0	3.5-4.5	10	12-13
1112829	CC	0-2	575	3.5-5.5	1000	7-9	1400	0	4	10	13
1112830	CC	0-2	575	3.5-5.5	1000	7-9	1400	0	7	12	17
1112833	CC	0	600	3	825	12	2000	0	9	10	16
1112834	CC	0	600	3	825	12	2000	0	9	10	16
1112835	C	0-5	500	5.5-7.5	1200	7.75-9.75	2000	0-2.5	6	7.25-8.75	16
1112836	C	0-5	500	5.5-7.5	1200	7.75-9.75	2000	0-2.5	10	7.25-8.75	16
1112837	C	0-4.25	500	4.5-6.5	1200	6.75-8.5	2000	0-2.5	6	7.25-8.75	16
1112838	C	0-4.25	500	4.5-6.5	1200	6.75-8.5	2000	0-2.5	10	7.25-8.75	16
1112839	C	0-5	500	5.5-7.5	1200	7.75-9.75	2000	0-2.5	6	7.25-8.75	16
1112840	C	0-5	500	5.5-7.5	1200	7.75-9.75	2000	0-2.5	10	7.25-8.75	16
1112841	C	0-4.25	500	4.5-6.5	1200	6.75-8.5	2000	0-2.5	6	7.25-8.75	16
1112842	C	0-4.25	500	4.5-6.5	1200	6.75-8.5	2000	0-2.5	10	7.25-8.75	16
1112845	C	0-2	500	6-8	1200	11-13	2000	0-2.5	6	7.25-8.75	16

1974 Distributor Specifications

DELCO-REMY DISTRIBUTOR SPECIFICATIONS (Cont.)

NOTE — FOR ENGINE RPM AND DEGREES, MULTIPLY SPECIFICATIONS BELOW BY 2

Distributor Part No.	Ref ①	Automatic Advance (Distr. Degrees & RPM)				Vacuum Advance (Distr. Deg. & In. of Hg.)			
		Deg.	RPM	Deg.	RPM	Deg.	In. Hg.	Deg.	In. Hg.
1112846	C	0	500	-----	----	0	3-5	7.5	9.5-10.5
1112847	--	0	550	5.5	1200	----	---	----	----
1112849	--	0	500	7.5	1200	0	2-4	7	7.5-8.5
1112850	---	0	500	7.5	1200	0	2-4	7	7.5-8.5
1112851	--	0	550	5.5	1200	0	2-4	7	7.5-8.5
1112852	--	0	600	6	1100	0	2-4	7	7.5-8.5
1112853	--	0	500	6	1100	0	2-4	7	7.5-8.5
1112854	--	0	500	-----	----	0	3-5	7.5	9.5-10.5
1112855	C	0-2	500	6-8	1200	0-2.5	6	7.25-8.75	16
1112856	CC	0	610	5	800	0	---	10	14
1112857	CC	0	610	5	800	0	---	10	14
1112859	CC	0	575	4	850	0	7	10	14.5
1112860	CC	0	575	4	850	0	7	10	14.5
1112871	CC	0	600	5	875	0	9	12.5	16
1112876	CC	0	600	3	775	0	9	10	16
1112878	CC	0	600	4	800	0	7	10	14

① — C (Clockwise), CC (Counterclockwise) viewed from rotor end.

1974 Distributor Specifications

FORD MOTOR CO. DISTRIBUTOR ADVANCE AND RETARD SPECIFICATIONS

NOTE — FOR ENGINE RPM AND DEGREES, MULTIPLY SPECIFICATIONS BELOW BY 2.

Distributor Part No.	Rot. [⊙]	Automatic Advance (Distr. Degrees @ RPM)								Vacuum Advance (Distr. Degrees) Operate Distr. @ 1000 RPM				Vacuum Retard (Distr. Degrees) Operate Distr. @ 1000 RPM				
		500	750	1000	1500	2000	5	10	15	20	5	10	15	20	5	10	15	20
		74HF-CA	C	0-2	3.5-5.5	5.5-7.5	7.5-9.5	10-12	0-2	1.5-3.5	1.5-3.5	1.5-3.5	0	0-2.5	2-4	2-4	0	0-2.5
74HF-EA	C	1-3	5-7	6.5-8.5	9.5-11.5	12-14	0-5	2-4	4-6	4-6	0	0-3.5	2-4	4-6	0	0-3.5	2-4	2-4
74HF-JA	C	0-5	0-1	3-5	6-8	8-10	0	0-2	3.5-5.5	3.5-5.5	0	0-3.5	0-2	3.5-5.5	0	0-3.5	2-4	2-4
74HF-LA	C	0-1	1-3	4-6	7-9	9.5-11.5	0-5	2-4	4-6	4-6	0	0-3.5	2-4	4-6	0	0-3.5	2-4	2-4
74TF-LA	C	0-5	1-3	3.5-5.5	7.5-9.5	8-10	0-1.5	2-4	2-4	2-4	0	0-4	2-4	2-4	0	0-4	5-7	5-7
74TF-MA	C	0-5	1-3	3.5-5.5	7.5-9.5	8-10	0-5	2-4	2-4	2-4	0	0-3.5	2-4	2-4	0	0-3.5	2-4	2-4
74TF-NA	C	0-5	1-3	3.5-5.5	7.5-9.5	8-10	0-1.5	2-4	2-4	2-4	0	0-3.5	2-4	2-4	0	0-3.5	5-7	5-7
74TF-RA	C	0-5	1-3	3.5-5.5	7.5-9.5	8-10	0-1.5	2-4	2-4	2-4	0	0-3.5	2-4	2-4	0	0-3.5	2-4	2-4
74TF-SA	C	0-5	1-3	3.5-5.5	7.5-9.5	8-10	0-1.5	2-4	2-4	2-4	0	0-3.5	2-4	2-4	0	0-3.5	2-4	2-4
74TF-TA	C	0-5	1-3	3.5-5.5	7.5-9.5	8-10	0-1.5	2-4	2-4	2-4	0	0-3.5	2-4	2-4	0	0-3.5	2-4	2-4
D3AF-AA	CC	0-1.5	4-6	6-8.25	10-12.5	14-16.5	0-2	6-9	9.5-12.5	10.5-13.25	0-3.5	5-7	5-7	5-7	0-3.5	5-7	5-7	5-7
D3BF-DA	CC	0-1.25	2.5-4.5	5.5-7.5	8.5-10.5	11.5-13.5	0-1	0-2	5.5-8.5	8.5-11.25	0-4	2-4	2-4	2-4	0-4	2-4	2-4	2-4
D3DF-FA	C	0-1.5	1.5-3.5	4.5-6.5	6.5-9	8.5-10.5	0-3	6.5-9.25	6.5-9.25	6.5-9.25	0-2	2-4	2-4	2-4	0-2	2-4	2-4	2-4
D3DF-HA	C	0-1.5	3.5-5.5	7.5-9.5	9.5-11.5	10-12.5	0-1	1-4	4.5-7.25	4.5-7.25	0-2	2-4	2-4	2-4	0-2	2-4	2-4	2-4
D3DF-KA	C	0-1.5	4.5-6.5	7.5-9.5	8.5-11	10-12.5	0-1	4-7	4.5-7.25	4.5-7.25	0-2	2-4	2-4	2-4	0-2	2-4	2-4	2-4
D3OF-DA	CC	0-1	0-1.5	4-6	7-9.5	8.5-11	0-1.25	2.5-5.25	2.5-5.25	2.5-5.25	0-2	3.5-7	5-7	5-7	0-2	3.5-7	5-7	5-7
D3OF-FA	CC	0-1	0-1.5	1-3	5-5.8	10.5-13	0-3	2.5-5.25	2.5-5.25	2.5-5.25	0-3.5	4.5-7	5-7	5-7	0-3.5	4.5-7	5-7	5-7
D3OF-GA	CC	0-1	0-1.5	1-3.5	6-8.5	11-13.5	0-3.5	2.5-5.25	2.5-5.25	2.5-5.25	0-3.5	4.5-7	5-7	5-7	0-3.5	4.5-7	5-7	5-7
D3OF-HB	CC	0-1.5	.5-3	2.5-5	6.5-9	10.5-13.5	0-1.5	4.5-7.5	8.5-11.25	8.5-11.25	0-3.5	4.5-7	5-7	5-7	0-3.5	4.5-7	5-7	5-7
D3OF-RA	C	0-1.5	3.5-7.5	5.5-7.5	6.5-8.5	7.5-10	.5-3.5	6.5-9.25	6.5-9.25	6.5-9.25	0-3.5	2-4	2-4	2-4	0-3.5	2-4	2-4	2-4
D3UF-EA	CC	0-1.25	2.5-4.5	5.5-7.5	9-11	12.25-14.5	0-1.5	6.5-9.25	6.5-9.25	6.5-9.25	0-4	5-7	5-7	5-7	0-4	5-7	5-7	5-7
D3ZF-GA	CC	0-1	0-2.5	2.25-4.25	5.5-7.5	8.25-11	0-1	2.25-4.25	6.5-9.5	6.5-9.5	0-3.5	4.5-7	5-7	5-7	0-3.5	4.5-7	5-7	5-7
D4AE-AA	CC	0-5	0-2	2.5-4.5	5.5-7.5	8.25-11	0-1	2.5-5.5	7-10	9.5-12.5	0-3.5	4.5-7	5-7	5-7	0-3.5	4.5-7	5-7	5-7
D4AE-HA	CC	0-1.5	5-7	6-8	8-10.5	10-12.5	0-1	2.5-5.5	6.5-9.5	6.5-9.5	0-4	5-7	5-7	5-7	0-4	5-7	5-7	5-7
D4DE-FA	C	0-1.5	4.5-6.5	7.5-9.5	9-11	10-12.5	0-1	2.5-5.5	6.5-9.5	6.5-9.5	0-2	2-4	2-4	2-4	0-2	2-4	2-4	2-4
D4DE-LA	C	0-1.5	4-6	4.5-6.5	6-8	7-9.5	0-1.5	6.5-9.25	6.5-9.25	6.5-9.25	0-4	2-4	2-4	2-4	0-4	2-4	2-4	2-4
D4DE-MA	CC	0-5	.5-2.5	3.5-5.5	7.5-9.5	10.5-13.5	0-1.5	4.5-7.5	8.5-11.5	8.5-11.5	0-3.5	4.5-7	5-7	5-7	0-3.5	4.5-7	5-7	5-7
D4DE-NA	C	0-1.5	3.5-5.5	5.5-7.5	6.5-8.5	7.5-10.5	0-1.5	4.5-7	6.5-9.25	6.5-9.25	0-2	2-4	2-4	2-4	0-2	2-4	2-4	2-4
D4DE-RA	C	0-1.5	3.5-5.5	5.5-7.5	6.5-8.5	7.5-10.5	0-4	6.5-9.25	6.5-9.25	6.5-9.25	0-3	2-4	2-4	2-4	0-3	2-4	2-4	2-4
D4OE-CA	CC	0-5	0-1.5	2-4	5.5-7.5	8-10.5	.5-4	8-11	10.5-13.5	10.5-13.5	0-3.5	4.5-7	5-7	5-7	0-3.5	4.5-7	5-7	5-7
D4VE-CA	CC	0-5	0-5	3-5	7-9	8.25-10.5	0-1.25	5-8	8.5-11.25	8.5-11.25	0-3.5	4.5-7	5-7	5-7	0-3.5	4.5-7	5-7	5-7
D4ZE-AA	C	0-1	1-3	4-6	9.5-11.5	11.5-14	0-2.5	4.5-7.5	4.5-7.5	4.5-7.5	0-3.5	4.5-7	5-7	5-7	0-3.5	4.5-7	5-7	5-7
D4ZE-BA	C	0-1	4-6	7-9	9.25-11.5	11.5-14	0-2.5	4.5-7.5	4.5-7.5	4.5-7.5	0-3.5	4.5-7	5-7	5-7	0-3.5	4.5-7	5-7	5-7
D4ZE-KA	C	0-1	4-6.5	7-9	9.25-11.5	11.5-14	0-2.5	4.5-7.5	4.5-7.5	4.5-7.5	0-3.5	4.5-7	5-7	5-7	0-3.5	4.5-7	5-7	5-7
D4AF-DA	C	0-1	1.5-3.5	6-8	9.5-11.5	11.5-14	0-2.5	2.5-5.5	2.5-5.5	2.5-5.5	0-3.5	4.5-7	5-7	5-7	0-3.5	4.5-7	5-7	5-7

⊙ — C (Clockwise), CC (Counterclockwise) viewed from rotor end.