

Ignition Distributors

1965 FORD MOTOR CO. DISTRIBUTOR ADVANCE SPECIFICATIONS

NOTE — FOR ENGINE RPM AND DEGREES, MULTIPLY SPECIFICATIONS BY 2.

Distributor Part No. ②	Rot ①	Automatic Advance (Distr. Degrees & RPM)				Vacuum Advance (Distr. Deg. & In. of Hg.)					
		Deg.	RPM	Deg.	RPM	Deg.	In. Hg.	Deg.	In. Hg.		
C5TF-B ③	CC	0-1	500	2-3	700	4.75-5.75	1200	.5-3.5	6	6-9	12
C5TF-C ③	CC	0-1	500	2-3	700	4.75-5.75	1200	.5-3.5	6	6-9	12
C5TF-K ③	C	.75-1.75	600	8.25-9.25	1200	11-12.5	2000	1-4	8	6.5-8.5	14
C5TF-L ③	C	0-1	600	7-8	1200	11-12.5	2000	1-4	8	4-7	12
C5TF-N ④	C	0	500	2.5-3.5	800	9.5-10.75	2000	0	.38	9.5-10.75	5.20
C5TF-R ④	C	1.5-2.5	800	5.25-6.25	1200	8.5-9.75	2000	0	.30	8.5-9.75	3.50
C5TF-Y ④	CC	1.75-2.75	600	5.5-6.5	800	12.5-14	2000	2-5	8	7-10	15
C5TF-Z ④	CC	1.75-2.75	450	7.75-8.75	1200	10.5-12	2000	2-5	8	6.5-9.5	14
C5UF-G ④	C	1-2	600	4.5-5.5	800	8.25-9.5	1200	1-2	.70	8.25-9.5	2.10
C5UF-J ④	C	.25-1.25	600	7-8	1200	11-12.25	2000	.25-1.25	.45	7-8	1.75
C5UF-K ④	C	1-2	500	3-4.25	800	9.5-10.75	2000	1-2	.35	6.25-7.25	1.80
C5AF-AD ④	C	1-2	600	4.5-5.5	800	8.25-9.5	1200	1-2	.70	8.25-9.5	2.10

① — C (Clockwise), CC (Counterclockwise) viewed from rotor end.

② — Basic number is 12127. Table gives prefix and suffix only.

③ — Ford Dual Advance Distributor.

④ — Ford Loadomatic Distributor.

⑤ — Transistor Ignition.

Ignition Distributors

1966 FORD MOTOR CO. DISTRIBUTOR ADVANCE SPECIFICATIONS

NOTE — FOR ENGINE RPM AND DEGREES, MULTIPLY SPECIFICATIONS BY 2.

Distributor Part No. ②	Rot ①	Automatic Advance (Distr. Degrees & RPM)						Vacuum Advance (Distr. Deg. & In. of Hg.)			
		Deg.	RPM	Deg.	RPM	Deg.	RPM	Deg.	In. Hg.	Deg.	In. Hg.
C5AF-B ③	CC	4.5-5.5	550	7.75-8.75	1200	10.5-12	2000	2-5	8	6.5-9.5	14
C5TF-A ③	CC	5.5-6.5	800	9.75-10.75	1400	12.25-14	2000	2-5	8	7-10	15
C5TF-AB ③ ④	CC	2-3	800	8-9.25	1500	9.25-10.75	2000	1.75-4.5	8	5.5-8.5	15
C5UF-J ④	C	.25-1.25	1200	7-8	1200	11-12.5	2000	3.5-4.5	.75	7-8	1.75
C6AF-Y ④	C	1-2	800	4.5-5.5	1200	8.75-10	2000	1-2	.90	7-8.25	3.6
C6AF-AA ④	C	1.25-2.25	600	7.25-8.5	1200	11.5-13	2000	3-6	7	9.5-12.5	14
C6AF-AD ④	C	0-5	300	5.75-6.75	1000	9.5-11	2000	0-1	4	8.5-11.5	15
C6TF-G ④ ⑤	CC	2.5-3.75	650	8.25-9.25	1100	11.5-13	1800	2-5	7	7-10	15
C6TF-H ④	CC	.5-1.5	400	6.25-7.25	800	9.75-11.25	1800	1-4	7	7-10	15
C6TF-AA ④ ⑤	CC	.75-1.75	500	11.5-12.5	1800	12.5-14	2000	0-1	5	7-10	15
C6TF-AB ④	CC	.75-1.75	500	6.75-8	1200	12.5-14	2000	0-1	5	7-10	15
C6TF-AC ④	C	4.5-5.5	800	9.25-10.5	1600	10.25-11.75	2000	4.5-5.5	1.2	9.25-10.5	3.70
C6TF-AD ④	C	0-1	600	4-5.25	900	8.5-10	2000	1-4	8	5.5-8.5	13
C6TF-AF ④	C	.75-1.75	600	8.25-9.25	1200	12.5-14	2000	1-4	8	6.5-8.5	14
C6TF-AG ④	C	0-1	600	7-8	1200	11-12.5	2000	1-4	8	4-7	12
C6TF-AH ④	C	0-1	600	6-7.25	1200	8.5-10	2000	1-4	6	7-10	12
C6TF-AJ ④	C	1-2	500	8.5-9.5	1100	9-11	2000	1-4	6	7-10	12
C6TF-AM ④ ⑤	C	1-2	600	7.5-8.5	1200	10.5-11.75	2000	1-2	0.7	7.5-8.5	2.10
C6TF-AN ④ ⑤	C	1-2	800	4.5-5.5	1200	8.75-10	2000	1-2	0.9	7-8.75	3.60
C6TF-AR ④ ⑤	C	0-1	600	6-7.25	1200	8.25-10	2000	1-4	8	5.5-8.5	13
C6TF-AS ④ ⑤	C	.75-1.75	600	8.25-9.25	1200	12.5-14	2000	1-4	8	6.5-8.5	14
C6TF-AT ④ ⑤	C	0-1	600	7-8	1200	11-12.5	2000	1-4	8	4-7	12
C6TF-AU ④ ⑤	C	0-1	600	6-7.25	1200	8.5-10	2000	1-4	6	7-10	12
C6TF-AV ④ ⑤	C	1-2	500	8.5-9.5	1100	9-11	2000	1-4	6	7-10	12
C6TF-AY ④	C	0-5	350	3.5-4.5	1050	8-9.5	1900	0-1	4	9-12	17
C6TF-BA ④	C	0-5	300	6-7	1000	10.25-11.75	2000	0-1	4	9.25-12.5	15
C6TF-BD ④ ⑤	C	0-5	300	5.75-6.75	1000	9.5-11	2000	0-1	4	8.5-11.5	15
C6TF-BE ④ ⑤	C	0-5	300	6-7	1000	10.5-11.75	2000	0-1	4	9.25-12.5	15
C6TF-BC ④ ⑤	C	0-5	300	3.25-4.25	1000	7.5-8.75	1800	0-1	4	8.5-11.5	15
C6UF-F ④	C	1-2	600	4.25-5.5	1200	8-9.5	1900	0-1	4	9-12	17
C6UF-H ④	C	0-5	300	5-6	700	7.5-9	1600	0-1	4	9-12	17
C7OF-A ④	CC	0-5	400	7.5-8.5	1000	12-13.75	2000	0-1	5	7.25-10.25	15
C7OF-B ④	CC	0-5	300	7.75-8.75	1000	10.5-12	2000	0-1	5	9.25-12.25	15
C7OF-D ④	CC	0-5	300	8-9	1000	12.5-14	2000	0-1	5	9.5-12.5	15
C7OF-E ④	CC	0-5	300	8.5-9.75	1000	12.25-13.75	2000	0-1	5	8.5-11.5	15

① — C(Clockwise), CC(Counterclockwise) viewed from rotor end.

② — Basic number is 12127. Table gives prefix and suffix only.

③ — Ford Dual Advance Distributor.

④ — Ford Loadomatic Distributor.

⑤ — Transistor Ignition.

Ignition Distributors

1967 FORD MOTOR CO. DISTRIBUTOR ADVANCE SPECIFICATIONS NOTE - FOR ENGINE RPM AND DEGREES, MULTIPLY SPECIFICATIONS BY 2.

Distributor Part No.	Rot ①	Automatic Advance (Distr. Degrees & RPM)						Vacuum Advance (Distr. Deg. & In. of Hg.)			
		Deg.	RPM	Deg.	RPM	Deg.	RPM	Deg.	In. Hg.	Deg.	In. Hg.
C5DF-C④	C	2.5-3.5	800	6.5-7.5	1200	10.25-11.5	2000	2.5-3.5	0.80	8.75-10	3.0
C5DF-K④	C	.75-1.75	800	3.75-4.75	1200	7-8.25	2000	.75-1.75	0.79	5.75-7	3.0
C5UF-J④	C	.25-1.25	600	7-8	1200	11-12.25	2000	.25-1.25	0.45	7-8	1.75
C5UF-K④	C	1-2	500	6.25-7.25	1200	9.5-10.75	2000	1-2	0.35	6.5-7.25	1.80
C6AF-Y④	C	1-2	800	4.5-5.5	1200	8.75-10	2000	1-2	0.90	7-8.25	3.60
C6AF-AD④	C	2.25-3.25	500	5.75-6.75	1000	7.5-9	1500	0-1	4	8.5-11.5	15
C6TF-AC④	C	4.25-5.5	800	7.5-8.75	1200	10.25-11.75	2000	4.25-5.5	1.20	9.25-10.5	3.70
C6TF-AF④	C	.75-1.75	600	8.25-9.25	1200	12.5-14	2000	1-4	8	6.5-8.5	14
C6TF-AG④	C	0-1	600	7-8	1200	11-12.5	2000	1-4	8	4-7	12
C6TF-AY④	C	1-2	600	4.25-5.5	1200	8-9.5	1900	0-1	4	9-12	17
C6TF-BA④	C	2.25-3.25	500	7.25-8.5	1300	10.25-11.75	2000	0-4	6	9.5-12.5	15
C6UF-F④	C	4.25-5.25	800	7.75-9	1200	10-11.75	1600	4.25-5.25	0.85	10-11.25	3.70
C6UF-H④	C	3-4	525	5-6	700	7.5-9	1600	0-1	4	9-12	17
C7DF-A④	C	2-3	500	8.75-10	1300	12.5-14	2000	0-1	5	4-7	15
C7OF-A④	CC	4.75-5.75	800	9.75-11	1500	12-13.75	2000	0-1	5	7.25-10.25	15
C7OF-D④	CC	3-4	600	8-9	1000	12.5-14	2000	0-1	5	9.5-12.5	15
C7TF-A④	CC	.75-1.75	500	9-10.25	1500	12.25-14	2000	0-1	5	7-10.25	15
C7TF-D④	C	1-2	600	3.75-5	1000	8-9.25	2000	0-1	4	6-9	15
C7TF-F④	CC	3.25-4.25	500	7-8	1000	10.5-12	2000	0-1	5	7-10	15
C7TF-J④	C	1-2	800	8-9	1400	11-12.5	2000	0-1	5	4-7	15
C7TF-R④	CC	5.5-6.5	1000	10.5-11.75	1500	13.5-14.75	2000	0-1	5	7-10	15

① - C(Clockwise), CC(Counterclockwise) viewed from rotor end.

② - Basic number is 12127. Table gives prefix and suffix only.

③ - Ford Dual Advance Distributor.

④ - Ford Loadomatic Distributor.

Ignition Distributors

1968 FORD MOTOR CO. DISTRIBUTOR ADVANCE SPECIFICATIONS

NOTE — FOR ENGINE RPM AND DEGREES, MULTIPLY SPECIFICATIONS BY 2.

Distributor Part No. ②	Rot ①	Automatic Advance (Distr. Degrees & RPM)				Vacuum Advance (Distr. Deg. & In. of Hg.)					
		Deg.	RPM	Deg.	RPM	Deg.	In. Hg.	Deg.	In. Hg.		
C5DF-C ④	C	2.5-3.5	800	6.5-7.5	1200	10.25-11.5	2000	0-5	0.3	6.5-7.5	1.8
C6AF-Y ④	C	1-2	800	4.5-5.5	1200	8.75-10	2000	1-2	.90	7-8.25	3.6
C6TF-AC ④	C	4.5-5.5	800	9.25-10.5	1600	10.25-11.75	2000	4.5-5.5	1.2	9.25-10.5	3.70
C6TF-AD ④	C	0-1	600	4-5.25	900	8.5-10	2000	1-4	8	5.5-8.5	13
C6TF-AF ④	C	.75-1.75	600	8.25-9.25	1200	12.5-14	2000	1-4	8	6.5-8.5	14
C6TF-AG ④	C	0-1	600	7-8	1200	11-12.5	2000	1-4	8	4-7	12
C8AF-A ④	C	0-5	500	2.25-4.5	1000	7.5-10	2000	0-7.5	5	5.5-8	15
C8TF-D ④	C	0-1	500	1.75-4	1000	6.5-9	2000	0-1	5	10-12.5	15
C8TF-F ④	CC	0-5	500	3.5-5.5	1000	8.75-11	2000	0-1	5	5.75-8.75	15
C8TF-G ④	CC	1.5-3.75	500	6.5-8.75	1000	12-14.5	2000	0-1	5	10-12.5	15
C8TF-H ④	CC	1.5-3.5	500	6.5-8.75	1000	12-14.5	2000	0-1	5	9.75-12.5	15
C8TF-L ④	CC	0-2	500	4.25-6.5	1000	12-14.5	2000	0-1	5	9.75-12.5	15
C8UF-D ④	C	0-5	500	3.75-5.75	1000	7.5-10	2000	0-1	5	6.25-9	15

① — C(Clockwise), CC(Counterclockwise) viewed from rotor end.

② — Basic number is 12127. Table gives prefix and suffix only.

③ — Ford Dual Advance Distributor.

④ — Ford Loadomatic Distributor.

Ignition Distributors

1969 FORD MOTOR CO. DISTRIBUTOR ADVANCE SPECIFICATIONS

NOTE — FOR ENGINE RPM AND DEGREES, MULTIPLY SPECIFICATIONS BY 2.

Distributor Part No..	Rot ①	Automatic Advance (Distr. Degrees & RPM)				Vacuum Advance (Distr. Deg. & In. of Hg.)					
		Deg.	RPM	Deg.	RPM	Deg.	In. Hg.	Deg.	In. Hg.		
C6AF-Y④	C	.75-2	800	4.5-5.5	1200	8.75-10	2000	0-5	.34	4.5-5.5	2.1
C6TF-AC④	C	4.75-5.5	800	7.5-8.75	1200	10.25-11.75	2000	0-5	.4	7.5-8.75	2.1
C6TF-AD③	C	0-5	500	4.5-6.5	1000	7.5-10	2000	0-1	5	6-8.5	15
C6TF-AF③	C	0-5	500	6-8.25	1000	11.5-14	2000	0-1	5	5.5-8.5	15
C6TF-AG③	C	0-5	500	4.5-6.5	1000	10-12.5	2000	0-1	5	4-7	15
C7OF-A③	CC	0-5	500	6.5-8.5	1000	11.25-13.75	2000	0-1	5	7.25-10.25	15
C7OF-B③	CC	1.75-3.75	500	6.75-8.75	1000	9.5-12	2000	0-1	5	9.5-12.25	15
C8AF-A③	C	0-5	500	2.25-4.5	1000	7.5-10	2000	0-7.5	5	5.5-8	15
C8TF-D③	C	0-1	500	1.75-4	1000	6.5-9	2000	0-1	5	10-12.5	15
C8TF-F③	CC	0-5	500	3.5-5.5	1000	8.75-11	2000	0-1	5	5.75-8.75	15
C8TF-H③	CC	1.5-3.5	500	6.5-8.75	1000	12-14.5	2000	0-1	5	9.75-12.5	15
C8TF-U③	C	0-5	500	4.5-6.5	1000	7.5-10	2000	0-1.5	5	8.75-11.75	15
C9TF-J③	C	0-1	500	1.75-4	1000	6.5-9	2000	0-1	5	10-12.5	15
C9UF-A③	C	0-5	500	2.25-4.5	1000	7.5-10	2000	0-7.5	5	5.5-8	15
C9UF-C③	CC	0-5	500	3.25-5.25	1000	9.75-12.25	2000	0-7.5	5	3.75-7	15
C9UF-F③	C	0-5	500	3.5-5.5	1000	9.5-12	2000	0-7.5	5	2.75-6	15

① — C(Clockwise), CC(Counterclockwise) viewed from rotor end.

② — Basic number is 12127. Table gives prefix and suffix only.

③ — Ford Dual Advance Distributor.

④ — Ford Loadomatic Distributor.

1970 FORD MOTOR CO. DISTRIBUTOR ADVANCE SPECIFICATIONS

NOTE — FOR ENGINE RPM AND DEGREES, MULTIPLY SPECIFICATIONS BY 2.

Distributor Part No. ②	Rot. ①	Automatic Advance (Distr. Degrees @ RPM)						Vacuum Advance (Distr. Degrees) Operate Distr. @ 1000 RPM			Vacuum Retard (Distr. Degrees) Operate Distr. @ 1000 RPM			
		500	750	1000	1500	2000	5	10	15	20	5	10	15	20
C8AF-A ③	C	0-5	0-1.5	2.25-4.5	6-8	7.5-10	0-75	.75-3.75	5.5-8	5.5-8	0-1.5	2.5-6	5-6	5-6
C8DF-A ③	C	0-2	6.25-8.25	6.75-11	10.5-13	0-1	3-6	5.5-8	5.5-8	0-1.75	3.5-6	5-6	5-6
C8TF-D ③	C	0-1	.75-2.75	1.75-4	4.25-6.5	6.5-9	0-1	6.75-9.75	10-12.5	10-12.5	0-1.25	2.75-6	5-6	5-6
C8TF-F ③	CC	0-5	0-2	3.5-5.5	7-9	8.75-11	0-1	2-5	5.75-8.75	8-11	0-1.75	3.5-6	5-6	5-6
C8TF-U ④	C	0-5	.75-3	4.5-6.5	6-8.25	7.5-10	0-1.5	5.75-8.75	8.75-11.25	10-12.5
C9UF-A ④	C	0-5	0-1.5	2.25-4.5	5.75-8	7.5-10	0-75	.75-3.75	5.5-8	5.5-8
C9UF-F ④	C	0-5	0-2	3.5-5.5	7.75-10	9.5-12	0-75	0-2	2.75-6	3.5-6	0-25	1.25-5.75	5-6	5-6
D0TF-G ④	CC	0-5	2.5-4.5	5-7	6.5-8.75	8-10.5	0-75	0-1.75	3.75-7	5.5-8
D0TF-H ④	CC	0-5	2.5-4.5	5-7	6.5-8.75	8-10.5	0-75	0-1.5	3.75-7	5.5-8	0-3.25	4.75-6	5-6	5-6
D0TF-J ③	CC	2.5-4.5	7.75-9.75	9-11	11.25-13.5	13.75-16.25	0-1.25	6.5-9	6.5-9	6.5-9	0-25	2-6	5-6	5-6
D0TF-K ④	CC	2.5-4.5	7.75-9.75	9-11	11.25-13.5	13.75-16.25	0-1.25	6-9	6.5-9	6.5-9

① — C(Clockwise), CC(Counterclockwise) viewed from rotor end.

② — Basic number is 12127. Table gives prefix and suffix only.

③ — Dual Vacuum Diaphragm Distributor.

④ — Single Vacuum Diaphragm Distributor.

Ignition Distributors

1971 FORD MOTOR CO. DISTRIBUTOR ADVANCE SPECIFICATIONS

NOTE — FOR ENGINE RPM AND DEGREES, MULTIPLY SPECIFICATIONS BY 2.

Distributor Part No.	Rot. ①	Automatic Advance (Distr. Degrees @ RPM)					Vacuum Advance (Distr. Degrees) Operate Distr. @ 1000 RPM					Vacuum Retard (Distr. Degrees) Operate Distr. @ 1000 RPM						
		500	750	1000	1500	2000	5	10	15	20	5	10	15	20	5	10	15	20
C8AF-A③	C	0-5	0-1.5	2.25-4.5	6-8	7.5-10	0-75	.75-3.75	5.5-8	5.5-8	0-1.5	2.5-6	5-7	0-1.5	2.5-6	5-7	5-7	5-7
C8DF-A③	C	0-2	6.25-8.25	6.75-11	4.25-6.5	6.5-9	0-1	3-6	5.5-8	5.5-8	0-1.75	3.5-6	5-6	0-1.75	3.5-6	5-6	5-6	5-6
C8TF-D③	C	0-1	.75-2.75	1.75-4	4.25-6.5	6.5-9	0-1	6.75-9.75	10-12.5	10-12.5	0-1.25	2.75-6	5-7	0-1.25	2.75-6	5-7	5-7	5-7
C8TF-U④	C	0-5	.75-3	4.5-6.5	6-8.25	7.5-10	0-1.5	5.75-8.75	8.75-11.75	10-12.5
C9UF-A④	C	0-5	0-1.5	2.25-4.5	6-8	7.5-10	0-75	.75-3.75	5.5-8	5.5-8
C9UF-F③	C	0-5	0-2	3.5-5.5	7.75-10	9.5-12	0-75	0-2	2.75-6	3.5-6	0-25	1.25-6.25	5-7	0-25	1.25-6.25	5-7	5-7	5-7
D0TF-J②	CC	2.5-4.5	7.75-9.75	9-11	11.25-13.5	13.75-16.25	0-1.25	6.5-9	6.5-9	6.5-9	0-25	2-7	5-7	0-25	2-7	5-7	5-7	5-7
D0TF-M③	CC	0-5	.5-2.5	6-8	8.5-10.75	9.75-12.25	0-75	0-2.25	5-8	8-10.5	0-3	4.5-7	5-7	0-3	4.5-7	5-7	5-7	5-7
D1TF-CA③	C	0-5	0-5	.5-2.5	5.75-8	7.75-10.25	0-1	1-4	5.5-8	5.5-8	0-1.25	2.5-7	5-7	0-1.25	2.5-7	5-7	5-7	5-7
D1TF-EA④	CC	0-75	2.5-5.75	9-11	11.25-13.5	13.5-16	0-1.25	6-9	6.5-9	6.5-9
D1UF-A④	CC	0-5	.5-2.5	6-8	8.5-10.75	9.75-12.25	0-1	0-2.25	5-8	8-10.5

① — C(Clockwise) CC(Counterclockwise) viewed from rotor end.

② — Basic number is 12127. Table gives prefix and suffix only.

③ — Dual Vacuum Diaphragm Distributor.

④ — Single Vacuum Diaphragm Distributor.

Ignition Distributors

1972 FORD MOTOR CO. DISTRIBUTOR ADVANCE SPECIFICATIONS NOTE - FOR ENGINE RPM AND DEGREES, MULTIPLY SPECIFICATIONS BY 2.

Distributor Part No.	Rot. ^①	Automatic Advance (Distr. Degrees @ RPM)						Vacuum Advance (Distr. Degrees) Operate Distr. @ 1000 RPM				Vacuum Retard (Distr. Degrees) Operate Distr. @ 1000 RPM					
		750		1000		1500		2000		5	10	15	20	5	10	15	20
		500															
D2AF-CA ^②	CC	0-5	0-1.5	4.5-6.5	7.5-9.5	8.5-11	0-1.25	2.5-5.5	2.5-5.5	2.5-5.5	2.5-5.5	0-2.25	3.25-7	5-7	5-7	5-7	5-7
D2AF-DA ^③	CC	0-5	0-1.5	4.5-6.5	7.5-9.5	8.5-11	0-1.25	2.5-5.5	2.5-5.5	2.5-5.5	2.5-5.5	0-2.25	3.25-7	5-7	5-7	5-7	5-7
D2BF-AA ^③	C	0-1	0-2	3.5-5.5	8-10	9.5-12	0-1	0-2.5	3.5-6.5	4.5-7.5	0-2.5	3.5-6.5	5-7	5-7	5-7	5-7	5-7
D2TF-AA ^③	CC	1.5-4.5	7.5-10	9-11.25	11.25-13.5	13.5-16	0-1.5	6.25-9.25	6.25-9.25	6.25-9.25	6.25-9.25	0-6.5	5-7	5-7	5-7	5-7	5-7
D2TF-EA ^④	C	0-5	1-3	4.5-6.5	6-8.25	7.5-10	0-2.5	6-9	10.5-13.5	10.5-13.5	0-6.5	5-7	5-7	5-7	5-7	5-7	5-7
D2TF-KA ^④	CC	1.5-4.5	7.5-10	9-11.25	11.25-13.5	13.5-16	0-1.5	6.25-9.25	6.25-9.25	6.25-9.25	0-6.5	5-7	5-7	5-7	5-7	5-7	5-7
D2TF-LB ^④	CC	0-1	2.5-6	9-11.25	11.25-13.5	13.5-16	0-1	1.5-4.5	6.5-9.25	6.5-9.25	0-6.5	5-7	5-7	5-7	5-7	5-7	5-7
D2TF-PA ^④	CC	0-1	2.56	9-11.25	11.25-13.5	13.5-16	0-1	1.5-4.5	6.5-9.25	6.5-9.25	0-6.5	5-7	5-7	5-7	5-7	5-7	5-7
D2UF-AA ^③	C	0-5	0-1.5	2.25-4.5	6-8	7.5-10	0-1	1-4	4.5-7.5	4.5-7.5	0-2.5	3.5-6.5	5-7	5-7	5-7	5-7	5-7
D2UF-CA ^④	C	0-5	0-1.5	2.25-4.5	6-8	7.5-10	0-1	1-4	5.5-8.5	6.5-9.5	0-6.5	5-7	5-7	5-7	5-7	5-7	5-7
D2UF-DA ^③	C	0-5	0-1.5	2.25-4.5	6-8	7.5-10	0-1	1-4	4.5-7.5	4.5-7.5	0-4.5	5-7	5-7	5-7	5-7	5-7	5-7
D2UF-EA ^④	CC	0-1	0-2.5	6-8	8.5-11	9.5-12.5	0-1	0-2	5.5-8.5	8.5-11.5	0-3	4-7	5-7	5-7	5-7	5-7	5-7
D2UF-GA ^④	CC	0-1	0-2.5	6-8	8.5-11	9.5-12.5	0-1	0-2	5.5-8.5	8.5-11.5	0-3	4-7	5-7	5-7	5-7	5-7	5-7
D2UF-LA ^④	CC	0-1.25	2.5-5	6-8	7.5-9.5	8.5-10.5	0-1.25	2.5-5.5	2.5-5.5	2.5-5.5	0-2.25	3.5-7	5-7	5-7	5-7	5-7	5-7
D2UF-MA ^④	CC	0-5	2.5-4.5	6.5-8.5	8.5-11.5	9.5-12	0-1	0-2	5.5-8.5	8.5-11.5	0-3	4-7	5-7	5-7	5-7	5-7	5-7

① - C(Clockwise), CC(Counterclockwise) Viewed from rotor end.

② - Basic number is 12127. Table gives prefix and suffix only.

③ - Dual Vacuum Diaphragm Distributor.

④ - Single Vacuum Diaphragm Distributor.

Ignition Distributors

1973 FORD MOTOR CO. DISTRIBUTOR ADVANCE SPECIFICATIONS NOTE - FOR ENGINE RPM AND DEGREES, MULTIPLY SPECIFICATIONS BY 2.

Distributor Part No. ②	Rot. ①	Automatic Advance (Distr. Degrees @ RPM)						Vacuum Advance (Distr. Degrees) Operate Distr. @ 1000 RPM						Vacuum Retard (Distr. Degrees) Operate Distr. @ 1000 RPM					
		500		750		1000		1500		2000		5	10	15	20	5	10	15	20
		Distr. Degrees	Distr. Degrees	Distr. Degrees	Distr. Degrees	Distr. Degrees	Distr. Degrees	Distr. Degrees	Distr. Degrees	Distr. Degrees	Distr. Degrees	Distr. Degrees	Distr. Degrees	Distr. Degrees	Distr. Degrees	Distr. Degrees	Distr. Degrees	Distr. Degrees	Distr. Degrees
D38F-AA ③	C	0-1.5	3.5-5.5	7.5-9.5	9.5-11.5	10.5-12.5	0-3.5	4.5-7.25	4.5-7.25	4.5-7.25	0-3.5	2-4	2-4	2-4	0-3.5	2-4	2-4	2-4	
D38F-BA ③	CC	0-1	2.5-4.5	6.5-8.5	8.5-11	9.5-12	0-1	0-2	5.5-8.5	5.5-8.5	0-1	4.5-7	4.5-7	4.5-7	0-3.5	4.5-7	4.5-7	4.5-7	
D38F-CA ③	C	0-1.5	3.5-5.5	7.5-9.5	9.5-11.5	10.5-12.5	0-3.5	4.5-7.25	4.5-7.25	4.5-7.25	0-3.5	2-4	2-4	2-4	0-3.5	2-4	2-4	2-4	
D38F-DA ③	CC	0-1.25	2.5-4.5	5.5-7.5	8.5-10.5	11.5-13.5	0-1	0-2	5.5-8.5	5.5-8.5	0-1	4.5-7	4.5-7	4.5-7	0-3.5	4.5-7	4.5-7	4.5-7	
D3TF-EA ④	CC	0-1.5	4.5-6.5	6.8	8-10.5	10-12.5	0-1.25	5.5-8.5	6.5-9.25	6.5-9.25	0-1.25	
D3TF-GA ④	C	0-1	.5-2.5	2.5-4.5	4-6	5.25-7.5	0-1.25	5-8	6.5-9.25	6.5-9.25	0-1.25	
D3TF-HA ④	CC	0-1.25	6-8	8-10	11.5-14	11.5-14	0-1	0-1.5	4-7	4.5-7.25	0-1	
D3TF-PA ④	CC	0-1.5	4.5-6.5	8-10	11.5-13.5	15-17.5	0-2.5	5.5-8.5	6.5-9.25	6.5-9.25	0-2.5	
D3TF-UA ④	CC	0-1.5	4.5-6.5	8-10	11.5-13.5	15-17.5	0-1.5	6.5-9.25	6.5-9.25	6.5-9.25	0-1.5	
D3TF-VA ④	CC	0-1	4.5-6.5	8-10	10.5-12.5	13-15.25	0-2.5	6-9	9.5-12.5	13-15.25	0-2.5	
D3TF-XA ④	CC	0-1	4.5-6.5	8-10	10.5-12.5	13-15.25	0-2.5	6-9	9.5-12.5	13-15.25	0-2.5	
D3UF-AA ③	C	0-5	0-2	5-7	7-9	8.25-10.5	0-1.5	6.25-9.25	8.5-11.5	8.5-11.25	0-1.5	0-4.25	5-7	5-7	5-7	
D3UF-BA ③	C	0-5	0-1.5	2.5-4.5	6-8	7.5-10	0-1	1-4.5	4.5-7.25	4.5-7.25	0-1	0-3.25	4.5-7	4.5-7	4.5-7	
D3UF-EA ③	CC	0-1.25	2.5-4.5	5.5-7.5	9-11	12.25-14.5	0-1.5	6.5-9.25	6.5-9.25	6.5-9.25	0-1.5	0-4	5-7	5-7	5-7	
D3UF-GA ③	CC	0-1	0-2.5	2-4.5	5.5-8.25	9.25-11.5	0-5	0-2.5	2.5-5.25	2.5-5.25	0-5	0-3	2-4	2-4	2-4	
D3UF-HA ③	CC	0-1	2.5-4.5	5-7	6.5-9	8.25-10.5	0-1	0-1.5	4-7	4.5-7.25	0-1	
D3UF-JA ③	CC	0-1.5	2.5-4.5	5-7	6.5-9	8.25-10.5	0-1	0-1.5	4-7	4.5-7.25	0-1	0-2	2-4	2-4	2-4	
D3UF-KA ③	CC	0-1.5	2.4	3.5-5.5	6.5-9	8.5-11	0-1	0-2	4-7	4.5-7.25	0-1	
D3UF-LA ③	C	0-5	0-2	5-7	7-9	8.25-10.5	0-1	1.5-4.5	4.5-7.25	4.5-7.25	0-1	0-3	4-7	5-7	5-7	
D3UF-MA ③	C	0-5	0-2	5-7	7-9	8.25-10.5	0-1.5	4.5-7.25	4.5-7.25	4.5-7.25	0-1.5	0-4.25	5-7	5-7	5-7	

- ① - C(Clockwise), CC(Counterclockwise) viewed from rotor end.
- ② - Basic number is 12127. Table gives prefix and suffix only.
- ③ - Dual Vacuum Diaphragm Distributor.
- ④ - Single Vacuum Diaphragm Distributor.

Ignition Distributors

1974 FORD MOTOR CO. DISTRIBUTOR ADVANCE SPECIFICATIONS

NOTE — FOR ENGINE RPM AND DEGREES, MULTIPLY SPECIFICATIONS BY 2.

Distributor Part No. ②	Rot. ①	Automatic Advance (Distr. Degrees @ RPM)						Vacuum Advance (Distr. Degrees) Operate Distr. @ 1000 RPM						Vacuum Retard (Distr. Degrees) Operate Distr. @ 1000 RPM													
		500		750		1000		1500		2000		5		10		15		20		5		10		15		20	
		Distr. Degrees	Distr. Degrees	Distr. Degrees	Distr. Degrees	Distr. Degrees	Distr. Degrees	Distr. Degrees	Distr. Degrees	Distr. Degrees	Distr. Degrees	Distr. Degrees	Distr. Degrees	Distr. Degrees	Distr. Degrees	Distr. Degrees	Distr. Degrees	Distr. Degrees	Distr. Degrees	Distr. Degrees	Distr. Degrees	Distr. Degrees	Distr. Degrees	Distr. Degrees	Distr. Degrees	Distr. Degrees	Distr. Degrees
D3BF-BA ③	CC	0-1	2.5-4.5	6.5-8.5	8.5-11	9.5-12	0-1	0-2	4.25-7.25	5.5-8.5	8.5-11.5	0-3.5	5-7	5-7	5-7	0-3.5	5-7	5-7	5-7	0-3.5	5-7	5-7	5-7	5-7	5-7	5-7	5-7
D3BF-CA ③	C	0-1.5	3.5-5.5	6.5-8.5	8.5-10.5	10-12.5	0-1.25	0-1.25	4.25-7.25	4.25-7.25	4.25-7.25	0-2	4.25-7.25	4.25-7.25	4.25-7.25	0-2	2-4	2-4	2-4	0-2	2-4	2-4	2-4	2-4	2-4	2-4	2-4
D3TF-GA ④	C	0-1	5-2.5	2.5-4.5	4-6	5.25-7.25	0-1.25	5-8	6.5-9.25	6.5-9.25	6.5-9.25	0-1.25	5-8	6.5-9.25	6.5-9.25	0-1.25	5-8	6.5-9.25	6.5-9.25	0-1.25	5-8	6.5-9.25	6.5-9.25	6.5-9.25	6.5-9.25	6.5-9.25	6.5-9.25
D3UF-BA ③	C	0-5	0-1.5	2.5-4.5	6-8	7.5-10	0-1	1-4.5	4.5-7.25	4.5-7.25	4.5-7.25	0-1	1-4.5	4.5-7.25	4.5-7.25	0-3	4.5-7	4.5-7	4.5-7	0-3	4.5-7	4.5-7	4.5-7	4.5-7	4.5-7	4.5-7	4.5-7
D3UF-FA ③	CC	0-1.5	6-8	7.25-9.25	9.5-11.5	11.5-14	0-1.5	6.5-9.5	10.5-13.2	10.5-13.2	10.5-13.2	0-1.5	6.5-9.5	10.5-13.2	10.5-13.2	0-4	2-4	2-4	2-4	0-4	2-4	2-4	2-4	2-4	2-4	2-4	2-4
D3UF-JA ③	CC	0-1.5	2.5-4.5	5-7	6.5-9	8.25-10.5	0-1	0-1.5	4.7	4.7	4.7	0-1	0-1.5	4.7	4.7	0-2	2-4	2-4	2-4	0-2	2-4	2-4	2-4	2-4	2-4	2-4	2-4
D3UF-KA ④ ⑤	CC	0-1.5	2-4	3.5-5.5	6.5-9	8.5-11	0-1	0-2	4.7	4.7	4.7	0-1	0-2	4.7	4.7	0-2	2-4	2-4	2-4	0-1	0-2	2-4	2-4	2-4	2-4	2-4	2-4
D3UF-PA ③	C	0-1	0-2.5	5-7	7-9	8.25-10.5	2.5-5.5	2.5-5.5	2.5-5.5	2.5-5.5	2.5-5.5	2.5-5.5	2.5-5.5	2.5-5.5	2.5-5.5	0-3	4.5-7	4.5-7	4.5-7	0-3	4.5-7	4.5-7	4.5-7	4.5-7	4.5-7	4.5-7	4.5-7
D3UF-RA ③	C	0-5	0-1.5	2.5-4.5	6-8	7.5-10	2.5-5.5	2.5-5.5	2.5-5.5	2.5-5.5	2.5-5.5	2.5-5.5	2.5-5.5	2.5-5.5	2.5-5.5	0-3	4.5-7	4.5-7	4.5-7	0-3	4.5-7	4.5-7	4.5-7	4.5-7	4.5-7	4.5-7	4.5-7
D4TE-CA ④ ⑤	CC	0-5	0-5	3-5	7-9	8.25-10.5	0-1.25	5-8	8.5-11.25	8.5-11.25	8.5-11.25	0-1.25	5-8	8.5-11.25	8.5-11.25	0-1.25	5-8	8.5-11.25	8.5-11.25	0-1.25	5-8	8.5-11.25	8.5-11.25	8.5-11.25	8.5-11.25	8.5-11.25	8.5-11.25
D4TE-HA ④ ⑤	CC	0-5	0-2.5	6-8	7.5-9.5	8.5-11.25	0-1.25	5-8	8.5-11.25	8.5-11.25	8.5-11.25	0-1.25	5-8	8.5-11.25	8.5-11.25	0-1.25	5-8	8.5-11.25	8.5-11.25	0-1.25	5-8	8.5-11.25	8.5-11.25	8.5-11.25	8.5-11.25	8.5-11.25	8.5-11.25
D4TE-NA ④ ⑤	CC	0-5	0-5	5-2.5	4.5-7	5.5-8.5	0-1.5	5-8	6.5-9.5	6.5-9.5	6.5-9.5	0-1.5	5-8	6.5-9.5	6.5-9.5	0-1.5	5-8	6.5-9.5	6.5-9.5	0-1.5	5-8	6.5-9.5	6.5-9.5	6.5-9.5	6.5-9.5	6.5-9.5	6.5-9.5
D4TE-PA ④ ⑤	CC	0-5	0-1.5	1.5-3.5	6-8	9-11.5	0-1	0-2	5-8.5	5-8.5	5-8.5	0-1	0-2	5-8.5	5-8.5	0-1	0-2	5-8.5	5-8.5	0-1	0-2	5-8.5	5-8.5	5-8.5	5-8.5	5-8.5	5-8.5
D4TE-TA ④ ⑤	CC	0-1	4-6	6-8	10-12	13.5-16.5	3.5-6.5	4.5-7.25	4.5-7.25	4.5-7.25	4.5-7.25	3.5-6.5	4.5-7.25	4.5-7.25	4.5-7.25	0-4.5	5-7	5-7	5-7	0-4.5	5-7	5-7	5-7	5-7	5-7	5-7	5-7
D4TE-YA ④ ⑤	CC	0-5	2.5-4.5	5.5-7.5	8.5-10.5	11-13.5	2.5-5.25	2.5-5.25	2.5-5.25	2.5-5.25	2.5-5.25	2.5-5.25	2.5-5.25	2.5-5.25	2.5-5.25	0-3.5	5-7	5-7	5-7	0-3.5	5-7	5-7	5-7	5-7	5-7	5-7	5-7
D4TZ-V ⑥ ⑦	CC	0-5	2.5-4.5	4.5-6.5	6-8	7.5-10	0-5	0-2	5.5-8.5	5.5-8.5	5.5-8.5	0-5	0-2	5.5-8.5	5.5-8.5	0-4.5	5-7	5-7	5-7	0-4.5	5-7	5-7	5-7	5-7	5-7	5-7	5-7
D4UE-CA ④ ⑤	CC	0-5	2.5-4.5	4-6	6.5-8.5	8.5-11	0-1	0-3	6.5-9.5	6.5-9.5	6.5-9.5	0-1	0-3	6.5-9.5	6.5-9.5	0-4	5-7	5-7	5-7	0-4	5-7	5-7	5-7	5-7	5-7	5-7	5-7
D4UE-HA ④ ⑤	CC	0-5	2.5-4.5	6.5-8.5	9-11	10-12.5	0-1.5	6.5-9.5	6.5-9.5	6.5-9.5	6.5-9.5	0-1.5	6.5-9.5	6.5-9.5	6.5-9.5	0-4	5-7	5-7	5-7	0-4	5-7	5-7	5-7	5-7	5-7	5-7	5-7

- ① — C(Clockwise), CC(Counterclockwise) viewed from rotor end.
- ② — Basic number is 12127. Table gives prefix and suffix only.
- ③ — Dual Vacuum Diaphragm Distributor.
- ④ — Single Vacuum Diaphragm Distributor.
- ⑤ — Breakerless Ignition.