

Ignition Distributors

1965-74 I.H.C. - HOLLEY DISTRIBUTOR ADVANCE SPECIFICATIONS NOTE - FOR ENGINE RPM AND DEGREES, MULTIPLY SPECIFICATIONS BY 2.

Distributor Part No. ②	Rot ①	Automatic Advance (Distr. Degrees & RPM)				Vacuum Advance (Distr. Deg. & In. of Hg.)					
		Deg.	RPM	Deg.	RPM	Deg.	In. Hg.	Deg.	In. Hg.		
285 093	C	0-2	350	6-8	700	12.5-14.5	2000	0	5-7	7	10.5-11.5
285 096	C	0-2	350	6-8	700	12.5-14.5	2000	0	5-7	7	10.5-11.5
285 098	C	0-2	350	6-8	700	12.5-14.5	2000	0	5-7	7	10.5-11.5
359 206	C	0-1	300	5.75-7.75	650	12.5-14.5	2000	0	5-7.5	6-8	12
359 212	C	0-1.5	350	5.75-7.75	650	12.5-14.5	2000	0	5-7	7	10.5-11
359 215	C	0-1	300	7.5-9.5	700	15-17	1800	0	5-7	7	10.5-11.25
359 217	C	0-1	300	5.75-7.75	650	12.5-14.5	2000	0	5-7.5	6-8	12
359 218	C	0-2	400	4-6	700	10.5-12.5	2000	0	5-7	6-8	11
359 220	C	0-1	300	5.75-7.75	650	12.5-14.5	2000	0	5-7.5	6-8	12
360 724	C	0-1	400	9-11	750	18-20	1900	0	5-7	4-6	11
379 282	C	0-1	400	7-9	700	13-15	2000	0	5-7	4-6	11
383 150	C	0-1	400	5.5-7.5	600	15-17	2000	0	5.5-7.5	4-6	11
383 151	C	0-1	400	7-9	700	13-15	2000	0	5-7	4-6	11
427 908	C	0-1	400	9-11	1100	15-17	2000	0	5-7	4-6	11
427 964	C	0-1	400	4-6	700	10.4-12.4	2000	0	5-7	2-4	8.5
427 965	C	0-1	400	4-6	700	10.4-12.4	2000	0	5-7	4-6	10
427 966	C	0-1	400	4-6	700	10.4-12.4	2000	0	5-7	2-4	8.5
427 967	C	0-1	400	4-6	700	10.4-12.4	2000	0	5-7	4-6	10
428 078	C	0-1	400	6-8	700	12.4-14.4	2000	0	5-7	2-4	8.5
428 079	C	0-1	400	6-8	700	12.4-14.4	2000	0	5-7	2-4	8.5
428 095	C	0-1	400	9-11	1100	15-17	2000	0	5-7	2-4	8.5
433 142	C	0-1	400	4-6	900	15-17	2000	0	5-7	2-4	8.5
436 869	C	0-1	400	7-9	1200	15-17	2000	0	5-7	4-6	11

① - C(Clockwise). CC(Counterclockwise) viewed from rotor end.

② - All part numbers end in C91.

1965-74 PRESTOLITE DISTRIBUTOR ADVANCE SPECIFICATIONS NOTE - FOR ENGINE RPM AND DEGREES, MULTIPLY SPECIFICATIONS BY 2.

Distributor Part No.	Rot ①	Automatic Advance (Distr. Degrees & RPM)				Vacuum Advance (Distr. Deg. & In. of Hg.)					
		Deg.	RPM	Deg.	RPM	Deg.	In. Hg.	Deg.	In. Hg.		
IAT-4416	CC	1	460	7.5	900	15	1400	4	8.75	7.5	12
IAT-4501	CC	16	1800	8
IAT-4502A	CC	21	1800	8
IAY-4012	CC	1	450	5	800	10	1425	2	6.75	9	15
IAY-4401	CC	6	1050	10	1575	11	1700	3	9.63	6	14
IAY-4401A	CC	1	560	6	900	11	2100	5	10	10	15.5
IAY-4401B	CC	0	450	4.5	550	13.5	1700

① - CC (Counterclockwise).