

1975 DISTRIBUTOR SPECIFICATIONS

CHRYSLER CORP. DISTRIBUTOR ADVANCE SPECIFICATIONS (Cont.)

NOTE — FOR ENGINE RPM AND DEGREES, MULTIPLY SPECIFICATIONS BELOW BY 2.

Distributor Part No.	Rot ⊙	Automatic Advance (Distr. Degrees & RPM)						Vacuum Advance (Distr. Deg. & In. of Hg.)			
		Deg.	RPM	Deg.	RPM	Deg.	RPM	Deg.	In. Hg.	Deg.	In. Hg.
3874082	C	1.0-4.5	600	8.0-10.5	900	11.5-14.0	2200	0.5-2.5	7	7.0-10.0	11.5
3874090	C	1.5-5.5	550	5.5-8.0	700	11.5-14.0	2200	0.5-2.5	7	10.0-12.0	12.5
3874097	C	1.0-4.5	650	8.5-11.0	950	13.5-16.0	2150	0.5-2.5	7	10.0-12.0	12.5
3874101	CC	0.5-3.0	600	6.0-8.5	950	10.0-12.0	2000	0.5-2.5	8	9.0-11.0	14.0
3874110	CC	1.0-3.5	600	6.0-8.5	900	10.0-12.0	2000	0.5-2.5	8	9.0-11.0	14.0
3874115	C	1.0-3.5	600	6.0-8.5	900	10.0-12.0	2000	0.5-2.5	7	10.0-12.0	12.5
3874173	CC	1.0-3.5	600	3.5-6.0	750	8.0-10.0	2000	0.5-2.5	8	9.0-11.0	14.0
3874298	C	0.5-3.5	700	7.0-10.0	1100	13.5-16.0	2100	0.5-2.5	9	9.5-12.5	15.5

⊙ — C (Clockwise), CC (Counterclockwise) viewed from rotor end.

DELCO-REMY DISTRIBUTOR ADVANCE SPECIFICATIONS

NOTE — FOR ENGINE RPM AND DEGREES, MULTIPLY SPECIFICATIONS BY 2

Distributor Part No.	Rot ⊙	Automatic Advance (Distr. Degrees & RPM)						Vacuum Advance (Distr. Deg. & In. of Hg.)			
		Deg.	RPM	Deg.	RPM	Deg.	RPM	Deg.	In. Hg.	Deg.	In. Hg.
1110650	C	0	550	3.5	1150	8	2100	0	3-5	8-9	11.5-12.5
1110651	C	0	540	3	1000	8	2050	0	5-7	9	10
1110652	C	0	550	7	1150	12	2050	0	5	12	15
1112495	CC	0	550	7	1100	4	2200	0	7	4	12
1112498	CC	0	600	2	700	8.5	1800	0	6	8.5	13
1112500	CC	0	600	3	800	10	2200	0	6-8	12.5	11.5
1112862	C	0	810	2.5	1000	11	1400	0	5	12	12
1112863	C	0	550	3.5	1100	8	2100	0	4	8	12-18
1112880	C	0	600	6	1000	11	2100	0	4	9	12
1112882	C	0	500	4	800	7.5	1400	0	8	7.5	15.5
1112883	C	0	550	6	800	11	2300	0	4	7.5	10
1112886	C	0	900	6	2100	0	4	9	7
1112888	C	0	550	6	800	8	2100	0	4	9	12
1112891	C	0	330	2.5-5	600	7.5-10	3000	0-2	5.5	13.5-14.5	16
1112892	C	1-3	600	5	1400	6-8	2500	1-3	6	13-14	16
1112893	CC	0	450	4.5	1000	8	1700	0	9	12	19.5
1112894	CC	0	675	4.5-6	1500	7-9	2200	0	4-6	7-10	11
1112896	CC	0	550	3	1050	6	2250	0	7	7	11.5
1112897	C	0	330	2.5-5	600	7.5-10	3000	0-2	6.5	9.5-10.5	14
1112918	CC	0	500	4	1000	7	2200	0	7	7	11

⊙ — C (clockwise), CC (counterclockwise) when viewed from rotor end.

DELCO-REMY DISTRIBUTOR ADVANCE SPECIFICATIONS (Cont.)

NOTE — FOR ENGINE RPM AND DEGREES, MULTIPLY SPECIFICATIONS BELOW BY 2.

Distributor Part No.	Rot ⊙	Automatic Advance (Distr. Degrees & RPM)						Vacuum Advance (Distr. Deg. & In. of Hg.)			
		Deg	RPM	Deg.	RPM	Deg.	RPM	Deg	In. Hg.	Deg.	In. Hg.
1112928	CC	0	600	2	700	8	2200	0	6-8	8	12
1112929	CC	0	500	4	700	10	2200	0	7	10	14
1112930	CC	0	700	3.5	1000	5	2200	0	7	5	12
1112933	C	0	600	4.5	1000	11	2000	0	3	8	8
1112936	CC	0	500	9.5	2000	0	6.5	12	16
1112937	CC	0	500	6.5	1800	0	8	9	13
1112945	CC	0	450	4.5	1000	8	1700	0	14.5	5	19
1112946	CC	0	500	4	700	10.5	1800	0	7	10.6	15
1112947	CC	0	600	2	700	10	1900	0	8	10	15
1112949	CC	0	500	5.5	1000	7	2200	0	7	7	14
1112950	CC	0	600	2	700	10	1900	0	7	10	11
1112951	CC	0	325	9.5	1200	14	2200	0	4	14	15
1112952	CC	0	500	3.5	1050	7	1800	0	8	9	13
1112953	CC	0	500	9.5	2000	0	8	9	16
1112956	CC	0	325	9.5	1200	14	2200
1112958	CC	0	600	2	700	8	2200	0	5	12.5	11

⊙ — C (Clockwise), CC (Counterclockwise) viewed from rotor end.