

# 1975 DISTRIBUTOR SPECIFICATIONS

## FORD MOTOR CO. DISTRIBUTOR ADVANCE SPECIFICATIONS

NOTE — FOR ENGINE RPM AND DEGREES, MULTIPLY SPECIFICATIONS BY 2

Distributor Part No.	Rot ①	Automatic Advance (Distr. Degrees & RPM)						Vacuum Advance (Distr. Deg. & In. of Hg.)			
		Deg.	RPM	Deg.	RPM	Deg.	RPM	Deg.	In. Hg.	Deg.	In. Hg.
D4VE-CA	CC	0-4	1650	14-18.5	3000	19.5-25	5000	0-6	6.3	17.5-22.5	14.6
D5AE-BA	CC	0-4	1800	7.5-12	3000	16-23	4300	0-6	5	21.2-26.5	13
D5AE-DA	CC	0-5	1950	7.5-12.5	3000	16.5-21.5	4300	0-7	5	25.5-30.5	13
D5AE-EA	CC	0-5	1950	7.5-12.5	3000	16.5-21.5	4300	0-7.5	4	21.5-26.5	11
D5DE-DA②	C	0-4	1400	12.5-17.2	3000	16-22	5000	0-6	3.6	9.5-14.5	5.25
D5DE-FA②	C	0-4	1160	10-15	3000	20-25.5	5000	0-6	6.25	5.5-10.5	8.5
D5DE-HA	CC	0-4	1100	14-18	3000	28-33	5000	0-6	6.5	21.5-26.5	19
D5DE-LA②	CC	0-4	1400	10-14	2800	19.5-25.5	5000	0-6	6.75	17.5-22.5	18
D5DE-UA	C	0-4	1400	13.5-18	3000	18.5-24.5	5000	0-6	3.75	9.5-14.5	6.5
D5DE-VA	C	0-4	1400	11.5-16	3000	20-25	4450	0-7.6	3.75	9.5-14.5	6.5
D5DE-ZA	CC	0-4	1320	9.6-14.5	3000	16.5-21.5	4760	0-6	6	17.5-22.5	14.25

① — C (Clockwise), CC (Counterclockwise) viewed from rotor end.

② — See Ford Motor Co. Distributor Retard Specifications.

## FORD MOTOR CO. DISTRIBUTOR RETARD SPECIFICATIONS

NOTE — FOR ENGINE RPM AND DEGREES, MULTIPLY SPECIFICATIONS BELOW BY 2.

Distributor Part No.	Vacuum Retard (Dist. Degrees & In. of Hg.)					
	Deg.	In. Hg.	Deg.	In. Hg.	Deg.	In. Hg.
D5DE-DA①	2	2.75-6.75	10	5.75-9.75	10-14	9.8
D5DE-FA①	2	4-8	4	5-9	4-8	9
D5DE-LA①	2	8.3-12.3	10	12.3-16.5	10-12	16.5

① — See Ford Motor Co. Distributor Advance Specifications.

## PRESTOLITE DISTRIBUTOR ADVANCE SPECIFICATIONS

NOTE — FOR ENGINE RPM AND DEGREES, MULTIPLY SPECIFICATIONS BELOW BY 2.

Distributor Part No.	Rot ①	Automatic Advance (Distr. Degrees & RPM)						Vacuum Advance (Distr. Deg. & In. of Hg.)			
		Deg.	RPM	Deg.	RPM	Deg.	RPM	Deg.	In. Hg.	Deg.	In. Hg.
IDJ-4001	C	0-4.3	500	6.4-8.5	1000	14-16	2300	0-2.2	4-5	6.5-8.5	12.7
IDJ-4001-A	C	0-2.5	500	8.2-10.2	1000	15-17	2200	0-2.2	4-6	6.5-8.5	12.7
IDJ-4001-B	C	4-2.9	500	4.5-7	750	15-17	2200	0-2.6	5-7	6.5-8.5	12.5
IDJ-4002-B	C	0-2	600	6-7.5	1000	13-15	2250	0-2.4	5-7	7-9	13.1
IDJ-4002-C	C	0-2	500	3.5-6	750	12-14	2250	0-2.4	5-7	7-9	13.1

① — C (Clockwise), CC (Counterclockwise) viewed from rotor end.