

4-10 1975-79 DISTRIBUTORS & IGNITION SYSTEMS

1975 Distributor Specifications

NOTE - FOR ENGINE RPM AND DEGREES, MULTIPLY SPECIFICATIONS BY 2

CHRYSLER CORP. DISTRIBUTOR ADVANCE SPECIFICATIONS

Distributor Part No.	Rot ①	Automatic Advance (Distr. Degrees & RPM)						Vacuum Advance (Distr. Deg. & In. of Hg.)			
		Deg.	RPM	Deg.	RPM	Deg.	RPM	Deg.	In. Hg.	Deg.	In. Hg.
3656667	C	0.5-3.5	550	7.0-9.0	900	13.5-16.0	2200	1.0-3.5	9.5	7.0-10.0	14.0
3656672	C	0.5-3.5	550	5.0-7.5	800	11.5-14.0	2200	0.5-2.5	10.0	7.5-9.5	15.0
3755056	C	1.0-4.5	550	4.5-7.9	700	11.5-14.0	2200	1.5-5.0	11.0	5.0-8.0	12.5
3755157	CC	0.5-3.5	650	5.5-8.0	900	9.5-12.0	2000	1.0-4.0	10.5	8.0-10.5	15.5
3755201	C	0.5-3.0	550	2.5-5.0	700	11.5-14.0	2150	0.5-2.5	10.0	7.5-9.5	15.0
3874082	C	1.0-4.5	600	8.0-10.5	900	11.5-14.0	2200	0.5-2.5	7.0	7.0-10.0	11.5
3874090	C	1.5-5.5	550	5.5-8.0	700	11.5-14.0	2200	0.5-2.5	7.0	10.0-12.0	12.5
3874302	C	1.5-5.5	550	5.5-8.0	700	11.5-14.0	2200	0.5-2.5	9.0	9.5-12.5	15.5
3874323	C	0.5-3.0	550	2.5-5.0	700	11.5-14.0	2150	1.5-5.0	11.0	5.0-8.0	12.5

① - C (Clockwise), CC (Counterclockwise) viewed from rotor end.

DELCO-REMY DISTRIBUTOR ADVANCE SPECIFICATIONS

Distributor Part No.	Rot ①	Automatic Advance (Distr. Degrees & RPM)						Vacuum Advance (Distr. Deg. & In. of Hg.)			
		Deg.	RPM	Deg.	RPM	Deg.	RPM	Deg.	In. Hg.	Deg.	In. Hg.
1110650	C	0	550	7	1150	8	2100	0	4	7	12
1112494	C	0	550	7	1400	10	2100	0	10	7	17
1112863	C	0	550	3.5	1150	8	2100	0	4	9	12
1112869	C	0	550	7	1400	10	2100	0	6	10	15
1112880	C	0	600	6	1000	11	2100	0	4	9	12
1112884	C	0	575	8.5	1450	11	2100	0	8	5	13
1112886	C	0	900	6	2100	0	4	9	17
1112887	C	0	550	7	1150	12	2100	0	10	5	13
1112888	C	0	550	6	800	8	2100	0	4	9	12
1112940	C	0	600	7.5	1350	10	2100	0	4	7.5	15.5
1112941	C	0	500	4	800	9.5	1725	0	8	5	13
1112943	C	0	550	5.5	1200	9	2100	0	6	10	15

① - C (Clockwise), CC (Counterclockwise) viewed from rotor end.

FORD MOTOR CO. DISTRIBUTOR ADVANCE SPECIFICATIONS

Distributor Part No.	Rot ①	Automatic Advance (Distr. Degrees & RPM)						Vacuum Advance (Distr. Deg. & In. of Hg.)			
		Deg.	RPM	Deg.	RPM	Deg.	RPM	Deg.	In. Hg.	Deg.	In. Hg.
D4TE-NA	CC	500	1000	1500	5	15
D5TE-AA	C	500	1000	1500	5	15
D5TE-AAA	C	-1.0-5	500	4.8-7	1000	7.2-9.5	1500	0.0-3.2	5	2.8-5.2	15
D5TE-ABA	CC	-1.0-5	500	0.0-2.8	1000	3.5-6.2	1500	0.0-1.3	5	8.8-12	15
D5TE-AEA	CC	-1.0-5	500	5.7-7.8	1000	8.4-10.6	1500	0.0-4	5	8.8-11.2	15
D5TE-AFA	CC	500	1000	1500	5	15
D5TE-AGA	CC	-1.0-5	500	-1-1	1000	6.8-8.8	1500	0.0-1.8	5	6.8-9.2	15
D5TE-AKA	CC	-0.8-0.5	500	-0.8-1.6	1000	3.5-5	1500	0.0-1	5	4.8-7.2	15
D5TE-DA	CC	-1.0-5	500	1-3	1000	3.5-5.8	1500	0.0-1	5	4.8-7.3	15
D5TE-EA	CC	-1.2-1.5	500	8-10	1000	11.8-14	1500	0.0-3	5	2.8-4.2	15
D5TE-FA	C	-1.0-5	500	2.4-4.4	1000	3.8-6	1500	0.0-1.2	5	6.8-9.4	15
D5TE-JA	CC	500	1000	1500	5	15
D5TE-LA	CC	-1.1-2	500	5.8-8	1000	8.5-10.8	1500	0.0-1.2	5	6.8-9.4	15
D5TE-MA	C	-1.0-5	500	4-6	1000	6.2-8.5	1500	0.0-2.2	5	4.8-7.3	15
D5TE-NA	C	-1.0-5	500	5-6.8	1000	7.2-9.5	1500	0.0-3	5	4.8-7.2	15
D5TE-PA	CC	-1.2-0.3	500	5.5-7.6	1000	8.4-10.6	1500	3.2-6.6	5	6.8-9.2	15
D5TE-RA	CC	-1.1-4	500	5.8-8	1000	8.5-10.7	1500	0.0-1.2	5	6.8-9.2	15
D5TE-SA	CC	-1.0-5	500	3.2-5.2	1000	7.3-9.5	1500	0.0-1.1	5	8.8-11.3	15
D5TE-TA	CC	-1.0-5	500	1.4-3.4	1000	3.3-5.7	1500	0.0-1	5	6.2-9.2	15
D5TE-UA	C	-1.0-5	500	-1.2-1	1000	5-7.1	1500	0.3-4	5	5.3-7.2	15
D5TE-ZA	CC	-1.0-5	500	4.5-6.6	1000	7.2-9.5	1500	3-6.3	5	6.8-9.4	15
D5TZ-C	CC	500	100	1500	5	15
D5TZ-T	CC	500	1000	1500	5	15
D5TZ-Y	CC	500	1000	1500	5	15
D5UE-BA	CC	-1.0-4	500	1-2.6	1000	3.5-6	1500	0.0-1.3	5	9.1-12.6	15
D5UE-CA	CC	-1.0-5	500	-1.8-0.5	1000	3.4-6	1500	0.0-1.3	5	2.8-5.3	15
D5UE-DA	CC	-0.8-0.5	500	1-3.6	1000	4.5-7	1500	0.0-3.1	5	10.7-13.2	15
D5UE-EA	CC	-1.0-5	500	-2.0-5	1000	3.4-6	1500	0.0-1.3	5	5.5-8.5	15

① - C (Clockwise), CC (Counterclockwise) viewed from rotor end.