

# 1975-79 DISTRIBUTORS & IGNITION SYSTEMS 4-15

## 1977 Distributor Specifications (Cont.)

NOTE - FOR DISTRIBUTOR RPM AND DEGREES, DIVIDE SPECIFICATIONS BY 2.

### FORD MOTOR CO. DISTRIBUTOR ADVANCE SPECIFICATIONS

Distributor Part No.	Rot <sup>⊙</sup>	Automatic Advance (Engine Degrees & RPM)						Vacuum Advance (Engine Deg. & In. of Hg.)			
		Deg.	RPM	Deg.	RPM	Deg.	RPM	Deg.	In. Hg.	Deg.	In. Hg.
D5TE-FA	C	0	1350	9.5	2500	16	5000	0	1	16	11.5
D5TE-UA	C	0	1900	12	3000	18.5	5000	0	1	12	8
D6TE-NA	CC	0	1900	14	2800	21	5000	0	6	28	16
D7AE-BA <sup>⊙</sup>	CC	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
D7TE-ABA <sup>⊙</sup>	CC	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
D7TE-ADA	CC	0	1500	11	3100	23.5	5000	0	2.5	28	17.5
D7TE-AHA <sup>⊙</sup>	CC	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
D7TE-AJA <sup>⊙</sup>	C	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
D7TE-AKA <sup>⊙</sup>	C	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
D7TE-BA	CC	0	1200	15	2100	30	5000	0	5	29	14
D7TE-EA <sup>⊙</sup>	CC	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
D7TE-GA	C	0	1200	9	1900	18	5000	0	2.5	28	13.5
D7TE-JA	CC	0	1200	7	1800	23	4600	0	2.5	28	17.5
D7TE-MA <sup>⊙</sup>	C	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
D7TE-NA	CC	0	1700	9	2400	20	5000	1	6	28	16
D7TE-PA	CC	0	1900	11.5	3000	19	4450	0	2.5	28	16
D7TE-RA	CC	0	1900	11.5	3000	19	4450	0	2.5	28	20
D7TE-TA	C	0	1200	9	2000	18	5000	0	6	26	18
D7TE-UA <sup>⊙</sup>	C	0	1000	12	3000	18	5000	0	2	12	8.5
D7UE-AA	CC	0	1600	12	3300	23	5000	2	4.5	24	14
D7UE-BA	CC	0	1300	10	2500	23	4000	1	6	28	16
D7UE-DA	CC	0	1300	10	3000	23	4800	2	5	12	10
D7UE-EA	CC	0	1000	14	3200	20.5	5000	1	5	24	17
D7UE-FA	CC	0	1400	4	2100	11	5000	1	5	12	10
D7UE-JA <sup>⊙</sup>	CC	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
D7UE-LA <sup>⊙</sup>	CC	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....

- ⊙ - Specifications not available at time of publication.
- ⊙ - Vacuum Retard Specifications (at crankshaft): 0° at 2.5 in. Hg.; -12° at 10 in. Hg.
- ⊙ - C (Clockwise), CC (Counterclockwise) viewed from rotor end.

### I.H.C. - HOLLEY DISTRIBUTOR ADVANCE SPECIFICATIONS

Distributor Part No.	Rot <sup>⊙</sup>	Automatic Advance (Engine Degrees & RPM)						Vacuum Advance (Engine Deg. & In. of Hg.)			
		Deg.	RPM	Deg.	RPM	Deg.	RPM	Deg.	In. Hg.	Deg.	In. Hg.
461270 C91	C	0	950	15-19	2000	30-34	4200	0-3	6	8-12	15
464359 C91	C	0	900	8-12	1200	31.5-35.5	4400	0-3	6	8-12	15
467073 C91	C	2-4	1200	10-14	2000	29.5-33.5	4200	10-16	10.5	12-16	19
469648 C91	C	2-4	1400	7-11	2000	24-28	4200	3-8	8	4-8	12

- ⊙ - C (Clockwise), CC (Counterclockwise) viewed from rotor end.

### PRESTOLITE DISTRIBUTOR ADVANCE SPECIFICATIONS

Distributor Part No.	Rot <sup>⊙</sup>	Automatic Advance (Engine Degrees & RPM)						Vacuum Advance (Engine Deg. & In. of Hg.)			
		Deg.	RPM	Deg.	RPM	Deg.	RPM	Deg.	In. Hg.	Deg.	In. Hg.
IDJ 4001E	C	0-7.5	1100	11-15	2400	22-26	4400	0-2.5	5	11.5-17	12.5
IDJ 4001F	C	0-7.5	1100	8-12	2400	15-19	4400	0-2.5	5	11.5-17	12.5
IDJ 4001G	C	0-7	1100	15-19	2400	18-22	4400	0-3	6	13-17	12.5
IDJ 4002F	C	0-4	1100	9.5-13.5	2400	18-22	4400	0-2.5	6	14-18	13

- ⊙ - C (Clockwise), CC (Counterclockwise) viewed from rotor end.