

4-16 1975-79 DISTRIBUTORS & IGNITION SYSTEMS

1978 Distributor Specifications

NOTE — FOR DISTRIBUTOR RPM AND DEGREES, DIVIDE SPECIFICATIONS BY 2.

CHRYSLER CORP. DISTRIBUTOR ADVANCE SPECIFICATIONS

Distributor Part No.	Rot ⊙	Automatic Advance (Engine Degrees & RPM)						Vacuum Advance (Engine Deg. & In. of Hg.)			
		Deg.	RPM	Deg.	RPM	Deg.	RPM	Deg.	In. Hg.	Deg.	In. Hg.
3656672	C	1.0-7.0	1000	10.0-15.0	1600	23.0-28.0	4400	1.0-5.0	10.0	15.0-19.0	15.0
3755056	C	2.0-9.0	1000	9.0-15.8	1400	23.0-28.0	4400	3.0-11.0	11.0	10.0-16.0	12.5
3755157	CC	1.0-7.0	1300	11.0-16.0	1800	19.0-24.0	4000	2.0-8.0	10.5	16.0-21.0	15.5
3875201	C	1.0-6.0	1100	5.0-10.0	1400	23.0-28.0	4300	1.0-5.0	10.0	15.0-19.0	15.0
3874115	C	2.6-6.2	1200	11.6-15.0	1600	20.0-24.0	4000	1.6-5.2	7.0	20.0-24.0	12.5
3874596	CC	3.0-7.0	1200	12.0-16.0	1600	15.0-20.0	4400	7.0-11.0	10.0	18.0-22.0	15.0
3874876	C	3.0-7.0	1300	4.0-8.0	1800	7.0-9.0	4400	2.0-12.0	8.0	20.0-24.0	12.5
3874887	CC	2.0-6.4	1300	7.6-11.8	1900	19.2-24.0	4800	3.2-6.2	7.0	10.6-16.0	11.5
4091661	C	3.0-7.0	1100	18.0-22.0	1700	24.0-28.0	4000	1.0-8.0	7.0	12.0-16.0	15.0
4091821	CC	1.0-5.0	1200	16.0-20.0	1800	24.0-28.0	4000	1.0-5.2	10.0	16.0-21.0	31.0

⊙ — C (Clockwise), CC (Counterclockwise) viewed from rotor end.

DELCO-REMY DISTRIBUTOR ADVANCE SPECIFICATIONS

Distributor Part No.	Rot ⊙	Automatic Advance (Engine Degrees & RPM)						Vacuum Advance (Engine Deg. & In. of Hg.)			
		Deg.	RPM	Deg.	RPM	Deg.	RPM	Deg.	In. Hg.	Deg.	In. Hg.
1103238	C	0	1100	14	2800	20	4200	0	10	15	17
1103240	C	0	1100	14	2800	20	4200	0	6	20	15
1103249	C	0	1000	8	1600	19	3450	0	6	15	12
1103250	C	0	1150	17	2900	22	4200	0	8	10	13
1103274	C	0	1200	15	2700	20	4200	0	4	18	12
1103281	C	0	1000	10	1700	20	3800	0	4	18	12
1103286	C	0	1100	16	2400	22	4600	0	6	15	12
1103301	C	0	1000	8	1600	19	3450	0	4	10	8
1103302	C	0	1100	17	2400	22	4600	0	6	15	12
1103338	C	0	1000	10	1700	20	3800	0	5	24	12
1103339	C	0	1100	16	2400	22	4600	0	4	10	8
1103358	C	0	1100	14	2800	20	4200	0	4	15	10
1110237	C	0	1000	10	1700	20	3800	0	8	10	13
1110715	C	0	1000	7	1600	20	4200	8	4	18	12
1110717	C	0	1100	14	2300	24	4100	8	4	18	12
1110719	C	0	1100	7	2300	16	4200	8	4	18	12
1110720	C	0	1100	14	2300	24	4100	0	10	0	13
1110721	C	0	1100	14	2300	24	4100	0	10	10	13

⊙ — C (Clockwise), CC (Counterclockwise) viewed from rotor end.

HOLLEY DISTRIBUTOR ADVANCE SPECIFICATIONS

Distributor Part No.	Rot ⊙	Automatic Advance (Engine Degrees & RPM)						Vacuum Advance (Engine Deg. & In. of Hg.)			
		Deg.	RPM	Deg.	RPM	Deg.	RPM	Deg.	In. Hg.	Deg.	In. Hg.
461270C91	C	0	950	15-19	2000	30-34	4200	0-3	6	8-12	15
464359C91	C	10	1200	9.5	2000	168	4400	0-3	6	8-12	15
467073C91	C	2-6	1200	10-14	2000	15.8	4200	10-16	10.5	12-16	19
469648C91	C	2-4	1400	7-11	2000	24-28	4200	3-8	8	4-8	12

⊙ — C (Clockwise), CC (Counterclockwise) viewed from rotor end.