

# 1980 Distributor Specifications

## DELCO-REMY DISTRIBUTOR ADVANCE SPECIFICATIONS (Cont.)

NOTE — FOR DISTRIBUTOR RPM & DEGREES, DIVIDE SPECIFICATIONS BY 2

Distributor Part No.	Rot. <sup>⊙</sup>	Automatic Advance (Engine Degrees & RPM)						Vacuum Advance (Engine Deg. & In. of Hg.)			
		Deg.	RPM	Deg.	RPM	Deg.	RPM	Deg.	In. Hg.	Deg.	In. Hg.
1103415 <sup>⊙</sup>	....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
1103416 <sup>⊙</sup>	....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
1103417	CC	0	2000	.....	.....	16	4400	0	5	24	12
1103419	CC	0	600	11	1200	23	3600	0	4	30	11
1103425 <sup>⊙</sup>	C	0	1200	9	2000	18	4600	0	4.5	20	10.5
1103444	C	0	1200	.....	.....	15	2000	0	7	20	13
1103447	CC	0	2000	.....	.....	16	4400	0	7	24	14.6
1103449 <sup>⊙</sup>	C	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
1103450	C	0	1300	.....	.....	19	3200	0	2	20	10.5
1110550	CC	0	1000	6	1200	15	4400	0	2	20	12
1110551	CC	0	1000	.....	.....	10	4400	.....	.....	.....	.....
1110552	C	0	925	6.5	2500	14	3400	0	3	24	8
1110554	CC	0	1600	6	2400	15	3600	0	2	24	12
1110555	C	0	1200	6	2400	16.5	3600	0	3.5	24	11
1110558	C	0	1200	9	2400	14	4000	0	3.5	16	6
1110559	C	0	1000	9	2400	14	4000	0	3.5	16	7
1110560	C	0	1000	8	2400	14	4400	0	3.5	20	10
1110561	C	0	1000	8	2400	14	4400	0	3	15	6.5
1110571	CC	0	1000	6	1200	15	4400	0	2	20	9
1110572	CC	0	1000	.....	.....	10	4400	.....	.....	.....	.....
1110573 <sup>⊙</sup>	....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
1110576	C	0	1000	16	2500	14	3400	0	3.5	24	8.5
1110650	C	0	1000	8	2400	14	4400	0	3.5	19	10
1110696	C	0	1000	10	1700	10	3800	0	2	16	7.5
1110716	C	0	1000	7	1600	20	4200	0	4	15	12
1110752	C	0	1400	9	2400	14	4100	0	4	16	7.5
1110756	C	0	1400	4	1700	14	3800	0	2	24	10
1110766	C	0	2000	.....	.....	15	3600	0	4	24	12
1110767	C	0	2000	.....	.....	15	3600	0	3	20	12
1110769	C	0	1000	6	2400	15	3600	0	4.5	24	9.5
1110782	C	0	1050	6	1300	21	4000	0	3.5	19	8
1110783	C	0	1400	6.5	1700	21	4000	0	4	19.5	10.5
1110884 <sup>⊙</sup>	C	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
1110786	C	0	1050	5	1300	21	4000	0	3.5	21	9
1110787	C	0	1050	7	1700	21	4000	0	3.5	20	9
1110788	C	0	1520	3	2200	16	5250	0	5	24	12
1110789	C	0	1200	8	2000	24	5700	0	3	20	2.7
1110792	C	0	1520	3	2200	16	5250	0	3	25	10
1110794	C	0	1520	3	2200	16	5250	0	3	16	6.5
1110795	C	0	1200	8	2000	24	5700	0	3	25	10

⊙ — C (Clockwise), CC (Counterclockwise) as viewed from rotor end.  
 ⊙ — Electronic Module Retard on Buick.

⊙ — Electronic Spark Selection.  
 ⊙ — Electronic Spark Timing.

## DELCO-REMY (AMERICAN MOTORS) DISTRIBUTOR ADVANCE SPECIFICATIONS

NOTE — FOR DISTRIBUTOR RPM & DEGREES, DIVIDE SPECIFICATIONS BY 2

Distributor Part No.	Rot. <sup>⊙</sup>	Automatic Advance (Engine Degrees & RPM)						Vacuum Advance (Engine Deg. & In. of Hg.)			
		Deg.	RPM	Deg.	RPM	Deg.	RPM	Deg.	In. Hg.	Deg.	In. Hg.
1110560	C	0 to -1	900	4.5-8.5	2000	11.5-16	5000	0	4	20	12
1110561	C	0 to -1	900	4.5-8.5	2000	11.5-16	4800	0	3	15	14
1110650	C	0 to -1	900	5-8.5	2000	11.5-16	4800	0	4	20	12

⊙ — C (Clockwise), CC (Counterclockwise) as viewed from rotor end.