

1981 Distributor Specifications

CHRYSLER CORP. DISTRIBUTOR ADVANCE SPECIFICATIONS

NOTE — FOR DISTRIBUTOR RPM AND DEGREES, DIVIDE SPECIFICATIONS BY 2.

Distributor Part No.	Rot. ①	Automatic Advance (Engine Degrees & RPM)				Vacuum Advance (Engine Deg. & In. of Hg)					
		Deg.	RPM	Deg.	RPM	Deg.	In. Hg	Deg.	In. Hg		
4091661	C	3-6	1100	11-15	1700	22-26	4000	1-4	7	12-16	15
4111501	C	1-3	1400	3-7	1800	15-20	4400	2-5	7	20-24	15
4111783	C	2-5	1100	8-10	1800	23-27	4200	1-5	10	15-19	15
4111950	C	1-5	1100	5-9	1800	16-20	4400	2-5	7	20-24	15
4145364	C	2-6	1000	7-11	1800	12-16	4200	0-2	6	20-24	13
4145602	C	1-5	1800	5-7	2400	11-15	4400	0-2	6	20-24	13
4145604	C	2-5	1200	3-7	2000	8-12	4400	0-2	6	20-24	13
4145751	C	Electronic Spark Advance									

① — C (Clockwise), CC (Counterclockwise) viewed from rotor end.

DELCO-REMY DISTRIBUTOR ADVANCE SPECIFICATIONS

NOTE — FOR DISTRIBUTOR RPM AND DEGREES, DIVIDE SPECIFICATIONS BY 2.

Distributor Part No. ①	Rot. ②	Automatic Advance (Engine Degrees & RPM)				Vacuum Advance (Engine Deg. & In. of Hg)					
		Deg.	RPM	Deg.	RPM	Deg.	In. Hg	Deg.	In. Hg		
1103339	C	0	1100	16	2400	22	4600	0	4	10	8
1103353	C	0	1100	16	2400	22	4600	0	4	20	10
1103369	C	0	1200	8	2000	20	4200	0	3	16	6.5
1103375	C	0	1150	17	2900	22	4200	0	4	10	8
1103376	C	0	1100	14	2800	20	4200	0	8	10	13
1103381	C	0	1200	8	2000	20	4200	0	3	10	7.5
1103420③	C	0	1000	17	1600	22	4200	0	4	15	10
1103420④	C	0	1800	—	—	24	4000	0	10	10	13
1103432	C	0	1000	10	2000	14	4000	0	4	15	12
1103433	C	0	1100	16	2400	22	4600	0	4	15	12
1110560	C	0	800	8	2400	14	4400	6	6	20	12
1110589	C	0	1100	14	2300	24	4100	0	3	16	6.5
1110590	C	0	1100	14	2300	24	4100	0	4	15	10
1110749	C	0	1100	7	2300	16	4200	0	4	10	8
1110753	C	0	1100	14	2300	24	4100	0	4	10⑤	8⑤
1111388	C	0	1100	14	2300	24	4100	0	4	20	7.5
1103464	C	Electronic Spark Control									
1103465	C	Electronic Spark Control									

① — Part numbers apply to GMC and Chevrolet except for 1110560, used on Jeep 4 cylinder 2.5L (151") engine.

② — C (Clockwise), CC (Counterclockwise) viewed from rotor end.

③ — Calif. Auto. Trans.

④ — Calif. Man. Trans.

⑤ — Specification is for 4.8L (292") engine. On 4.1L (250") engine, vacuum is 15° @ 10 in. Hg.