

1968-70 Distributor Specifications

1962-70 AUTOLITE DISTRIBUTOR ADVANCE SPECIFICATIONS

NOTE — FOR ENGINE RPM & DEGREES, MULTIPLY SPECIFICATIONS BELOW BY 2

Distributor Part No. ①	Centrifugal Advance (Dist. Degrees & RPM)						Vacuum Advance (Dist. Degrees & In. of Hg.)							
	Deg.	RPM	Deg.	RPM	Deg.	RPM	Deg.	RPM	Deg.	In. Hg.	Deg.	In. Hg.	Deg.	In. Hg.
C6AH-A	0	500	4-6	900	8½-10½	1500	12½-14½	2000	0	5.0	6-8	10.0	9-11	15.0-20.0
C6AH-B	0	600	4½-6½	1200	9-11	1800	12-14	2500	0	5.0	6½-9	10.0	11-13	15.0-20.0
C6BH-C	½-2½	600	4½-6½	800	7½-9½	1200	8½-10½	2000	½-3½	9.0	4½-7½	16.0	5-8	20.0
C7BH-D	0-2¼	600	10-12	1300	16-18	2780	18	Limit	1-4	6.0	4¾-7¼	8.0	5½-8½	10.0
C7BH-K	¼-2¼	600	7-9	1075	10½-12½	3000	13	Limit	1-4	6.0	4¾-7¼	8.0	5½-8½	10.0
C8EH-G	2-3½	700	5-7½	1000	13-15½	2000	16-18½	2500	0-7	5.5	7½-11	7.0	10-13	9.0
70AB-A, DA ②	0 ± ½	200-450	5½-7½	800	8.6-10.6	1500	13.2-15.2	2500	0	2.5	0-1	4.2	5-8	10.0
70BB-A-A	0 ± ½	200-450	10-12	1100	12½-14½	1900	16¼-18¼	3100	0-1	8.0	1½-4	12.5	5½-8½	17.0

① — Basic Ford Part No. is 12127 (Ex: C7BH-12127-D).

② — Vacuum Retard Range — 0-7° at 5-17" of Hg.

1962-70 BOSCH DISTRIBUTOR ADVANCE SPECIFICATIONS

NOTE — FOR ENGINE RPM & DEGREES, MULTIPLY SPECIFICATIONS BELOW BY 2.

Bosch Part Number Model Number	Centrifugal Advance (Dist. Degrees & RPM)						Vacuum Advance (Dist. Degrees & In. of Hg.)							
	Deg.	RPM	Deg.	RPM	Deg.	RPM	Deg.	RPM	Deg.	In. Hg.	Deg.	In. Hg.	Deg.	In. Hg.
0231110026	0	300-450	5	500-600	10	800-1100	16½	1450-2650
0231112006	Begin	450-600	7	1000	10	1700	15	3500	Begin	1.0-3.0	5.0	5-8
0231112016	Begin	200-300	10	500-1200	15	1600-2000	16-19	2000-2400	Begin	3.5-5.25	Max.	10.63	4-7
0231112031	Begin	200-400	5	350-550	10	800-1250	12-15	1550-1900	Begin	2.75-5.5	Max.	19.69	7-9
0231112034	Begin	200-350	10	650-900	15	1650-2000	16-19	2200-3300	Begin	3.5-5.25	Max.	10.63	4-7
0231112043	Begin	150-380	10	750-1150	15	1450-1900	17½-20½	2250-2600	Begin	3.15-5.5	Max.	10.25-14.5	9½-11½
0231112044	Begin	150-350	10	700-1050	15	1350-1800	15-18½	1850-2300	Begin	2.36-4.33	Max.	7.0-11.5	7-9
0231112046	Begin	375-525	5	650-925	10	1150-1450	9½-12½	1400-1650	Begin	2.36-4.33	Max.	7.0	5½-9½
0231112053	Begin	225-500	10	800-1300	15	1600-2100	Max.	2500-2750	Begin	8.75-11.5	Max.	15.25-17.75	5-8
0231112056	Begin	150-380	5	380-600	10	750-1150	17½-20½	1450-1900	Begin	3.15-5.5	Max.	10.25-14.5	9½-11½
0231112057	Begin	150-350	5	325-550	10	700-1050	15-18½	1350-1800	Begin	2.36-4.33	Max.	7.0-11.41	7-9
0231114016	Begin	300-360	5	420-500	10	840-1060	13½-16½	1340-1560	Begin	2.75-4.33	Max.	12.60	8½-11
0231115006	Begin	300-440	10	500-640	15	820-1150	17-20	1200-1500	Begin	3.5-4.75	Max.	8.75	4½-7½
0231115008	Begin	250-500	5	800-1100	10	1400-1650	12½-15½	1860-2100	Begin	3.5-4.75	Max.	9.1	4-5
0231115016	Begin	200-300	10	500-1200	15	1600-2000	16-19	2000-2400	Begin	3.5-5.25	Max.	10.63	4-7
0231115027	Begin	150-350	10	600-950	15	1550-2100	16-19	2250-2600	Begin	3.15-5.5	Max.	13.75	4-7
0231115029	Begin	300-550	10	750-1000	20	1600-1950	20½-23½	2000-2350	Begin	3.15-5.5	Max.	9.5-11.75	4-7
0231115040	Begin	500-650	5	1250-1450	6-9	1600-1850	Begin	3.5-5.5	Max.	15.0	6½-8½
0231115040(Late)	Begin	420-710	5	1160-1480	6-9	1750-2100	Begin	3.15-6.30	Max.	10.63-14.76	3½-6½
0231115045	9-11	500	11½-13½	750	14-16	1000	17½-19½	1250-1350	Begin	4.75-6.0	Max.	7.75-8.25	10