

1972 Distributor Specifications

LUCAS DISTRIBUTOR ADVANCE SPECIFICATIONS

NOTE — FOR ENGINE RPM & DEGREES, MULTIPLY SPECIFICATIONS BELOW BY 2.

Distributor Part No.	Rot. ^⓪	Automatic Advance (Distr. Degrees @ RPM)				Vacuum Advance (Distr. Degrees) Operate Distr. @ 1000 RPM				Vacuum Retard (Distr. Degrees) Operate Distr. @ 1000 RPM			
		Deg.	RPM	Deg.	RPM	Deg.	RPM	Deg.	RPM	Deg.	RPM	Deg.	RPM
41219	CC	175 1.0-3.5	450 6.5-9.0	800 8.5-10.5	1300 12.0-14.0	2000 13.0-15.0
41202	CC	450 0-1	850 4-6	1500 6-8	2500 9-11	3000 9-11	4 0-3	2.5-7.0 6-9	8 7-9	15 7-9	4.0 0-3	8.0 5-8	15.0 7-9
41306	CC	450 0-1	850 4-6	1500 6-8	2500 9-11	3000 9-11	4 0-2.5	2.5-7.0 6-9	8 7-9	15 7-9	4.0 0-3	8.0 5-8	15.0 7-9
41352	CC	650 1.0-3.5	900 6.5-9.0	1100 8.5-10.5	2200 12.0-14.0	2800 13.0-15.0	4.0 2.5-5.0	5.0 3-5	8.0 3-5
41385	CC	600 1.0-3.0	900 4.0-6.0	1200 6.0-8.0	2200 10.5-12.5	2800 12.0-14.0	4.0 3.5	8.0 4-7	15.0 6-8

⓪ — Viewed from rotor.

LUCAS DISTRIBUTOR ADVANCE SPECIFICATIONS

NOTE — FOR ENGINE RPM & DEGREES, MULTIPLY SPECIFICATIONS BELOW BY 2.

Distributor Part No.	Centrifugal Advance (Dist. Degrees & RPM)						Vacuum Advance (Dist. Degrees & In. of Hg.)					
	Deg.	RPM	Deg.	RPM	Deg.	RPM	Deg.	In. Hg.	Deg.	In. Hg.	Deg.	In. Hg.
41301D	0-2	500	8.5-10.5	1000	12-14	2000	15-17	0-5	7	1.5-4	16	3-5.5
41321	1-3.5	550	6-8	950	11-13	2900	11.5-13.5	7-9 ^⓪	7-13	0 ^⓪	1	...
41315	0-4	300	6-8	600	15-17	1750	19-21	Begins	3.5	Max. 25
41264	0	400	6	800	15	Begins	5	Max. 11
41275	1-3.5	400	7-9	1200	9-11	1750	10-12	0-5	8	8.5-10.5	13.5	9-11
41060A	0-1.5	525	6.5-8.5	1250	8.5-10.5	1800	8.5-10.5	0-3	7.5	6.0-8.5	13.0	7-9

⓪ — Retarded.

⓪ — No Retard.